DRIVER MATRIX | CONSTANT CURRENT - NOT DIMMABLE

number of products allowed per driver

	19	19 115
	□ C€ IP20	☐ C € IP20
Reference	12403730	12400730
Dimensions (LxWxH)	115x34x19	115x34x19
,		
Input	220-240V 50/60Hz	220-240V 50/60Hz
Ambient temperature	-25°C to +45°C	-25°C to +45°C
Power factor (max)	0.54	0.54
Dimming	-	-
Max drivers on MCB 16A type B	27	27
Output	350mA / 15W 1-43V DC	500mA / 12W 1-24V DC
Chapeau 1x LED 1000Im GE	2	1
Duell recessed 1x LED <900Im GE	2	1
Duell recessed 2x LED <900lm GE	1	
Grib LED <250Im GE	4	Λ
Hipy 67 IP67 LED <1500lm GE	2 1	1 1
Intro IP44 <900lm GE Julien IP54 1x LED <350lm GE	4	I .
K-0 LED <900lm GE	2	1
K-1 LED <900Im GE	2	1
Kurk IP40 LED <600LM GE	2	1
Kurk Surface <600lm GE	2	1
LED tile 596x596 LED<4000L LED module 7W <450Im GE	1	
Lotis adjustable LED <900lm GE	2	1
Lotis bathroom LED<900lm	2	1
Lotis LED <900lm GE	2	1
Lotis mini IP55 LED <250lm GE	14	8
Marty LED <150lm GE	14	
Mini A(r)mor LED <150lm GE Mini Hipy 67 IP67 LED <350lm GE	4	
Mini Thub metal LED <900lm GE	2	1
Mini-multiple 1x LED <900lm GE	2	1
Mini-multiple 2Lx LED <900lm GE	1	
Mini-multiple 3Lx LED <900lm GE		
Mini-multiple 4SQx LED <900lm GE Nano Cake IP55 LED <250lm GE	14	8
Nomad 2x LED <900lm GE	1	0
Nomad 4x LED <900lm GE		
Qliv IP67 LED <1500lm GE	2	1
Scotty adjustable LED <1200lm GE	1	
Scotty LED <1400lm GE Slide square clockwork LED<900lm GE	1 2	1
Slide square clockwork LED<900lm GE Slide square IP44 LED<900lm GE	2 2	1
Slide square LED <900lm GE	2	1
Slide twin LED <900lm GE	1	
Smart Cake 115 LED 1100-3000lm GE	1	
Smart Cake 82 LED <900lm GE	2	1
Smart Cake adjustable 115 LED <900lm GE Smart Kup 115 LED 1100-3000lm GE	2	1
Smart Kup 82 LED <900lm GE	2	1
Smart Kup adjustable 115 LED <900lm GE	2	1
Smart Lotis 115 LED 1100-3000lm GE	1	
Smart Lotis 82 LED <900lm GE	2	1
Smart Lotis adjustable 115 LED <900lm GE	2	1
Stove LED <1000lm GE	2	I