Status	Finished
Started	Thursday, 15 October 2026, 10:10 PM
Completed	Thursday, 15 October 2026, 10:29 PM
Duration	19 mins 8 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

def cal(n1) : What is n1?

a. None of the mentioned
b. Argument
c. Keyword
d. Parameter ✓

Question **2**

Correct

Mark 1.00 out of 1.00

Which of the following number can never be generated by the following code: random.randrange(0, 100)

a. 100 ✓
b. 0
c. 99
d. 1

Question **3**

Correct

Mark 1.00 out of 1.00

Write the output of : print(max([1, 2, 3, 4], [4, 5, 6], [7]))

a. [1, 2, 3, 4]
b. [7] ✓
c. [4, 5, 6]
d. 7

Question **4**

Correct

Mark 1.00 out of 1.00

The function can be called in the program by writing function name followed by _____.

a. ( ) ✓

b. { }

c. [ ]

d. None of the mentioned

Question **5**

Correct

Mark 1.00 out of 1.00

Function defined to achieve some task as per the programmer's requirement is called a _____.

a. library function

b. built in functions

c. user defined function ✓

d. All of the mentioned

Question **6**

Correct

Mark 1.00 out of 1.00

A variable that is defined inside any function or a block is known as a _____.

a. Function Variable

b. Global variable

c. Local variable ✓

d. inside variable

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the following function call?

```
def outer_fun(a, b):
    def inner_fun(c, d):
        return c + d
        return inner_fun(a, b)
    return a
result = outer_fun(5, 10)
print(result)
```

a. Syntax Error

b. (15,5)

c. 5 ✓

d. 15

Question **8**

Correct

Mark 1.00 out of 1.00

Which of the following statement is not true regarding functions?

a. Function header always ends with a colon (🙂 .

b. A function may or may not return value.

c. A function may or may not have parameters.

d. A function definition begins with "define" ✓

Question **9**

Correct

Mark 1.00 out of 1.00

The _____ statement returns the values from the function to the calling function.

a. return ✓

b. take

c. give

d. send

Question **10**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def sayHello():
    print('Hello World!')
sayHello()
sayHello()
```

a. None of the mentioned

b. 'Hello World!'
'Hello World!'

c. Hello
Hello

d. Hello World! ✓
Hello World!

Question **11**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def printMax(a, b):
    if a > b:
        print(a, 'is maximum')
    elif a == b:
        print(a, 'is equal to', b)
    else:
        print(b, 'is maximum')
printMax(3, 4)
```

a. 4

b. 3

c. None of the mentioned

d. 4 is maximum ✓

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following function definition header is wrong?

a. def sum(n1, n2, n = 3):
b. def mul(p1, n1, m1):
c. def scan(p1, p2 = 4, p3 = 5):
d. def div(p1=4, p2, p3): ✓

Question **13**

Correct

Mark 1.00 out of 1.00

Choose the incorrect statement.

a. print(pow(2, 3))
b. None of the mentioned ✓
c. print(pow(2.3, 3.2))
d. print(pow(2, 3, 2))

Question **14**

Correct

Mark 1.00 out of 1.00

The return statement in function is used to _____.

a. returns the control to the calling function
b. None of the mentioned
c. return value
d. Both return value and returns the control to the calling function ✓

Question **15**

Correct

Mark 1.00 out of 1.00

Write the output of : print(abs(-45))

a. -45
b. 45 ✓
c. 45.0
d. None of the mentioned

Status	Finished
Started	Thursday, 15 October 2026, 10:37 PM
Completed	Thursday, 15 October 2026, 10:47 PM
Duration	10 mins 35 secs
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 2.00 out of 2.00

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
`print(christmasDiscount(578))`	12

Answer: (penalty regime: 0 %)

Reset answer

```
def christmasDiscount(orderValue):
    total = 0
    for digit in str(orderValue):
        if digit in ('2', '3', '5', '7'):
            total += int(digit)
    return total
```

	Test	Expected	Got	
✓	`print(christmasDiscount(578))`	12	12	✓

	Test	Expected	Got	
✓	print(christmasDiscount(57))	12	12	✓
✓	print(christmasDiscount(222))	6	6	✓
✓	print(christmasDiscount(77777))	35	35	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **2**

Correct

Mark 2.00 out of 2.00

complete function to implement coin change making problem i.e. finding the minimum

number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
1
2 def coinChange(amount):
3     return amount // 4 + (amount % 4 + 2) // 3
```

	Test	Expected	Got	
✓	`print(coinChange(16))`	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **3**

Correct

Mark 2.00 out of 2.00

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: U = 2^a * 3^b * 5^c, where a, b and c are nonnegative integers.

For example:

Test	Result
`print(checkUgly(6))`	`ugly`
`print(checkUgly(21))`	`not ugly`

Answer: (penalty regime: 0 %)

Reset answer

```
def checkUgly(n):
    if n <= 0:
        return "not ugly"

    for p in [2, 3, 5]:
        while n % p == 0:
            n //= p

    if n == 1:
        return "ugly"
    else:
        return "not ugly"
```

	Test	Expected	Got	
✓	`print(checkUgly(6))`	`ugly`	`ugly`	✓
✓	`print(checkUgly(21))`	`not ugly`	`not ugly`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **4**

Correct

Mark 2.00 out of 2.00

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

Example 1:

Input:

69

Output:

true

Example 2:

Input:

88

Output:

true

Example 3:

Input:

962

Output:

false

Example 4:

Input:

1

Output:

true

For example:

Test	Result
`print(Strobogrammatic(69))`	`True`
`print(Strobogrammatic(962))`	`False`

Answer: (penalty regime: 0 %)

Reset answer

```
def Strobogrammatic(num):
    num = str(num)
    rotate = {'0': '0', '1': '1', '6': '9', '8': '8', '9': '6'}

    for i in range(len(num)):
        if num[i] not in rotate:
            return False
        if rotate[num[i]] != num[len(num) - 1 - i]:
            return False

    return True
```

	Test	Expected	Got	
✓	`print(Strobogrammatic(69))`	`True`	`True`	✓
✓	`print(Strobogrammatic(88))`	`True`	`True`	✓
✓	`print(Strobogrammatic(962))`	`False`	`False`	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.

Question **5**

Correct

Mark 2.00 out of 2.00

Write a function that returns the value of a+aa+aaa+aaaa with a given digit as the value of a.

Suppose the following input is supplied to the program:

9

Then, the output should be:

9+99+999+9999=11106

Sample Input Format:

9

Sample Output format:

11106

For example:

Test	Result
print(Summation(8))	9872

Answer: (penalty regime: 0 %)

Reset answer

```
def Summation(n):
    a = str(n)
    result = int(a) + int(a * 2) + int(a * 3) + int(a * 4)
    return result
```

	Test	Expected	Got	
✓	print(Summation(8))	9872	9872	✓
✓	print(Summation(10))	10203040	10203040	✓

Passed all tests! ✓

Correct

Marks for this submission: 2.00/2.00.