

CA02 - Training Perceptron and Adaline models

Make sure you: a) describe briefly what you intend to do using markdown cells; b) comment your code properly but briefly, such that the reader can easily understand what the code is doing.

Imports

In [291...

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from adaline import AdalineGD
from perceptron import Perceptron

# Import the relevant classes from adaline.py and perceptron.py in the classi
```


Loading and exploring data

Visualise the raw data with appropriate plots and inspect it for possible outliers or inconsistencies. Comment briefly on what you see and how this will impact the performance of the perceptron and adaline. For this use no more than three sentences.

In [292...


```
# Insert your code below
# =====
raw_data = pd.read_csv('diabetes_data.csv') # loading the data
nan_values = raw_data.isna().sum() # Checking for nan values , this gave a ze.
corr_data=raw_data[raw_data.columns].corr() # finding the correlation values

# Here is where we plot
plt.figure(figsize=(20,10))
sns.heatmap(corr_data, annot=True)
plt.show()
```




In [293]...

```
# The plot for boxplots, trying to understand the outliers of the problem
y = raw_data.columns[1:-1]
fig, axes = plt.subplots(2,4,figsize = (20,10))
for ycols,ax in zip(y, axes.flatten()):
    sns.boxplot(x = raw_data['class'], y = ycols, data = raw_data, ax = ax)
plt.show()
```



In [294]...

```
# The plot for violinplots, trying to understand the the connection between t.
ycol = raw_data.columns[1:-1]
fig, axes = plt.subplots(2,4,figsize = (20,10))
for ycols,ax in zip(ycol, axes.flatten()):
    sns.violinplot(x = raw_data['class'], y = ycols, data = raw_data, ax = ax)
plt.show()
```



Preprocessing data and training models

- Split the data into training and test_sets, where 400 samples are used for training, the remaining rows should be used for testing.
- Make sure the target values are appropriate for the Adaline and Perceptron classifiers
- Make sure that no data leakage occurs when scaling the data

With each of the 400 models, you should predict the classes of the unseen samples in the test data and compute the test set classification accuracy. Store the results in a (8 x 50) numpy array or a pandas dataframe.

Preprocessing:

In [295...

```
# Insert your code below
# =====
df = raw_data.copy()
# seperatin the training set from the test set
xtrain = df.iloc[0:400, 1:-1]
ytrain = df.iloc[0:400, -1]
ytrain = np.where(ytrain == 1, 1,-1)

xtest = df.iloc[400: , 1:-1]
ytest = df.iloc[400: , -1]
ytest = np.where(ytest == 1, 1,-1)

# The scaling if the x values
x_scaled_train = (xtrain - np.mean(xtrain, axis=0)) / np.std(xtrain, axis = 0)
x_scaled_test = (xtest - np.mean(xtest, axis=0)) / np.std(xtest, axis = 0)
```

Training:

In [296...

```
# Insert your code below
# =====

# Empty numpy array that will be updated
results_perceptron = np.zeros((8,50))
results_adaline = np.zeros((8,50))

# The updating of the numpy arrays using the preceptron and adaline to train
```

```

for i in range (1,9):

    for j in range(1,51):

        xctr = x_scaled_train[:50*i].to_numpy()
        ytr = ytrain[:50*i]

        ppn = Perceptron(eta = 0.0001, n_iter=j).fit(xctr,ytr)
        ada = AdalineGD (eta=0.0001 , n_iter= j).fit(xctr,ytr)

        ypred_ppn = ppn.predict(x_scaled_test)
        ypred_ada = ada.predict(x_scaled_test)

        accuarcy_ppn = ((ytest == ypred_ppn).sum())/ x_scaled_test.shape[0]
        accuarcy_ada = ((ytest == ypred_ada).sum())/ x_scaled_test.shape[0]

        results_perceptron[i-1][j-1] = accuarcy_ppn
        results_adaline [i-1][j-1] = accuarcy_ada

```

Visualizing results

Plot a heatmap of the results (test set classification accuracy) using Python plotting packages matplotlib or seaborn . See canvas for images of what the heatmaps should look like for the two classification algorithms.

In [297...


```

# Perceptron Heatmap

xticks = [f'{i} epochs' for i in range(1,51)]
yticks = [f'{i} out of 400' for i in range(50,450,50)]

plt.figure(figsize=(20,10))
sns.heatmap(results_perceptron, annot=False, xticklabels=xticks, yticklabels=
plt.show()

```



In [298...


```

#Adaline Heatmap

xticks = [f'{i} epochs' for i in range(1,51)]
yticks = [f'{i} out of 400' for i in range(50,450,50)]

```

```
plt.figure(figsize=(20,10))
sns.heatmap(results_adaline, annot=False, xticklabels=xticks, yticklabels=yticks,
plt.show()
```



Metrics

Provide the maximum test set classification accuracy for each, the perceptron classifier and the adaline classifier and information on with which combination of number training data samples and number of epochs the best classification accuracy was achieved.

In [299...

```
# Insert your code below
# =====

# Perceptron

p_max = results_perceptron.max() # Finding the max value for the array
index = np.where( results_perceptron == np.amax(results_perceptron)) # Locatin

# The size of the data that gave us the max value
df_size_p1 = (index[0][0] + 1) * 50
df_size_p2 = (index[0][1] + 1) * 50
# The epoch in which the high values were achieved
epoch_p1 = (index[1][0] + 1)
epoch_p2 = (index[1][1] + 1)

print(f'The perceptron had the highest values in two places, when the epoch is
```

The perceptron had the highest values in two places, when the epoch is 38 and 34 for data sizes of 100 and 150 the highest accuracy for both cases was 0.7581521739130435

In [300...

```
# Insert your code below
# =====

# Adaline
```

```

a_max = results_adaline.max()# Finding the max value for the array
index =np.where( results_adaline == np.amax(results_adaline)) # Locating the

# The size of the date that gave us the max value
df_size_a1 = (index[0][0] + 1) * 50

# The epoch in which the high values were achieved
epoch_a1 = (index[1][0] + 1)
epoch_a2 = (index[1][1] + 1)

print(f'The perceptron had the highest values in two places, when the epoch is

```

The perceptron had the highest values in two places, when the epoch is 47 and 48 for data sizes of 400 for both, and the highest accuracy for both cases was 0.7771739130434783

Discussion

1. The training time of the simpler perceptron algorithm is quite a bit longer than the training time of the adaline algorithm. What might be the reason for this?
2. The heatmap of the classification accuracy for the adaline algorithm is smoother than the perceptron heatmap. What might be the reason for this?

Insert your answer below

=====

1) The difference in time is related to when the algorithms update their weights to get a better fit. Perceptron updates more often, and during one epoch. While Adaline updates after the epoch, thus having less iterations and less running time. 2) The adaline uses a stochastic gradient descent approach to update the weights, while perceptron compares the updated weights with the older weight and corrects the value that way in the fitting process. The continuous use of the gradient descent, gives us a linear improvement of the fit.
