SIEMENS

Product data sheet **3SU1051-6AA20-0AA0**

INDICATOR LIGHT, 22MM, ROUND, METAL,
SHINY, RED, SMOOTH LENS

product brand name		SIRIUS ACT
Product designation		Commanding and signaling devices
Actuator:		
Design of the product		Pilot Light
Color / of the actuating element		Red
Material / of the actuating element		plastic
Shape / of the actuating element		round
Outer diameter / of the actuating element	mm	29.45
Product component / front ring		No
General technical data:		
Vibration resistance / acc. to IEC 60068-2-6		10 ... 500 Hz: 5g
Reference code		
• acc. to DIN EN 61346-2		P
• acc. to DIN EN 81346-2		P
Ambient conditions:		
Ambient temperature		
• during operation	°C	-25 … +70
• during storage	°C	-40 … +80
Climate class / during operation / acc. to EN 60721		3K6, 3C3, 3S2, 3M6

12/19/2014

Installation/ mounting/ dimensions:

Shape / of the installation opening		round
Installation width	mm	29.45
Mounting diameter	mm	22
Mounting height	mm	11.3
Installation depth	mm	26.3

Certificates/ approvals:

Further information:

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)
http://www.siemens.com/industrymall

Cax online generator
http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
http://support.automation.siemens.com/WW/view/en/3SU1051-6AA20-0AA0/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SU1051-6AA20-0AA0

last change: Nov 13, 2014