



INDICATOR LIGHT, 22MM, ROUND, PLASTIC,  
WHITE, SMOOTH LENS

product brand name		SIRIUS ACT
Product designation		Commanding and signaling devices

### Actuator:

Design of the product		Pilot Light
Color / of the actuating element		White
Material / of the actuating element		plastic
Shape / of the actuating element		round
Outer diameter / of the actuating element	mm	29.45
Product component / front ring		No

### General technical data:

Vibration resistance / acc. to IEC 60068-2-6		10 ... 500 Hz: 5g
Reference code		
• acc. to DIN EN 61346-2		P
• acc. to DIN EN 81346-2		P

### Ambient conditions:

Ambient temperature		
• during operation	°C	-25 ... +70
• during storage	°C	-40 ... +80
Climate class / during operation / acc. to EN 60721		3K6, 3C3, 3S2, 3M6

**Installation/ mounting/ dimensions:**

<b>Shape / of the installation opening</b>		round
<b>Installation width</b>	mm	29.45
<b>Mounting diameter</b>	mm	22
<b>Mounting height</b>	mm	11.3
<b>Installation depth</b>	mm	26.3

**Certificates/ approvals:****Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3SU1001-6AA60-0AA0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3SU1001-6AA60-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SU1001-6AA60-0AA0)

**last change:**

Nov 13, 2014