SIEMENS

TRANSVERSE AUX. SWITCH, 2 S,
SCREW CONNECTION,
FOR CIRCUIT-BREAKERS SZ S00/S0

General technical data:		
product brand name		SIRIUS
product designation		auxiliary switch, transverse on the front
Design of the product		transverse auxiliary switches
Size of the circuit-breaker		S00
Protection class IP / on the front		IP20
Ambient temperature		
• during storage	°C	-50 … 80
• during the operating phase	°C	-20 … 60

Auxiliary circuit:		
Number of NC contacts / for auxiliary contacts		
• instantaneous switching		0
Number of NO contacts / for auxiliary contacts		
• instantaneous switching		2
Number of changeover contacts / of the auxiliary contacts		
• instantaneous switching		0
Operating current / of the auxiliary contacts		
• at AC-12		
• at 24 V	A	2.5
• at 230 V	A	2.5

• maximum	A	10
• at AC-15		
• at 24 V	A	2
• at 230 V	A	0.5
• at DC-13		
• at 24 V	A	1
• at 48 V	A	0.3
• at 60 V	A	0.15

Installation/mounting/dimensions:

Type of mounting		plug-in fixing
Width	mm	45
Height	mm	12
Depth	mm	17

Connections:

Design of the electrical connection		
• for auxiliary and control current circuit		screw-type terminals
Type of the connectable conductor cross-section		
• for auxiliary contacts		
• solid		2x (0.5 ... 1.5 mm2), 2x (0.75 ... 2.5 mm2)
• finely stranded		
• with conductor end processing		2x (0.5 ... 1.5 mm2), 2x (0.75 ... 2.5 mm2)
• for AWG conductors / for auxiliary contacts		2x (20 ... 14)

Certificates/approvals:

Verification of suitability		CE / UL / CSA / CCC

General Product Approval		**Test Certificates**	
CQC		Manufacturer	

Shipping Approval		**other**	
ABS	PRS	Manufacturer	other
	RINA		

Further information:

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)
http://www.siemens.com/industrial-controls/mall

CAx-Online-Generator
http://www.siemens.com/cax

45

11

38.9

7.5

13   23

14   24

last change: Apr 4, 2011