



Faculty of Software Engineering and Computer Systems

Programming


Lecture #0
Introduction and more.

Instructor of faculty
Pismak Alexey Evgenievich
Gavrilov Anton Valerievich
Kronverksky Pr. 49, 1331 room
pismak@itmo.ru
avgavrilov@itmo.ru

Saint-Petersburg


Class Introduction

- Who are your teacher(s)
 - Experience with Java
 - Experience with ITMO
 - Experience with IT
- Communication (tg chat)



Introduction. Course objectives


- Learn Java from basics to advanced technology
- In this course, you will acquire programming skills at a sufficient level to work in IT
- After this course, you will be able to stay awake for two nights in a row and feel ~~great~~



Introduction. Course objectives

After this course, you should be able to do the following:

- Create simple and complex Java-applications
- Learn to apply programming paradigms such as inheritance, encapsulation, and polymorphism. This skill is useful in programming in any language
- Learn to compile, build and run Java applications of any complexity
- ...
- stay awake for two nights in a row and feel great




Introduction. Prerequisites

To successfully complete this course, you must know:


- basics of programming and informatics
- about two hours of time each day for this course
- how to stay awake **one** night and feel great




Introduction. Grades



Introduction. Materials and news





se.ifmo.ru/courses/programming




tg channel

Introduction. Lectures & guides (partly)



* Если сможешь




Introduction. Course parts

- How many labs
- How many tests
- Lectures
- Exams



Introduction. Tools

- Text editor (SublimeText, Notepad++)
- JDK
- IDE (intelliJ IDEA, Eclipse, NetBeans)
- CMD/Terminal (Putty, WinSCP, shell, helios)

Why Java?



Introduction. Why Java?



| | Aug 2022 | Aug 2021 | Change | Programming Language | Ratings | Change |
|----|----------|----------|--------|----------------------|---------|--------|
| 1 | 2 | | ▲ | Python | 15.42% | +3.56% |
| 2 | 1 | | ▼ | C | 14.59% | +2.03% |
| 3 | 3 | | | Java | 12.40% | +1.96% |
| 4 | 4 | | | C++ | 10.17% | +2.81% |
| 5 | 5 | | | C# | 5.59% | +0.45% |
| 6 | | | | Visual Basic | 4.99% | +0.33% |
| 7 | | | | JavaScript | 2.33% | -0.61% |
| 9 | | | ▲ | Assembly language | 2.17% | +0.14% |
| 10 | | | ▲ | SQL | 1.70% | +0.23% |
| 8 | | | ▼ | PHP | 1.39% | -0.80% |


| Rank | Language | Type | Score |
|------|-------------|------|-------|
| 1 | Python▼ | | 100.0 |
| 2 | Java▼ | | 95.3 |
| 3 | C▼ | | 94.6 |
| 4 | C++▼ | | 87.0 |
| 5 | JavaScript▼ | | 79.5 |
| 6 | R▼ | | 78.6 |
| 7 | Arduino▼ | | 73.2 |
| 8 | Go▼ | | 73.1 |
| 9 | Swift▼ | | 70.5 |
| 10 | Matlab▼ | | 68.4 |

Introduction. Why Java?

- high threshold for entry into IT (low competition)
- Java is a very large and complex product. Knowing Java is easy to master other areas
- cross-platform



Introduction. Cross-platform



Introduction. Cross-platform


```
public class Object
    public Object() {}

    ...
}
```



```
Compiled from "Object.java"
public class java.lang.Object
{
    public java.lang.Object();
        Code:
            0: return
    public boolean
equals(java.lang.Object);
        Code:
            0: aload_0
            1: aload_1
            2: if_acmpne      9
            5: iconst_1
            6: goto           10
            9: iconst_0
           10: ireturn
    ...
}
```

Introduction. Cross-platform



НИЧОСИ



Java

Java. Comments

Однострочные комментарии

// комментарии

Многострочные комментарии

/
комментарии
/


Специальные комментарии (javadoc)

*/**
*
* @author James Gosling
/

Java. First application

Main.java

```
1. public class Main {  
2.  
3.     public static void main(String[] args) {  
4.  
5.         System.out.println("Внимание!");  
6.  
7.     }  
8.  
9. }
```



Java. Simple math-application

```
1.  public class SimpleProgram {  
2.  
3.      public static void main(String[] args) {  
4.  
5.          var x = 5.0D;  
6.  
7.          var result = Math.pow(x, 2.5);  
8.  
9.          System.out.println(result);  
10.  
11.      }  
12.  
13. }
```

Java. Program is written. What's next?

JDK

- compiler
- debugger
- byte-code tools
- JVM
- standard library

Java. Program is written. What's next?

1. Compilation

```
javac    Main.java
```

```
javac    -d    target    Main.java
```

```
javac    --help
```

2. Packaging to jar

```
jar      -cfm    app.jar    MANIFEST.mf    *.class
```



3. Run

```
java     -jar    app.jar
```

```
java     Main
```

4. Debugging

Java. Variables and constants




Java. Variables and constants

```
int x;
```

```
int y = 5;
```

```
data_type variable_name [ = default_value ] ;
```




Java. Variables and constants

```
final double E = 5.0;
```

```
final double R;  
// ...  
R = 5.0;
```

what is it for?

```
int total = 8 * 5 * 4 * 12;
```



Java. Variables and constants

what is it for?

```
int total = 8 * 5 * 4 * 12; // BAD
```

```
final int HOURS = 8, DAYS = 5, WEEKS = 4, MONTHS = 12;  
// ...  
int total = HOURS * DAYS * WEEKS * MONTHS; // GOOD
```



Java. Data types

Целочисленные

Вещественные

Логические

Объекты

byte

double

boolean

short

float

char


int

long


Java. Data types

| Data type | Size (bit) | Values |
|----------------|----------------|---|
| byte | 8 | ○T -128 до 127 |
| short | 16 | ○T -32768 до 32767 |
| char | 16 | ○T 0 до 65535 |
| int | 32 | ○T -2147483648 до 2147483647 |
| long | 64 | ○T -9223372036854775808 до 9223372036854775807 |
| float | 32 | ○T -1.4e-45f до 3.4e+38f |
| double | 64 | ○T -4.9e-324 до 1.7e+308 |
| boolean | 1 or 32 | true or false |

Java. Convert data types



Java. Casting data types



```
double e = 2.7;
```

```
int notE = (int) e;    // notE = 2
```

```
int roundE = (int) Math.round(e);    // roundE = 3
```

Java. Operators

Unary

-
--
++
~
!
[]

Binary

- +

/ *

| ||

& &&

== !=

```
int x = -y;
```

```
// унарный "минус"
```

```
int r = x - y;
```

```
// бинарный "минус"
```

Java. Operators

| № | Operator |
|----|-------------------------------------|
| 1 | [] . () |
| 2 | ! ~ ++ -- + - (cast) new |
| 3 | * / % |
| 4 | + - (binary) |
| 5 | >> << >>> |
| 6 | < <= > >= instanceof |
| 7 | == != |
| 8 | & |
| 9 | ^ |
| 10 | |
| 11 | && |
| 12 | |
| 13 | ?: |
| 14 | = += -= *= /= %= = ^= <<= >>= >>>= |

Java. Math functions

| Функция | Конструкция |
|--------------------------------------|-----------------------------------|
| Абсолютное значение x | <code>Math.abs (x);</code> |
| Косинус x | <code>Math.cos (x);</code> |
| Синус x | <code>Math.sin (x);</code> |
| Экспонента | <code>Math.exp (x);</code> |
| Квадратный корень x | <code>Math.sqrt (x);</code> |
| Корень суммы квадратов (гипотенуза) | <code>Math.hypot (x, y);</code> |
| Натуральный логарифм | <code>Math.log (x);</code> |
| Округление до ближайшего | <code>Math.round (x);</code> |
| Возведение ' x ' в степень ' y ' | <code>Math.pow(x, y);</code> |

<https://docs.oracle.com/en/java/javase/17/docs/api/java.base/java/lang/Math.html>

Java. Math constants

- `Math.PI` `// 3.14159265358979323846`
- `Math.E` `// 2.7182818284590452354`

```
double res1 = 3 * Math.PI / 2;
```

```
double res2 = Math.log(5) * Math.E;
```

Java. Just in time test

```
1. public class PracticValiables {  
2.  
3.     public static void main(String[] args) {  
4.  
5.         byte x = 127;  
6.  
7.         x++;  
8.  
9.         System.out.println(x) ;  
10.  
11.     }  
12. }
```

128

1

-1

127

Java. Strings

```
String name = "Alis";
```

```
String lastName = new String("Parker");
```

```
String a = "Java\u2122";           // Java™  
String b = "";                   // пустая строка
```

<https://docs.oracle.com/en/java/javase/17/docs/api/java.base/java/lang/String.html>


Java. Formatting output

```
double x = 5.683;
```

```
double y = Math.pow(x, 2.5);
```

```
System.out.printf("%.2f ^ 2.5 = %.3f", x, y);
```

Output: 5,68 ^ 2.5 = 76,890



Java. Formatting output

```
printf(String format, Object... args)
```

```
printf("%.4f", Object... args)
```

What is "format"?

```
%[argument_index$][flags][width][.precision]conversion
```

Эльфийско-русский словарь

%[argument_index\$][flags][width][.precision]conversion

argument_index\$ — целое десятичное число, указывающее позицию аргумента в списке аргументов

flags — специальные символы для форматирования. Например, флаг "+" означает, что числовое значение должно включать знак +, флаг "-" означает выравнивание результата по левому краю, флаг «,» устанавливает разделитель тысяч у целых чисел.

[width] — положительное целое десятичное число, которое определяет минимальное количество символов, которые будут выведены

[.precision] — неотрицательное целое десятичное число с точкой перед ним. Обычно используется для ограничения количества символов.

conversion — это символ, указывающий, как аргумент должен быть отформатирован. Например **d** для целых чисел, **s** для строк, **f** для чисел с плавающей точкой.

* copy-paste from Java documentation

Java. Summary about you next steps

- You will do the lab work at home
 - Write code
 - Copy it to server (helios.cs.ifmo.ru)
 - Compile and run it
- Your teacher may give you additional practice tasks
- Examination of lab work
 - Be ready to hear the question, made up from unfamiliar words
 - Try to find answer and repeat discuss with teacher

