

Ex No: 2c

IMPLEMENTATION OF BACKWARD CHAINING

Aim:

To implement backward chaining.

Procedure:

Program:

Facts: The knowledge base containing information about facts

facts = {

 'a': True,

 'b': True,

 'c': False

}

Rules: List of rules where each rule is a tuple (conclusion, conditions)

rules = [

 ('d', ['a', 'b']), # d can be concluded if a and b are true

 ('e', ['b', 'c']), # e can be concluded if b and c are true

 ('f', ['d', 'e']) # f can be concluded if d and e are true

]

Backward Chaining Function

def backward_chaining(goal, facts, rules):

 # Check if the goal is already a fact

 if goal in facts:

 return facts[goal]

```

    # Check if the goal can be concluded from any rule
    for rule in rules:
        head, body = rule
        if head == goal:
            # Check if all the conditions in the body of the rule are true
            if all(backward_chaining(fact, facts, rules) for fact in body):
                return True

    # If the goal cannot be proved
    return False

# Example Usage:
goal = 'f'

if backward_chaining(goal, facts, rules):
    print(f"The goal '{goal}' can be achieved.")
else:
    print(f"The goal '{goal}' cannot be achieved.")

```

Output:

Expected Output for the Goal 'f':

The goal 'f' cannot be achieved.

Expected Output for the Goal 'd':

The goal 'd' can be achieved.

```
Expected Output for the Goal 'f':  
The goal 'f' cannot be achieved.
```

```
Expected Output for the Goal 'd':  
The goal 'd' can be achieved.
```

```
...Program finished with exit code 0  
Press ENTER to exit console.□
```