

et
Win-1
192.50.20.1

QEMU (Win-1)

C:\WINDOWS\system32\cmd.exe

Microsoft Windows XP [Version 5.1.2600]
<C> Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix	:	:
IP Address	:	192.50.20.100
Subnet Mask	:	255.255.255.0
Default Gateway	:	192.50.20.1

C:\Documents and Settings\user>ping 223.0.50.10

Pinging 223.0.50.10 with 32 bytes of data:

Reply from 12.0.0.2: Destination host unreachable.
Reply from 12.0.0.2: Destination host unreachable.
Reply from 12.0.0.2: Destination host unreachable.
Reply from 12.0.0.2: Destination host unreachable.

Ping statistics for 223.0.50.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\Documents and Settings\user>ping 223.0.50.10

Pinging 223.0.50.10 with 32 bytes of data:

Reply from 223.0.50.10: bytes=32 time=4ms TTL=125
Reply from 223.0.50.10: bytes=32 time=1ms TTL=125
Reply from 223.0.50.10: bytes=32 time=2ms TTL=125
Reply from 223.0.50.10: bytes=32 time=2ms TTL=125

Ping statistics for 223.0.50.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 4ms, Average = 2ms

C:\Documents and Settings\user>_



C:\WINDOWS\system32\cmd.exe

C:\Documents and Settings\user>ping 172.36.0.10

Pinging 172.36.0.10 with 32 bytes of data:

Reply from 172.36.0.10: bytes=32 time=3ms TTL=124

Reply from 172.36.0.10: bytes=32 time=2ms TTL=124

Reply from 172.36.0.10: bytes=32 time=2ms TTL=124

Reply from 172.36.0.10: bytes=32 time=2ms TTL=124

Ping statistics for 172.36.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 2ms, Maximum = 3ms, Average = 2ms

C:\Documents and Settings\user>

```
C:\Documents and Settings\user>ping 192.50.20.100
```

```
Pinging 192.50.20.100 with 32 bytes of data:
```

```
Reply from 192.50.20.100: bytes=32 time=2ms TTL=125
```

```
Reply from 192.50.20.100: bytes=32 time=1ms TTL=125
```

```
Reply from 192.50.20.100: bytes=32 time=1ms TTL=125
```

```
Reply from 192.50.20.100: bytes=32 time=1ms TTL=125
```

```
Ping statistics for 192.50.20.100:
```

```
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
```

```
Approximate round trip times in milli-seconds:
```

```
    Minimum = 1ms, Maximum = 2ms, Average = 1ms
```

Pinging 172.36.0.10 with 32 bytes of data:

Reply from 172.36.0.10: bytes=32 time=1ms TTL=124

Reply from 172.36.0.10: bytes=32 time=2ms TTL=124

Reply from 172.36.0.10: bytes=32 time=2ms TTL=124

Reply from 172.36.0.10: bytes=32 time=1ms TTL=124

Ping statistics for 172.36.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>

C:\WINDOWS\system32\cmd.exe

```
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>ping 192.50.20.100
```

Pinging 192.50.20.100 with 32 bytes of data:

```
Reply from 192.50.20.100: bytes=32 time=3ms TTL=124
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124
Reply from 192.50.20.100: bytes=32 time=3ms TTL=124
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124
```

Ping statistics for 192.50.20.100:

```
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 3ms, Average = 2ms
```

```
C:\Documents and Settings\user>
```



C:\WINDOWS\system32\cmd.exe

```
Reply from 192.50.20.100: bytes=32 time=3ms TTL=124
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124
Reply from 192.50.20.100: bytes=32 time=3ms TTL=124
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124
```

Ping statistics for 192.50.20.100:

```
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 3ms, Average = 2ms
```

C:\Documents and Settings\user>ping 223.0.50.10

Pinging 223.0.50.10 with 32 bytes of data:

```
Reply from 223.0.50.10: bytes=32 time=3ms TTL=124
Reply from 223.0.50.10: bytes=32 time=2ms TTL=124
Reply from 223.0.50.10: bytes=32 time=3ms TTL=124
Reply from 223.0.50.10: bytes=32 time=2ms TTL=124
```

Ping statistics for 223.0.50.10:

```
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 3ms, Average = 2ms
```

C:\Documents and Settings\user>

!!!!!! Neenga kudutha fees !!!!!

R1

ia - IS-IS inter area, * - candidate default, U - per-user static route
 o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
 a - application route
 + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

12.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 12.0.0.0/8 is directly connected, Ethernet0/1

L 12.0.0.1/32 is directly connected, Ethernet0/1

S 23.0.0.0/8 [1/0] via 12.0.0.2

S 24.0.0.0/8 [1/0] via 12.0.0.2

S 26.0.0.0/8 [1/0] via 12.0.0.2

S 32.0.0.0/8 [1/0] via 12.0.0.2

S 45.0.0.0/8 [1/0] via 12.0.0.2

172.36.0.0/24 is subnetted, 1 subnets

S 172.36.0.0 [1/0] via 12.0.0.2

192.50.20.0/24 is variably subnetted, 2 subnets, 2 masks

C 192.50.20.0/24 is directly connected, Ethernet0/0

L 192.50.20.1/32 is directly connected, Ethernet0/0

S 223.0.50.0/24 [1/0] via 12.0.0.2

R1#

R1#

R1#

23.1

e0/2

e0/3

24.1



R6

e0/0

.1



R2

Gateway of last resort is not set

```
12.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    12.0.0.0/8 is directly connected, Ethernet0/0
L    12.0.0.2/32 is directly connected, Ethernet0/0
23.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    23.0.0.0/8 is directly connected, Ethernet0/2
L    23.0.0.1/32 is directly connected, Ethernet0/2
24.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    24.0.0.0/8 is directly connected, Ethernet0/3
L    24.0.0.1/32 is directly connected, Ethernet0/3
26.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    26.0.0.0/8 is directly connected, Ethernet0/1
L    26.0.0.1/32 is directly connected, Ethernet0/1
S    32.0.0.0/8 [1/0] via 23.0.0.2
S    45.0.0.0/8 [1/0] via 23.0.0.2
122.0.0.0/24 is subnetted, 1 subnets
S    122.0.50.0 [1/0] via 26.0.0.2
S    172.36.0.0/16 [1/0] via 23.0.0.2
S    192.50.20.0/24 [1/0] via 12.0.0.1
S    223.0.50.0/24 [1/0] via 26.0.0.2
Router#
Router#
Router#
```

12.2

e0/0

R2

26.1

e0/1

26.2

e0/1

R6

e0/0



R3



i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

```
S    12.0.0.0/8 [1/0] via 23.0.0.1
    23.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    23.0.0.0/8 is directly connected, Ethernet0/0
L    23.0.0.2/32 is directly connected, Ethernet0/0
S    24.0.0.0/8 [1/0] via 23.0.0.1
S    26.0.0.0/8 [1/0] via 23.0.0.1
    32.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    32.0.0.0/8 is directly connected, Ethernet0/1
L    32.0.0.1/32 is directly connected, Ethernet0/1
S    45.0.0.0/8 [1/0] via 32.0.0.2
S    172.36.0.0/16 [1/0] via 32.0.0.2
S    192.50.20.0/24 [1/0] via 23.0.0.1
S    223.0.50.0/24 [1/0] via 23.0.0.1
```

Router#

Router#

Router#

R4

i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

```
S    12.0.0.0/8 [1/0] via 24.0.0.1
S    23.0.0.0/8 [1/0] via 24.0.0.1
    24.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      24.0.0.0/8 is directly connected, Ethernet0/0
L      24.0.0.2/32 is directly connected, Ethernet0/0
S    26.0.0.0/8 [1/0] via 24.0.0.1
S    32.0.0.0/8 [1/0] via 45.0.0.2
    45.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      45.0.0.0/8 is directly connected, Ethernet0/1
L      45.0.0.1/32 is directly connected, Ethernet0/1
S    172.36.0.0/16 [1/0] via 45.0.0.2
S    192.50.20.0/24 [1/0] via 24.0.0.1
S    223.0.50.0/24 [1/0] via 24.0.0.1
```

Router#

Router#

Router#

```
Router>
Router>
Router>en
Router#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR
```

Gateway of last resort is not set

```
S    12.0.0.0/8 [1/0] via 26.0.0.1
S    23.0.0.0/8 [1/0] via 26.0.0.1
S    24.0.0.0/8 [1/0] via 26.0.0.1
    26.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C        26.0.0.0/8 is directly connected, Ethernet0/1
L        26.0.0.2/32 is directly connected, Ethernet0/1
S    32.0.0.0/8 [1/0] via 26.0.0.1
S    45.0.0.0/8 [1/0] via 26.0.0.1
S    172.36.0.0/16 [1/0] via 26.0.0.1
S    192.50.20.0/24 [1/0] via 26.0.0.1
    223.0.50.0/24 is variably subnetted, 2 subnets, 2 masks
C        223.0.50.0/24 is directly connected, Ethernet0/0
L        223.0.50.1/32 is directly connected, Ethernet0/0
```

```
Router#
Router#
Router#
```