

+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

```
S    10.0.0.0/8 [1/0] via 30.0.0.1
      30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      30.0.0.0/8 is directly connected, Ethernet0/1
L      30.0.0.2/32 is directly connected, Ethernet0/1
      40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      40.0.0.0/8 is directly connected, Ethernet0/0
L      40.0.0.1/32 is directly connected, Ethernet0/0
```

R3#conf t

Enter configuration commands, one per line. End with CNTL/Z.

R3(config)#ip route 10.0.0.0 255.0.0.0 30.0.0.1

% Incomplete command.

R3(config)#ip route 20.0.0.0 255.0.0.0 30.0.0.1

R3(config)#exit

R3#

\*Jul 15 09:03:46.499: %SYS-5-CONFIG\_I: Configured from console by console

R3#show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2  
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2  
ia - IS-IS inter area, \* - candidate default, U - per-user static route  
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP  
a - application route  
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

```
S    10.0.0.0/8 [1/0] via 30.0.0.1
S    20.0.0.0/8 [1/0] via 30.0.0.1
      30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      30.0.0.0/8 is directly connected, Ethernet0/1
L      30.0.0.2/32 is directly connected, Ethernet0/1
      40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      40.0.0.0/8 is directly connected, Ethernet0/0
L      40.0.0.1/32 is directly connected, Ethernet0/0
```

R3#

```
S      10.0.0.0/8 [1/0] via 30.0.0.0
      30.0.0.0/8 is variably subne
C      30.0.0.0/8 is directly co
L      30.0.0.2/32 is directly c
      40.0.0.0/8 is variably subne
C      40.0.0.0/8 is directly co
L      40.0.0.1/32 is directly c
R3#conf t
Enter configuration commands, one
R3(config)#ip route 10.0.0.0 255.0
% Incomplete command.

R3(config)#ip route 20.0.0.0 255.0
R3(config)#exit
R3#
*Jul 15 09:03:46.499: %SYS-5-CONF
R3#show ip route
Codes: L - local, C - connected, S
      D - EIGRP, EX - EIGRP exte
      N1 - OSPF NSSA external typ
      E1 - OSPF external type 1,
      i - IS-IS, su - IS-IS summa
```

```
R2#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R2(config)#ip route 10.0.0.0 255.0.0.0 20.0.0.1
R2(config)#ip route 40.0.0.0 255.0.0.0 30.0.0.2
R2(config)#exir
      ^
% Invalid input detected at '^' marker.

R2(config)#exit
R2#
*Jul 15 08:43:09.552: %SYS-5-CONFIG_I: Configured from console by console
R2#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

S    10.0.0.0/8 [1/0] via 20.0.0.1
    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    20.0.0.0/8 is directly connected, Ethernet0/0
L    20.0.0.2/32 is directly connected, Ethernet0/0
    30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    30.0.0.0/8 is directly connected, Ethernet0/1
L    30.0.0.1/32 is directly connected, Ethernet0/1
S    40.0.0.0/8 [1/0] via 30.0.0.2
```

```

R1(config)#ip route 30.0.0.0 255.0.0.0 20.0.0.2
R1(config)#ip route 40.0.0.0 255.0.0.0 20.0.0.2
R1(config)#exit
R1#s
*Jul 15 08:35:07.664: %SYS-5-CONFIG_I: Configured from console by console
R1#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       10.0.0.0/8 is directly connected, Ethernet0/0
L       10.0.0.1/32 is directly connected, Ethernet0/0
    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       20.0.0.0/8 is directly connected, Ethernet0/1
L       20.0.0.1/32 is directly connected, Ethernet0/1
S       30.0.0.0/8 [1/0] via 20.0.0.2
S       40.0.0.0/8 [1/0] via 20.0.0.2
R1#

```



```
Pinging 40.0.0.10 with 32 bytes of data:
```

```
Ping statistics for 40.0.0.10:
```

```
C:\Documents and Settings\user>
```

Internet Explorer



Cisco ASDM-1...





My Documents

My Computer

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-I...

Old Java ASDM

PuTTY

C:\WINDOWS\system32\cmd.exe

Microsoft Windows XP [Version 5.1.2600]  
<C> Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time=1ms TTL=125  
Reply from 10.0.0.10: bytes=32 time=1ms TTL=125  
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125  
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125

Ping statistics for 10.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),  
Approximate round trip times in milli-seconds:  
Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>\_