







# Technical Datasheet QP-3000\_V

 QUICKLINE® 1K Primer



<b>Description</b>	<b>Quickline 1K Primer, QP-3000</b> , is a 1K Aerosol Primer is designed and formulated for “Rub throughs” to bare metal and small spot repairs. It can be overcoated directly with <i>Quickline</i> topcoat systems.	
<b>Products</b>	QP-3000 <i>Quickline</i> 1K Primer	
<b>Mixing</b> 	Supplied Ready for use.  Shake aerosol for at least 1 minute before use.	
<b>Application</b> 	Spraying Distance: 15 – 25cm	
<b>Coats</b> 	2 coats (thickness – approx 25 microns)	
<b>Flash Time</b> 	3 – 5 minutes between coats at 20°C	
<b>Drying</b> 	Air Dry at 20°C:	Recoatable: 10 -15 min.
<b>Recoat</b> 	<i>Quickline</i> 1K Primer can be directly recoated with <i>Quickline</i> 2K Primers or <i>Quickline</i> topcoats.	
<b>VOC Information</b>  The EU limit value for this product (product category: IIB.e) in ready to use form is max. 840g/litre of VOC. The VOC content of this product in ready to use form is max. 840g/litre. Depending on the chosen mode of use, the actual ready to use VOC of this product may be lower than that specified by the EU Directive code.		

These products are for professional painting only, and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

*Quickline* is a registered trademark of PPG Industries Ohio, Inc.  
© 2018 PPG Industries, all rights reserved.

Aug 2018

PPG Industries (UK) Ltd  
Auto Refinish  
Customer Service & Sales Group,  
Needham Road  
Stowmarket, Suffolk.  
IP14 2AD  
Tel: 01449 771775

**QUICKLINE®**