

FH AACHEN  
UNIVERSITY OF APPLIED SCIENCES

Search here...

Add Filter

SS 2020

MM

MUSTER MANN

Ihre Übersicht

Einstellungen

SPACES

Studiengänge

Vorlesungsverzeichnis

Einrichtungen

Veranstaltungen

Prüfungen

Study

Kurse

Abgaben

Web Drive

Bookmarks / Notizen

Forum

Kalender

Stundenplan

Kalender-Verwaltung

E-mail

Posteingang135

Gesendete Elemente

Entwürfe25

ABMELDEN

Study

Kurse

UCPM

Vorlesung

Vorlesungsblock 1 - Usability und Usability Engineering

Anhang 1 - FOLIEN UCPM Usability1.pdf

PREVIEW

Anhang 1 - FOLIEN UCPM Usability1.pdf

1 von 14

Automatischer Zoom

# Trace-based Just-in-Time Type Specialization for Dynamic Languages

Andreas Gal<sup>\*+</sup>, Brendan Eich<sup>\*</sup>, Mike Shaver<sup>\*</sup>, David Anderson<sup>\*</sup>, David Mandelin<sup>\*</sup>, Mohammad R. Haghighat<sup>§</sup>, Blake Kaplan<sup>\*</sup>, Graydon Hoare<sup>\*</sup>, Boris Zbarsky<sup>\*</sup>, Jason Orendorff<sup>\*</sup>, Jesse Ruderman<sup>\*</sup>, Edwin Smith<sup>#</sup>, Rick Reitmaier<sup>#</sup>, Michael Bebenita<sup>+</sup>, Mason Chang<sup>+ #</sup>, Michael Franz<sup>+</sup>

{gal,brendan,shaver,danderson,dmandelin,mrbkap,graydon,bz,jorendorff,jruderman}@mozilla.com

{edwsmith,rreitmai}@adobe.com

{mohammad.r.haghighat}@intel.com

{mbebenit,changm,franz}@uci.edu

## Abstract

Dynamic languages such as JavaScript are more difficult to compile than statically typed ones. Since no concrete type information is available, traditional compilers need to emit generic code that can handle all possible type combinations at runtime. We present an alternative compilation technique for dynamically-typed languages that identifies frequently executed loop traces at run-time and then generates machine code on the fly that is specialized for the actual dynamic types occurring on each path through the loop. Our method provides cheap inter-procedural type specialization, and an elegant and efficient way of incrementally compiling lazily discovered alternative paths through nested loops. We have implemented a dynamic compiler for JavaScript based on our technique and we have measured speedups of 10x and more for certain benchmark programs.

**Categories and Subject Descriptors** D.3.4 [Programming Languages]: Processors — *Incremental compilers, code generation.*

**General Terms** Design, Experimentation, Measurement, Performance.

**Keywords** JavaScript, just-in-time compilation, trace trees.

## 1. Introduction

Dynamic languages such as JavaScript, Python, and Ruby, are popular since they are expressive, accessible to non-experts, and make deployment as easy as distributing a source file. They are used for small scripts as well as for complex applications. JavaScript, for example, is the de facto standard for client-side web programming

and is used for the application logic of browser-based productivity applications such as Google Mail, Google Docs and Zimbra Collaboration Suite. In this domain, in order to provide a fluid user experience and enable a new generation of applications, virtual machines must provide a low startup time and high performance.

Compilers for statically typed languages rely on type information to generate efficient machine code. In a dynamically typed programming language such as JavaScript, the types of expressions may vary at runtime. This means that the compiler can no longer easily transform operations into machine instructions that operate on one specific type. Without exact type information, the compiler must emit slower generalized machine code that can deal with all potential type combinations. While compile-time static type inference might be able to gather type information to generate optimized machine code, traditional static analysis is very expensive and hence not well suited for the highly interactive environment of a web browser.

We present a trace-based compilation technique for dynamic languages that reconciles speed of compilation with excellent performance of the generated machine code. Our system uses a mixed-mode execution approach: the system starts running JavaScript in a fast-starting bytecode interpreter. As the program runs, the system identifies *hot* (frequently executed) bytecode sequences, records them, and compiles them to fast native code. We call such a sequence of instructions a *trace*.

Unlike method-based dynamic compilers, our dynamic compiler operates at the granularity of individual loops. This design choice is based on the expectation that programs spend most of their time in hot loops. Even in dynamically typed languages, we expect hot loops to be mostly *type-stable*, meaning that the types of values are invariant. (12) For example, we would expect loop counters that start as integers to remain integers for all iterations. When both of these expectations hold, a trace-based compiler can cover the program execution with a small number of type-specialized, efficiently compiled traces.

Each compiled trace covers one path through the program with one mapping of values to types. When the VM executes a compiled trace, it cannot guarantee that the same path will be followed or that the same types will occur in subsequent loop iterations.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

PLDI'09, June 15–20, 2009, Dublin, Ireland.

Copyright © 2009 ACM 978-1-60558-392-1/09/06...\$5.00

Add Comment

Ask Creator

Comments (3)

MM

Muster Mann

- Student

Remove

Reply

MM

Muster Mann

- Student

@John Doe

Remove

Reply

JD

John Doe

- Creator

Remove

Reply