

BANK DC: ADVANCED REFERENCE

VLAN Inventory & Addressing

VLAN	Name	Subnet	Gateway (VIP)
10	MANAGEMENT	10.0.10.0/24	10.0.10.254
20	SERVERS	10.0.20.0/24	10.0.20.254
30	DATABASE	10.0.30.0/24	10.0.30.254
50	SOC	10.0.50.0/24	10.0.50.254
80	PEERING	10.0.80.0/24	10.0.80.254

Verification Command Cheat Sheet

- `show ip bgp summary` - Verify ISP peering status.
- `show standby brief` - Confirm which Core switch is handling traffic.
- `show ip nat translations` - Monitor active traffic through the edge.
- `show access-list` - Check for firewall drops/hits.

Packet Flow Scenario: Web Access

1. User requests 203.0.113.150.
2. ISP Router forwards to CORE-R1 via BGP.
3. CORE-R1 performs Static NAT to 10.0.20.100.
4. ASA Firewall checks ACL (Permit Port 80).
5. Packet reaches Load Balancer in VLAN 20.

Common Failure Points

Issue	Check
No Inter-VLAN routing	Check if 'ip routing' is enabled on L3 switches.
HSRP "Speak" state	Verify VLAN propagation on all trunks.
BGP "Idle"	Check neighbor IP and AS number mismatch.