

BANK DC: CONFIG WALKTHROUGH

Phase 1: Trunking & VLANs

Initialize trunks on all inter-switch links to allow tagged traffic.

```
interface range g0/1 - 2
  switchport mode trunk
  switchport trunk allowed vlan 10,20,30,40,50,60,70,80,99
  switchport nonegotiate
```

Phase 2: Core Routing & HSRP

Enable Layer 3 routing and configure the virtual gateways.

```
! On CORE-SW1
interface Vlan20
  ip address 10.0.20.1 255.255.255.0
  standby 20 ip 10.0.20.254
  standby 20 priority 110
  standby 20 preempt
  standby 20 authentication BANKHSRP
```

Phase 3: OSPF Implementation

```
router ospf 1
  router-id 3.3.3.1
  network 10.0.0.0 0.255.255.255 area 0
  area 0 authentication message-digest
  interface Vlan20
    ip ospf message-digest-key 1 md5 BANKOSPF2026
```

Phase 4: ASA Firewall Logic

Set security levels and NAT for the DMZ.

```
interface GigabitEthernet1/1
  nameif outside
  security-level 0
  ip address 203.0.113.2 255.255.255.248
!
object network SERVER_LB
  host 10.0.20.100
  nat (inside,outside) static 203.0.113.150
```