



3-PM-IO module



3-PM-IO-INV module



External 3-PM-IO and 3-PM-IO-INV module

To avoid hazards from mains power outages, the functionality of the light distributors for the general lighting must be continuously monitored in order to turn on safety lighting in the event of a disruption. Consequently, the 3-PM-IO and 3-PM-IO-INV modules are an important element of the safety system.

- Test button for mains emergency light fault, so there is no need to interrupt mains voltage and, therefore, no disruptions to operations in progress
- 3-PM-IO module: Eight measurement inputs for monitoring up to three phases and up to five * light switches
- 3-PM-IO-INV module: Eight inverted measurement inputs for monitoring up to three phases and up to five* light switches
- Programmable allocation of 3-PM-IO and 3-PM-IO-INV modules
- Meets the requirements of future standards. Reduces the risk of cost incurred from retrofitting
- No E30 wiring by virtue of short circuit/interruption-tolerant communication. This results in significantly simpler installation and cost savings.
- Does not require that mains power to general lighting be shut off during weekly function testing by virtue of simple manual testing of the circuit monitoring function via the test button. This avoids the disruption of operations in progress and the resulting costs thereof
- Automatic record keeping in inspection log. The documentation requirements for safety equipment are thus satisfied
- Meets all EMC requirements for industrial and commercial use
- DEKRA system certification documents product quality and compliance with standards for the entire system

* If the phase monitoring function is not required, all eight measuring inputs can be used for the light switch query

	3-PM-IO	3-PM-IO-INV
Rated voltage of device	24V DC (min. 19V, max. 30V)	
Current consumption (all 8 channels connected)	20 mA ± 5 mA	
Degree of protection	IP20	
Protection class	I	
Ambient temperature range	-10° – +40°C.	
Input channels 8	8 (potential separated $U_N = 230V$)	8 (potential separated $U_N = 230V$)
3-PM (channel 1–8)	3-PM (chan. 1–8) > 195V-> ON	3-PM (chan. 1–8) < 195V-> OFF
3-PH (channel 1–5)	< 138V-> OFF	> 138V-> ON
Data bus/address range	RS 485/1-25	
Weight	0.2 kg	
Dimensions (L x W x H) mm	105 x 85 x 60	
Assembly	DIN rail	
Terminals	2.5 mm ² rigid and flexible	

Order details

Model	Included with delivery	Order no.
3-PM-IO module with test button	Module for DIN support rail installation	40071361670
3-PM-IO-INV module with test button	Module for DIN support rail installation with inverted input logic	40071361680
DIN support rails	4 DIN support rails for mounting external modules in the switch cabinet including mounting material	40071347125