HallSync

Complete Database Implementation Guide

Lecture Hall Booking Management System

Faculty of Science prototype | University of Kelaniya, Sri Lanka

MySQL 8.0.46 | Database implementation v2 | 11 November 2026

Tables	Columns	Foreign keys
11	61	14

A study guide for understanding the database, running the complete setup, explaining the rules in a presentation, and connecting an object-oriented application later.

Your existing department record is preserved. The main continuation script adds the remaining database objects without dropping the database.

Validation: 100 checks passed against MySQL 8.0.46. This includes independent-connection approval races, approval-versus-closure races, and a hall-lock waiting check.

The scripts are complete in the repository. They create the database objects on your laptop only when you execute them in Workbench.

1. Start here: the one-file continuation

You have already created hallsync_db, the DEPARTMENT table and the Industrial Management row. Use database/complete_existing_database.sql to finish that database in one execution.

- Download the latest repository ZIP and extract it to a normal writable folder.

- Open your existing MySQL Workbench connection and open complete_existing_database.sql.

- Enable Stop Script Execution On Errors. Execute the complete file with no text selected.

- If an error appears, stop and send the error message. Do not drop the database or blindly rerun the file.

- Refresh SCHEMAS. The final verification grid should show the expected object counts below.

Object	Expected
Base tables	11
Columns in base tables	61
Primary keys	11
Foreign keys	14
Additional unique keys	7
CHECK constraints	28
Views	4
Procedures	25 (19 public + 6 internal)

The preflight requires exactly the department table from step 02. It refuses to continue over a partially completed or different schema. This is deliberate: CREATE TABLE IF NOT EXISTS would hide differences in an existing definition.

MySQL DDL can commit independently. A multi-statement installation is not one rollbackable transaction. Preserve the error output if installation stops partway through.

```
USE hallsync_db;
SHOW TABLES;
SELECT COUNT(*) AS TableCount FROM information_schema.tables
WHERE table_schema = DATABASE() AND table_type = 'BASE TABLE';
```

2. Files and execution order

File	Purpose and when to run
01_create_database.sql	Already completed. Creates the empty project database.
02_create_department.sql	Already completed. Creates the first table.
03_insert_sample_department.sql	Already completed. Repeating its INSERT creates another department row.
complete_existing_database.sql	Recommended now. Combines 04, 05, 06, 07, 10 and 08. Run once on your existing one-table database.
fresh_install.sql	Alternative for a new empty installation. Requires the hallsync_db name to be unused.
04_complete_schema.sql	Individual script: validates DEPARTMENT and adds the other 10 tables.
05_business_workflows.sql	Individual script: installs public procedures and internal helpers.
06_views_and_reports.sql	Individual script: creates four reporting views.
07_demo_data.sql	Individual script: synthetic catalogue and SQL demonstration accounts; keeps existing matching records.
08_verify_database.sql	Read-only structure and data-integrity checks; safe to run after setup.
09_workflow_example.sql	Optional changing-data example: creates and approves a future demo Event request.
10_application_role.sql	Creates a least-privilege MySQL role; does not create a login or password.
tests/run_checks.py	Developer validation. Creates isolated generated schemas, tests them, then removes only those schemas.

Choose the combined continuation OR the individual 04-10 setup sequence. Once the combined file succeeds, use 08 to inspect it. The fresh-install file is for a different starting condition.

Every setup/business connection uses Asia/Colombo civil time through the +05:30 offset. This works without loading named MySQL timezone tables. Application connections must follow the same convention.

3. The design: nine entities become eleven tables

Each strong entity becomes a table. Each 1:N relationship stores the parent identifier in a child foreign-key column. Two M:N relationships need junction tables, bringing the total from nine entities to eleven tables.

Table	Purpose
DEPARTMENT	Department catalogue shared by accounts, courses and groups.
BUILDING	Building codes and locations used to identify lecture halls.
FACILITY	Equipment types, such as Projector. Quantities belong to hall assignments.
USER_ACCOUNT	People, account activation, one effective role and password hashes.
COURSE_UNIT	Course catalogue and its owning department.
STUDENT_GROUP	Teaching groups by department and intake, not individual enrolment.
LECTURE_HALL	Physical hall identity, capacity and operational status.
BOOKING	One request, one responsible requester, one hall and at most one review decision.
HALL_BLOCK	Dated maintenance or other hall closures, including multi-day periods.
HALL_FACILITY	Hall-to-facility M:N assignment, with total and working quantities.
BOOKING_GROUP	Booking-to-student-group M:N assignment.

Key legend: PRI = primary key, UNI = unique key, FK = foreign key. Req. means NOT NULL.

A report is a query over existing data, so the design has no stored REPORT entity. The four views provide report datasets. SQL tables describe stored facts; OOP classes will also describe behaviour and do not have to map one-to-one to tables.

Names are not substituted for identifiers. For example, a booking stores RequesterID and HallID, while joins retrieve the current account and hall names.

4. Data dictionary: DEPARTMENT

Department catalogue shared by accounts, courses and groups.

Column	SQL type	Req.	Key	Meaning / reason
DepartmentID	int	Yes	PRI	Department identifier. Auto-generated in DEPARTMENT; a parent reference elsewhere. MySQL generates this primary-key value; gaps are allowed.
DepartmentName	varchar(100)	Yes	-	Required catalogue name. The CHECK rejects empty strings and ordinary-space-only names. Names are not a declared unique key.

5. Data dictionary: BUILDING

Building codes and locations used to identify lecture halls.

Column	SQL type	Req.	Key	Meaning / reason
BuildingID	int	Yes	PRI	Building identifier; halls reference the building that contains them. MySQL generates this primary-key value; gaps are allowed.
BuildingCode	varchar(20)	Yes	UNI	Stable unique code used for building lookup.
BuildingName	varchar(100)	Yes	-	Required readable building name.
LocationDescription	varchar(255)	No	-	Optional description of the building location.

6. Data dictionary: FACILITY

Equipment types, such as Projector. Quantities belong to hall assignments.

Column	SQL type	Req.	Key	Meaning / reason
FacilityID	int	Yes	PRI	Facility-type identifier. The same type can occur in several halls. MySQL generates this primary-key value; gaps are allowed.
FacilityName	varchar(100)	Yes	UNI	Unique type name, such as Projector.
Description	varchar(255)	No	-	Optional explanation of the facility type.

7. Data dictionary: USER_ACCOUNT

People, account activation, one effective role and password hashes.

Column	SQL type	Req.	Key	Meaning / reason
AccountID	int	Yes	PRI	Account identifier. Reused as requester, reviewer or block recorder through differently named FKs. MySQL generates this primary-key value; gaps are allowed.
DepartmentID	int	No	FK	Department identifier. Auto-generated in DEPARTMENT; a parent reference elsewhere.
FullName	varchar(150)	Yes	-	Required display name.
Email	varchar(254)	Yes	UNI	Unique account email; application validates email format.
Username	varchar(50)	Yes	UNI	Unique login identifier; the database default collation makes lookup case-insensitive.
PasswordHash	varchar(255)	Yes	-	Encoded salted password hash. ASCII binary collation preserves its case-sensitive representation.
Role	enum('Student', 'Lecturer', 'AdminStaff')	Yes	-	One effective role: Student, Lecturer or AdminStaff. Privileged roles are provisioned by an administrator. Default: Student.
IsActive	BOOLEAN / TINYINT(1)	Yes	-	BOOLEAN alias for TINYINT(1). A CHECK restricts values to 0 or 1. Default: 1.

PasswordHash stores no plaintext password. Hashing and password verification use a maintained Argon2id library in the application. The procedure checks the encoded prefix and length, not the original password or its strength.

8. Data dictionary: COURSE_UNIT

Course catalogue and its owning department.

Column	SQL type	Req.	Key	Meaning / reason
CourseID	int	Yes	PRI	Course identifier. Optional in a booking overall; mandatory for Lecture and Tutorial. MySQL generates this primary-key value; gaps are allowed.
DepartmentID	int	Yes	FK	Department identifier. Auto-generated in DEPARTMENT; a parent reference elsewhere.
CourseCode	varchar(20)	Yes	UNI	Unique catalogue code.
CourseTitle	varchar(150)	Yes	-	Required readable course title.

9. Data dictionary: STUDENT_GROUP

Teaching groups by department and intake, not individual enrolment.

Column	SQL type	Req.	Key	Meaning / reason
GroupID	int	Yes	PRI	Student-group identifier. MySQL generates this primary-key value; gaps are allowed.
DepartmentID	int	Yes	FK	Department identifier. Auto-generated in DEPARTMENT; a parent reference elsewhere.
GroupName	varchar(100)	Yes	-	Teaching-group label; its department/intake/name combination is unique.
IntakeYear	smallint unsigned	Yes	-	Unsigned small integer, checked between 1900 and 9999.
StudyYear	tinyint unsigned	Yes	-	Unsigned tiny integer, checked to be at least 1.

10. Data dictionary: LECTURE_HALL

Physical hall identity, capacity and operational status.

Column	SQL type	Req.	Key	Meaning / reason
HallID	int	Yes	PRI	Lecture-hall identifier. Every booking and hall block refers to one hall. MySQL generates this primary-key value; gaps are allowed.
BuildingID	int	Yes	FK	Building identifier; halls reference the building that contains them.
HallNo	varchar(20)	Yes	-	Room identifier, unique within its building rather than across all buildings.
Floor	varchar(10)	No	-	Optional text so values such as G or 1 can be represented.
Capacity	int	Yes	-	Positive integer capacity. Procedures compare attendance with this parent value.
OperationalStatus	enum('Active', 'Inactive')	Yes	-	Active or Inactive. Time availability is calculated from reservations and blocks. Default: Active.

The hall has no permanent Booked flag. One hall can be reserved for one period and free for another. OperationalStatus describes the physical hall, while availability is calculated for the requested interval.

11. Data dictionary: HALL_FACILITY

Hall-to-facility M:N assignment, with total and working quantities.

Column	SQL type	Req.	Key	Meaning / reason
HallID	int	Yes	PK part + FK	Lecture-hall identifier. Every booking and hall block refers to one hall.
FacilityID	int	Yes	PK part + FK	Facility-type identifier. The same type can occur in several halls.
Quantity	int	Yes	PK part + FK	Positive integer total of this facility type in this hall.
WorkingQuantity	int	Yes	PK part + FK	Integer between zero and Quantity inclusive; zero working units is valid.

The two key columns are unique together. Either individual value can repeat in other rows. This represents an M:N relationship without a comma-separated list.

12. Data dictionary: BOOKING

One request, one responsible requester, one hall and at most one review decision.

Column	SQL type	Req.	Key	Meaning / reason
BookingID	int	Yes	PRI	Unique identifier for one request, including requests retained after cancellation or rejection. MySQL generates this primary-key value; gaps are allowed.
RequesterID	int	Yes	FK	Responsible account. Supplied from the authenticated session; there is no separate booked-for lecturer.
HallID	int	Yes	FK	Lecture-hall identifier. Every booking and hall block refers to one hall.
CourseID	int	No	FK	Course identifier. Optional in a booking overall; mandatory for Lecture and Tutorial.
BookingDate	date	Yes	-	Session date, interpreted with StartTime and EndTime in Asia/Colombo.
StartTime	time	Yes	-	Same-day start clock time. Procedures require the combined start instant to be in the future.
EndTime	time	Yes	-	Same-day end clock time, strictly after StartTime and before 24:00.
Purpose	varchar(255)	Yes	-	Required reason, limited to 255 characters.
BookingType	enum('Lecture', 'Tutorial', 'Exam', 'Event')	Yes	-	Lecture, Tutorial, Exam or Event. Academic types impose extra course/group requirements.
ExpectedAttendance	int	Yes	-	Positive integer expected headcount. Individual student enrolments are outside v1.
BookingStatus	enum('Pending', 'Approved', 'Rejected', 'Cancelled', 'Completed')	Yes	-	Current lifecycle state: Pending, Approved, Rejected, Cancelled or Completed. Default: Pending.
RequestedAt	datetime	Yes	-	Local date/time when the request was recorded. Default: CURRENT_TIMESTAMP.
ReviewerID	int	No	FK	Optional administrator reference; different from RequesterID when a review exists.
Decision	enum('Approved', 'Rejected')	No	-	Approved or Rejected. Preserve an earlier approval after later cancellation.
ReviewedAt	datetime	No	-	Optional local review timestamp; cannot be before RequestedAt.
ReviewNote	varchar(500)	No	-	Optional review explanation, up to 500 characters.

A review is stored in this row because the agreed workflow allows at most one review decision. The reviewer ID, decision and review time are populated together. ReviewNote remains optional. The groups are separate BOOKING_GROUP rows.

13. Data dictionary: HALL_BLOCK

Dated maintenance or other hall closures, including multi-day periods.

Column	SQL type	Req.	Key	Meaning / reason
BlockID	int	Yes	PRI	Unique hall-closure identifier. MySQL generates this primary-key value; gaps are allowed.
HallID	int	Yes	FK	Lecture-hall identifier. Every booking and hall block refers to one hall.
RecordedByID	int	Yes	FK	Administrator who recorded the closure.
BlockStart	datetime	Yes	-	Closure start date/time; can be on a different date from BlockEnd.
BlockEnd	datetime	Yes	-	Closure end date/time, strictly later than BlockStart.
Reason	varchar(255)	Yes	-	Required explanation of the closure.
BlockStatus	enum('Active', 'Cancelled')	Yes	-	Active or Cancelled. Cancellation retains the closure record. Default: Active.

14. Data dictionary: BOOKING_GROUP

Booking-to-student-group M:N assignment.

Column	SQL type	Req.	Key	Meaning / reason
BookingID	int	Yes	PK part + FK	Unique identifier for one request, including requests retained after cancellation or rejection.
GroupID	int	Yes	PK part + FK	Student-group identifier.

The two key columns are unique together. Either individual value can repeat in other rows. This represents an M:N relationship without a comma-separated list.

15. Primary keys, foreign keys and normalisation

Child table.column	Parent table.column
BOOKING.CourseID	COURSE_UNIT.CourseID
BOOKING.HallID	LECTURE_HALL.HallID
BOOKING.RequesterID	USER_ACCOUNT.AccountID
BOOKING.ReviewerID	USER_ACCOUNT.AccountID
BOOKING_GROUP.BookingID	BOOKING.BookingID
BOOKING_GROUP.GroupID	STUDENT_GROUP.GroupID
COURSE_UNIT.DepartmentID	DEPARTMENT.DepartmentID
HALL_BLOCK.HallID	LECTURE_HALL.HallID
HALL_BLOCK.RecordedByID	USER_ACCOUNT.AccountID
HALL_FACILITY.FacilityID	FACILITY.FacilityID
HALL_FACILITY.HallID	LECTURE_HALL.HallID
LECTURE_HALL.BuildingID	BUILDING.BuildingID
STUDENT_GROUP.DepartmentID	DEPARTMENT.DepartmentID
USER_ACCOUNT.DepartmentID	DEPARTMENT.DepartmentID

A foreign key checks that a referenced parent exists. It does not prove that an account is an administrator, that attendance fits the hall, or that two time intervals do not overlap. Those checks belong in the business procedures and authenticated application flow.

RequesterID and ReviewerID both reference USER_ACCOUNT.AccountID but describe different relationships. They are not new entities. A reviewer can review many bookings; an ordinary many-side FK must therefore not be made UNIQUE.

The junctions prevent repeated pairs. For example, one booking can serve groups 10 and 11, and group 10 can appear in other bookings. Only the duplicate pair is prohibited.

Parent records referenced by history use default InnoDB NO ACTION behaviour. Normal application permissions prohibit raw booking deletes. Deactivating a user or hall is different from deleting the referenced record.

16. Constraints and data types

Choice	Reason
INT identifiers	Compact surrogate keys; generated IDs identify rows and are not record counts.
VARCHAR lengths	Bound the size of text values. The chosen limits are project design choices, not measured university limits.
DATE + TIME	Same-day bookings use a date and two clock times. Overnight bookings are outside this version.
DATETIME	Records request, review and hall-closure local timestamps. DATETIME itself stores no timezone identifier.
ENUM	Restricts the known role, status, type and decision vocabulary for this prototype.
NULL	Represents an optional or not-yet-known fact. It differs from an empty string and from zero.
NOT NULL + CHECK	NOT NULL rejects a missing value; a length check also rejects empty or ordinary-space-only text.
utf8mb4	Unicode storage suitable for multilingual data. Connection encoding must also use utf8mb4.
ascii_bin PasswordHash	Encoded hashes are ASCII and case-sensitive, even though catalogue names use the database collation.
InnoDB	Supports foreign keys, row locks and transactions.

TRIM in a CHECK is used to evaluate the condition; it does not rewrite the stored column. The public write procedures trim selected human-readable inputs before saving them.

The attendance API accepts a decimal parameter so it can reject a fractional value before inserting the required integer. Other raw form input, including email syntax and password policy, must also be validated by the application.

17. Row-level CHECK inventory


These 28 checks are taken from the validated MySQL schema. Required foreign-key links and uniqueness rules are additional constraints.

Table / constraint	Expression
BOOKING / ck_booking_attendance	(`ExpectedAttendance` > 0)
BOOKING / ck_booking_clock	((`StartTime` >= _utf8mb4\'00:00:00\') and (`StartTime` < _utf8mb4\'24:00:00\') and (`EndTime` >= _utf8mb4\'00:00:00\') and (`EndTime` < _utf8mb4\'24:00:00\') and (`EndTime` > `StartTime`))
BOOKING / ck_booking_course	((`BookingType` not in (_utf8mb4\'Lecture\',_utf8mb4\'Tutorial\')) or (`CourseID` is not null))
BOOKING / ck_booking_no_self_review	((`ReviewerID` is null) or (`ReviewerID` <> `RequesterID`))
BOOKING / ck_booking_purpose	(char_length(trim(`Purpose`)) > 0)
BOOKING / ck_booking_review_bundle	(((`ReviewerID` is null) and (`Decision` is null) and (`ReviewedAt` is null) and (`ReviewNote` is null)) or ((`ReviewerID` is not null) and (`Decision` is not null) and (`ReviewedAt` is not null)))
BOOKING / ck_booking_review_state	(((`BookingStatus` = _utf8mb4\'Pending\') and (`ReviewerID` is null)) or ((`BookingStatus` in (_utf8mb4\'Approved\',_utf8mb4\'Completed\')) and (`ReviewerID` is not null) and (`Decision` = _utf8mb4\'Approved\')) or ((`BookingStatus` = _utf8mb4\'Rejected\') and (`ReviewerID` is not null) and (`Decision` = _utf8mb4\'Rejected\')) or ((`BookingStatus` = _utf8mb4\'Cancelled\') and ((`ReviewerID` is null) or (`Decision` = _utf8mb4\'Approved\'))))
BOOKING / ck_booking_review_time	((`ReviewedAt` is null) or (`ReviewedAt` >= `RequestedAt`))
BUILDING / ck_building_buildingcode	(char_length(trim(`BuildingCode`)) > 0)
BUILDING / ck_building_buildingname	(char_length(trim(`BuildingName`)) > 0)
COURSE_UNIT / ck_course_unit_coursecode	(char_length(trim(`CourseCode`)) > 0)
COURSE_UNIT / ck_course_unit_coursetitle	(char_length(trim(`CourseTitle`)) > 0)
DEPARTMENT / ck_department_departmentname	(char_length(trim(`DepartmentName`)) > 0)
FACILITY / ck_facility_facilityname	(char_length(trim(`FacilityName`)) > 0)
HALL_BLOCK / ck_hall_block_interval	(`BlockEnd` > `BlockStart`)
HALL_BLOCK / ck_hall_block_reason	(char_length(trim(`Reason`)) > 0)
HALL_FACILITY / ck_hall_facility_total	(`Quantity` > 0)
HALL_FACILITY / ck_hall_facility_working	((`WorkingQuantity` >= 0) and (`WorkingQuantity` <= `Quantity`))
LECTURE_HALL / ck_lecture_hall_capacity	(`Capacity` > 0)
LECTURE_HALL / ck_lecture_hall_hallno	(char_length(trim(`HallNo`)) > 0)
STUDENT_GROUP / ck_student_group_groupname	(char_length(trim(`GroupName`)) > 0)

Table / constraint	Expression
STUDENT_GROUP / ck_student_group_intake	(`IntakeYear` between 1900 and 9999)
STUDENT_GROUP / ck_student_group_level	(`StudyYear` >= 1)
USER_ACCOUNT / ck_user_account_active	(`IsActive` in (0,1))
USER_ACCOUNT / ck_user_account_email	(char_length(trim(`Email`)) > 0)
USER_ACCOUNT / ck_user_account_fullname	(char_length(trim(`FullName`)) > 0)
USER_ACCOUNT / ck_user_account_passwordhash	(char_length(trim(`PasswordHash`)) > 0)
USER_ACCOUNT / ck_user_account_username	(char_length(trim(`Username`)) > 0)

A permanent future-date CHECK is intentionally absent: an approved booking must remain valid history after its date passes. Future-start validation happens when creating, editing or approving a request.

18. Booking lifecycle and retained history



State	Rules
Pending	Can be edited by its requester. Can be approved, rejected or cancelled. Does not reserve a slot.
Approved	Reserves the hall interval. Rescheduling requires cancellation and a new request.
Rejected	Terminal; retains its single rejection decision.
Cancelled	Terminal; retains a previous approval if it had one, along with group links.
Completed	Terminal; reached only from Approved after the session end.

An authorised administrator can approve or reject another account request. Lecturers and authorised AdminStaff can submit their own requests; an administrator request still needs a different administrator to review it. Public registration creates only Student accounts.

The v1 schema preserves lifecycle records and one decision. It is not a complete audit log of every edit, cancellation actor or previous catalogue value.

19. Availability and overlapping intervals

```
newStart < existingEnd AND newEnd > existingStart
```

Existing approved session	New request	Result
09:00-10:00	09:30-10:30	Conflict
09:00-10:00	10:00-11:00	Allowed adjacency
09:00-10:00	08:00-09:00	Allowed adjacency
09:00-10:00	09:00-10:00	Conflict

The interval is half-open: the end of one session can equal the start of another. Booking comparisons use the same hall and booking date. For closures, TIMESTAMP(BookingDate, StartTime/EndTime) allows comparison with multi-day DATETIME block intervals.

An approval also requires an active hall, sufficient capacity, an active eligible requester and a future start instant. Lecture/Tutorial requires a course and at least one valid group.

Availability search is a snapshot. Another transaction can reserve the hall after the screen loads. Approval always rechecks the current data under the common hall lock.

Pending requests can overlap each other. Once one is approved, approving another overlapping request fails and leaves that second request Pending.

20. Transactions, locks and maintenance priority

- Begin a transaction using READ COMMITTED.

- Lock the relevant LECTURE_HALL row with SELECT ... FOR UPDATE.

- For an edit moving a Pending request, lock both halls in ascending HallID order.

- Lock the booking row, confirm its hall has not changed, and validate the actor and lifecycle state.

- Recheck future time, course/groups, capacity, approved bookings and active hall blocks.

- Write all related changes together, then COMMIT. On a SQL exception, ROLLBACK and return the error.

The common hall row is the coordination point. Booking approval and hall-block creation take the same lock. The second operation waits, then sees the first committed result before deciding whether it can proceed.

The selected READ COMMITTED isolation level avoids checking a snapshot created before waiting for the hall lock. Relevant hall-capacity and operational-status changes follow the same protocol.

A maintenance block cannot silently displace an approved booking. Conflicting future reservations must first be cancelled explicitly. A hall cannot become inactive or too small while that would invalidate an existing not-ended approved reservation.

Each public write procedure owns its transaction. Call it with application autocommit enabled and without an existing outer transaction. Handle SQLSTATE 45000 as a business-rule rejection; deadlocks and timeouts need rollback-aware retry. A network timeout after commit must not be blindly retried as a new request.

21. Public procedure reference

sp_create_booking

Creates a Pending booking and group links atomically. The actor is the requester.

```
sp_create_booking(IN p_actor INT,IN p_hall INT,IN p_course INT,IN p_date DATE,IN p_start TIME,IN
    p_end TIME,IN p_purpose TEXT,IN p_type VARCHAR(20),IN p_attendance DECIMAL(20,6),IN p_groups
    JSON,OUT p_booking_id INT)
```

sp_update_pending_booking

Owner-only Pending edit; can move halls using ordered locking. Replaces its group set atomically.

```
sp_update_pending_booking(IN p_actor INT,IN p_booking INT,IN p_hall INT,IN p_course INT,IN p_date
    DATE,IN p_start TIME,IN p_end TIME,IN p_purpose TEXT,IN p_type VARCHAR(20),IN p_attendance
    DECIMAL(20,6),IN p_groups JSON)
```

sp_review_booking

Admin review of Pending; rechecks availability on approval and writes review fields together.

```
sp_review_booking(IN p_actor INT,IN p_booking INT,IN p_decision VARCHAR(10),IN p_note TEXT)
```

sp_cancel_booking

Owner or admin cancels a future Pending/Approved request, preserving review and group history.

```
sp_cancel_booking(IN p_actor INT,IN p_booking INT)
```

sp_complete_booking

Admin marks an ended Approved session Completed.

```
sp_complete_booking(IN p_actor INT,IN p_booking INT)
```

sp_create_hall_block

Admin creates a dated closure after checking approved reservations under the hall lock.

```
sp_create_hall_block(IN p_actor INT,IN p_hall INT,IN p_start DATETIME,IN p_end DATETIME,IN p_reason
     TEXT,OUT p_block_id INT)
```

sp_cancel_hall_block

Admin cancels an Active closure while retaining its row.

```
sp_cancel_hall_block(IN p_actor INT,IN p_block INT)
```

sp_update_hall

Admin changes capacity/status only when approved reservations remain valid.

```
sp_update_hall(IN p_actor INT,IN p_hall INT,IN p_capacity INT,IN p_status VARCHAR(10))
```

sp_set_hall_facility

Admin inserts or updates a hall/type pair with valid total and working quantities.

```
sp_set_hall_facility(IN p_actor INT,IN p_hall INT,IN p_facility INT,IN p_quantity INT,IN p_working
    INT)
```

sp_register_student

Public registration contract. Role is fixed to Student; input is already a password hash.

```
sp_register_student(IN p_department INT,IN p_name TEXT,IN p_email TEXT,IN p_username TEXT,IN
    p_password_hash TEXT,OUT p_account_id INT)
```

sp_provision_account

Administrator creates an account, including privileged lecturer/staff roles.

```
sp_provision_account(IN p_actor INT,IN p_department INT,IN p_name TEXT,IN p_email TEXT,IN
    p_username TEXT,IN p_password_hash TEXT,IN p_role VARCHAR(20),OUT p_account_id INT)
```

sp_get_login_record

Backend-only username lookup for password verification; its hash must never reach public clients.

```
sp_get_login_record(IN p_username VARCHAR(50))
```

sp_find_available_halls

Read-only future availability and capacity filter; it does not reserve a slot.

```
sp_find_available_halls(IN p_date DATE,IN p_start TIME,IN p_end TIME,IN p_attendance DECIMAL(20,6))
```

sp_add_department

Admin adds a department catalogue record.

```
sp_add_department(IN p_actor INT,IN p_name VARCHAR(100),OUT p_id INT)
```

sp_add_building

Admin adds a building catalogue record.

```
sp_add_building(IN p_actor INT,IN p_code VARCHAR(20),IN p_name VARCHAR(100),IN p_location
    VARCHAR(255),OUT p_id INT)
```

sp_add_facility

Admin adds a facility-type catalogue record.

```
sp_add_facility(IN p_actor INT,IN p_name VARCHAR(100),IN p_description VARCHAR(255),OUT p_id INT)
```

sp_add_course

Admin adds a course with an existing owning department.

```
sp_add_course(IN p_actor INT,IN p_department INT,IN p_code VARCHAR(20),IN p_title VARCHAR(150),OUT
    p_id INT)
```

sp_add_student_group

Admin adds a teaching group with department/intake identity.

```
sp_add_student_group(IN p_actor INT,IN p_department INT,IN p_name VARCHAR(100),IN p_intake SMALLINT
     UNSIGNED,IN p_year TINYINT UNSIGNED,OUT p_id INT)
```

sp_add_hall

Admin adds a physical hall in an existing building.

```
sp_add_hall(IN p_actor INT,IN p_building INT,IN p_number VARCHAR(20),IN p_floor VARCHAR(10),IN
    p_capacity INT,OUT p_id INT)
```

The six _hs_* helpers are implementation details: actor validation, hall locking, input validation, slot checks, group insertion and account-field validation. Application accounts receive EXECUTE on public procedures only, not helpers.

22. Run a complete booking example

After setup, the synthetic catalogue contains HS-DEMO / DEMO-01, a practice course, one student group and four demonstration accounts. The codes are invented for testing, not an official University of Kelaniya inventory.

```
SET @lecturer = (SELECT AccountID FROM USER_ACCOUNT WHERE Username='demo_lecturer');
SET @admin = (SELECT AccountID FROM USER_ACCOUNT WHERE Username='demo_admin_a');
SET @hall = (SELECT h.HallID FROM LECTURE_HALL h
 JOIN BUILDING b ON b.BuildingID=h.BuildingID
 WHERE b.BuildingCode='HS-DEMO' AND h.HallNo='DEMO-01');
SET @date = DATE_ADD(CURRENT_DATE(), INTERVAL 30 DAY);
CALL sp_create_booking(@lecturer,@hall,NULL,@date,'09:00','10:00',
 'Demo seminar','Event',30,JSON_ARRAY(),@booking);
CALL sp_review_booking(@admin,@booking,'Approved','Checked availability');
SELECT * FROM v_booking_details WHERE BookingID=@booking;
```

This Event does not need a course or student group. A Lecture/Tutorial passes an existing CourseID and JSON_ARRAY(group_id, ...). JSON is only an input format; the database stores one BOOKING_GROUP row per group.

Run database/09_workflow_example.sql once if you want this demonstration to create data. Repeating it can create another Pending request or fail because the earlier session is already approved.

To demonstrate cancellation later, call sp_cancel_booking with the requester or an administrator. The status becomes Cancelled while the earlier Approved decision remains recorded.

23. Views, reports and indexes

View	Meaning
v_booking_details	One row per booking, joined with requester, hall/building, optional course and reviewer.
v_hall_facilities	Hall/type assignments with total, working and calculated non-working quantities.
v_booking_status_totals	Counts booking rows by their current state.
v_hall_usage	Counts approved/completed sessions and sums reserved minutes by hall/date.

Joining a booking to multiple student groups can multiply result rows. Count bookings before joining, use an appropriate distinct count, or aggregate the junction separately. The provided status totals avoid this duplication.

Unique keys cover email, username, building code, facility name, course code, department/intake/group-name, and building/hall-number. The two junction primary keys also enforce unique pairs.

The booking interval index starts with HallID, BookingDate and BookingStatus. The block interval index starts with HallID and BlockStatus. These help find relevant rows; indexes alone do not forbid overlapping intervals.

Reserved minutes are scheduled session time, not actual measured hall use. The system does not track individual student attendance or enrolments.

24. Security and the application boundary

- The database validates roles for the supplied actor ID, but it cannot establish a human login session.

- The application must verify the password, check activation and derive actor IDs from that authenticated session.

- Never accept RequesterID or reviewer identity from an editable user form.

- Use a maintained Argon2id library. Validate password policy before hashing; the hash cannot reveal the original password length.

- The procedure hash-prefix check is a guard against obvious plaintext input, not proof that an encoded hash is genuine or uses adequate cost settings.

- Use prepared/parameterised calls in the application and a dedicated database login, not the setup administrator.

- Assign hallsync_application to that login. It permits approved interfaces and reads, while denying direct table writes and internal helper calls.

The demo hashes were generated from random discarded passwords. They enable SQL procedure demonstrations by account ID, but do not provide known login credentials. Provision real account credentials during the authentication lesson.

A privileged database administrator can bypass normal application rules through direct SQL or DDL. Operational users must use the restricted application interfaces. A shared database login is not an end-user identity system; production campus deployment should place database credentials in a trusted backend.

A first administrator and existing timetable data are controlled DBA bootstrap operations. Ordinary public registration can never choose Lecturer or AdminStaff.

25. Verification and test evidence

The read-only 08 script checks metadata and searches for conflicting approved bookings, approved/block overlaps, academic bookings without groups, and future reservations invalidated by hall capacity/status.

This package passed 100 checks on MySQL 8.0.46. The report is docs/database_validation.json. Tests create generated hallsync_validation_* schemas and never reset your hallsync_db.

Category	What was checked
Structure	11 tables, 61 columns, 11 PKs, 14 FKs, 7 other unique keys, 28 CHECKs, 4 views and 25 procedures.
Upgrade and fresh setup	Existing department ID/name preserved; demo seed repeats safely; fresh installation builds the same shape.
Integrity	Missing parents, duplicate equipment pairs, blank names, zero capacity and invalid equipment counts.
Business rules	Invalid times, fractional/zero/too-large attendance, course/group requirements, privileges and self-approval.
Lifecycle	Pending edits, rollback of invalid changes, cancellation history and terminal states.
Concurrency	5 simultaneous conflicting-approval races, 3 approval/block races and a check that approval waits on the common hall lock.
Least privilege	Application login cannot insert raw bookings, read the raw password table or call internal helpers.

Passed check names

Check	Result
Upgrade preserves existing department ID 1	PASS
11 tables	PASS
61 columns	PASS
11 PRIMARY KEY	PASS
14 FOREIGN KEY	PASS
7 UNIQUE	PASS
28 CHECK	PASS
4 views	PASS
25 procedures	PASS
Demo seed can repeat without duplicate accounts	PASS
Blank department	PASS
NULL department	PASS
Missing parent	PASS
Zero capacity	PASS
Duplicate hall facility	PASS
Working exceeds total	PASS
Zero facility quantity	PASS
Student request	PASS
Attendance zero	PASS
Fractional attendance	PASS
Capacity overflow	PASS
Blank purpose	PASS

Check	Result
Equal times	PASS
Overnight times	PASS
Past start	PASS
Lecture missing course	PASS
Tutorial missing group	PASS
Unknown course	PASS
Unknown group	PASS
Duplicate groups	PASS
String group ID	PASS
Failed requests leave no booking rows	PASS
Overlapping Pending requests allowed	PASS
Group created with booking	PASS
Student cannot approve	PASS
Approval metadata consistent	PASS
Conflicting second approval	PASS
Failed review rolls back	PASS
Approved edit forbidden	PASS
Adjacent intervals allowed	PASS
Block cannot override approval	PASS
Capacity shrink cannot break reservation	PASS
Inactive cannot break reservation	PASS
Other requester cannot cancel	PASS

Check	Result
Cancellation retains approval	PASS
Cancellation retains groups	PASS
Cancelled terminal	PASS
Group history protects parent	PASS
Account history protects parent	PASS
Self approval prohibited	PASS
Different admin may approve staff request	PASS
Cannot complete before session end	PASS
Approval rechecks multi-day closure	PASS
Cancelled closure releases availability	PASS
Closure cancellation is terminal	PASS
Lecturer cannot create closure	PASS
Only owner edits Pending	PASS
Pending edit updates groups	PASS
Invalid edit rolls back	PASS
Old values retained after failed edit	PASS
Rejected terminal	PASS
Rejected cannot cancel	PASS
Pending cancellation needs no review	PASS
Ended approval can complete	PASS
Completed terminal	PASS
Student cannot provision lecturer	PASS

Check	Result
Plaintext password refused	PASS
Public registration fixes Student role	PASS
Admin provisions privileged role	PASS
Inactive requester refused	PASS
Working quantity zero allowed	PASS
Invalid inventory update	PASS
Student cannot manage inventory	PASS
Lecturer cannot add hall	PASS
Inactive hall refuses requests	PASS
Unreserved hall state can change	PASS
Details view has one row per booking	PASS
Status report totals match	PASS
Concurrent conflicting approvals 1	PASS
Race leaves exactly one Approved 1	PASS
Concurrent conflicting approvals 2	PASS
Race leaves exactly one Approved 2	PASS
Concurrent conflicting approvals 3	PASS
Race leaves exactly one Approved 3	PASS
Concurrent conflicting approvals 4	PASS
Race leaves exactly one Approved 4	PASS
Concurrent conflicting approvals 5	PASS
Race leaves exactly one Approved 5	PASS

Check	Result
Concurrent approval versus closure 1	PASS
Concurrent approval versus closure 2	PASS
Concurrent approval versus closure 3	PASS
Approval waits for the common hall lock	PASS
Application cannot insert raw bookings	PASS
Application cannot read raw password table	PASS
Application cannot call internal helper	PASS
Application can read approved reporting interface	PASS
Application can call availability interface	PASS
Fresh installation creates 11 tables	PASS
Fresh installation creates 61 columns	PASS
No approved overlaps remain	PASS

26. Timetable setup, scope and limitations

Availability is reliable only after existing future timetable reservations are entered with their responsible requester and a different authorised reviewer. Demo records are not a substitute for the real timetable. Controlled initial import is distinct from an ordinary user booking on behalf of someone else.

- No recurring booking series, automatic timetable generation, individual student enrolment tracking or multi-stage approvals.

- One booking uses one hall and one same-day session. Hall blocks can span multiple days.

- Faculty of Science is the fixed prototype context; there is no separate faculty catalogue.

- Reports are derived from stored facts. The model does not store a complete revision-by-revision audit log.

- Catalogue labels can change over time; the booking keeps identifiers and its own purpose/attendance, not historical snapshots of every parent field.

- Account credential verification, session handling, UI validation and user-facing messages are application work.

- No real university hall inventory, staff accounts or timetable has been imported by these scripts.

Store all system times consistently in Asia/Colombo. A start later today is valid when it is still in the future; an already started session cannot be submitted or approved as a new request.

27. Troubleshooting in Workbench

Symptom	Action
Database/table already exists	You may have run a creation step already. Inspect with 08 and SHOW CREATE TABLE; preserve data instead of resetting.
Preflight expected only DEPARTMENT	The continuation starting condition differs, or a previous run stopped partway through. Share the exact error and existing table list.
Syntax error near DELIMITER	Open the SQL file and execute the whole procedure definition. DELIMITER is a client directive, not SQL to send as a server statement.
Procedure does not exist	Complete 05 first. Check the selected database and routine list.
Transaction characteristics cannot change	A write procedure was called within an existing transaction. Resolve that transaction and call the procedure outside an outer transaction.
CHECK / FK / duplicate-key error	Input violates a named rule. Fix the supplied values or create the parent record first.
SQLSTATE 45000	Business-rule rejection. Display its message and leave the existing record unchanged.
Permission denied while saving a file	Use Save Script As in a writable normal folder. This file error is separate from database creation.
Password cannot log in	Demo passwords are intentionally unknown. Real credentials require application-side hashing/provisioning.

Setup statements can partly succeed before an error. Retain Action Output and request a targeted repair. The scripts do not drop the project database or delete existing department rows.

28. Presentation questions and answers

Why 11 tables for nine entities?

The two M:N relationships become HALL_FACILITY and BOOKING_GROUP junction tables.

Why both NOT NULL and CHECK?

NULL and an empty string are different. A required text value also needs an appropriate non-empty rule.

Why not store group IDs in one text column?

Separate junction rows support foreign keys, joins and pair uniqueness without parsing lists.

Does a foreign key prove an administrator role?

It proves that the account exists. Role/activation checks are separate business logic.

Why does Pending not reserve the hall?

Several requests may be reviewed; only an approved reservation guarantees that interval. Approval rechecks under a lock.

Why use a transaction when approving?

The role/time/capacity/conflict checks and review/status update must succeed together or roll back.

Why lock the hall row?

It exists even when no reservation exists yet, giving approvals and blocks a shared coordination point.

Why can 10:00 follow a session ending 10:00?

The overlap test uses strict inequalities, so adjacent half-open intervals do not overlap.

Why keep Decision after cancellation?

BookingStatus describes the current lifecycle, while Decision preserves the single earlier review.

Is a foreign key OOP inheritance?

No. It is a relational reference. Classes, interfaces, encapsulation and polymorphism describe the application design.

What will a BookingRepository do?

Expose save/search/review operations and translate object data into parameterised database calls.

Where are password length rules checked?

Before hashing in the application. Only the salted encoded hash is stored.

29. Next: connect an OOP application

After you run the continuation script and confirm the 08 results, the next stage is the application model. Start with UserAccount, LectureHall and Booking responsibilities, then an interface such as BookingRepository and a database implementation.

A booking service coordinates authenticated actions. A repository calls the stored procedures and converts their results into objects. The UI presents information and explains rejections. Java can use JDBC with MySQL Connector/J; another chosen OOP language uses its supported MySQL driver.

Encapsulation protects object state, abstraction gives a clear repository contract, and polymorphism allows a test implementation of that contract. Use inheritance only for a justified is-a relationship. The database remains the authority for concurrent reservation decisions.

Your first application connection lesson will create a dedicated database login with a private password, assign hallsync_application, configure the timezone/encoding and test one read. No password belongs in a public repository.

30. SQL vocabulary used in these scripts

Keyword / expression	What it means here
CREATE TABLE / DDL	Defines stored structure. DDL is not the same as inserting department or booking records.
INSERT / UPDATE / DELETE	Change rows. Deleting a Pending booking group set during an edit is distinct from deleting booking history.
PROCEDURE / CALL	A stored operation with parameters; CALL invokes it. Public procedures are the application entry points.
IN / OUT parameters	IN supplies a value. OUT returns a generated identifier through a caller variable.
DECLARE versus @variable	DECLARE creates a local routine variable. An @variable belongs to one client connection.
LAST_INSERT_ID()	Returns that connection generated ID; using MAX(ID) instead could select another user row.
IF / EXISTS / SELECT 1	Conditional checks. EXISTS asks whether any matching row exists, without needing all its columns.
TRIM / CHAR_LENGTH	Evaluate text after removing outer ordinary spaces, and count characters rather than bytes.
FLOOR	Checks that attendance has no fractional part before storing an integer.
JSON_ARRAY / JSON_TABLE	Send several group IDs in one input, then turn them into rows. Group links are stored relationally.
JSON_ARRAYAGG / COALESCE	Collect existing group IDs for revalidation; substitute an empty array when none exist.
SIGNAL SQLSTATE 45000	Raise a controlled business-rule rejection with a useful message.
EXIT HANDLER / RESIGNAL	On a SQL exception, roll back this procedure transaction and propagate the original error.
START TRANSACTION / COMMIT	Begin one atomic business operation and make its successful changes permanent.
ROLLBACK	Undo this transaction changes after failure. It does not undo an entire earlier DDL installation.
FOR UPDATE / FOR SHARE	Take row locks. Hall writes coordinate with FOR UPDATE; account checks hold a shared read lock.
READ COMMITTED	Each new consistent read sees the latest committed data, including after a hall-lock wait.
ON DUPLICATE KEY UPDATE	Update the existing hall/facility pair when its composite key already exists.
JOIN / LEFT JOIN	Require a matching parent or retain a row when optional course/reviewer data is absent.
SQL SECURITY DEFINER	Execute the stored operation using its installer privileges; the caller still needs EXECUTE permission.
GRANT / MySQL role	Control database-login privileges. This is separate from USER_ACCOUNT.Role for application users.

Keyword / expression	What it means here
DELIMITER	A Workbench/client directive for sending a complete procedure body containing internal semicolons.

The controller must still authenticate a human user. SQL SECURITY DEFINER and a MySQL role do not turn a caller-supplied actor ID into proof of identity.

Database CHECK expressions use SQL NULL semantics. Required columns and explicit IS NULL / IS NOT NULL review-bundle checks are necessary to express the intended rules.

MySQL TIME can also represent durations beyond one day. The booking clock CHECK narrows it to the same-day interval supported by this project.

31. Technical references

MySQL CREATE TABLE and CHECK constraints

https://dev.mysql.com/doc/refman/8.0/en/create-table-check-constraints.html

MySQL foreign keys

https://dev.mysql.com/doc/refman/8.0/en/create-table-foreign-keys.html

MySQL locking reads

https://dev.mysql.com/doc/refman/8.0/en/innodb-locking-reads.html

MySQL transaction isolation

https://dev.mysql.com/doc/refman/8.0/en/innodb-transaction-isolation-levels.html

MySQL JSON_TABLE

https://dev.mysql.com/doc/refman/8.0/en/json-table-functions.html

MySQL stored-object access control

https://dev.mysql.com/doc/refman/8.0/en/stored-objects-security.html

OWASP Password Storage Cheat Sheet

https://cheatsheetseries.owasp.org/cheatsheets/Password_Storage_Cheat_Sheet.html

Java OOP learning material

https://dev.java/learn/language/oop/

MySQL Connector/J

https://dev.mysql.com/doc/connector-j/en/connector-j-overview.html

Project specification: the agreed HallSync Chen-to-relational mapping, the discussed booking rules, and the SQL files in this repository. Synthetic catalogue values are explicitly labelled as demo data.