

2K THINNER

PRODUCT DESCRIPTION

Emirates 2K Thinner is a Specially formulated thinner designed to adjust the viscosity of all 2k paints.

PRODUCT FEATURES

- Universal solvent for 1K & 2K Emirates Products
- Gives a better flow of Emirates products during application

RECOMMENDED USE

This product is recommended for any car refinish coating application at any given temperature.

TECHNICAL SPECIFICATIONS

Color	Transparent Clear
Specific Gravity	0.85 ± 0.02
Packaging Size	1L + 3.6L + 18L
Flash Point	10°C
Odour	Strong Odour



2K THINNER

APPLICATION DATA

Application Instructions

As per Requirement

SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

RECOMMENDED SYSTEM

Application Method

Mix with paint



2K THINNER

HEALTH & SAFETY

Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.

STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

