

CHROMA EMALUX BASE COAT

PRODUCT DESCRIPTION

Chroma Emalux Base Coat is a 1K single-component system acrylic resin-based base coat, designed to be used as a basic coat for finishing Chroma clear coat.

PRODUCT FEATURES

- Outstanding color accuracy
- Excellent Hiding/opacity power & low consumption
- Fast drying
- Easy to apply
- Highly durable finish good
- Excellent metallic/pearl flakes orientation
- Can be used for spot, panel, and overall repair
- Excellent weather durability.

RECOMMENDED USE

This product is recommended to be applied over 1K Numix Primer, 2K Numix Primer, old or original paintwork, and all existing OEM finishes on metal surfaces.

*Used for Automotive applications.

TECHNICAL SPECIFICATIONS

Color	As per Chroma's Shade Card
Finish	Matt
Spreading Rate	6 - 8 M ² / litre
Volume Solids (ASTM d2697)	Variable and dependable on the color
Specific Gravity	Dependable on the colors
Dry Film Thickness	15 - 18 Microns / Coat
Packaging Size	1L + 3.6L + 18L
Flash Point	22°C



CHROMA EMALUX BASE COAT

APPLICATION DATA

Application Method	Spray
Thinner	Chroma Thinner (5 – 10% depends on method of application)
Airless Spray Requirements	Nozzle Size: 0.051" - 0.059" Pressure: 29 - 43.5 psi
Mixing Ratio (by weight)	One pack
Pot life @30°C	NA

SURFACE PREPARATION

The surface must be clean, dry, and free from oil, grease, dust, and loose particles before application.

DRY TIME

Touch Dry	30 - 60 minutes
Dry to Recoat	10 - 15 minutes
Full Dry	1 - 2 hours

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

Chroma Emalux Primer	2 - 3 Coats
Chroma Emalux Base Coat	2 - 3 Coats
Chroma Emalux Topcoat	2 - 3 Coats



CHROMA EMALUX BASE COAT

HEALTH & SAFETY

Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.

STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

