

CHROMA EMALUX PRIMER

PRODUCT DESCRIPTION

Chroma Emalux Primer is a fast-drying Acrylic primer, engineered for advanced adhesion and easy-to-sand properties to create a smooth and even base for optimal finish.

PRODUCT FEATURES

- Fast drying
- Excellent adhesion
- Excellent sanding properties
- Easy to apply and optimal finish
- Corrosion protection for metal surfaces

RECOMMENDED USE

This product is recommended for automotive refinishing systems, steel surfaces, and cabinet work applications.

*Used for Automotive applications.

TECHNICAL SPECIFICATIONS

Color	Grey, White, Black
Finish	Matt
Spreading Rate	11 - 14 M ² /Litre
Volume Solids	52 ± 4%
Specific Gravity	1.60 ± 0.02
Dry Film Thickness	40 - 50 Microns / Coat
Wet Film Thickness	40 Microns / Coat
Packaging Size	1L + 3.6L + 18L



CHROMA EMALUX PRIMER

APPLICATION DATA

Application Method	Brush, Roller, Spray
Thinner (Volume)	Chroma Thinner (20 - 30% depends on method of application)
Airless Spray Requirements	Nozzle Size: 0.063" - 0.079" Atomizing Pressure: 29.0 - 43.5 psi
Mixing Ratio (Volume)	(4:1) (Base: Hardener)
Pot life @30°C	2 hours

SURFACE PREPARATION

The surface must be clean, dry, and free from oil, grease, dust, and loose particles before application.

DRY TIME

Touch Dry	5 minutes
Dry to Recoat	30 minutes
Full Dry	1 hour

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

Chroma Emalux Primer	2 - 3 Coats
Chroma Emalux Topcoat	2 - 3 Coats



CHROMA EMALUX PRIMER

HEALTH & SAFETY

Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.

STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use.

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

