

# CHROMA 2K PRIMER

## PRODUCT DESCRIPTION

Chroma 2K Primer is a fast-drying Acrylic primer, engineered for advanced adhesion and easy-to-sand properties to create a smooth and even base for optimal finish.

## PRODUCT FEATURES

- Fast drying
- Excellent adhesion
- Excellent sanding properties
- Easy to apply and optimal finish
- Corrosion protection for metal surfaces

## RECOMMENDED USE

This product is recommended for automotive refinishing systems, steel surfaces, and cabinet work applications.

\*Used for Automotive applications.

## TECHNICAL SPECIFICATIONS

|                    |                                |
|--------------------|--------------------------------|
| Color              | Grey, White, Black             |
| Finish             | Matt                           |
| Spreading Rate     | 11 - 14 m <sup>2</sup> / litre |
| Volume Solids      | 52 ± 4%                        |
| Specific Gravity   | 1.60 ± 0.02                    |
| Dry Film Thickness | 40 - 50 Microns / Coat         |
| Wet Film Thickness | 40 Microns / Coat              |
| Packaging Size     | 1L + 3.6L + 18L                |



## CHROMA 2K PRIMER

### APPLICATION DATA

|                          |                                                                     |
|--------------------------|---------------------------------------------------------------------|
| Application Method       | Brush, Roller, Spray                                                |
| Thinner (Volume)         | Chroma Thinner<br>(20 - 30% depends on method of application)       |
| Conv. Spray requirements | Nozzle Size: 0.063" - 0.079"<br>Atomizing Pressure: 29.0 - 43.5 psi |
| Mixing Ratio (Volume)    | (4:1) (Base:Hardener)                                               |
| Pot Life @30° C          | 2 hours                                                             |

### SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

### DRY TIME

|               |            |
|---------------|------------|
| Touch Dry     | 5 minutes  |
| Dry to Recoat | 30 minutes |
| Full Dry      | 1 hour     |

\*Based on temperatures at 30 degrees Celsius.

\*Humidity, air movement, film thickness and number of coats may impact dry time.

### RECOMMENDED SYSTEM

|                   |             |
|-------------------|-------------|
| Chroma 2K Primer  | 2 - 3 Coats |
| Chroma 2K Topcoat | 2 - 3 Coats |



# CHROMA 2K PRIMER

## HEALTH & SAFETY

*Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.*

## STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use

## SHELF LIFE

\*For best results, please use within 18 months of the production date.

\*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

## DISCLAIMER

*The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.*

