

CHROMA NC PUTTY

PRODUCT DESCRIPTION

Chroma NC Putty is a nitrocellulose-based putty, designed with excellent adhesion, filling properties, and sanding ability for wooden and steel surfaces.

PRODUCT FEATURES

- Fast drying
- Excellent adhesion
- Excellent filling properties
- Easy to sand

RECOMMENDED USE

This product is recommended as a body filler for automotive surfaces and leveling of wooden surfaces.

*Used for Automotive applications.

TECHNICAL SPECIFICATIONS

Color	White, Grey, Red and Brown
Finish	Matt
Spreading Rate	7.5 - 9.5 m ² / litre
Volume Solids	38 ± 2%
Specific Gravity	1.33 ± 0.05
Dry Film Thickness	40 - 50 Microns / Coat
Wet Film Thickness	100 - 130 Microns / Coat
Packaging Size	1L + 3.6L + 18L
Flash Point	7°C



CHROMA NC PUTTY

APPLICATION DATA

Application Method	Glazing Knife
Thinner (Volume)	Emirates Lacquer Thinner (Ready to use)
Mixing Ratio (Volume)	NA
Pot Life @30° C	NA

SURFACE PREPARATION

The surface must be clean, dry and free from oil, grease, dust and loose particles prior to application.

DRY TIME

Touch Dry	30 - 60 minutes
Dry to Recoat	3 - 4 hours
Full Dry	4 - 5 hours

*Based on temperatures at 30 degrees Celsius.

*Humidity, air movement, film thickness and number of coats may impact dry time.

RECOMMENDED SYSTEM

Chroma NC Primer	1 Coat
Chroma NC Putty	2 Coats
Chroma NC Primer	1 Coat
Chroma NC Topcoat	2 Coats



CHROMA NC PUTTY

HEALTH & SAFETY

Oil-based (solvent-based) paints require extra precautions due to their fumes and flammability. We highly recommend following your local safety regulations. Ensure you are working in a well-ventilated space to reduce the inhalation of harmful vapors and wear a suitable respirator mask when painting in enclosed areas. To avoid skin and eye contact, always wear protective gear such as solvent-resistant gloves and goggles. In case of skin contact, wash thoroughly with soap and water. If the paint gets into your eyes or is accidentally ingested, seek medical attention immediately. Please keep paints and solvents out of the reach of children and pets.

STORAGE & HANDLING

We highly recommend storing our paints in proper storage conditions as per your local regulations. Keep the paint container tightly sealed and away from direct sunlight and extreme temperatures. Ensure oil-based paints are stored away from any ignition sources, such as heat, sparks, or open flames, due to their flammability. Do not return unused paint to the original container to prevent contamination. For disposal, follow local hazardous waste protocols. Avoid washing brushes or spills down drains, as these paints require special disposal. Handle with care and mix thoroughly before use

SHELF LIFE

*For best results, please use within 18 months of the production date.

*Shelf life can be highly affected by storage conditions, in particular, the method of sealing the container.

DISCLAIMER

The data provided is based on our present state of knowledge and is intended to provide general information about our product and its uses. Emirates Paints will not be responsible for any claims after the product had been used without proper testing. Any existing industrial property rights must be observed. The quality of our product is guaranteed under our general conditions of sales.

