API DEVELOPED FOR THE PROJECT

1. Register User
   End Point: /register
   Data format:

```
{
    "name":"Shah Adil",
    "email":"s@shah.com",
    "password":"shah@123",
    "phone":"7878787878",
     "role": ""
    }
```

2. /Login user

   End Point: /Login
   Data format:

```
{
    "email":"shat@shah.com",
    "password":"shah@123"
}
```

3. addProduct

   End Point: /Login
   Data format:

```
{
    "PRODUCT_NAME":"Shah Adil",
    "PRODUCT_DESCRIPTION":"shat@shah.com",
    "PRODUCT_QUANTITY":"shah@123",
    "PRODUCT_PRICE":"778"
    }
```

HEADER: Authorization
VALUE: Bearer <your token here>

4 deleteProduct
   End Point: /deleteProduct
   Data format:

```
{   "PRODUCT_ID" : "Shahyw2hf" }
```

HEADER: Authorization
VALUE: Bearer <your token here>

5 deleteProduct

5. updateProduct
End Point: / updateProduct
Data format:

```json
{
    "PRODUCT_DESCRIPTION":"shat@shah.com",
    "PRODUCT_QUANTITY":"67",
    "PRODUCT_PRICE":"778",
    "PRODUCT_ID" : "Shahs1wl8"
    }
```

HEADER: Authorization
VALUE: Bearer <your token here>

6. seeAll
End Point: / seeAll
 HEADER: Authorization
VALUE: Bearer <your token here>