

Figure 1: Pinout & Configuration

STM32CubeMX Assignment2.ioc: STM32F103C8Tx

File Window Help myST

Home > STM32F103C8Tx > Assignment2.ioc - Pinout & Configuration > **GENERATE CODE**

Pinout & Configuration Clock Configuration Project Manager Tools

Software Packs Pinout

Pinout view System view

Categories A->Z

System Core

- DMA
- GPIO
- IWDG
- NVIC
- RCC
- ⚠ SYS
- WWDG

Analog >

Timers

- RTC
- TIM1
- ⚠ TIM2
- ✓ TIM3
- TIM4

Connectivity >

Computing >

Middleware and Soft... >

STM32F103C8Tx LQFP48

GPIO_Exti1 PA1

GPIO_Exti2 PA2

GPIO_Exti3 PA3

I2C_SCL PB10

I2C_SDA PB11

VDD VSS PA13 PA12 PA11 PA10 PA9 PA8 PB15 PB14 PB13 PB12

VBAT PC13... PC14... PC15... PD0-O... PD1-O... NRST VSSA VDDA PA0-...

10:15 AM 7/2/2026

Figure 2: I2C2 Configuration

STM32CubeMX Assignment2.ioc: STM32F103C8Tx

STM32CubeMX

FileWindowHelp

myST

10

f

▶

X

ST

HomeSTM32F103C8TxAssignment2.ioc - Pinout & ConfigurationGENERATE CODE

Pinout & Configuration

Clock Configuration

Project Manager

Tools

Software Packs

Pinout

Search

Categories

A->Z

NVIC

RCC

▲SYS

WWDG

Analog

Timers

RTC

TIM1

▲TIM2

✓TIM3

TIM4

Connectivity

CAN

I2C1

✓I2C2

SPI1

SPI2

USART1

✗USART2

✗USART3

USB

I2C2 Mode and Configuration

Mode

I2C I2C

Configuration

Reset Configuration

Parameter Settings

User Constants

NVIC Settings

DMA Settings

GPIO Settings

Search Signals

Search (Ctrl+F)

Show only Modified Pins

Pin Name	Signal on Pin	GPIO output level	GPIO mode	GPIO Pull-up/P...	Maximum output...	User Label	Modified
PB10	I2C2_SCL	n/a	Alternate Functi...	n/a	High		☐
PB11	I2C2_SDA	n/a	Alternate Functi...	n/a	High		☐

Pinout view

System view

GPIO_Output

GPIO_EXTI1

GPIO_EXTI2

PA0

PA1

PA2

PA3

PA4

PA5

PA6

PA7

PB0

PB1

PB2

PB10

PB11

VSS

VDD

PC13

PC14

PC15

PD0

PD1

NRST

VSSA

VDDA

VBAT

VSS

PA15

PA14

PA13

PA12

PA11

PA10

PA9

PA8

PB15

PB14

PB13

PB12

I2C2_SCL

I2C2_SDA

Type here to search

KOG +3,12%

10:18 AM

7/2/2026

Figure 3: TIM3 Parameter Settings

STM32CubeMX Assignment2.ioc: STM32F103C8Tx

File Window Help myST

Home > STM32F103C8Tx > Assignment2.ioc - Pinout & Configuration > **GENERATE CODE**

Pinout & Configuration Clock Configuration Project Manager Tools

Software Packs Pinout

Search (Ctrl+F)

Categories A-Z

- NVIC
- RCC
- SYS
- WWDG

Analog >

Timers >

- RTC
- TIM1
- TIM2
- TIM3**
- TIM4

Connectivity >

- CAN
- I2C1
- I2C2**
- SPI1
- SPI2
- USART1
- USART2**
- USART3**
- USB

TIM3 Mode and Configuration

Mode

Slave Mode: Disable

Trigger Source: Disable

☒ Internal Clock

Channel1: Disable

Channel2: Disable

Channel3: Disable

Channel4: Disable

Configuration

Reset Configuration

Parameter Settings User Constants NVIC Settings DMA Settings

Configure the below parameters:

Search (Ctrl+F)

Counter Settings

- Prescaler (PSC - 16 bits value): 7199
- Counter Mode: Up
- Counter Period (AutoReload Register - 16 bits value): 4999
- Internal Clock Division (CKD): No Division
- auto-reload preload: Disable

Trigger Output (TRGO) Parameters

- Master/Slave Mode (MSM bit): Disable (Trigger input effect not delayed)
- Trigger Event Selection: Reset (UG bit from TIMx_EGR)

Pinout view System view

STM32F103C8Tx LQFP48

GPIO pins: PA0-PA15, PB0-PB15, PC0-PC15, PD0-PD15, PE0-PE15, PF0-PF15, PG0-PG15, PH0-PH15, PI0-PI15, PJ0-PJ15, PK0-PK15, PL0-PL15, PM0-PM15, PN0-PN15, PO0-PO15

GPIO pin assignments:

- GPIO_Output: PA0
- GPIO_EXTI1: PA1
- GPIO_EXTI2: PA2
- I2C_SCL: PB10
- I2C_SDA: PB11

Windows taskbar: 10:19 AM 7/2/2026

STM32CubeMX Assignment2.ioc: STM32F103C8Tx

STM32CubeMX

FileWindowHelpmyST

HomeSTM32F103C8TxAssignment2.ioc - Pinout & ConfigurationGENERATE CODE

Pinout & ConfigurationClock ConfigurationProject ManagerTools

Software PacksPinout

SearchCategoriesA-ZSystem CoreDMAGPIOIWDGNVICRCCSYSWWDGAnalogTimersRTC TIM1TIM2TIM3TIM4ConnectivityCANI2C1I2C2SPI1SPI2

NVIC Mode and Configuration

Configuration

NVICCode generation

Priority Group4 bits for pre-emption priority 0 bit.Sort by Preemption Priority and Sub PrioritySort by interrupts names

SearchSearch (Ctrl+F)Showavailable interruptsForce DMA channels Interrupts

NVIC Interrupt Table	Enabled	Preemption Priority	Sub Priority
Non maskable interrupt	☒	0	0
Hard fault interrupt	☒	0	0
memory management fault	☒	0	0
Prefetch fault, memory access fault	☒	0	0
Undefined instruction or illegal state	☒	0	0
System service call via SWI instruction	☒	0	0
Debug monitor	☒	0	0
Pendable request for system service	☒	0	0
Time base: System tick timer	☒	15	0
PVD interrupt through EXTI line 16	☐	0	0
Flash global interrupt	☐	0	0
RCC global interrupt	☐	0	0
EXTI line1 interrupt	☒	0	0
EXTI line2 interrupt	☒	0	0
EXTI line3 interrupt	☒	0	0
TIM3 global interrupt	☒	0	0
I2C2 event interrupt	☐	0	0
I2C2 error interrupt	☐	0	0

☐ EnabledPreemption PrioritySub Priority

Pinout viewSystem view

Pinout diagram of the STM32F103C8Tx LQFP48 package. The diagram shows the physical layout of the 48 pins, with labels for various functions such as VDD, VSS, VBAT, PC13, PC14, PC15, PDD, PD1, NRST, VSSA, VDDA, PA0, PA1, PA2, PA3, PA4, PA5, PA6, PA7, PA8, PA9, PA10, PA11, PA12, PA13, PA14, PA15, PB0, PB1, PB2, PB3, PB4, PB5, PB6, PB7, PB8, PB9, PB10, PB11, PB12, PB13, PB14, PB15, I2C2_SCL, I2C2_SDA, VSS, and VDD. The package is labeled STM32F103C8Tx LQFP48.

Type here to search

10:20 AM 7/2/2026