

LinkUp Vibes & U Vibe

Developer Change Notes — Profile, Follow, Gifting & Thank-You Systems

Prepared for: LinkUp development team

Covers: 01-Consumer App/LinkUp-App.html (phone app) and 06-Vibes Website/index.html (web app)

Canonical source folder: **Desktop/New Master File/**

What's in this document

- A plain-English summary of every feature added to Vibes and U Vibe in this round of work.
- Which shared systems these features reuse (messaging, coin economy, gift ledger) vs. what's new.
- The exact, current code for every new function, plus the surgical edits made to existing functions — copy-pasted directly from the live files, not reconstructed from memory.
- A table of new localStorage/DB keys and in-memory state introduced.
- Known limitations and what's intentionally fake/demo data vs. real app state.

1. Overview

This round of work turned the Vibes and U Vibe feeds from simple photo/post streams into a fuller social layer: tapping a name now opens a real Instagram-style profile (stats, bio, follow, shop, a supporter leaderboard), gifting ("Send a Vibe") now closes the loop with an automatic thank-you reply, and a proper "Say Thank You" composer was added in three places so gratitude is never more than one tap away. Every one of these features was then replicated in U Vibe (the campus feed), reusing the same underlying systems wherever the data model already lined up.

Everything below is live in both platforms — the phone app (LinkUp-App.html) and the web app (index.html) — with feature parity. Where the two implementations differ it's only in syntax (the phone app is ES5 with string concatenation; the website is modern JS with template literals) and in how a "page" is shown (the phone app uses a modal; the website's Vibes/U Vibe profile is now a full page reached via the app's own router, not a modal).

2. Files Touched

- **01-Consumer App/LinkUp-App.html** — the phone app. Single self-contained HTML file.
- **06-Vibes Website/index.html** — the desktop web app. Single self-contained HTML file.
- No backend/schema files were touched. Nothing here requires a database migration — every new piece of state is either an in-memory JS object (phone app) or a new localStorage key read/written through the existing DB.get ()/DB.set () helper (website).

3. Shared Systems — what's reused vs. new

Before adding anything, it's worth knowing what already existed and was deliberately reused, rather than duplicated:

- **Messaging** (vibeChats / lk_vibe_chats) — Vibes and U Vibe already shared one inbox before this work (U Vibe's message icon already called the Vibes openVibeInbox ()). Every new feature that sends a message (auto thank-you, manual Thank You composer) writes into this same thread store, keyed by plain name/handle string.
- **Coin economy & gift catalog** (VIBES / VIBES_GIFTS) — the person-to-person "Send a Vibe" gift catalog (Wha Gwaan → Island Royalty) already existed for the dating swipe deck. It's now also reachable from Vibes and U Vibe profiles/posts — same catalog, same coin balance, no fork.
- **Gift ledger** (GIFT_ACTIVITY / lk_gift_activity) — the app-wide "who sent/received what" ledger under Profile → Gifts → Activity already existed. The new header-level "■ Say Thank You" picker and the new reaction buttons both read/write this same ledger — it is genuinely one shared list across Vibes and U Vibe, not two separate ones.
- **Deterministic "fake" social-proof numbers** — follower counts, the "Followed by X, Y and N others" line, and the Top Vibes Senders leaderboard are *not* backed by a real social graph (there is no multi-user backend). They're generated by hashing the handle/name into a stable number, so the same person always shows the same follower count on every visit, but it is cosmetic, not real relationship data. This mirrors a pattern already used elsewhere in the app for demo data.

Note on naming: the phone app is ES5 (var/function, string concatenation with +). The website is modern JS (const/let, template literals). Function names are suffixed **Web** on the website purely to avoid collisions where both files happen to share a global scope pattern — they are independent

implementations of the same feature, not shared code between the two files.

4. Feature: Instagram-Style Profile Pages

Tapping a person's name/avatar anywhere in Vibes or U Vibe (a post header, a search result, a story ring) now opens a full profile: avatar, stats row (Posts / Followers / Following), a category badge, a "Followed by..." mutuals line, My Earnings, Follow/Message/Send-a-Vibe actions, a Shop section, the Top Vibes Senders leaderboard, and a 3-column posts grid.

Phone app: this is a modal (`openVibeProfile()` / `openUVibeProfile()`), consistent with how every other detail view in the phone app works.

Website: this is a full page reached through the app's own router (`go('vibeProfile')` / `go('uvibeProfile')`), with a Back link — this matches a real desktop profile page (e.g. Instagram.com) rather than a popover, and was a deliberate change requested mid-project (the website version briefly used a modal too, before being converted).

4.1 Vibes — Phone app

New helper functions (posts grid, follow state, category badge, mutuals line):

01-Consumer App/LinkUp-App.html

```
// Posts grid for another user's profile – Instagram-style: every post type shows here.
// Reels open the full-screen viewer scoped to this handle; Photos/Carousels open the
// existing comments sheet (which already renders the image), matching how the main
// feed opens a single post.
function userPosts(handle){
  return (typeof vibes!=='undefined'?vibes:[]).filter(function(p){return p.user===handle;});
}
function profilePostsGrid(handle){
  var posts=userPosts(handle);
  if(!posts.length)return '<p class="text-center text-slate-400 font-bold py-10 text-sm">No posts yet.</p>';
  var reels=userReels(handle);
  return '<div class="grid grid-cols-3 gap-0.5">'+posts.map(function(p){var img=p.imgs?p.imgs[0]:p.img;
    var icon=p.type==='Reel'?'clapperboard':(p.type==='Carousel'?'copy':'');
    var tap=p.type==='Reel'
      ?'closeModal();openReels('+reels.indexOf(p)+','+handle.replace('/','/g','')+''+
      :'closeModal();openVibeComments('+p.id+'');
    return '<button onclick="'+tap+'" class="relative aspect-square bg-slate-100">'+
      ''+
      (icon?'<i data-lucide="'+icon+'" class="w-3.5 h-3.5 absolute top-1.5 right-1.5 text-white drop-shadow"></i>:'+
      '<span class="absolute bottom-1 left-1 text-white text-[10px] font-black flex items-center gap-0.5 drop-shadow"><i data-lucide="heart" class="w-3
h-3" fill="currentColor"></i>'+fmt(p.likes)+'</span></button>';
  }).join('')+</div>';
}
// Following state is deliberately its own in-memory object (like vibeChats/vibeComments) –
// Vibes state stays separate from LinkUp's own follow/match graph.
let vibeFollowing={};
function vibeFollowerSeed(handle){
  var h=0;for(var i=0;i<handle.length;i++){h=(h*31+handle.charCodeAt(i))>>>0;
  return 60+(h%3200);
}
function vibeFollowerCount(handle){return vibeFollowerSeed(handle)+(vibeFollowing[handle]?1:0);}
```

```

var VIBE_CATEGORIES=['Creator','Artist','Traveler','Foodie','DJ','Photographer','Dancer','Chef'];
function vibeCategory(handle){return VIBE_CATEGORIES[vibeFollowerSeed(handle+'c')%VIBE_CATEGORIES.length];}
// "Followed by X, Y and N others" – cheap social-proof line, same seeded-fake approach as the
// follower count (deterministic per handle, not meant to be a real mutuals query).
function vibeMutualsLine(handle){
  var others=vibesPeople().filter(function(p){return p.handle!==handle;});
  if(!others.length)return '';
  var seed=vibeFollowerSeed(handle+'m');
  var a=others[seed%others.length], b=others[(seed+7)%others.length];
  var extra=3+(seed%27);
  var avs=[a,b].map(function(p){return p.img?'':<div class="h-6 w-6 rounded-full border-2 border-white -ml-1.5 first:ml-0 grid place-items-center text-white text-[8px] font-black" style="background: linear-gradient(135deg, #6366f1, #ec4899)">'+p.name.slice(0,1).toUpperCase()+'</div>';}).join('');
  return '<div class="flex items-center justify-center gap-2 pb-1"><div class="flex">'+avs+'</div><p class="text-[11px] text-slate-500">Followed by <b>'+a.name+'</b>, <b>'+b.name+'</b> and '+extra+' others</p></div>';
}
function vibeFollowBtnHtml(handle){
  var on=!!vibeFollowing[handle];
  return '<button id="vibeFollowBtn" onclick="vibeToggleFollow(''+handle.replace(/'/g,'')+'')" class="rounded-2xl py-3 font-black flex items-center justify-center gap-1.5 '+ (on?'border-2 border-slate-200 text-slate-700':'text-white')+'"'+ (on?'':'style="background: var(--lk-blue)")'+>'+ (on?'Following':'Follow')+'</button>';
}
function vibeToggleFollow(handle){
  vibeFollowing[handle]=!vibeFollowing[handle];
  var btn=$('#vibeFollowBtn');
  if(btn)btn.outerHTML=vibeFollowBtnHtml(handle);
  var cnt=$('#vibeFollowerCount');if(cnt)cnt.textContent=fmt(vibeFollowerCount(handle));
  toast(vibeFollowing[handle]?'Following '+handle:'Unfollowed '+handle);
  if(window.lucide)lucide.createIcons();
}

```

The full profile modal (assembles everything above, plus My Earnings, Shop, and the leaderboard):

```

function openVibeProfile(handle,loc){
  var pr=vibeUserProfile(handle);
  var name=pr?pr.name:handle.replace(/@/, '');
  var img=pr?pr.img:'';
  var avatar=img?'':<div class="h-20 w-20 rounded-full mx-auto grid place-items-center text-white font-black text-2xl border-4 border-white shadow" style="background: linear-gradient(135deg, #6366f1, #ec4899)">'+handle.slice(1,3).toUpperCase()+'</div>';
  var meta=pr?(pr.flag+' '+pr.country+(pr.age?' · '+pr.age:'))+(typeof pr.km!=='undefined'? · ■ '+pr.km+' km':'');
  var linkUpRow=pr
    ? '<button onclick="closeModal();go('dating');toast('Opening '+name.replace(/'/g,'')+' on LinkUp')" class="w-full rounded-2xl py-3 font-black text-white flex items-center justify-center gap-1.5" style="background: linear-gradient(135deg, #db2777, #f43f5e)"><i data-lucide="heart" class="w-4 h-4"></i> View LinkUp Profile</button>'
    : '<div class="rounded-2xl bg-slate-50 text-slate-500 text-[12px] font-bold p-3 text-center">Not yet on LinkUp dating – you can still message or send a Vibe.</div>';
  var postCount=userPosts(handle).length;
  var statsRow='<div class="flex items-center justify-center gap-6 py-1"><div class="text-center"><p class="font-black text-sm">'+postCount+'</p><p class="text-[10px] text-slate-400 font-bold uppercase">Posts</p></div><div class="text-center"><p id="vibeFollowerCount" class="font-black text-sm">'+fmt(vibeFollowerCount(handle))+</p><p class="text-[10px] text-slate-400 font-bold uppercase">Followers</p></div><div class="text-center"><p class="font-black text-sm">'+fmt(vibeFollowerSeed(handle+'f'))+'</p><p class="text-[10px] text-slate-400 font-bold uppercase">Following</p></div></div>';
}

```

```

    openModal('<div class="p-5 text-center text-white" style="background:linear-gradient(135deg,#6366f1,#2f9bef 55%,#ec4899)"><div class="flex
justify-end"><button onclick="closeModal()"><i data-lucide="x" class="w-5 h-5"></i></button></div>'+avatar+'<h3 class="text-xl font-black
mt-2">'+handle+'</h3><p class="text-white/85 text-xs">'+meta+'</p>'+(pr?'<span class="inline-block mt-1 rounded-full bg-white/20 px-2.5 py-0.5
text-[10px] font-black">■ Also on LinkUp</span>':'')+'</div>'+
    '<div class="p-4 space-y-2">'+
        '<button onclick="closeModal();openMyEarnings('vibe')" class="w-full flex items-center justify-between rounded-2xl px-4 py-2.5 text-white"
style="background:linear-gradient(135deg,#059669,#10b981)"><span class="flex items-center gap-2 font-black text-sm"><i data-lucide="trending-up"
class="w-4 h-4"></i>My Earnings · $'+(affEarnings.pending+affEarnings.available+affEarnings.paid).toFixed(2)+'</span><i data-lucide="chevron-right"
class="w-4 h-4"></i></button>'+
        '<p class="text-center text-[11px] font-black text-slate-400 uppercase
tracking-wide">'+vibeCategory(handle)+'</p>'+statsRow+vibeMutualsLine(handle)+linkupRow+
        '<div class="grid grid-cols-2 gap-2">'+vibeFollowBtnHtml(handle)+'<button onclick="vibeMessage(''+name.replace(/'/g,"")+',''+(img||'')+''')"
class="rounded-2xl py-3 font-black border-2 border-slate-200 flex items-center justify-center gap-1.5"><i data-lucide="message-circle" class="w-4
h-4"></i> Message</button></div>'+
        '<div class="grid grid-cols-2 gap-2"><button onclick="vibeSendVibeTo(''+name.replace(/'/g,"")+',''+(img||'')+''')" class="rounded-2xl py-3 font-black
text-white flex items-center justify-center gap-1.5" style="background:linear-gradient(135deg,#f59e0b,#ec4899)">■ Send a Vibe</button>'+
        '<button onclick="vibeLinkUp(''+name.replace(/'/g,"")+',''+(img||'')+''')" class="rounded-2xl py-3 font-black text-white flex items-center
justify-center gap-1.5" style="background:var(--lk-blue)"><i data-lucide="user-plus" class="w-4 h-4"></i> Link Up</button></div>'+
        '</div>'+profileShopSection(handle)+profileTopSenders(handle)+'<div class="px-0.5 pb-2">'+profilePostsGrid(handle)+'</div>');
    setTimeout(function(){lucide.createIcons();},30);
}

```

4.2 Vibes — Website (full page, not a modal)

Same feature set, ported to a page reached via the router. Helper functions:

06-Vibes Website/index.html

```
function userPostsWeb(handle){
  const hidden=DB.get('lk_vibes_hidden',[]);
  return DB.get('lk_vibes_posts',SEED.vibes_posts).filter(p=>p.handle===handle&&!hidden.includes(p.id));
}
function vibesPeopleWeb(){
  const map={};
  DB.get('lk_vibes_posts',SEED.vibes_posts).forEach(p=>{if(!map[p.handle])map[p.handle]={handle:p.handle,avatar:p.avatar}});
  SEED.stories.forEach(s=>{if(!map[s.handle])map[s.handle]={handle:s.handle,avatar:s.avatar}});
  return Object.values(map);
}
// Following state persisted like vibeChats (DB/localStorage), separate from any LinkUp
// dating follow/match graph. Follower count is a deterministic fake (hashSeed), same
// approach as the phone app's vibeFollowerSeed, so it's stable across renders/handles.
function vibeFollowingAll(){return DB.get('lk_vibe_following',{});}
function vibeIsFollowing(handle){return !!vibeFollowingAll()[handle];}
function vibeFollowerCountWeb(handle){return 60+(hashSeed(handle)%3200)+(vibeIsFollowing(handle)?1:0);}
function vibeToggleFollowWeb(handle){
  const all=vibeFollowingAll();
  all[handle]=!all[handle];
  DB.set('lk_vibe_following',all);
  const btn=$( 'vibeFollowBtnWeb' );
  if(btn)btn.outerHTML=vibeFollowBtnHtmlWeb(handle);
  const cnt=$( 'vibeFollowerCountWeb' );if(cnt)cnt.textContent=num(vibeFollowerCountWeb(handle));
  toast(all[handle]?'Following '+handle:'Unfollowed '+handle);
  if(window.lucide)lucide.createIcons();
}
function vibeFollowBtnHtmlWeb(handle){
  const on=vibeIsFollowing(handle);
  return `<button id="vibeFollowBtnWeb" onclick="vibeToggleFollowWeb('${handle}')" class="rounded-xl px-5 py-2 text-sm font-black flex items-center justify-center gap-1.5 ${on?'border-2 border-slate-200 text-slate-700':'text-white'}"
  ${on?'':'style="background:var(--lk-blue)"}>${on?'Following':'Follow'}</button>`;
}
const VIBE_CATEGORIES_WEB=['Creator','Artist','Traveler','Foodie','DJ','Photographer','Dancer','Chef'];
function vibeCategoryWeb(handle){return VIBE_CATEGORIES_WEB[hashSeed(handle+'c')%VIBE_CATEGORIES_WEB.length];}
function vibeMutualsLineWeb(handle){
  const others=vibesPeopleWeb().filter(p=>p.handle!==handle);
  if(!others.length)return '';
  const seed=hashSeed(handle+'m');
  const a=others[seed%others.length], b=others[(seed+7)%others.length];
  const extra=3+(seed%27);
  const avs=[a,b].map(p=>``).join('');
  return `<div class="flex items-center gap-2"><div class="flex">${avs}</div><p class="text-[13px] text-slate-500">Followed by <b class="text-slate-700">${a.handle.replace(/^\//,'')}</b>, <b class="text-slate-700">${b.handle.replace(/^\//,'')}</b> and ${extra} others</p></div>`;
}
function profilePostsGridWeb(handle){
  const posts=userPostsWeb(handle);
```

```

if(!posts.length)return `
```

The router-driven profile page and its opener:

```

// A user's Vibes profile is its own page (VIEWS.vibeProfile), not a modal – selecting a name
// in Vibes navigates like any other route via go(), with a Back link to wherever you came from.
let vibeProfileHandle=null, vibeProfileBackView='vibes';
function openUserProfile(handle,backView){
  vibeProfileHandle=handle;
  vibeProfileBackView=backView||current||'vibes';
  go('vibeProfile');
}
// Layout mirrors Instagram's desktop profile header: avatar left, everything else stacked
// right of it (handle+badge, stats row, bio line, mutuels, action buttons) – not the
// centered/stacked mobile-card look this used before.
VIEWS.vibeProfile=()=>>{
  const handle=vibeProfileHandle;
  if(!handle)return `

{const a=affEarnings();return a.pending+a.available+a.paid;}}())}</p></button>
    <div class="card p-6 md:p-8">
      <div class="flex flex-col sm:flex-row gap-6 sm:gap-10">
        


```



```

<div class="flex-1 min-w-0 w-full">
  <div class="flex items-center gap-2 flex-wrap">
    <h1 class="text-2xl font-black">${handle}</h1>
    ${pr&&pr.verified?'<i data-lucide="badge-check" class="w-5 h-5 text-sky-500"></i>':''}
  </div>
  ${pr?'<p class="text-slate-700 font-semibold mt-0.5">${pr.name}</p>':''}
  <div class="flex items-center gap-6 mt-4 flex-wrap">
    <p class="text-sm"><b class="text-base">${postCount}</b> posts</p>
    <p class="text-sm"><b id="vibeFollowerCountWeb" class="text-base">${num(vibeFollowerCountWeb(handle))}</b> followers</p>
    <p class="text-sm"><b class="text-base">${num(60+(hashSeed(handle+'f')%3200))}</b> following</p>
  </div>
  <p class="text-sm text-slate-600 font-semibold mt-3 flex items-center gap-1">${vibeCategoryWeb(handle)}${p&&p.location?'<span
class="text-slate-400">· <i data-lucide="map-pin" class="w-3 h-3 inline"></i> ${p.location}</span>':''}</p>
  <div class="mt-2">${vibeMutualsLineWeb(handle)}</div>
  <div class="flex flex-wrap items-center gap-2 mt-4">
    ${vibeFollowBtnHtmlWeb(handle)}
    <button onclick="openVibeThread('${handle}')" class="rounded-xl px-5 py-2 text-sm font-black border-2 border-slate-200 flex items-center
justify-center gap-1.5"><i data-lucide="message-circle" class="w-4 h-4"></i>Message</button>
  </div>
</div>
</div>
  <button onclick="openSendVibe('${handle}')" class="w-full mt-6 rounded-2xl py-3 font-black text-white flex items-center justify-center gap-1.5"
style="background: linear-gradient(135deg, #f59e0b, #ec4899)">■ Send a Vibe</button>
</div>
  ${profileShopSectionWeb(handle)}
  ${profileTopSendersWeb(handle)}
  <div class="mt-4">${profilePostsGridWeb(handle)}</div>
</div>`;
};

```

5. Feature: Shop Section on Profile

Any post the person has tagged with a product or event (phone app: `p.shop`; website: `p.tag` — this was already the two platforms' existing field naming for a tagged product/event, kept as-is) now shows as a real storefront row on their profile. Tapping it reuses the existing buy/ticket flow (`openVibeTag()`), so nothing new had to be built for checkout — this is purely a new way to *reach* an existing detail screen.

5.1 Phone app

01-Consumer App/LinkUp-App.html

```
// Shop section – every post this handle has tagged with a product/event (p.shop), turning
// the profile into a real storefront instead of just a photo grid. Reuses the existing
// openVibeTag() detail flow so buying/tickets works exactly like it does from the feed.
function userShopItems(handle){
  return (typeof vibes!=='undefined'?vibes:[]).filter(function(p){return p.user===handle&&p.shop;});
}
function profileShopSection(handle){
  var items=userShopItems(handle);
  if(!items.length)return '';
  return '<div class="px-1 pb-2"><p class="text-[11px] font-black text-slate-400 uppercase mb-2 flex items-center gap-1.5"><i data-lucide="shopping-bag"
class="w-3.5 h-3.5"></i> Shop '+handle+'</p><div class="space-y-2">'+
  items.map(function(p){var t=p.shop, ev=t.kind==='event', img=p.imgs?p.imgs[0]:p.img;
    return '<button onclick="openVibeTag(''+p.id+'')" class="w-full flex items-center gap-3 rounded-2xl border border-slate-100 p-2.5 text-left"><div class="flex-1 min-w-0"><p class="font-black text-sm truncate">'+(ev?'■■■
': '')+t.name+'</p><p class="text-[11px] text-slate-500">'+t.price.toFixed(2)+'</p></div><span class="rounded-full text-white px-3 py-1.5 text-xs
font-black shrink-0" style="background:var(--lk-blue)">'+(ev?'Tickets': 'Shop')+'</span></button>';
  }).join('')+</div></div>';
}
```

5.2 Website

06-Vibes Website/index.html

```
function userShopItemsWeb(handle){
  return DB.get('lk_vibes_posts', SEED.vibes_posts).filter(p=>p.handle===handle&&p.tag);
}
function profileShopSectionWeb(handle){
  const items=userShopItemsWeb(handle);
  if(!items.length)return '';
  return `<div class="card p-5 mt-4"><p class="text-xs font-black text-slate-400 uppercase mb-3 flex items-center gap-1.5"><i data-lucide="shopping-bag"
class="w-3.5 h-3.5"></i>Shop ${handle}</p><div class="space-y-2">${items.map(p=>{
  const t=p.tag, ev=t.kind==='event', img=(p.imgs||[p.media])[0];
  return `<button onclick="openVibeTag(${p.id})" class="w-full flex items-center gap-3 rounded-2xl border border-slate-100 p-2.5 text-left
hover:bg-slate-50"><div class="flex-1 min-w-0"><p class="font-black text-sm
truncate">${ev?'■■■ ': ''}${t.title}</p><p class="text-[11px] text-slate-500">${money(t.price)}</p></div><span class="rounded-full text-white px-3 py-1.5
text-xs font-black shrink-0" style="background:var(--lk-blue)">${ev?'Tickets': 'Shop'}</span></button>`;
}).join('')}</div></div>`;
}
```


6. Feature: Top Vibes Senders Leaderboard

A ■■■■ ranked list of top gifters shows on every profile. **Important caveat for the dev team:** the app has no real backend and therefore no actual cross-user gift ledger to query for "who has sent this specific person the most coins." This leaderboard is **deterministic demo data** — three names picked from a small pool, seeded by hashing the profile handle, so it's stable across visits but not real. When a real backend/gift-ledger-by-recipient table exists, `vibeTopSenders()` / `vibeTopSenderWeb()` are the two functions to swap out for a real query — everything downstream (the leaderboard row markup, the Thank buttons) is agnostic to where the data comes from.

6.1 Phone app

01-Consumer App/LinkUp-App.html

```
// Top Vibes Senders – a lightweight, deterministic-fake leaderboard (same seeded-fake
// approach as vibeFollowerCount) since the app has no real cross-user gift ledger to query;
// purely social-proof texture, not tied to actual GIFT_ACTIVITY (which only tracks the
// logged-in user's own sent/received gifts).
var VIBE_SUPPORTER_POOL=['Aaliyah','Marcus','Simone','Renee','Devon','Kayla','Chris','Nadia','Josh','Tia'];
function vibeTopSenders(handle){
  var seed=vibeFollowerSeed(handle+'ldb'),picks=[];
  for(var i=0;i<3;i++){
    var idx=(seed+i*13)%VIBE_SUPPORTER_POOL.length;
    picks.push([VIBE_SUPPORTER_POOL[idx],200+((seed*(i+2))%1800)]);
  }
  picks.sort(function(a,b){return b[1]-a[1]});
  return picks;
}
function profileTopSenders(handle){
  var list=vibeTopSenders(handle),medals=['■','■','■'];
  return '<div class="px-1 pb-2"><p class="text-[11px] font-black text-slate-400 uppercase mb-2 flex items-center gap-1.5"><i data-lucide="crown"
class="w-3.5 h-3.5"></i> Top Vibes Senders</p><div class="space-y-1.5">'+
  list.map(function(s,i){return '<div class="flex items-center justify-between rounded-xl bg-slate-50 px-3 py-2"><span class="text-sm
font-bold">'+medals[i]+' '+s[0]+'</span><div class="flex items-center gap-2"><span class="text-xs font-black text-amber-600">■
'+fmt(s[1])+'</span><button onclick="openThankSender(''+s[0].replace(/'/g,"")+'')" class="rounded-full bg-white border border-slate-200 px-2.5 py-1
text-[11px] font-black text-slate-600">■ Thank</button></div></div>'}).join('')+</div></div>';
}
```

6.2 Website

06-Vibes Website/index.html

```
const VIBE_SUPPORTER_POOL_WEB=['Aaliyah','Marcus','Simone','Renee','Devon','Kayla','Chris','Nadia','Josh','Tia'];
function vibeTopSendersWeb(handle){
  const seed=hashSeed(handle+'ldb'); const picks=[];
  for(let i=0;i<3;i++){
    const idx=(seed+i*13)%VIBE_SUPPORTER_POOL_WEB.length;
    picks.push([VIBE_SUPPORTER_POOL_WEB[idx], 200+((seed*(i+2))%1800)]);
  }
}
```

```

    picks.sort((a,b)=>b[1]-a[1]);
    return picks;
}
function profileTopSendersWeb(handle){
    const list=vibeTopSendersWeb(handle), medals=['■','■','■'];
    return `
```

7. Feature: Send a Vibe Gifting + Automatic Thank-You Reply

"Send a Vibe" (🎁) already existed as a coin-gift feature for the dating swipe deck (catalog: Wha Gwaan → Island Royalty). It's now reachable from: (a) every Vibes/U Vibe profile page as a full-width button, and (b) a small 🎁 icon directly on every feed post header, for a one-tap gift without opening the profile first.

New behavior: about 1.5 seconds after a gift is sent, the recipient automatically "replies" with a thank-you message in the shared Vibes/U Vibe chat thread (randomly picked from VIBE_THANKYOU_REPLIES, and it name-checks the specific gift sent), plus a notification. This was added because sending a gift previously felt like a one-way action with no acknowledgment.

7.1 Phone app — vibeSend() (existing function, gift-completion tail rewritten)

```
function vibeSend(){if(!vibeSel)return;var c=vibeSel[2];if(c>coins){toast('Not enough Coins');return;}if(c)setCoins(coins-c);
  if(vibeRecipient){var orig=profiles.find(function(p){return p.name===vibeRecipient.name;});if(orig)orig.earned=(orig.earned||0)+c;}
  recordGift('SENT','Vibe · '+vibeSel[0],c,vibeRecipient?vibeRecipient.name:'-');
  var rn=vibeRecipient?vibeRecipient.name:'them',giftName=vibeSel[0],giftEmoji=vibeSel[1];closeModal();
  toast(giftEmoji+' '+giftName+' sent! '+rn+' earned '+c+' 🎁 (~$'+(c*0.01).toFixed(2)+'')');
  notify('Gifts','Vibe sent '+giftEmoji,'You sent '+rn+' a '+giftName+' ('+c+' coins).');
  // Close the loop on gifting – the recipient "says thank you" back in the Vibes chat thread
  // (VIBE_THANKYOU_REPLIES), same auto-reply pattern as a regular message, so the gift feels
  // like part of a conversation instead of a one-way toast.
  if(vibeRecipient){
    setTimeout(function(){
      var th=vibeEnsureThread(rn);
      var reply=VIBE_THANKYOU_REPLIES[Math.floor(Math.random()*VIBE_THANKYOU_REPLIES.length)]+' Thanks for the '+giftName+' '+giftEmoji;
      th.push({from:'them',text:reply,t:'now'});
      renderVibeThread(rn);
      notify('Gifts','🎁 '+rn,rn+' said thank you for your '+giftName+'! Tap to see their reply.','',rn);
    },1500);
  }
  // (closing brace of vibeSend continues unchanged below)
}
```

New constant added alongside the existing VIBE_AUTOREPLIES:

```
var VIBE_THANKYOU_REPLIES=['Awww thank you so much! 🎁','You\'re so sweet, thank you! 🎁','OMG thank you!! 🎁','Appreciate you! 🎁','Thank you, that made my day! 🎁'];
```

7.2 Website — the gift picker & send flow (VIBES_GIFTS existed already for other flows; openSendVibe onward is new)

06-Vibes Website/index.html

```
let vibeGiftRecipient=null, vibeGiftSel=null;
function openSendVibe(handle){vibeGiftRecipient=handle;vibeGiftSel=null;renderSendVibe();}
function renderSendVibe(){
```

```

const bal=WALLET.coins, rn=vibeGiftRecipient||'someone';
const cost=vibeGiftSel?vibeGiftSel[2]:null, after=vibeGiftSel?bal-vibeGiftSel[2]:null, afford=!vibeGiftSel||vibeGiftSel[2]<=bal;
const grid=VIBES_GIFTS.map((g,k)=>{const sel=vibeGiftSel===g, off=g[2]>bal;
  return `<button ${off?'disabled':''} onclick="vibeGiftPick(${k})" class="text-left rounded-2xl p-3 bg-white border ${sel?'border-2 border-indigo-500
bg-indigo-50':'border-slate-100'} ${off?'opacity-40':''}"><div class="h-10 w-10 rounded-xl bg-fuchsia-50 grid place-items-center text-xl
mb-1">${g[1]}</div><p class="font-black text-sm leading-tight">${g[0]}</p><p class="text-[11px] text-slate-500 min-h-[28px] leading-tight
mt-0.5">${g[3]}</p><span class="inline-block mt-1 rounded-full ${g[2]===0?'bg-yellow-100 text-yellow-800':'bg-blue-400 text-white'} px-3 py-0.5 text-xs
font-black">${g[2]===0?'Free':`<span class="inline-flex items-center gap-1"><i data-lucide="coins" class="w-3 h-3"></i>${g[2]}</span>`}</span></button>`;
}).join('');
$('modalCard').className='card w-full max-w-lg max-h-[88vh] flex flex-col fade';
openModal(`<div class="p-4 shrink-0" style="background:linear-gradient(120deg,#dbeafe,#fae8ff,#fef9c3)"><div class="flex items-start
justify-between"><div class="flex items-center gap-2"><div class="h-10 w-10 rounded-xl bg-blue-100 grid place-items-center text-xl">■</div><div><h3
class="text-xl font-black text-slate-900">Send a Vibe</h3><p class="text-slate-500 text-sm">Send ${rn} a gift – they earn the coins
■</p></div></div><button onclick="closeModal()" class="h-9 w-9 rounded-full bg-white grid place-items-center shrink-0">X</button></div></div>
<div class="px-4 py-2 flex items-center justify-between border-b border-slate-100 shrink-0"><span class="rounded-full bg-blue-400 text-white px-4
py-1.5 font-black text-sm inline-flex items-center gap-1"><i data-lucide="coins" class="w-3.5 h-3.5"></i>${num(bal)} Coins</span><span class="font-black
text-slate-900 text-sm">${vibeGiftSel?vibeGiftSel[0]:'Pick a gift'}</span></div>
<div class="p-3 grid grid-cols-3 gap-2 overflow-y-auto" style="flex:1">${grid}</div>
<div class="border-t border-slate-100 p-3 shrink-0"><button onclick="vibeGiftSend()" ${(!vibeGiftSel||!afford)?'disabled':''} class="w-full
rounded-2xl py-3 font-black text-white ${(!vibeGiftSel||!afford)?'bg-slate-300':'bg-slate-950'}">${!afford?'Not enough
Coins':`Send'+(vibeGiftSel?(cost===0?'Free':` `'+cost+' ` `):'')}</button><div class="flex justify-between mt-2 text-xs font-bold
text-slate-500"><span>Selected: <b class="text-slate-900">${vibeGiftSel?vibeGiftSel[0]:'-'}</b></span><span>Cost: <b
class="text-slate-900">${vibeGiftSel?(cost===0?'Free':cost):'-'}</b></span><span>After: <b
class="text-slate-900">${after===null?'-':`num(after)`}</b></span></div></div>`);
}
function vibeGiftPick(k){vibeGiftSel=VIBES_GIFTS[k];renderSendVibe();}
function vibeGiftSend(){
  if(!vibeGiftSel)return; const c=vibeGiftSel[2];
  if(c>WALLET.coins){toast('Not enough Coins');return;}
  if(c){WALLET.coins-=c;DB.set('lk_wallet',WALLET);}
  const rn=vibeGiftRecipient||'them', giftName=vibeGiftSel[0], giftEmoji=vibeGiftSel[1];
  recordGift('SENT','Vibe `'+giftName,c,rn);
  closeModal();
  toast(giftEmoji+' '+giftName+' sent! '+rn+' earned '+c+' ■ (~$'+(c*0.01).toFixed(2)+'')');
  render();
  // Close the loop on gifting – the recipient "says thank you" back in the Vibes chat thread
  // (VIBE_THANKYOU_REPLIES), same auto-reply pattern as a regular message, so the gift feels
  // like part of a conversation instead of a one-way toast.
  if(vibeGiftRecipient){
    setTimeout(()=>{
      const all=vibeChatsAll(); const th=all[rn]||(all[rn]=[]);
      const reply=VIBE_THANKYOU_REPLIES[Math.floor(Math.random()*VIBE_THANKYOU_REPLIES.length)]+' Thanks for the '+giftName+' '+giftEmoji;
      th.push({from:'them',text:reply,t:'now'});
      DB.set('lk_vibe_chats',all);
      renderVibeThread(rn);
      pushNotif('gift',`■ '+rn,rn+' said thank you for your '+giftName+'! Tap to see their reply.',rn,rn);
    },1500);
  }
}
}

```

8. Feature: "Say Thank You" Composer + 3 Entry Points

A user asked to thank a supporter proactively — not just receive the automatic reply above. This opens a proper dialog with a warm, pre-written message that mentions Vibes/coins, in an editable textarea, rather than firing a canned one-liner on tap.

Reachable from three places (all open the same composer):

- The Top Vibes Senders leaderboard on any profile (per-supporter "■ Thank" button).
- Profile → Gifts → Activity — every real RECEIVED row in the app-wide gift ledger now has the same button, plus two one-tap emoji reactions (♥■ / ■) as a lighter alternative — see Section 9.
- A new ■ icon in the main Vibes/U Vibe dashboard header, which opens a picker of everyone who has actually sent a real gift (deduped from the shared ledger) — this was added because the composer was originally two levels deep with no way to reach it directly from the dashboard.

8.1 Phone app

01-Consumer App/LinkUp-App.html

```
// Explicit "say thank you" action – the counterpart to the automatic thank-you a recipient
// sends back after YOU give them a Vibe (see vibeSend()). This is the reverse direction: you
// choosing to thank one of your top supporters. Opens a proper composer with a warm, ready-to-
// send message (mentioning their Vibes/coin support) instead of firing a canned line on tap –
// the user can send it as-is or edit it into their own words first.
var VIBE_THANKS_TEMPLATE='Hey! I just wanted to say thank you so much for the Vibes and coins you've sent my way – it really means a lot and I truly
appreciate the support! ■■';
function openThankSender(name){
  openModal('<div class="p-4 shrink-0 flex items-center justify-between border-b border-slate-100"><h3 class="text-lg font-black flex items-center
gap-2">■ Say Thank You</h3><button onclick="closeModal()"><i data-lucide="x" class="w-5 h-5"></i></button></div>'+
  '<div class="p-4 space-y-3">'+
  '<p class="text-sm text-slate-500">Sending a thank-you message to <b class="text-slate-900">'+name+'</b> for their support.</p>'+
  '<textarea id="thankMsgInput" rows="5" class="w-full rounded-2xl border border-slate-200 p-3 text-sm
outline-none">'+VIBE_THANKS_TEMPLATE+'</textarea>'+
  '<p class="text-[11px] text-slate-400">Feel free to edit this into your own words before sending.</p>'+
  '<button onclick="sendThankSender(''+name.replace(/'/g,"")+')" class="w-full rounded-2xl py-3 font-black text-white flex items-center justify-center
gap-1.5" style="background:var(--lk-blue)"><i data-lucide="send" class="w-4 h-4"></i> Send Thank You</button>'+
  '</div>');
  setTimeout(function(){lucide.createIcons();},30);
}
function sendThankSender(name){
  var i=$('#thankMsgInput');var text=(i&i.value||').trim();if(!text)return;
  var th=vibeEnsureThread(name);
  th.push({from:'me',text:text,t:'now'});
  closeModal();
  toast('■ Thanks sent to '+name);
  setTimeout(function(){th.push({from:'them',text:VIBE_AUTOREPLIES[Math.floor(Math.random()*VIBE_AUTOREPLIES.length)],t:'now'});renderVibeThread(name);},
1200);
}
// Entry point from the main Vibes header (■ icon) – previously "Say Thank You" only lived
```



```
// two levels deep (inside a specific profile's Top Senders list, or Profile → Gifts →
// Activity), with nothing reachable directly from the Vibes dashboard itself. This lists
// everyone who's actually sent you a real gift (GIFT_ACTIVITY, deduped, most recent first),
// each opening the same openThankSender() composer.
function openThankSomeone(){
  var seen={},rows=[];
  GIFT_ACTIVITY.filter(function(a){return a.type==='RECEIVED';}).forEach(function(a){if(!seen[a.to]){seen[a.to]=true;rows.push(a);}});
  openModal('<div class="p-4 shrink-0 flex items-center justify-between border-b border-slate-100"><h3 class="text-lg font-black flex items-center
gap-2">■ Say Thank You</h3><button onclick="closeModal()"><i data-lucide="x" class="w-5 h-5"></i></button></div>'+
  '<div class="p-2 overflow-y-auto scrollbar">'+
    (rows.length?rows.map(function(a){return '<button onclick="closeModal();openThankSender(''+a.to.replace(/'/g,'')+'')" class="w-full flex items-center
justify-between gap-2 rounded-2xl p-3 text-left hover:bg-slate-50"><div class="flex items-center gap-3 min-w-0"><div class="h-10 w-10 rounded-full
bg-slate-700 text-white grid place-items-center font-black text-xs shrink-0">'+a.to.slice(0,2).toUpperCase()+</div><div class="min-w-0"><p
class="font-black text-sm truncate">'+a.to+'</p><p class="text-[11px] text-slate-400 truncate">Sent you '+a.gift+' · ■ '+a.coins+'</p></div></div><span
class="text-[11px] font-black text-blue-600 shrink-0">Thank →</span></button>');}).join('')
    :<p class="text-center text-slate-400 font-bold py-10 text-sm px-4">No Vibes gifts received yet – once someone sends you one, they'll show up here
so you can thank them.</p>')+
  '</div>');
  setTimeout(function(){lucide.createIcons();},30);
}
```

Header icon wiring (Vibes dashboard header, and identically in the U Vibe header):

```
<button onclick="openThankSomeone()" class="rounded-full bg-white/20 backdrop-blur h-9 w-9 grid place-items-center" title="Say Thank You"><span
style="font-size:1.05rem;line-height:1">■</span></button>
```

8.2 Website

06-Vibes Website/index.html

```
const VIBE_THANKS_TEMPLATE_WEB='Hey! I just wanted to say thank you so much for the Vibes and coins you've sent my way – it really means a lot and I truly
appreciate the support! ■■';
function openThankSenderWeb(name){
  $('modalCard').className='card w-full max-w-md fade';
  openModal('<div class="p-4 shrink-0 flex items-center justify-between border-b border-slate-100"><h3 class="text-lg font-black flex items-center
gap-2">■ Say Thank You</h3><button onclick="closeModal()"><i data-lucide="x" class="w-5 h-5"></i></button></div>
  <div class="p-4 space-y-3">
    <p class="text-sm text-slate-500">Sending a thank-you message to <b class="text-slate-900">${name}</b> for their support.</p>
    <textarea id="thankMsgInputWeb" rows="5" class="w-full rounded-2xl border border-slate-200 p-3 text-sm
outline-none">${VIBE_THANKS_TEMPLATE_WEB}</textarea>
    <p class="text-[11px] text-slate-400">Feel free to edit this into your own words before sending.</p>
    <button onclick="sendThankSenderWeb('${name}')" class="w-full rounded-2xl py-3 font-black text-white flex items-center justify-center gap-1.5"
style="background:var(--lk-blue)"><i data-lucide="send" class="w-4 h-4"></i>Send Thank You</button>
  </div>');
}
function sendThankSenderWeb(name){
  const i=$('#thankMsgInputWeb'); const text=(i&&i.value||').trim(); if(!text)return;
  const all=vibeChatsAll(); const th=all[name]||(all[name]=[]);
  th.push({from:'me',text:text,t:'now'});
  DB.set('lk_vibe_chats',all);
}
```

```

    closeModal();
    toast('■ Thanks sent to '+name);
    setTimeout(()=>{const all2=vibeChatsAll();const th2=all2[name]||(all2[name]=[]);th2.push({from:'them',text:VIBE_AUTOREPLIES[Math.floor(Math.random()*VIBE_AUTOREPLIES.length)],t:'now'}});DB.set('lk_vibe_chats',all2);renderVibeThread(name);},1200);
  }
  // Entry point from the main Vibes header (■ icon) – previously "Say Thank You" only lived
  // two levels deep (inside a specific profile's Top Senders list, or Profile → Gifts →
  // Activity), with nothing reachable directly from the Vibes dashboard itself. This lists
  // everyone who's actually sent you a real gift (giftActivity(), deduped, most recent first),
  // each opening the same openThankSenderWeb() composer.
  function openThankSomeoneWeb(){
    const seen={}, rows=[];
    giftActivity().filter(g=>g.type==='RECEIVED').forEach(g=>{if(!seen[g.from]){seen[g.from]=true;rows.push(g)}});
    $('modalCard').className='card w-full max-w-md max-h-[80vh] overflow-y-auto fade';
    openModal(`<div class="p-4 shrink-0 flex items-center justify-between border-b border-slate-100"><h3 class="text-lg font-black flex items-center gap-2">■ Say Thank You</h3><button onclick="closeModal()"><i data-lucide="x" class="w-5 h-5"></i></button></div>
    <div class="p-2">${rows.length?rows.map(g=>`<button onclick="closeModal();openThankSenderWeb('${g.from}')" class="w-full flex items-center justify-between gap-2 rounded-2xl p-3 text-left hover:bg-slate-50"><div class="flex items-center gap-3 min-w-0"><div class="h-10 w-10 rounded-full bg-slate-700 text-white grid place-items-center font-black text-xs shrink-0">${g.from.slice(0,2).toUpperCase()}</div><div class="min-w-0"><p class="font-black text-sm truncate">${g.from}</p><p class="text-[11px] text-slate-400 truncate">Sent you ${g.gift} . ■ ${num(g.coins)}</p></div></div><span class="text-[11px] font-black shrink-0" style="color:var(--lk-blue)">Thank →</span></button>`.join('')
    :`<p class="text-center text-slate-400 font-bold py-10 text-sm px-4">No Vibes gifts received yet – once someone sends you one, they'll show up here so you can thank them.</p>`</div>`);
  }

```

Header icon wiring:

```

<button onclick="openThankSomeoneWeb()" class="btn btn-ghost h-11 w-11 grid place-items-center text-lg" title="Say Thank You">■</button>

```

9. Feature: One-Tap Gift Reactions

On the real, app-wide Gift Activity ledger (Profile → Gifts → Activity), every RECEIVED row now has 🍷 and 🍷 buttons as a lighter alternative to writing a full thank-you message. Tapping toggles the reaction on/off; state is stored directly on the ledger row.

9.1 Phone app

01-Consumer App/LinkUp-App.html

```
// One-tap reaction on a received gift – a lighter alternative to the full Thank You composer
// for when a whole written message feels like overkill. Toggle: tapping the active emoji again
// clears it. Stored directly on the GIFT_ACTIVITY row, mirroring how p.liked/p.likes mutate
// in place elsewhere in this file.
function vibeReactGift(id,emoji){
  var a=GIFT_ACTIVITY.find(function(x){return x.id===id;});if(!a)return;
  a.reacted=(a.reacted===emoji)?null:emoji;
  if(typeof renderProfile==='function'&&document.getElementById('profBody'))renderProfile();
  if(a.reacted)toast(emoji+' sent to '+a.to);
}
```

Row markup added inside the existing Gift Activity list (RECEIVED rows only):

```
var reactions=!sent?'<div class="flex items-center gap-1.5 mt-2">'+
  '<button onclick="openThankSender('+a.to.replace(/'/g,"")+')" class="rounded-full bg-white border border-slate-200 px-2.5 py-1 text-[11px]
font-black text-slate-600">🍷 Thank</button>'+
  '<button onclick="vibeReactGift('+a.id+', '+a.reacted===emoji?'🍷':'🍷')'" class="rounded-full h-7 w-7 grid place-items-center text-sm border
'+(a.reacted===🍷?'bg-rose-50 border-rose-200':'bg-white border-slate-200')+'">🍷</button>'+
  '<button onclick="vibeReactGift('+a.id+', '+a.reacted===🍷?'🍷':'🍷')'" class="rounded-full h-7 w-7 grid place-items-center text-sm border '+
  (a.reacted===🍷?'bg-amber-50 border-amber-200':'bg-white border-slate-200')+'">🍷</button>'+
  '</div>':'';
```

9.2 Website

06-Vibes Website/index.html

```
// One-tap reaction on a received gift – a lighter alternative to the full Thank You composer
// for when a whole written message feels like overkill. Toggle: tapping the active emoji
// again clears it.
function vibeReactGiftWeb(id,emoji){
  const list=giftActivity();
  const g=list.find(x=>x.id===id); if(!g)return;
  g.reacted=(g.reacted===emoji)?null:emoji;
  saveGiftActivity(list);
  render();
  if(g.reacted)toast(emoji+' sent to '+g.from);
}
```

Row markup added inside the existing Gift Activity list (RECEIVED rows only):

```
const reactions=g.type==='RECEIVED'?`<div class="flex items-center gap-1.5 mt-2">
  <button onclick="openThankSenderWeb('${g.from}')" class="rounded-full bg-white border border-slate-200 px-2.5 py-1 text-[11px] font-black
text-slate-600 hover:bg-slate-50">■ Thank</button>
  <button onclick="vibeReactGiftWeb('${g.id}','❤️')\" class="rounded-full h-7 w-7 grid place-items-center text-sm border
${g.reacted==='❤️'?'bg-rose-50 border-rose-200':'bg-white border-slate-200'}">❤️</button>
  <button onclick="vibeReactGiftWeb('${g.id}','■')\" class="rounded-full h-7 w-7 grid place-items-center text-sm border ${g.reacted==='■'?'bg-amber-50
border-amber-200':'bg-white border-slate-200'}">■</button>
</div>`:'';

```

10. Bug Fix: Notification Deep-Linking

The bug: the thank-you notification correctly appeared in the Notifications panel, but tapping it did nothing — the notification card had no click handler at all wired to a destination. The underlying message was always correctly saved to the chat thread; there was simply no way to navigate to it from the notification itself. Also, the gift-thank-you notification was filed under a category ('Vibes') that didn't exist in the style/icon map, so it silently fell back to a generic bell icon instead of the correct Gifts icon.

10.1 Phone app — `notify()` gains an optional 5th argument, and the notification list gains a click handler

01-Consumer App/LinkUp-App.html

```
function notify(cat,title,body,img,vibeThread){
  if(!notifPrefs.push)return; if(notifPrefs[cat]===false)return;
  var st=NOTIF_STYLE[cat]||NOTIF_STYLE.System;
  NOTIFS.unshift({ic:st[0],img:img||'https://i.pravatar.cc/80?img=12',cat:cat,ccls:st[1],title:title,body:body,time:'now',unread:true,vibeThread:vibeThread||null});
  updateNotifDot(); if(typeof renderNotifBody==='function'&&document.getElementById('notifList'))renderNotifBody();
}
```

Inside `renderNotifBody()` — the row is now a real button when it carries a destination:

```
var clickable=n.spark||n.vibeThread;
var clickAttr=n.spark?' onclick="closeModal();openSparkResponse(''+n.spark.name.replace(/'/g,'')+''"'
:(n.vibeThread?' onclick="closeModal();openVibeThread(''+n.vibeThread.replace(/'/g,'')+''"'':'');
return '<'+(clickable?'button':'div')+clickAttr+' class="w-full text-left rounded-2xl bg-white border '+n.unread?'border-blue-200':'border-slate-100')+'
p-3 flex gap-3 relative">'+
  (n.unread?'<span class="absolute top-3 right-3 h-2 w-2 rounded-full bg-blue-500"></span>':''')+
  ''+
  '<div class="flex-1 min-w-0"><p class="font-black text-slate-900 leading-tight">'+n.title+'</p>'+
    '<p class="text-sm text-slate-600 mt-0.5">'+n.body+'</p>'+
    '<div class="flex items-center gap-2 mt-1.5"><span class="rounded-full px-2 py-0.5 text-[10px] font-black '+n.ccls+'">'+n.cat+'</span><span
class="text-[11px] text-slate-400 font-bold">'+n.time+'</span>'+(n.spark?'<span class="ml-auto text-[11px] font-black text-pink-600">Respond
→</span>':(n.vibeThread?'<span class="ml-auto text-[11px] font-black text-blue-600">Open chat →</span>':''))+'</div>'+
  '</div></'+(clickable?'button':'div')+'>';
```

And the call site that triggers this notification now correctly uses category 'Gifts' (was 'Vibes', which doesn't exist in `NOTIF_STYLE`) and passes the recipient name as the deep link:

```
notify('Gifts','■ '+rn,rn+' said thank you for your '+giftName+'! Tap to see their reply.','',rn);
```

10.2 Website — `pushNotif()` gains the same 5th argument

06-Vibes Website/index.html

```
function pushNotif(kind,title,body,who,vibeThread){
  const list=notifList();
  list.unshift({id:Date.now()+Math.floor(Math.random()*1000),kind,title,body,who:(who||'!').slice(0,2).toUpperCase(),color:(NOTIF_ICON[kind]||[])[1]||'#
```

```

64748b', read:false, when:Date.now(),vibeThread:vibeThread||null});
  if(list.length>60)list.length=60;
  DB.set('lk_notifications', list);
  syncNotifBadge();
  if(current==='notifications')render();
}
// Notifications were a dead end for gift thank-yous – tapping one just toggled read/unread
// with no way to reach the actual Vibes chat thread it was about. vibeThread (set by
// pushNotif's 5th arg) deep-links straight into that conversation instead.
function openNotifTarget(id){
  const list=notifList();const n=list.find(x=>x.id===id);
  toggleNotifRead(id);
  if(n&&n.vibeThread)openVibeThread(n.vibeThread);
}
function notifCard(n){
  const[icon,color]=NOTIF_ICON[n.kind]||['bell', '#64748b'];
  const catLabel=(NOTIF_CATS.find(c=>c[0]===n.kind)||['',''])[1];
  return `<div onclick="openNotifTarget(${n.id})" class="card p-4 flex items-start gap-3 cursor-pointer hover:shadow-sm transition"
style="${!n.read?'border-color:var(--lk-blue);border-width:2px':''}">
  <span class="relative shrink-0">
    <span class="h-11 w-11 rounded-full grid place-items-center text-white font-black text-sm" style="background:${n.color}">${n.who}</span>
    ${!n.read?'<span class="absolute -top-0.5 -right-0.5 h-3 w-3 rounded-full border-2 border-white" style="background:var(--lk-blue)"></span>':''}
  </span>
  <div class="flex-1 min-w-0">
    <p class="font-black text-sm">${n.title}</p>
    <p class="text-slate-500 text-sm mt-0.5 truncate">${n.body}</p>
    <div class="flex items-center gap-2 mt-1.5"><span class="rounded-full px-2.5 py-0.5 text-[10px] font-black"
style="background:${color}1a;color:${color}">${catLabel}</span><span class="text-[11px]
text-slate-400">${notifTimeAgo(n.when)}</span>${n.vibeThread?'<span class="ml-auto text-[11px] font-black" style="color:var(--lk-blue)">Open chat
→</span>':''}</div>
    </div>
    <span class="h-9 w-9 rounded-xl grid place-items-center shrink-0" style="background:${color}1a;color:${color}"><i data-lucide="${icon}" class="w-4
h-4"></i></span>
  </div>`;
}

```

11. Feed & Dashboard Header Edits (follower counts, quick-gift icon)

Small, surgical edits to the existing post-header markup in both the Vibes feed and U Vibe feed: each post header now (a) shows the author's follower count inline, (b) has a  quick-send icon so gifting doesn't require opening the profile first, and (c) the name/avatar tap now opens the full profile instead of jumping straight to a message thread.

11.1 Phone app — Vibes feed post header (inside `renderVibes()`)

01-Consumer App/LinkUp-App.html

```
'<div class="flex items-center gap-2 px-3 py-2.5"><button onclick="openVibeProfile(''+p.user.replace(/'/g,"")+''+', ''+String(p.loc).replace(/'/g,"")+'')'
class="flex items-center gap-2 flex-1 min-w-0 text-left">...avatar...<div class="flex-1 min-w-0"><p class="font-black text-sm">'+p.user+'</p><p
class="text-[11px] text-slate-500 flex items-center gap-1"><span class="rounded-full bg-indigo-50 text-indigo-600 px-1.5 font-black
text-[9px]">'+p.type+'</span>'+(p.org?' · <span class="rounded-full bg-amber-50 text-amber-700 px-1.5 font-black text-[9px]">'+p.orgType+'</span>:'+')+'
· '+fmt(vibeFollowerCount(p.user))+ ' followers</p></div></button><button onclick="vibeSendVibeTo(''+p.user.replace(/^\@/, '').replace(/'/g,"")+''+', '')'
title="Send a Vibe" class="shrink-0"><img alt="quick-send icon" data-bbox="358 368 373 383"/></button><button onclick="openVibeOptions(''+p.id+'')">...</button></div>
```

U Vibe feed post header (inside `uvCard()`) — same treatment:

```
'<div class="p-3 flex items-center gap-2"><button onclick="openUVibeProfile(''+(p.author||'').replace(/'/g,"")+'')' class="flex items-center gap-2 flex-1
min-w-0 text-left"><div class="h-9 w-9 rounded-xl grid place-items-center text-white font-black text-sm shrink-0"
style="background: '+u.color+'">'+u.flag+'</div>'+
'<div class="flex-1 min-w-0"><p class="font-black text-sm leading-tight truncate flex items-center gap-1">'+u.name+(p.verified?' <i
data-lucide="badge-check" class="w-3.5 h-3.5 text-blue-500"></i>:'+')+'</p><p class="text-[10px] text-slate-400">'+p.author+' ·
'+fmt(uvFollowerCount(p.author))+ ' followers · '+p.when+' ago</p></div></button>'+
'<button onclick="vibeSendVibeTo(''+(p.author||'').replace(/'/g,"")+''+', '')' title="Send a Vibe" class="shrink-0"><img alt="quick-send icon" data-bbox="538 528 553 543"/></button>'+
'<span class="rounded-full px-2 py-0.5 text-[10px] font-black shrink-0" style="background:#eef2ff;color:#4f46e5">'+uvCatLabel(p.type)+'</span></div>'+
```

Header icon rows (both dashboards gained the  icon; already shown in Section 8):

```
<!-- Vibes dashboard header -->
<button onclick="openVibesActivity()" ...heart icon...></button>
<button onclick="openThankSomeone()" class="rounded-full bg-white/20 backdrop-blur h-9 w-9 grid place-items-center" title="Say Thank You"><span
style="font-size:1.05rem;line-height:1"><img alt="thank icon" data-bbox="638 658 653 673"/></span></button>
<button onclick="openCreateVibe()" ...>Post</button>

<!-- U Vibe dashboard header -->
<button onclick="openVibeInbox()" ...message-circle icon...></button>
<button onclick="openThankSomeone()" class="h-10 w-10 rounded-full bg-white/20 grid place-items-center" title="Say Thank You"><span
style="font-size:1.05rem;line-height:1"><img alt="thank icon" data-bbox="738 748 753 763"/></span></button>
<button onclick="openUVibePost()" ...>Post</button>
```

11.2 Website — Vibes feed post header (inside `vibeCard()`)

06-Vibes Website/index.html

```
<div class="flex-1 min-w-0"><p class="font-black text-sm flex items-center gap-1.5">${p.handle}${p.org?'`<span ...>${p.org.toUpperCase()}</span>':''}`</p>
<p class="text-xs text-slate-500 flex items-center gap-1"><i data-lucide="map-pin" class="w-3 h-3"></i>${p.location} ${p.kind==='reel'?'.<span
```

```

class="text-lkblue2 font-bold">Reel</span>':''} · ${num(vibeFollowerCountWeb(p.handle))} followers</p></div>
</button>
${p.shoppable?'<span ...>Shop</span>':''}
<button onclick="openSendVibe('${p.handle}')" title="Send a Vibe" class="text-lg shrink-0">■</button>
<button onclick="openVibePostMenu(${p.id})" class="text-slate-400"><i data-lucide="more-horizontal" class="w-5 h-5"></i></button>

```

U Vibe feed post header (inside uvibePostCard()):

```

<button onclick="openUVibeProfile('${(p.org||'').replace('/'/g,'')}')" class="flex items-center gap-3 flex-1 min-w-0 text-left">
  <span class="h-11 w-11 rounded-xl bg-violet-100 text-violet-700 grid place-items-center font-black shrink-0">${p.org.slice(0,1)}</span>
  <div class="flex-1 min-w-0"><p class="font-black text-sm flex items-center gap-1 truncate">${p.org}${p.verified?'<i data-lucide="badge-check"
...></i>':''}</p><p class="text-[11px] text-slate-400 truncate">${p.group} · ${num(uvFollowerCountWeb(p.org))} followers · ${p.time}</p></div>
</button>
<button onclick="openSendVibe('${(p.org||'').replace('/'/g,'')}')" title="Send a Vibe" class="text-lg shrink-0">■</button>
<span class="chip shrink-0" ...>${p.tagLabel}</span>

```

Header icon rows:

```

<!-- VIEWS.vibes header actions -->
<button onclick="openVibeInbox()" ...>Messages</button>
<button onclick="openReelsBrowse()" ...>Reels</button>
<button onclick="openThankSomeoneWeb()" class="btn btn-ghost h-11 w-11 grid place-items-center text-lg" title="Say Thank You">■</button>
<button onclick="composeVibe()" ...>Post</button>

<!-- VIEWS.uvibe header actions -->
<button onclick="openVibeInbox()" ...>Messages</button>
<button onclick="openThankSomeoneWeb()" class="h-11 w-11 rounded-xl bg-white/20 grid place-items-center text-lg" title="Say Thank You">■</button>
<button onclick="composeUVibe()" ...>Post</button>

```


12. U Vibe — Full Profile System (mirrors everything above)

Everything in Sections 4–9 was ported to U Vibe. Because U Vibe already shared its messaging (vibeChats) and gifting infrastructure with Vibes before this work, most of it reuses the exact same functions (vibeMessage, vibeSendVibeTo/openSendVibe, profileTopSenders/profileTopSendersWeb, openThankSender/openThankSenderWeb, openThankSomeone/openThankSomeoneWeb) — only the follow graph, category badge, mutuals line, and post/shop lookups needed their own U-Vibe-specific versions, because U Vibe authors are plain org/person name strings, not @handles, and must not collide with the separate Vibes follow graph for a same-named person.

12.1 Phone app — full new block (helpers + profile modal)

01-Consumer App/LinkUp-App.html

```
// ----- U Vibe profile — exact parity with the Vibes profile (stats, follow, gift, shop,
// leaderboard, thank-you), reusing the SAME shared systems wherever the data is generic
// (vibeChats messaging, the VIBES gift catalog, GIFT_ACTIVITY ledger, vibeTopSenders(),
// openThankSender()/openThankSomeone()). Follow state/category/mutuals stay in their own
// uv*-prefixed namespace since U Vibe authors are plain org/person names, not @handles, and
// shouldn't collide with the separate Vibes follow graph for a same-named person.
function uvibePeople(){
  var map={};
  UVIBES.forEach(function(p){if(!map[p.author])map[p.author]={name:p.author}});
  return Object.keys(map).map(function(k){return map[k]});
}
function userUVibePosts(name){return UVIBES.filter(function(p){return p.author===name});}
function userUVibeShopItems(name){return UVIBES.filter(function(p){return p.author===name&&p.shop});}
let uvFollowing={};
function uvFollowerSeed(name){var h=0;for(var i=0;i<name.length;i++){h=(h*31+name.charCodeAt(i))>>>0;}return 40+(h%1800);}
function uvFollowerCount(name){return uvFollowerSeed(name)+(uvFollowing[name]?1:0);}
var UV_CATEGORIES=['Student Leader','Committee','Society','Organizer','Student Union','Campus Creator'];
function uvCategory(name){return UV_CATEGORIES[uvFollowerSeed(name+'c')%UV_CATEGORIES.length];}
function uvMutualsLine(name){
  var others=uvibePeople().filter(function(p){return p.name!==name});
  if(!others.length)return '';
  var seed=uvFollowerSeed(name+'m');
  var a=others[seed%others.length],b=others[(seed+7)%others.length];
  var extra=3+(seed%20);
  return '<div class="flex items-center justify-center gap-2 pb-1"><p class="text-[11px] text-slate-500">Followed by <b>'+a.name+'</b>, <b>'+b.name+'</b>
and '+extra+' others</p></div>';
}
function uvFollowBtnHtml(name){
  var on=!!uvFollowing[name];
  return '<button id="uvFollowBtn" onclick="uvToggleFollow(''+name.replace(/'/g,'"')+')" class="rounded-2xl py-3 font-black flex items-center
justify-center gap-1.5 '+ (on?'border-2 border-slate-200 text-slate-700':'text-white')+'>'+
'+(on?'':'style="background:var(--lk-blue)')+'>'+(on?'Following':'Follow')+'</button>';
}
function uvToggleFollow(name){
  uvFollowing[name]=!uvFollowing[name];
  var btn=$('#uvFollowBtn');if(btn)btn.outerHTML=uvFollowBtnHtml(name);
  var cnt=$('#uvFollowerCount');if(cnt)cnt.textContent=fmt(uvFollowerCount(name));
}
```

```

    toast(uvFollowing[name]?'Following '+name:'Unfollowed '+name);
    if(window.lucide)lucide.createIcons();
  }
  function profileUVibeShopSection(name){
    var items=userUVibeShopItems(name);
    if(!items.length)return '';
    return '<div class="px-1 pb-2"><p class="text-[11px] font-black text-slate-400 uppercase mb-2 flex items-center gap-1.5"><i data-lucide="shopping-bag"
class="w-3.5 h-3.5"></i> Shop '+name+'</p><div class="space-y-2">'+
    items.map(function(p){var t=p.shop,ev=t.kind==='event',img=t.img||(p.imgs?p.imgs[0]:p.img)||'';
    return '<button onclick="openUVibeTag('+p.id+')" class="w-full flex items-center gap-3 rounded-2xl border border-slate-100 p-2.5 text-left"><div class="flex-1 min-w-0"><p class="font-black text-sm truncate">'+(ev?'
':t.name)+'</p><p class="text-[11px] text-slate-500">$'+t.price.toFixed(2)+'</p></div><span class="rounded-full text-white px-3 py-1.5 text-xs
font-black shrink-0" style="background:var(--lk-blue)">'+(ev?'Tickets':'Shop')+'</span></button>';
    }).join('')+'</div></div>';
  }
  // Grid taps just open the full post card in a modal (uvCard() is self-contained) – U Vibe has
  // no dedicated Reels/comments viewers to branch into like the Vibes profile grid does.
  function profileUVibePostsGrid(name){
    var posts=userUVibePosts(name);
    if(!posts.length)return '<p class="text-center text-slate-400 font-bold py-10 text-sm">No posts yet.</p>';
    return '<div class="grid grid-cols-3 gap-0.5">'+posts.map(function(p){
    var img=(p.imgs?p.imgs[0]:p.img)||'';
    if(!img)return '<button onclick="openUVibePostModal('+p.id+')" class="relative aspect-square bg-slate-100 grid place-items-center p-2"><span
class="text-[11px] font-bold text-slate-500 line-clamp-4 text-center">'+p.title+'</span></button>';
    return '<button onclick="openUVibePostModal('+p.id+')" class="relative aspect-square bg-slate-100"><span class="absolute bottom-1 left-1 text-white text-[10px] font-black flex items-center gap-0.5 drop-shadow"><i data-lucide="heart"
class="w-3 h-3" fill="currentColor"></i>'+p.likes+'</span></button>';
    }).join('')+'</div>';
  }
  function openUVibePostModal(id){
    var p=UVIBES.find(function(x){return x.id===id;});if(!p)return;
    openModal('<div class="p-3 flex justify-end border-b border-slate-100"><button onclick="closeModal()"><i data-lucide="x" class="w-5
h-5"></i></button></div>'+uvCard(p));
    setTimeout(function(){lucide.createIcons();},30);
  }
  function openUVibeProfile(name){
    var postCount=userUVibePosts(name).length;
    var avatar='<div class="h-20 w-20 rounded-full mx-auto grid place-items-center text-white font-black text-2xl border-4 border-white shadow"
style="background:linear-gradient(135deg,#6366f1,#ec4899)">'+name.slice(0,2).toUpperCase()+'</div>';
    var statsRow='<div class="flex items-center justify-center gap-6 py-1"><div class="text-center"><p class="font-black text-sm">'+postCount+'</p><p
class="text-[10px] text-slate-400 font-bold uppercase">Posts</p></div><div class="text-center"><p id="uvFollowerCount" class="font-black
text-sm">'+fmt(uvFollowerCount(name))+'</p><p class="text-[10px] text-slate-400 font-bold uppercase">Followers</p></div><div class="text-center"><p
class="font-black text-sm">'+fmt(uvFollowerSeed(name+'f'))+'</p><p class="text-[10px] text-slate-400 font-bold uppercase">Following</p></div></div>';
    openModal('<div class="p-5 text-center text-white" style="background:linear-gradient(135deg,#6366f1,#2f9bef 55%,#ec4899)"><div class="flex
justify-end"><button onclick="closeModal()"><i data-lucide="x" class="w-5 h-5"></i></button></div>'+avatar+'<h3 class="text-xl font-black
mt-2">'+name+'</h3></div>'+
    '<div class="p-4 space-y-2">'+
    '<button onclick="closeModal();openMyEarnings('uvibe')> class="w-full flex items-center justify-between rounded-2xl px-4 py-2.5 text-white"
style="background:linear-gradient(135deg,#059669,#10b981)"><span class="flex items-center gap-2 font-black text-sm"><i data-lucide="trending-up"
class="w-4 h-4"></i>My Earnings · $'+(affEarnings.pending+affEarnings.available+affEarnings.paid).toFixed(2)+'</span><i data-lucide="chevron-right"
class="w-4 h-4"></i></button>'+
    '<p class="text-center text-[11px] font-black text-slate-400 uppercase tracking-wide">'+uvCategory(name)+'</p>'+statsRow+uvMutualsLine(name)+

```

```
'<div class="grid grid-cols-2 gap-2">' + uvFollowBtnHtml(name) + '<button onclick="vibeMessage(' + name.replace(/'/g, '"') + ', ')" class="rounded-2xl py-3 font-black border-2 border-slate-200 flex items-center justify-center gap-1.5"><i data-lucide="message-circle" class="w-4 h-4"></i> Message</button></div>' +  
'<button onclick="vibeSendVibeTo(' + name.replace(/'/g, '"') + ', ')" class="w-full rounded-2xl py-3 font-black text-white flex items-center justify-center gap-1.5" style="background: linear-gradient(135deg, #f59e0b, #ec4899)">■ Send a Vibe</button>' +  
'</div>' + profileUVibeShopSection(name) + profileTopSenders(name) + '<div class="px-0.5 pb-2">' + profileUVibePostsGrid(name) + '</div>';  
setTimeout(function(){lucide.createIcons();}, 30);  
}
```

12.2 Website — full new block (helpers + router page)

06-Vibes Website/index.html

```
// ----- U Vibe profile — exact parity with the Vibes profile (stats, follow, gift, shop,
// leaderboard, thank-you), reusing the SAME shared systems wherever the data is generic
// (vibeChats messaging, the VIBES_GIFTS catalog, giftActivity() ledger, profileTopSendersWeb(),
// openThankSenderWeb()/openThankSomeoneWeb()). Follow state/category/mutuals stay in their own
// uv*Web namespace since U Vibe orgs are plain names, not @handles, and shouldn't collide with
// the separate Vibes follow graph for a same-named person.
function uvibePeopleWeb(){
  const map={};
  DB.get('lk_uvibe_posts',UVIBE_POSTS_SEED).forEach(p=>{if(!map[p.org])map[p.org]={name:p.org}}});
  return Object.values(map);
}
function userUVibePostsWeb(name){return DB.get('lk_uvibe_posts',UVIBE_POSTS_SEED).filter(p=>p.org===name);}
function userUVibeShopItemsWeb(name){return DB.get('lk_uvibe_posts',UVIBE_POSTS_SEED).filter(p=>p.org===name&&p.tag);}
function uvFollowingAllWeb(){return DB.get('lk_uv_following',{})};
function uvIsFollowingWeb(name){return !!uvFollowingAllWeb()[name]};
function uvFollowerSeedWeb(name){return 40+(hashSeed(name)%1800)};
function uvFollowerCountWeb(name){return uvFollowerSeedWeb(name)+(uvIsFollowingWeb(name)?1:0)};
const UV_CATEGORIES_WEB=['Student Leader','Committee','Society','Organizer','Student Union','Campus Creator'];
function uvCategoryWeb(name){return UV_CATEGORIES_WEB[hashSeed(name+'c')%UV_CATEGORIES_WEB.length];}
function uvMutualsLineWeb(name){
  const others=uvibePeopleWeb().filter(p=>p.name!==name);
  if(!others.length)return '';
  const seed=hashSeed(name+'m');
  const a=others[seed%others.length], b=others[(seed+7)%others.length];
  const extra=3+(seed%20);
  return `
```

```

truncate">${ev?'■■ ':''}${t.title}</p><p class="text-[11px] text-slate-500">${money(t.price)}</p></div><span class="rounded-full text-white px-3 py-1.5 text-xs font-black shrink-0" style="background:var(--lk-blue)">${ev?'Tickets':'Shop'}</span></button>;
}).join('')}</div></div>;
}
// Grid taps just open the full post card in a modal (uvibePostCard() is self-contained) – U
// Vibe has no dedicated Reels/comments viewers to branch into like the Vibes profile grid does.
function profileUVibePostsGridWeb(name){
  const posts=userUVibePostsWeb(name);
  if(!posts.length)return `<p class="text-center text-slate-400 font-bold py-10 text-sm">No posts yet.</p>`;
  return `<div class="grid grid-cols-3 gap-1">${posts.map(p=>{
    const img=(p.imgs&&p.imgs.length)?p.imgs[0]:p.image;
    if(!img)return `<button onclick="openUVibePostModalWeb(${p.id})" class="relative aspect-square bg-slate-100 rounded-lg grid place-items-center p-2"><span class="text-[11px] font-bold text-slate-500 text-center line-clamp-4">${p.title}</span></button>`;
    return `<button onclick="openUVibePostModalWeb(${p.id})" class="relative aspect-square bg-slate-100 rounded-lg overflow-hidden"><span class="absolute bottom-1 left-1 text-white text-[10px] font-black flex items-center gap-0.5 drop-shadow"><i
data-lucide="heart" class="w-3 h-3" fill="currentColor"></i>${num(p.likes)}</span></button>`;
  }).join('')}</div>`;
}
function openUVibePostModalWeb(id){
  const p=DB.get('lk_uvibe_posts',UVIBE_POSTS_SEED).find(x=>x.id===id); if(!p)return;
  $('modalCard').className='card w-full max-w-lg max-h-[88vh] overflow-y-auto fade';
  openModal(uvibePostCard(p));
}
// A U Vibe org/person's profile is its own page (VIEWS.uvibeProfile), matching the Vibes
// profile's page-not-modal treatment – selecting a name navigates via go(), with a Back link.
let uvProfileName=null, uvProfileBackView='uvibe';
function openUVibeProfile(name,backView){
  uvProfileName=name;
  uvProfileBackView=backView||current||'uvibe';
  go('uvibeProfile');
}
VIEWS.uvibeProfile=()=>{
  const name=uvProfileName;
  if(!name)return `<div class="fade"><p class="text-slate-400 font-bold text-center py-16">No profile selected.</p></div>`;
  const postCount=userUVibePostsWeb(name).length;
  return `<div class="fade max-w-3xl mx-auto">
    <button onclick="go('${uvProfileBackView}')" class="flex items-center gap-1.5 text-slate-500 hover:text-slate-700 font-bold text-sm mb-4"><i
data-lucide="arrow-left" class="w-4 h-4"></i>Back</button>
    <button onclick="openAffiliateHub('earnings')" class="w-full rounded-2xl p-4 mb-4 text-white text-left flex items-center justify-between"
style="background:linear-gradient(135deg,#059669,#10b981)"><div><p class="font-black text-sm flex items-center gap-1.5"><i data-lucide="trending-up"
class="w-4 h-4"></i>My Earnings</p><p class="text-[11px] text-white/80 mt-0.5">Commission from tagged sales</p></div><p class="text-xl
font-black">${money(((()=>{const a=affEarnings();return a.pending+a.available+a.paid;}))())}</p></button>
    <div class="card p-6 md:p-8">
      <div class="flex flex-col sm:flex-row gap-6 sm:gap-10">
        <div class="h-32 w-32 sm:h-36 sm:w-36 rounded-full grid place-items-center text-white font-black text-4xl shrink-0 mx-auto sm:mx-0"
style="background:linear-gradient(135deg,#6366f1,#ec4899)">${name.slice(0,2).toUpperCase()}</div>
        <div class="flex-1 min-w-0 w-full">
          <h1 class="text-2xl font-black">${name}</h1>
          <div class="flex items-center gap-6 mt-4 flex-wrap">
            <p class="text-sm"><b class="text-base">${postCount}</b> posts</p>
            <p class="text-sm"><b id="uvFollowerCountWeb" class="text-base">${num(uvFollowerCountWeb(name))}</b> followers</p>
            <p class="text-sm"><b class="text-base">${num(40+(hashSeed(name+'f')%1800))}</b> following</p>
          </div>

```

```

        <p class="text-sm text-slate-600 font-semibold mt-3">${uvCategoryWeb(name)}</p>
        <div class="mt-2">${uvMutualsLineWeb(name)}</div>
        <div class="flex flex-wrap items-center gap-2 mt-4">
            ${uvFollowBtnHtmlWeb(name)}
            <button onclick="openVibeThread('${name}')" class="rounded-xl px-5 py-2 text-sm font-black border-2 border-slate-200 flex items-center justify-center gap-1.5"><i data-lucide="message-circle" class="w-4 h-4"></i>Message</button>
        </div>
        </div>
    </div>
    <button onclick="openSendVibe('${name}')" class="w-full mt-6 rounded-2xl py-3 font-black text-white flex items-center justify-center gap-1.5" style="background: linear-gradient(135deg, #f59e0b, #ec4899)">■ Send a Vibe</button>
</div>
    ${profileUVibeShopSectionWeb(name)}
    ${profileTopSendersWeb(name)}
    <div class="mt-4">${profileUVibePostsGridWeb(name)}</div>
</div>`;
};

```

13. Seed Data Additions

Two small demo-data additions were needed to make the Shop section visibly testable (neither is required for the feature to work — they just prove it end-to-end for QA):

- Phone app: added a shop object to the existing UVIBES seed post 'uv1' (Carnival Committee's fete).
- Website: added a tag object to the existing UVIBE_POSTS_SEED post id 1 (same event).
- Phone app: extended the vibes seed array from 4 posts to 12 (3 per existing creator handle) so profile grids and feeds have more than one lonely photo to show per person.
- Website: extended SEED.vibes_posts similarly (from 4 posts to 11).

Example — phone app UVIBES shop tag:

```
{id:'uv1',uni:'uwistaug',type:'party',author:'Carnival Committee',verified:true,title:'Campus Carnival Fete ■', ...,
  shop:{id:'uv1',name:'Campus Carnival Fete – Ticket',price:30,kind:'event',img:'...',when:'Friday 8PM',loc:'SAC Quad'}}
```

Example — website UVIBE_POSTS_SEED tag:

```
{id:1, org:'UWI St. Augustine', ..., title:"Campus Carnival Fete ■", price:30, ...,
  tag:{kind:'event', title:'Campus Carnival Fete – Ticket', price:30, date:'2026-10-30', location:'SAC Quad', image:PIC('uv1',800,600)}},
```

14. New State & Storage Keys — Reference Table

Name	Platform	Type	Purpose
vibeFollowing	Phone	In-memory object	Vibes follow state, keyed by @handle
lk_vibe_following	Website	localStorage (via DB)	Same, persisted across reloads
uvFollowing	Phone	In-memory object	U Vibe follow state, keyed by author name
lk_uv_following	Website	localStorage (via DB)	Same, persisted across reloads
a.reactd (on GIFT_ACTIVITY row)	Phone	In-memory field	♥👍/👍 reaction on a received gift
g.reactd (on lk_gift_activity row)	Website	localStorage field	Same, persisted
n.vibeThread (on NOTIFS row)	Phone	In-memory field	Deep-link target for a notification
n.vibeThread (on lk_notifications row)	Website	localStorage field	Same, persisted
vibeProfileHandle / vibeProfileBackView	Website	Global vars	Which profile VIEWS.vibeProfile renders, and where Back goes
uvProfileName / uvProfileBackView	Website	Global vars	Same, for VIEWS.uvibeProfile
vibeGiftRecipient / vibeGiftSel	Website	Global vars	Active Send-a-Vibe modal state

15. Notes for the Dev Team

- **No backend/schema changes.** Everything above is front-end-only. When a real backend exists, the two functions worth swapping first are `vibeTopSenders()`/`vibeTopSendersWeb()` (currently fake, deterministic) — replace with a real "top gifters to this recipient" query — and the follower count functions, which should eventually read a real follows table instead of hashing the handle.
- **The leaderboard and follower counts are cosmetic/demo data** by design, not a bug — see Section 6 and the architecture note in Section 3. They're stable per-handle (same person always shows the same numbers) but not tied to any real social graph.
- **Messaging is intentionally one shared system** for both Vibes and U Vibe (this was already true before this round of work — U Vibe's message icon already opened the same inbox). Do not fork it into two separate chat stores; several new features (auto thank-you, the header Thank-You picker) depend on it staying unified.
- **The gift ledger (GIFT_ACTIVITY / lk_gift_activity) is also intentionally shared** across Vibes and U Vibe. The header ■ picker on both dashboards pulls from the same list, so a gift given/received on either surface shows up thank-able from either dashboard.
- **Testing tip:** the phone app gates the whole Profile tab behind a KYC "Verify your ID" modal on a fresh load. To reach the Gift Wallet screen while developing, set `kycStatus='verified'` in the console first, or click through the real verification flow.
- **Testing tip:** both files are opened directly as local files. Because of a macOS sandbox quirk with some preview tools, if a preview server can't read the Desktop folder directly, copy the project folder to `/tmp` and serve from there — the real, canonical files always live in `Desktop/New Master File/`.

End of document.