



Bill of Materials

<Parameter Title not found>

Source Data From: ET-COM.PrjPCB

Project: ET-COM.PrjPCB

Variant: None

Creation Date: 2018/5/27 22:50:59

Print Date: 43247 43247.95217

Footprint	Comment	LibRef	Designator	Description	Quantity
LC-0805_C	1uF (105) 10%		C7	贴片电容	
		10% 50V			
LC-0805_C	100nF(104) 10%	0805	C8		
	50V	100nF(104) 10%			
		50V			
LC-0805_C	22nF (223) 10%	0805 22nF (223)	C9		
	50V	10% 50V			
LC-SOD-123	B5819W SL	SOD-123	D1	肖特基二极管	
		B5819W SL			
LC-SMB(DO-	P6SMB6.8CA	SMB/DO-214AA	D2	TVS	
214AA) S1		P6SMB6.8CA			
SOD-123	B5819W SL	SOD-123	D3	—————————————————————————————————————	
		B5819W SL			
LC-1206_L	Fuse 1	Fuse 1	F1	Fuse	
connector_x3	Header 3	Header 3	P1	Header, 3-Pin	
HDR1X15		Header 15	P2, P3	Header, 15-Pin	
LC-SOT-	2SC3356-T1B-A		Q1		
23(SOT-23-3)	S/YS档	2SC3356-T1B-A			
		S/YS档			
LC-0805_R	1KΩ (1001) 1%		R3		
	` ′	(1001) 1%			
LC-0805_R	15KΩ (1502)	0805 15KΩ	R4		
	1%	(1502) 1%			
LC-SOIC-	ADUM1200ARZ-	ADUM1201ARZ-	U2		
8_150mil	RL7	RL7			
RE-24 N	AD5422AREZ	AD5422AREZ	U3	Single 16-Bit Current Source Digital-to-	
_				Analog Converter with Serial Interface and	
				HART Connectivity, -40 to +85 degC, RE-	
				24, Pb-Free, Tube	
LC-SOIC-	ADUM1201ARZ-	ADUM1201ARZ-	U4		
8_150mil	RL7	RL7		,	
				•	10
Approved		Notes			