

Python homework unit four

1. A local variable in python is a variable that is? Accessible from within the function
2. Which of the following statements are the advantages of using functions? Reduce duplication of code, clarity of code, reuse of code
3. The keyword that is used to define the block of statements in a function? `def`
4. The characteristics of docstrings are a suitable way of using documentation, a function should have a docstring, can be accessed by `__doc__`
5. The two types of functions used in python are built-in and user-defined,
6. `math` refers to built-in mathematical functions? `sqrt`
7. The variable defined outside the function is referred to as? Global
8. Functions without a return statement do not return a value and it is? Nothing
9. The data type of the elements in `sys.argv`? string
10. The length of `sys.argv` is? Total number of arguments excluding the filename
11. The syntax of keyword arguments specified in the function header? `**` followed by an identifier
12. The number of arguments that can be passed to a function is? 0 or more
13. The library that is used to create, manipulate, format and convert dates, times and timestamps in python is? `datetime`
14. The command-line argument is stored in? `sys.argv`
15. The command that is used to install a third-party module in python is? `pip`
16. Judge the output of the following code.

```
import math
```

```
math.sqrt(36) = 6.0
```

17. The function `divmod(10/20)` is evaluated as `(10//20, 10%20)`
18. Predict the output of the following code?

```
def tweet():
```

```
    print("python programming!")
```

```
tweet()          python programming
```

19. The output of the following code is

```
def display_message(message, times = 1):
```

```
    print(message * times)
```

```
display_message("date")
```

```
display_message("science", 5)
```

date science science science science science

20. Guess the output of the following code

```
Def quad(x):  
    Return x*X*X*X*  
  
X = quad(3)  
  
Print(x)  
  
81
```

21. The output of the following code is

```
Def add (*args):  
    X= 0  
    For l in range:  
        X+=i  
    Return x  
Print(add(1,2,3,))  
Print(add(1,2,3,4,5))  
615
```

22. Gauge the output of the following code

```
Def foo():  
    Return total +1  
  
Total = 0  
Print(foo())  
Output = 1
```

23. The default argument specified in the function header is an?
Identifier following by an = and default value

Mohammad Reza Tawana