



UNSUPERVISED LEARNING IN R

# Introduction to PCA

# Unsupervised learning

- Two methods of clustering — finding groups of homogeneous items
- Next up, dimensionality reduction
  - Find structure in features
  - Aid in visualization

# Dimensionality reduction


- A popular method is principal component analysis (PCA)
- Three goals when finding lower dimensional representation of features:
  - Find linear combination of variables to create principal components
  - Maintain most variance in the data
  - Principal components are uncorrelated (i.e. orthogonal to each other)

# PCA intuition

2 dimensions:  
x and y


PCA

1 dimension:  
One principal component




# PCA intuition

Regression line represents the principal component




# PCA intuition


Projected values on principal component is called **component scores** or **factor scores**




# Visualization of high dimensional data



Two-dimensional





Three-dimensional



Four-dimensional

# Visualization





# PCA in R

```
> pr.iris <- prcomp(x = iris[-5], scale = FALSE, center = TRUE)
> summary(pr.iris)
```

Importance of components:

	PC1	PC2	PC3	PC4
Standard deviation	2.0563	0.49262	0.2797	0.15439
Proportion of Variance	0.9246	0.05307	0.0171	0.00521
Cumulative Proportion	0.9246	0.97769	0.9948	1.00000



UNSUPERVISED LEARNING IN R


**Let's practice!**



UNSUPERVISED LEARNING IN R



# **Visualizing and interpreting PCA results**

# Biplot



# Scree plot

When number of PCs and number of original features are the same, the cumulative proportion of variance explained is 1



# Biplots and scree plots in R


```
> # Creating a biplot
> pr.iris <- prcomp(x = iris[-5], scale = FALSE, center = TRUE)
> biplot(pr.iris)

> # Getting proportion of variance for a scree plot
> pr.var <- pr.iris$sdev^2
> pve <- pr.var / sum(pr.var)


> # Plot variance explained for each principal component
> plot(pve, xlab = "Principal Component",
      ylab = "Proportion of Variance Explained",
      ylim = c(0, 1), type = "b")
```

# Biplots and scree plots in R

## Biplot



## Scree plot





UNSUPERVISED LEARNING IN R

**Let's practice!**





UNSUPERVISED LEARNING IN R

# Practical issues with PCA

# Practical issues with PCA

- Scaling the data
- Missing values:
  - Drop observations with missing values
  - Impute / estimate missing values
- Categorical data:
  - Do not use categorical data features
  - Encode categorical features as numbers

# Scaling

```
> data(mtcars)
> head(mtcars)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

```
# Means and standard deviations vary a lot
```



```
> round(colMeans(mtcars), 2)
```

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
20.09	6.19	230.72	146.69	3.60	3.22	17.85	0.44	0.41	3.69	2.81

```
> round(apply(mtcars, 2, sd), 2)
```

mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
6.03	1.79	123.94	68.56	0.53	0.98	1.79	0.50	0.50	0.74	1.62

# Importance of scaling data



# Scaling and PCA in R

```
> prcomp(x, center = TRUE, scale = FALSE)
```



UNSUPERVISED LEARNING IN R


**Let's practice!**



UNSUPERVISED LEARNING IN R



# **Additional uses of PCA and wrap-up**

# Dimensionality reduction








# Data visualization



# Interpreting PCA results



# Importance of data scaling



# Up next

```
# URL to cancer dataset hosted on DataCamp servers
> url <- "http://s3.amazonaws.com/assets.datacamp.com/production/
course_1903/datasets/WisconsinCancer.csv"

# Download the data: wisc.df
> wisc.df <- read.csv(url)
> wisc.data[1:6, 1:5]
```

	radius_mean	texture_mean	perimeter_mean	area_mean	smoothness_mean
842302	17.99	10.38	122.80	1001.0	0.11840
842517	20.57	17.77	132.90	1326.0	0.08474
84300903	19.69	21.25	130.00	1203.0	0.10960
84348301	11.42	20.38	77.58	386.1	0.14250
84358402	20.29	14.34	135.10	1297.0	0.10030
843786	12.45	15.70	82.57	477.1	0.12780



UNSUPERVISED LEARNING IN R

**Let's practice!**