ITI – RedHat Admin 1 – Lab2

Mohammad Tarek Omar – Data Management

1) Create a user account with the following attribute

```
mohammadtarek@localhost:~
[mohammadtarek@localhost ~]$ useradd -c "Islam Askar" islam
useradd: Permission denied.
useradd: cannot lock /etc/passwd; try again later.
[mohammadtarek@localhost ~]$ sudo useradd -c "Islam Askar" islam

We trust you have received the usual lecture from the local System
Administrator. It usually boils down to these three things:

    #1) Respect the privacy of others.
    #2) Think before you type.
    #3) With great power comes great responsibility.

[sudo] password for mohammadtarek:
Sorry, try again.
[sudo] password for mohammadtarek:
Sorry, try again.
[sudo] password for mohammadtarek:
[mohammadtarek@localhost ~]$ useradd -c "Islam Askar" islam
useradd: user 'islam' already exists
[mohammadtarek@localhost ~]$ passwd islam
passwd: Only root can specify a user name.
[mohammadtarek@localhost ~]$ sudo passwd islam
Changing password for user islam.
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: all authentication tokens updated successfully.
[mohammadtarek@localhost ~]$
```

2) Create a user account with the following attribute

```
mohammadtarek@localhost:~
[mohammadtarek@localhost ~]$ sudo useradd -c "Bad User" baduser
[mohammadtarek@localhost ~]$ sudo passwd baduser
Changing password for user baduser.
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: all authentication tokens updated successfully.
[mohammadtarek@localhost ~]$
```

3) Create a supplementary (Secondary) group called pgroup with group ID of 30000

4)Create a supplementary group called badgroup

```
[mohammadtarek@localhost ~]$ sudo groupadd -g 30000 pgroup
[mohammadtarek@localhost ~]$ sudo groupadd badgroup
[mohammadtarek@localhost ~]$
```

5) Add islam user to the pgroup group as a supplementary group

```
[mohammadtarek@localhost ~]$ sudo usermod -aG pgroup islam
[sudo] password for mohammadtarek:
[mohammadtarek@localhost ~]$
```

6) Modify the password of islam's account to password

```
[mohammadtarek@localhost ~]$ passwd islam
passwd: Only root can specify a user name.
[mohammadtarek@localhost ~]$ sudo passwd islam
Changing password for user islam.
New password:
BAD PASSWORD: The password fails the dictionary check - it is based on a diction
ary word
Retype new password:
passwd: all authentication tokens updated successfully.
[mohammadtarek@localhost ~]$
```

7) Modify islam's account so the password expires after 30 days

```
[mohammadtarek@localhost ~]$ chage -M 30 islam
chage: Permission denied.
[mohammadtarek@localhost ~]$ sudo chage -M 30 islam
[mohammadtarek@localhost ~]$ ls -l islam
```

```
[mohammadtarek@localhost ~]$ sudo chage -l islam
[sudo] password for mohammadtarek:
Last password change                                    : Nov 08, 2025
Password expires                                        : Dec 08, 2025
Password inactive                                       : never
Account expires                                         : never
Minimum number of days between password change          : 0
Maximum number of days between password change          : 30
Number of days of warning before password expires       : 7
[mohammadtarek@localhost ~]$ S
```

8) Lock bad user account so he can't log in

```
[mohammadtarek@localhost ~]$ usermod -L baduser
usermod: Permission denied.
usermod: cannot lock /etc/passwd; try again later.
[mohammadtarek@localhost ~]$ sudo usermod -L baduser
[mohammadtarek@localhost ~]$
```

9) Delete bad user account

```
[mohammadtarek@localhost ~]$ userdel -r baduser
userdel: Permission denied.
userdel: cannot lock /etc/passwd; try again later.
[mohammadtarek@localhost ~]$ sudo userdel -r baduser
```

10) Delete the supplementary group called badgroup.

```
[mohammadtarek@localhost ~]$ sudo groupdel badgroup
[mohammadtarek@localhost ~]$
```

13) Create a folder called myteam in your home directory and change its permissions to read only for the owner.

```
[mohammadtarek@localhost ~]$ chmod u=r myteam
[mohammadtarek@localhost ~]$ ls -ld myteam
dr--r-xr--. 2 mohammadtarek mohammadtarek 6 Nov  8 13:54 myteam
```

14) Log out and log in by another user

```
[mohammadtarek@localhost ~]$ su - islam
Password:
[islam@localhost ~]$ pwd
/home/islam
[islam@localhost ~]$
```

15) Try to access (by cd command) the folder (myteam)

```
[mohammadtarek@localhost ~]$ su - islam
Password:
[islam@localhost ~]$ cd myteam
-bash: cd: myteam: No such file or directory
[islam@localhost ~]$
```

16)

```
[mohammadtarek@localhost ~]$ touch oldpasswd
[mohammadtarek@localhost ~]$ chmod u=rw,g=wx,o=x oldpasswd
[mohammadtarek@localhost ~]$ chmod 631 oldpasswd
[mohammadtarek@localhost ~]$ umask 035
[mohammadtarek@localhost ~]$
[mohammadtarek@localhost ~]$ ls -l oldpasswd
-rw--wx--x. 1 mohammadtarek mohammadtarek 0 Nov  8 14:36 oldpasswd
[mohammadtarek@localhost ~]$
```

- **umask for dictionaries is 777, and for files is 666.**

```
[mohammadtarek@localhost ~]$ umask 777
[mohammadtarek@localhost ~]$ mkdir dir1
[mohammadtarek@localhost ~]$ ls -ld dir1
d---------. 2 mohammadtarek mohammadtarek 6 Nov  8 14:40 dir1
[mohammadtarek@localhost ~]$ touch file2
[mohammadtarek@localhost ~]$ ls -l dile2
ls: cannot access 'dile2': No such file or directory
[mohammadtarek@localhost ~]$ ls -l file2
----------. 1 mohammadtarek mohammadtarek 0 Nov  8 14:40 file2
[mohammadtarek@localhost ~]$
```

17) What are the minimum permission needed for:

1. r, x

2. r, x

3. no permissions needed but must make it's dic has permission w

4. x

5. r

6. r

7. w

18) Create a file with permission 444. Try to edit in it and to remove it? Note what happened.

```
[mohammadtarek@localhost ~]$ touch file1
[mohammadtarek@localhost ~]$ chmod 444 file1
[mohammadtarek@localhost ~]$ ls -l file1
-r--r--r--. 1 mohammadtarek mohammadtarek 0 Nov  8 14:18 file1
[mohammadtarek@localhost ~]$ rm echo "ll" >> file1
-bash: file1: Permission denied
[mohammadtarek@localhost ~]$ rm file1
rm: remove write-protected regular empty file 'file1'? y
[mohammadtarek@localhost ~]$
```

19) What is the difference between the “x” permission for a file and for a directory?

Execute in file allows you to run it’s script, but execute in dictionary allows you to just see it’s name and what is inside it.