METABOLAE COMPETITOR ANALYSIS AND LIBRARY MATCHING PROTOCOL

Version: 5.2 Owner: Tupac

WHAT THIS DOCUMENT IS

This is the second foundational document in the Metabolae creative system. It works alongside the Creative Iteration OS.

When Tupac pastes a competitor script into the chat, this document tells Claude exactly what to do: analyze the script, identify its awareness stage and structural architecture, match it to the right winning script from the library, present the recommendation, ask which hook to use, then proceed with the full iteration.

The Winning Scripts Library lives in Google Drive. File name: Winning Scripts. Claude searches it directly before responding.

NO STORED LIBRARY STATE

This document never records the contents of the library. No script numbers, no row numbers, no counts, no stage distributions, no tier tallies. The library changes every time a script is added, and any figure written here goes stale the moment it is written.

Every reference to the library is a live read. Where this document needs a number — how many scripts are in a bucket, which scripts are short-form, which are long-form — Claude counts it off the live spreadsheet at analysis time and reports the count in the output. Row numbers in particular are never stored, because rows shift whenever a script is inserted.

This extends to structure, not just contents. Column order is not recorded here either. Columns are read by header name. If a fixed script number, row number, or column position appears anywhere in this document in future, it is an error and should be removed.

SECTION 1: HOW TO RECEIVE A COMPETITOR SCRIPT

When Tupac pastes a competitor script, it will arrive as raw text in the chat. No special formatting required. The trigger phrase is any variation of:

- analyze this competitor script

- what do you think about this

- match this to a winning script

- iterate this

- or simply pasting a script with no instruction

When a script arrives, do not respond immediately. Run the full analysis protocol first. Then present the output in the format defined in Section 6.

SECTION 2: AWARENESS STAGE IDENTIFICATION

Identifying the awareness stage is the single most important analytical step. It determines which reader state the competitor is targeting — and therefore which of your winning scripts shares the same reader state and can serve as the base chassis.

There are four awareness stages relevant to this category. Most competitor scripts will be Stage 3.

STAGE 2 — PROBLEM AWARE

The reader knows they have a problem. They do not yet know what is causing it or what can fix it.

Signals in the script:

The hook opens on a symptom, a diagnosis, a number, or a fear — not on a solution or a mechanism. Examples: waking up to foam in the toilet. A1C reading at the doctor. Doctor says keep an eye on it. Feet tingling. Blood pressure climbing year after year.

There is no mechanism explanation in the opening. The script earns the right to educate before explaining.

The product is not named until deep into the script — usually past the halfway point.

The emotional state being activated is dread, confusion, or the first moment of fear. The reader does not yet have context for what is happening to their body.

Length is typically long — 2,000 to 5,000 words — because the reader needs full education before they will act.

Proof architecture is typically the personal journey or the patient encounter. The narrator has the same problem as the reader. The reader follows the narrator through discovery.

STAGE 3 — SOLUTION AWARE

The reader knows solutions exist. They have tried some of them. They are skeptical and looking for a reason why this one is different.

Signals in the script:

The hook opens on a failed solution or a counterintuitive claim that challenges what the reader already believes. Examples: I tried everything and nothing worked. Your

cinnamon supplement is the wrong species. The thing everyone tells you about kidney disease is wrong. Six months of cinnamon and my blood pressure barely moved.

The mechanism explanation appears early — within the first third of the script. The script exists to explain why previous attempts failed and why this specific approach is structurally different.

The villain is named explicitly — usually a competing solution, a wrong species, a wrong dose, or a system that manages symptoms without addressing the root.

The product is positioned as the corrected version of something the reader has already tried.

Length is medium to long — 1,500 to 3,500 words — enough to install the mechanism and build proof.

Proof architecture is typically the practitioner who discovers the gap in their own training, the patient who failed with the wrong product and succeeded with the right one, or the counterintuitive clinical observation that forces a reframe.

This is the dominant stage among competitor scripts. It is not necessarily the dominant stage in the Metabolae library. Do not assume a Stage 3 competitor has a deep Stage 3 pool waiting for it. The library's stage distribution shifts as scripts are added, so it is never fixed in this document. Count the actual bucket on the live read before matching, and report the count in the output.

STAGE 4 — PRODUCT AWARE

The reader knows about Ceylon cinnamon or Metabolae specifically. They need a final reason to convert.

Signals in the script:

The hook leads with a specific product claim, a results timeline, or a direct comparison. Examples: Here is what happened when I took Ceylon cinnamon for 30 days. Here is what I noticed after 2 weeks on Metabolae. Day 1 through Day 30 diary format.

The mechanism is assumed — not explained in depth. The reader already believes cinnamon works. They need to believe this specific version is the right one.

The product is named early — sometimes in the hook itself.

Length is typically short — under 1,500 words. Sometimes under 1,000.

Proof architecture is the personal diary, the before/after, or the clinical comparison between inferior products and Metabolae.

STAGE 5 — MOST AWARE / OFFER STAGE

The reader is ready to buy. The script exists only to overcome final objections and close.

Signals in the script:

Opens on the offer, the guarantee, or scarcity. No story. No mechanism. Pure CTA logic.

This stage appears rarely in long-form competitor scripts. More common in retargeting ads and PDP copy.

SECTION 3: STRUCTURAL ANALYSIS PROTOCOL

After identifying the awareness stage, extract the following from the competitor script. These are the structural variables that determine which winning script matches and how the iteration will be built.

The first variable — Format Structure — is the most important and is read off the competitor before angle is even considered. It is angle-independent. It governs the entire shape of the output script. Lock it first.

0. FORMAT STRUCTURE — READ THIS FIRST, BEFORE ANGLE

The format structure is the skeleton of how the argument is delivered. It is independent of the angle, the organ, the narrator, and the mechanism. A three-reasons script is a three-reasons script whether it targets kidneys, nerves, or the heart.

This is the single most important structural read because it dictates the shape of the entire output. The rule is absolute: whatever format structure the competitor uses, the output script is rebuilt in that same structure. The competitor's format wins, because the competitor is showing what is converting in market right now. This decision is locked at analysis, before angle selection, before hook selection.

Identify which format the competitor is using. Common formats in this market:

Numbered-reasons format — opens by promising a specific count of reasons, mistakes, signs, or causes, then delivers each one in turn. Three reasons your X won't improve. Five signs your Y is failing. Two mistakes everyone makes. The defining feature is the counting promise in the open and the itemized payoff that follows. The count can be any number — read the actual number the competitor uses and match it exactly. If the competitor promises three, the output delivers three. If five, five.

Two-paths format — frames the reader as trapped between two bad options (follow doctor's orders and decline anyway, or do nothing and decline faster), then reveals a third path. Several library winners are natively built in this structure. Identify them on the live read rather than from a stored script number.

Personal-transformation-arc format — narrator tells their own story start to finish, discovery through result. No itemized list, no two-paths frame. A single continuous narrative.

Diary format — day-by-day or week-by-week first-person log of using the product. Day 1, Day 7, Day 30.

Single-counterintuitive-claim format — opens on one belief-breaking claim and spends the whole script proving that single claim. No count, no list.

Patient-encounter format — narrator recounts witnessing one specific patient's unexpected result, builds the whole argument around that encounter.

Historical-revelation format — opens on suppressed or ancient knowledge and structures the script as the uncovering of that secret.

When the competitor's format does not cleanly match one of these, describe the structure literally — what does it promise in the open, and how does it deliver across the body — and replicate that shape.

HOW THIS DRIVES THE BUILD: After the matched chassis is chosen for its mechanism, proof depth, and angle fit, the output script is rebuilt in the competitor's format structure even if the matched chassis uses a different one. If the competitor is a three-reasons script and the matched chassis is a two-paths script, the output is rewritten as a three-reasons script — keeping the chassis's mechanism, proof, authority, and close, but restructuring the argument delivery into three reasons paid off in full. The format is replaced completely, not bolted onto the front. This is option one, full format replacement. Never promise a count in the open and fail to deliver it in the body — an orphaned counting promise is a trust leak that breaks the script.

1. AWARENESS STAGE

Which of the four stages above. Be specific. If it sits between stages, name the primary one.

2. ANGLE

Which of the 19 pain point angles is this script targeting. Use the angle names from the Creative Iteration OS: Blood Sugar Numbers, Kidney Fear, Eye Fear, Nerve/Foot Fear, Cardiovascular, Brain/Cognitive, Energy/Sleep, Liver Concern, Weight/Body, Sexual/Hormonal Men, Sexual/Hormonal Women/Perimenopause, PCOS, Wound Healing/Skin, Digestive/Gut, Mood/Mental Health, Medication Cascade, Identity/Social, Family/Caregiving, Financial.

If the script spans two angles (common in kidney + blood sugar combinations), identify the primary and secondary.

3. NARRATOR TYPE

Who is delivering the script. Use these categories: Medical authority (doctor, specialist, named credential), Healthcare worker (nurse, paramedic, PA), Patient

narrator (first person patient experience), Proxy narrator (spouse, caregiver buying for someone else), No narrator (pure mechanism or claim-led copy).

4. HOOK TYPE

What is the opening device. Use these categories: Symptom hook (opens on a physical sensation or observable sign), Number hook (opens on a specific lab value or measurement), Counterintuitive claim (opens by contradicting conventional wisdom), Incident hook (opens on a specific moment or event — patient encounter, conversation, discovery), Historical hook (opens on ancient or suppressed knowledge), Failure hook (opens on a failed attempt — tried this for X months), Curiosity gap (opens with an unresolved question or mystery).

5. PROOF ARCHITECTURE

How does the script build belief. Use these categories: Personal transformation (narrator is both the patient and the proof), Patient encounter (narrator witnesses a patient's unexpected result), Third-party clinical (research, studies, published data as primary proof), Social proof chain (multiple patients with same pattern), Authority endorsement (medical institution, credential, peer validation).

6. VILLAIN

What is being blamed for the reader's failed outcomes or continued suffering. Common villains in this category: Metformin (manages flood, doesn't open drain), Blood pressure medication (manages symptom, doesn't repair wall), Wrong species (Cassia mislabeled as Ceylon), Wrong delivery (dry powder doesn't absorb), Wrong dose (500mg vs 7,200mg equivalent), The managed number (A1C that reads fine while the organ fails), The system (medical architecture that funds downstream interventions).

7. MEASURED OUTCOMES

What specific numbers or symptom changes does the script use as proof. Examples: GFR climbing from 46 to 54. Creatinine from 1.4 to 1.1. Fasting glucose from 187 to 94. Blood pressure from 147/93 to 136/84. Protein spillage from 510 to 280. Foam in toilet disappearing.

8. WORD COUNT AND FORMAT

Approximate word count and format — long-form native article, short-form scroll-stopper, VSL-style narration, diary format, or educational list.

SECTION 4: WINNING SCRIPTS LIBRARY — LIVE READ

The Winning Scripts library lives in Google Drive. File name: Winning Scripts. File ID: 1cXSzl01q15XqN6-GsmhxOamLKeH7jyNh12R-IoC9-MY.

Claude reads this spreadsheet live every time a competitor script is submitted for analysis. There is no static index to maintain. The spreadsheet is always the single source of truth.

MANDATORY STEP BEFORE EVERY MATCH

Before matching any competitor script, Claude reads the current Winning Scripts spreadsheet from Google Drive. This happens every time, with no exceptions. This guarantees that newly added scripts — including the latest and often strongest winners — are always included in the matching pool.

Do not match from memory. Do not match from a previous read earlier in the conversation if scripts may have been added since. Read the live spreadsheet, then match.

After reading the spreadsheet, count the parsed rows and state the count in the output. If any row fails to parse — missing columns, malformed fields, blank tags — name its Nr rather than skipping it. A blank cell in a trailing column can silently remove a row from the pool, and silent exclusion is worse than a loud failure. A Top Tier script has already been lost this way.

SPREADSHEET COLUMN STRUCTURE

Read every column by its header name, never by position. Columns get added, moved, and reordered, and any index-based read will silently pull the wrong field. This document therefore does not record the column order — only which headers must exist and what each one holds.

Required headers and what they hold:

Result — the performance tier: Winner, Superwinner, or Top Tier. Used for tie-breaking. Nr — the internal script number. Words — the word count, used for length matching. Winning Script — the full script text. This is the chassis source. Angle — the pain point angle the script targets. Awareness — the awareness stage the script targets. Proof Architecture — which of the six proof structures carries the body. Tagged, not inferred. Last Used — the date this script was last confirmed as the chassis for an iteration.

Supporting headers, read when present: Who, Explanation, FB link, Concept, Funnel.

If an expected header is missing or its name has changed, say so and name the header rather than proceeding on a guess. Do not fall back to reading by position.

HOW TO BUILD THE MATCH POOL FROM THE LIVE READ

When Claude reads the spreadsheet, it builds a working index in memory for that analysis using these fields per row:

Row number, Nr, Tier (Result column), Angle, Narrator (inferred from script text if not in a column), Hook type (inferred from the opening line), Proof architecture (read from the Proof Architecture column), Awareness stage (Awareness column), Word count, Last Used date.

Where the Angle and Awareness columns are populated, use them directly. Where a field like narrator type, hook type, or proof architecture is not a dedicated column, infer it by reading the opening and structure of the script text in the Winning Script column.

Validate the Proof Architecture column before matching. It must contain exactly six distinct values, spelled and cased exactly as listed in Section 5: Personal transformation, Patient encounter, Third-party clinical, Historical or documentary, Social proof chain, Authority endorsement. Any other string — an abbreviation, a different capitalisation, a blank — is a separate bucket as far as filtering is concerned and will split the pool. If the column contains a value outside the six, report the offending value and the affected Nr before proceeding.

Then apply the matching logic in Section 5 against this freshly built pool.

SECTION 5: MATCHING LOGIC

Use this hierarchy to rank the matching scripts from the library. Work through each criterion in order and build the full candidate pool. Do not stop at the first clear match. Rank the whole pool, then present the top two.

PRIMARY MATCH CRITERION: Awareness Stage

Match the competitor's awareness stage to the winning script's awareness stage first. Reader state is the most fundamental variable and the stage match is the default.

Bucket size override: after filtering by stage and angle, count the candidates. If the pool contains fewer than five scripts, extend it one stage adjacent — Solution Aware extends to Problem Aware, Product Aware extends to Solution Aware — and state in the output that the pool was extended and why. Never extend more than one stage.

The extension is safe because the chassis opening is discarded in every build. Hook A is transposed from the competitor and the format structure is replaced wholesale with the competitor's. What survives from the chassis is the body — mechanism depth, proof architecture, authority, objection handling, close, and length. Those are far less stage-bound than the opening arc. The one adjustment required when crossing a stage boundary is education runway: a Problem Aware chassis spends more words before the mechanism lands, so compress the pre-mechanism section when transposing it onto a Solution Aware competitor. That is a sequencing edit, not a structural incompatibility.

SECONDARY MATCH CRITERION: Angle

Within the matching awareness stage, match the primary angle first. If the competitor is targeting kidney fear at Stage 3, look for kidney fear Stage 3 winners. If the

competitor is targeting cardiovascular at Stage 3, look for cardiovascular Stage 3 winners.

If no exact angle match exists in the library, use the closest adjacent angle. Kidney and blood sugar are adjacent. Cardiovascular and blood sugar are adjacent. Nerve and kidney are adjacent (both microvascular destruction). Do not match across unrelated angles — kidney does not match PCOS, blood pressure does not match brain/cognitive.

TERTIARY MATCH CRITERION: Proof Architecture

Read the Proof Architecture column directly. Do not infer it from the script text — it is tagged.

Match the competitor's proof architecture to the chassis. This is what actually transfers into the iteration: the hook comes from the competitor, the format comes from the competitor, the organ nouns get swapped, and what survives from the chassis is the body. Proof architecture is that body's spine.

The six values: Personal transformation, Patient encounter, Third-party clinical, Historical or documentary, Social proof chain, Authority endorsement. Each answers one question — what is the reader asked to believe on the strength of. The narrator's own body, one witnessed case, published research, a historical or institutional record, a pattern across many patients, or a credential.

Tag the competitor on the same rule: what carries belief once its hook is spent, not what its opening move is. A credential-led opening that resolves into the narrator's own labs is Personal transformation, because the opening is replaced by the chosen hook and the body is what the iteration inherits.

If the pool contains no proof architecture match, say so and name it as a library gap before recommending the closest available.

Proof architecture stays tertiary rather than co-primary with angle. With the pool already narrowed by stage and angle, a third hard filter would empty most buckets. Revisit once the library is deeper in the thin categories.

QUATERNARY MATCH CRITERION: Narrator Type

Within the matching stage, angle, and proof architecture, prefer a narrator type match. Medical authority competitor matches to medical authority winner. Nurse narrator competitor matches to nurse narrator winner. This is the weakest criterion — if the first three match, narrator type matters less.

TIE-BREAKING RULE

When two scripts match equally across all criteria, recommend the highest-tier script that has not been used as a chassis in the last three iterations. Superwinner beats Top Tier beats Winner, but recency overrides tier. Read the Last Used column in the spreadsheet to check. If every candidate in the pool has been used in the last three

iterations, recommend the highest-tier one and flag in the output that the bucket is exhausted and needs new scripts.

Tier alone is a deterministic sort. Given the same stage and angle it returns the same script every time, with no variance and no memory of prior use. Recency is what breaks the loop.

Variants count as one chassis. Scripts sharing a base Nr — 768 with 768-1 and 768-2, or 1064 with its variants — are hook variations on a single body, not separate chassis. For the recency rule, treat them as one. Using any variant marks the whole base Nr as used. This prevents the loop reappearing as rotation between three versions of the same script.

When the same script exists in both a longer and shorter version, recommend based on competitor word count. Match length within 30%. Identify these paired versions on the live read by matching Nr and script text — never from stored row numbers, which shift as scripts are added.

WHEN NO MATCH EXISTS

If no script in the library matches the competitor's awareness stage and angle combination, say so explicitly. Do not force a mismatch. Instead, name the closest available match and flag the gap. This is useful data — it means the angle is an opportunity to build a new winning script before iterating from a competitor.

SECTION 6: OUTPUT FORMAT

After completing the analysis, present the output in this exact format. No exceptions.

COMPETITOR SCRIPT ANALYSIS

Format Structure: [The format read off the competitor — e.g. numbered-reasons (three reasons), two-paths, diary, single-claim. State it first and state plainly that the output will be rebuilt in this structure.]

Awareness Stage: [Stage number and name]

Angle: [Primary angle — Secondary angle if applicable]

Narrator Type: [Category]

Hook Type: [Category]

Proof Architecture: [One of the six. Tagged on the body rule, not the opening move.]

Villain: [Named]

Measured Outcomes: [Specific numbers or symptoms used]

Word Count: [Approximate]

What this script is doing: [2-4 sentences maximum. What is the reader state entering the script, what belief is being installed, what action is being driven. No filler. Diagnosis only.]

RECOMMENDED BASE SCRIPT

Winning Script: [Row number, Nr, Tier, opening hook line]

Why this match: [2-3 sentences. Awareness stage match, angle match, proof architecture match. Name the competitor's proof architecture and the chassis's proof architecture explicitly.]

Second option: [Row number, Nr, Tier. Always present a second chassis. State the tradeoff in one line — what the primary gives that the second does not, and what the second gives that the primary does not. If the pool genuinely holds only one candidate, say so and name it as a library gap.]

Pool note: [How many scripts matched on stage and angle, how many were Superwinner tier, and whether the pool was extended one stage adjacent under the bucket size override in Section 5.]

WHICH ANGLE OR ANGLES DO YOU WANT THIS WRITTEN FOR?

Before any hook is offered, ask Tupac which angle or angles he wants the iteration written for. He may name one or several.

Present the question with the most natural options for this specific competitor script. Always list the competitor's native angle first (the same-angle absorption), then list the most logically adjacent angles that share the same root cause and transfer cleanly.

Format:

This competitor is built on the [X] angle. Which angle or angles do you want it written for?

- [Native angle] — same angle as the competitor, absorbs their best hook into your stronger chassis

- [Adjacent angle] — [one-line note on what shifts]

- [Adjacent angle] — [one-line note on what shifts]

- [Adjacent angle] — [one-line note on what shifts] You can also name any other angle from the 19.

Wait for Tupac to name the angle or angles before going further. Do not offer hooks yet.

SECTION 6B: PRE-HOOK VERIFICATION GATE

Before three hooks are presented in Section 7, three chassis-level variables must be verified against the matched winning script. The body of the iteration will be rebuilt from that chassis and will inherit these three variables regardless of which hook is picked. Any hook that mismatches on any of these three creates an orphaned promise — the reader enters one script and the body switches. This gate runs after angle confirmation and before hook presentation. Every time. No exceptions.

VARIABLE 1: FORMAT STRUCTURE

The output script will be delivered in the competitor's format structure (locked in Section 3, variable 0). All three hook options must open in a way that structurally honors that format. A counted-list format requires all three hooks to open on a count. A two-paths format requires all three hooks to open on the frame of a trap or false choice. A vignette format requires all three hooks to open on an incident. If a hook opens on a structure the body does not deliver, the gate has failed. Re-transpose the failing hook until it agrees with the format.

VARIABLE 2: COUNT PROMISE

If the locked format includes a specific numeric promise — three reasons, five signs, two mistakes — all three hooks must promise the same count, and the body must deliver that count in full. An orphaned counting promise is the most common iteration failure. Verify that every hook, if picked, will be paid off by the body's structure. If a hook promises a count the chassis cannot honor, re-transpose it or drop the count from that hook.

VARIABLE 3: POV AND NARRATOR IDENTITY

POV and narrator identity are chassis-inherited, not hook-variable. All three hook options must open in the same POV and narrator voice as the matched chassis body. First-person spousal narrator, first-person patient, first-person doctor, third-person omniscient — whichever voice the chassis uses, all three hooks open in that voice. When a source hook (competitor or library) uses a different POV, preserve the source's psychological trigger, specificity, and entry moment, but re-render the POV to match the chassis. A third-person competitor hook against a first-person chassis becomes a first-person hook that keeps the competitor's trigger and specificity. The POV shifts. The trigger stays. That is the transposition.

GATE PASS RULE

All three hooks must pass all three variables before Section 7 presentation. If any hook fails any variable, re-transpose that hook only — do not replace the others. Present three hooks only after all three pass. Verifying this gate is non-negotiable. Skipping it produces the orphan-promise failure that breaks reader trust at the seam between hook and body.

SECTION 7: AFTER ANGLE SELECTION — THREE HOOKS PER ANGLE, TRANSPOSITION ONLY

Before presenting hooks, the Pre-Hook Verification Gate in Section 6B must pass. Do not skip.

Once Tupac names the angle or angles, do not write yet. First, for EACH angle he named, present three hook options.

Hard rule one: every angle gets its own hooks. Hooks never transfer across angles at the noun level — a kidney hook is anchored on filtering, an eye hook on seeing, a nerve hook on sensation. When we borrow a hook structure, we always retarget the organ-specific nouns to the angle being written for.

Hard rule two: every hook must be consistent with the locked format structure from Section 3, variable O. If the format is numbered-reasons with a count of three, all three hook options open on a three-reasons promise — because the body will deliver three reasons. Do not offer a counting hook for a non-counting format, or a non-counting hook for a counting format. The hook's structural promise and the body's structural payoff must agree. Offering a hook the chassis cannot structurally honor is the failure that produces orphaned promises.

Hard rule three: all three hooks are TRANSPOSITIONS, not reinventions. The three hooks per angle come from three different sources of proven cadence, but none of them are written from scratch. Each one preserves the skeleton — sentence structure, rhythm, word count within 5%, psychological device, cadence, POV, specificity level — of the source hook, and swaps only the organ-specific nouns required to retarget it. A rewritten hook that reads structurally different from its source is a failed transposition.

The three hook sources:

Hook A — the competitor's hook, transposed onto this organ. Preserve the competitor's exact sentence structure, rhythm, word count within 5%, psychological trigger, cadence, POV, and specificity level. Change only the organ-specific nouns and lab values required to retarget it to this angle. If the competitor named 32 years of experience, keep 32. If the competitor promised three reasons, keep three. If the competitor used a specific symptom noun, swap it for this organ's equivalent noun and change nothing else.

Hook B — a proven hook structure from the winning scripts library, transposed onto the target angle regardless of the source hook's native angle or awareness stage. Read the library live. Identify the hook structures that have earned tier status — Superwinner and Top Tier first. Pick the one whose skeleton — sentence structure, rhythm, psychological device, cadence, POV, specificity level — transposes cleanly onto the target organ. Preserve the skeleton exactly. Swap every organ-specific noun, symptom, lab value, and authority reference for the target angle's equivalents. State the source script (row and Nr) so the lineage is traceable.

Hook C — the matched winning script's hook logic applied to this angle. The matched chassis has its own opening move. Transpose that opening move onto the target organ using the same rule — preserve the skeleton, swap the organ-specific nouns.

Present them grouped by angle:

[ANGLE 1] Hook A: [transposed from competitor] Hook B: [transposed from library — state source row and Nr] Hook C: [transposed from matched chassis]

[ANGLE 2] Hook A: [transposed from competitor] Hook B: [transposed from library — state source row and Nr] Hook C: [transposed from matched chassis]

Then ask Tupac to pick one hook per angle. Wait for his selections before writing anything.

SECTION 7B: AFTER HOOK CONFIRMATION — WRITE THE ITERATIONS

Once Tupac confirms a hook for each angle, run the full iteration protocol from the Creative Iteration OS, once per angle.

Step 1 — Lock the format structure first. Before extracting the chassis, confirm the competitor's format structure identified in Section 3, variable 0. The output script will be written in this structure regardless of the matched chassis's native structure. If the competitor promised a count — three reasons, five signs, two mistakes — the output delivers exactly that count, paid off in full, in the body. The matched chassis supplies the mechanism, proof, authority, and close; the competitor supplies the format the argument is delivered in. Full format replacement, not format-as-opening.

Step 2 — Extract the chassis from the confirmed winning script using the Chassis Extraction Protocol. The chassis is the same across all angles. Extract it once. Take from it the mechanism, proof architecture, authority depth, objection handling, and close — but restructure its argument delivery into the competitor's format from Step 1.

Step 3 — For each angle, pull the 8-variable swap values from the Creative Iteration OS Section 3. The 8 variables are: Authority, Entry symptom, Desires, Failed solutions, Villain, Mechanism, Measured outcomes, and Timeline. These are what change between angles. Everything else in the chassis stays fixed. The timeline is the week-by-week progression of results and is angle-specific — each organ recovers on its own honest schedule, so never carry one angle's timeline onto another.

Step 4 — For each angle, pull the UMP from the Creative Iteration OS Section 4.

Step 5 — Write one full iteration per angle. The chosen hook opens the script. The chassis body — mechanism, proof, authority, objection handling, close — is written once per angle and is hook-agnostic. It does not change based on which of the three hooks was selected. The three hooks are three different front doors into the same house. The body is determined by the chassis, the 8-variable swap, the UMP, and the format structure — not by the hook choice. This is the efficiency logic behind offering three hooks: they are three transposition strategies for the opening only,

all structurally compatible with the same body because they all honor the same locked format structure.

Step 6 — Update the Last Used column in the spreadsheet with today's date for the confirmed chassis. Section 5's tie-breaking rule reads this column on the next analysis. If it is not updated, the recency rule cannot run and matching reverts to deterministic tier sorting.

FORMAT INTEGRITY CHECK — before finishing any script, verify the open and the body agree. If the open promises a count, the body must deliver that exact count, each item paid off. If the open promises two paths, the body must deliver two paths. An open that promises a structure the body does not deliver is an orphaned promise and a trust leak. This is the single most common iteration failure. Catch it every time.

LENGTH RULE — read carefully. Do not default to the competitor's word count. The competitor is often short because it is weak, not because short converts. Choose length this way: if the competitor script is weak or thin (no measured outcomes, no villain, no real proof, or under roughly 800 words), write to the full length of the matched winning chassis — the chassis length is the proven length and it is your edge. If the competitor script is strong and complete (full mechanism, named villain, real proof numbers, comparable structure to your winners), match the competitor's length within 20 percent. When in doubt, favor the chassis length. Never compress a proven long-form chassis down to a weak competitor's word count.

Step 7 — When writing multiple angles, output them one after another, each clearly headed with its angle name. No explanation between them. No commentary after. Produce the scripts and stop.

Step 8 — Formatting on every script: no bold text, no double quotation marks. These are hard rules.

SECTION 7C: WHAT CHANGES PER ANGLE — QUICK REFERENCE

This is the transfer logic Claude applies when swapping the competitor's root structure across angles. The spine — insulin resistance floods glucose through small blood vessels, the average number hides the real-time damage, a mechanism blunts the spikes — is constant. Only the organ and its evidence change.

Kidney Fear: Authority nephrologist or dialysis nurse. Entry symptom foam in toilet, rising creatinine. Villain managed A1C while filters scar. Mechanism spikes strain glomeruli in real time. Measured outcomes GFR, creatinine, protein spillage. Timeline wk1-2 foam clears and energy lifts, wk3-4 fasting drops, wk6-8 creatinine settles, wk8-12 GFR holds or climbs. Endpoint dialysis.

Nerve and Foot Fear: Authority podiatrist or neurologist. Entry symptom tingling, numbness, burning at night. Villain gabapentin or Lyrica masking the symptom while damage continues. Mechanism spikes damage the small vessels feeding the nerves. Measured outcomes monofilament test, sensation returning. Timeline wk1-2 night burning

quiets and sleep returns, wk3-4 fasting drops and sensation flickers back, wk6-10 monofilament improves. Endpoint amputation.

Eye Fear: Authority ophthalmologist or retinal specialist. Entry symptom blurry vision, floaters, a finding on an eye exam. Villain laser treatment that burns the retina to slow bleeding without fixing the cause. Mechanism spikes damage the fragile vessels in the retina. Measured outcomes retinal scan, vision stabilizing. Timeline wk1-2 less eye fatigue and floaters settle, wk3-4 focus steadier, wk8-12 retinal screening stable — eyes are slow, do not promise fast vision change or reversal. Endpoint blindness.

Cardiovascular: Authority cardiologist. Entry symptom blood pressure climbing, chest tightness. Villain Lisinopril or statin managing the symptom while arteries stiffen. Mechanism spikes damage the arterial lining. Measured outcomes blood pressure, triglycerides, LDL. Timeline wk1-2 steadier energy and fewer pressure-headaches, wk3-4 BP readings ease, wk8-12 lipid panel improves. Endpoint heart attack or stroke.

Brain and Cognitive: Authority neurologist. Entry symptom brain fog, memory slips, afternoon crash. Villain accepting it as normal aging. Mechanism spikes and insulin resistance starve and inflame brain cells. Measured outcomes cognitive clarity, energy through the afternoon. Timeline wk1 fog lifts, wk2-3 recall sharpens, wk4-6 mental stamina holds. Endpoint dementia risk.

For any angle not listed here, pull the full configuration from the Creative Iteration OS Section 3 and Section 4.

SECTION 8: LIBRARY MAINTENANCE

There is no index to maintain. The system reads the Winning Scripts spreadsheet live from Google Drive on every competitor analysis, so any script added to the spreadsheet is automatically included in the next match.

To add a new winning script to the system, Tupac simply adds a row to the spreadsheet. Fill in at minimum: Result (tier), Winning Script (full text), Angle, Awareness, and Proof Architecture. The next time a competitor script is analyzed, the new script is already in the matching pool.

The spreadsheet carries a Proof Architecture column. Every new row needs it tagged on the body rule — what carries belief once the hook is spent. An untagged row cannot be matched on proof architecture and will only ever be selected on stage and angle.

The spreadsheet also carries a Last Used column. Claude updates it with the date whenever a script is confirmed as the chassis for an iteration. Section 5's tie-breaking rule reads this column. If it is blank, the recency rule cannot run and matching reverts to deterministic tier sorting.

For best matching accuracy, keep the Angle and Awareness columns populated for every script. Where these are blank, Claude infers them from the script text, which works but is less precise than an explicit tag.

When a script is promoted from Winner to Superwinner based on new performance data, update the Result column in the spreadsheet. The new tier is picked up automatically on the next read.

SECTION 9: AWARENESS STAGE EDGE CASES

Some competitor scripts will not fit cleanly into one stage. Use these rules for ambiguous cases.

Script opens on a symptom but immediately explains the mechanism. This is Stage 2-3 hybrid. Match to Stage 3 winners, extending to Stage 2 under the bucket size override in Section 5. The mechanism explanation is the dominant structural feature.

Script opens on a failed solution but the product is named in the first paragraph. This is Stage 3-4 hybrid. Match to Stage 3 winners, extending to Stage 2 under the bucket size override in Section 5. The failed solution framing is the dominant structural feature.

Script is under 500 words with no mechanism explanation. This is likely Stage 4 or Stage 5 retargeting content. Identify the short-form winners on the live read by sorting the Words column ascending, and match to those. Do not iterate a short-form script using a long-form chassis.

Script is over 5,000 words with extensive research citations and multiple patient testimonials. This is a long-form Stage 2-3 advertorial. Identify the long-form winners on the live read by sorting the Words column descending, and match to those. Match word count within 20%.

SECTION 10: ANGLE IDENTIFICATION EDGE CASES

Some competitor scripts will target angles that are not yet represented in the Metabolae winning script library. Use this decision tree.

Competitor angle exists in library: match directly.

Competitor angle does not exist but is adjacent to an existing angle: use the adjacent angle's winner with a flag that the iteration requires a new authority figure and new measured outcomes not currently in the library. Name what needs to be created.

Competitor angle does not exist and has no adjacent angle: do not attempt the iteration. Flag the gap as a creative opportunity. Recommend building a new winning script for this angle before using competitor scripts in this category as iteration targets.

SECTION 11: WHAT TO DO WITH COMPETITOR SCRIPTS THAT ARE WEAK

Not every competitor script worth analyzing is worth iterating from. Some will have structural weaknesses that make them poor base chassis for an iteration.

Flag the following as weak and recommend against using as a base chassis:

Script uses unsubstantiated shock claims with no mechanism explanation. These convert initially but fatigue fast and generate chargebacks.

Script has no villain. Without a villain, the reader has no explanation for why their previous attempts failed and no reason to believe this is different.

Script jumps to product within the first 200 words without installing the mechanism. The reader's belief hasn't been built before the pitch arrives.

Script uses generic testimonials with no specific numbers. Numbers are proof. Without them the script is hope marketing.

For weak competitor scripts, say so. Name the specific structural failure. Then recommend the closest winning script from the library that does the same job correctly. The question becomes not how do I iterate this but what would a strong version of what this competitor is attempting look like.

END OF DOCUMENT