CS23336/GE23231/GE23233-IPP/PUP/PSPP

Status	Finished
Started	Thursday, 8 October 2026, 11:37 AM
Completed	Thursday, 8 October 2026, 11:40 AM
Duration	3 mins 9 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1

Correct
Mark 2.00 out of 2.00
Flag question

Question text

complete function to implement coin change making problem i.e. finding the minimum

number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer:(penalty regime: 0 %)

Reset answer

```
def coinChange(n):
    return (n + 3) // 4
```

```
def coinChange(n):
    return (n + 3) // 4
```

Feedback

Test	Expected	Got
`print(coinChange(16))`	4	4

Passed all tests!

Correct
Marks for this submission: 2.00/2.00.

Question 2

Correct
Mark 2.00 out of 2.00
Flag question

Question text

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

Example 1:

Input:

69

Output:

true

Example 2:

Input:

88

Output:

true

Example 3:

Input:

962

Output:

false

Example 4:

Input:

1

Output:

true

For example:

Test	Result
`print(Strobogrammatic(69))`	`True`
`print(Strobogrammatic(962))`	`False`

Answer:(penalty regime: 0 %)

Reset answer

```
def Strobogrammatic(n):
    s = str(n)
    d = {'0':'0', '1':'1', '6':'9', '8':'8', '9':'6'}

    for i in range(len(s)):
        if s[i] not in d or d[s[i]] != s[len(s)-1-i]:
            return False
    return True

```


```
def Strobogrammatic(n):
    s = str(n)
    d = {'0':'0', '1':'1', '6':'9', '8':'8', '9':'6'}

    for i in range(len(s)):
        if s[i] not in d or d[s[i]] != s[len(s)-1-i]:
            return False
    return True

```

Feedback

Test	Expected	Got
`print(Strobogrammatic(69))`	`True`	`True`
`print(Strobogrammatic(88))`	`True`	`True`
`print(Strobogrammatic(962))`	`False`	`False`

Passed all tests!

Correct
Marks for this submission: 2.00/2.00.

Question 3

Correct
Mark 2.00 out of 2.00
Flag question

Question text

Write a function that returns the value of a+aa+aaa+aaaa with a given digit as the value of a.

Suppose the following input is supplied to the program:

9

Then, the output should be:

9+99+999+9999=11106

Sample Input Format:

9

Sample Output format:

11106

For example:

Test	Result
`print(Summation(8))`	`9872`

Answer:(penalty regime: 0 %)

Reset answer

```
def Summation(a):
    return a + int(str(a)*2) + int(str(a)*3) + int(str(a)*4)
```


```
def Summation(a):
    return a + int(str(a)*2) + int(str(a)*3) + int(str(a)*4)
```


Feedback

Test	Expected	Got
`print(Summation(8))`	`9872`	`9872`
`print(Summation(10))`	`10203040`	`10203040`

Passed all tests!

Correct
Marks for this submission: 2.00/2.00.

Question 4

Correct
Mark 2.00 out of 2.00
Flag question

Question text

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, …] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: U = 2^a * 3^b * 5^c, where a, b and c are nonnegative integers.

For example:

Test	Result
`print(checkUgly(6))`	`ugly`
`print(checkUgly(21))`	`not ugly`

Answer:(penalty regime: 0 %)

Reset answer

```
def checkUgly(n):
    if n <= 0:
        return "not ugly"

    for p in [2, 3, 5]:
        while n % p == 0:
            n //= p

    if n == 1:
        return "ugly"
    return "not ugly"
```

```
    return "not ugly"
```

```
def checkUgly(n):
    if n <= 0:
        return "not ugly"

    for p in [2, 3, 5]:
        while n % p == 0:
            n //= p

    if n == 1:
        return "ugly"
    return "not ugly"
```

Feedback

Test	Expected	Got
`print(checkUgly(6))`	`ugly`	`ugly`
`print(checkUgly(21))`	`not ugly`	`not ugly`

Passed all tests!

Correct
Marks for this submission: 2.00/2.00.

Question 5

Correct
Mark 2.00 out of 2.00
Flag question

Question text

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all

the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
`print(christmasDiscount(578))`	`12`

Answer:(penalty regime: 0 %)

Reset answer

```
def christmasDiscount(orderValue):
    return sum(int(d) for d in str(orderValue) if d in "2357")
```

```python
def christmasDiscount(orderValue):
    return sum(int(d) for d in str(orderValue) if d in "2357")
```

Feedback

Test	Expected	Got
`print(christmasDiscount(578))`	12	12
`print(christmasDiscount(57))`	12	12
`print(christmasDiscount(222))`	6	6
`print(christmasDiscount(77777))`	35	35

Passed all tests!

Correct
Marks for this submission: 2.00/2.00.
Finish review

Blocks

Skip Quiz navigation

Quiz navigation

Question 1 This page Question 2 This page Question 3 This page Question 4 This page Question 5 This page

Blocks

Skip to main content
REC-CIS

CS23336/GE23231/GE23233-IPP/PUP/PSPP

Status	Finished
Started	Thursday, 8 October 2026, 11:25 AM
Completed	Thursday, 8 October 2026, 11:35 AM
Duration	9 mins 56 secs
Grade	**13.00** out of 15.00 (**86.67**%)

Question 1

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Which module is to be imported for using randint function?

Question 1 Answer

a.
randrange

b.
randomrange

c.
random

d.
rand

Question 2

Incorrect
Mark 0.00 out of 1.00
Flag question

Question text

Function defined to achieve some task as per the programmer's requirement is called a _____.

Question 2 Answer

a.
All of the mentioned

b.
user defined function

c.
built in functions

d.
library function

Question 3

Correct
Mark 1.00 out of 1.00
Flag question

Question text

The part of the program where a variable is accessible is known as the _____ of that variable

Question 3 Answer

a.
none of the mentioned

b.
module

c.
scope

d.
part

Question 4

Incorrect
Mark 0.00 out of 1.00
Flag question

Question text

Which of the following function headers is correct?

Question 4 Answer

a.

def fun(a, b = 2, c = 3)

b.

def fun(a, b, c = 3, d)

c.

def fun(a = 2, b, c = 3)

d.

def fun(a = 2, b = 3, c)

Question 5

Correct
Mark 1.00 out of 1.00
Flag question

Question text

cal(n1) : What is n1?

Question 5 Answer

a.
Argument

b.
Parameter

c.
None of the mentioned

d.
Keyword

Question 6

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Which of the following number can never be generated by the following code: random.randrange(0, 100)

Question 6 Answer

a.
100

b.
99

c.
1

d.
0

Question 7

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Which one of the following is the correct way of calling a function?

Question 7 Answer

a.

call function_name()

b.

function function_name()

c.

function_name()

d.

ret function_name()

Question 8

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Which of the following statement is not true regarding functions?

Question 8 Answer

a.
A function may or may not return value.

b.
A function may or may not have parameters.

c.
A function definition begins with "define"

d.
Function header always ends with a colon (.

Question 9

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Which keyword is used to begin the definition of a function?

Question 9 Answer

a.
def

b.
Define

c.
DEF

d.
Def

Question 10

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Which of the following function definition header is wrong?

Question 10 Answer

a.
def scan(p1, p2 = 4, p3 = 5):

b.
def mul(p1, n1, m1):

c.
def div(p1=4, p2, p3):

d.
def sum(n1, n2, n = 3):

Question 11

Correct
Mark 1.00 out of 1.00
Flag question

Question text

The process of dividing a computer program into separate independent blocks of code with specific functionalities is known as _____.

Question 11 Answer

a.
More Programming

b.
Step Programming

c.
Modular Programming

d.
Programming

Question 12

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Which of the following items are present in the function header?

Question 12 Answer

a.

B. parameter list

b.

A. function name

c.

Both A and B

d.

return value

Question 13

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What will be the output of the following Python code?

```
def maximum(x, y):
    if x > y:
        return x
    elif x == y:
        return 'The numbers are equal'
    else:
        return y
print(maximum(2, 3))
```

Question 13 Answer

a.

None of the mentioned

b.

3

c.

The numbers are equal

d.

2

Question 14

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Functions which do not return any value is called _____.

Question 14 Answer

a.
default function

b.
void function

c.
null function

d.
zero function

Question 15

Correct
Mark 1.00 out of 1.00
Flag question

Question text

The function can be called in the program by writing function name followed by _____.

Question 15 Answer

a.

None of the mentioned

b.

{ }

c.

[ ]

d.

( )

Finish review

Blocks

Skip Quiz navigation

Quiz navigation

Question 1 This page Question 2 This page Question 3 This page Question 4 This page Question 5 This page Question 6 This page Question 7 This page Question 8 This page Question 9 This page Question 10 This page Question 11 This page Question 12 This page Question 13 This page Question 14 This page Question 15 This page
Show one page at a timeFinish review

Blocks