CS23336/GE23231/GE23233-IPP/PUP/PSPP

Status	Finished
Started	Thursday, 29 October 2026, 9:52 PM
Completed	Thursday, 29 October 2026, 9:59 PM
Duration	7 mins 37 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

Example Input:

5

1 2 2 3 4

Output:

1 2 3 4

Example Input:

6

1 1 2 2 3 3

Output:

1 2 3

For example:

Input Result

```
5
1
2
2
3
4
```

```
1 2 3 4
```

Answer:(penalty regime: 0 %)

```
n = int(input())
arr = []

while len(arr) < n:
    arr.extend(map(int, input().split()))

distinct = list(dict.fromkeys(arr))
print(*distinct)
```


```
n = int(input())
arr = []

while len(arr) < n:
    arr.extend(map(int, input().split()))

distinct = list(dict.fromkeys(arr))
print(*distinct)
```


Feedback

Input	Expected	Got
5 1 2	1 2 3 4	1 2 3 4

Input	Expected	Got
2 3 4		
6 1 1 2 2 3 3	1 2 3	1 2 3
5 11 22 11 22 11	11 22	11 22
10 1 2 3 4 5 1 2 3 4 5	1 2 3 4 5	1 2 3 4 5

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 2

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Given an array of integers `nums` containing `n + 1` integers where each integer is in the range `[1, n]` inclusive.There is only **one repeated number** in `nums`, return *this repeated number*. Solve the problem using set.

Example 1:

```
Input: nums = [1,3,4,2,2]
```

```
Output: 2
```

Example 2:

```
Input: nums = [3,1,3,4,2]
```

```
Output: 3
```

For example:

Input	Result
1 3 4 4 2 4	

Answer:(penalty regime: 0 %)

```
def findDuplicate(nums):
    seen = set()

    for num in nums:
        if num in seen:
            return num
        seen.add(num)

n = list(map(int, input().split()))
print(findDuplicate(n))
```


```
def findDuplicate(nums):
    seen = set()

    for num in nums:
        if num in seen:
            return num
        seen.add(num)

n = list(map(int, input().split()))
print(findDuplicate(n))
```


Feedback

Input	Expected	Got
1 3 4 4 2	4	4
1 2 2 3 4 5 6 7 2	2	2

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 3

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Write a program to eliminate the common elements in the given 2 arrays and print only the non-repeating

elements and the total number of such non-repeating elements.

Input Format:

The first line contains space-separated values, denoting the size of the two arrays in integer format respectively.

The next two lines contain the space-separated integer arrays to be compared.

Sample Input:

5 4

1 2 8 6 5

2 6 8 10

Sample Output:

1 5 10

3

Sample Input:

5 5

1 2 3 4 5

1 2 3 4 5

Sample Output:

NO SUCH ELEMENTS

For example:

Input	Result
5 4 1 2 8 6 5 2 6 8 10	1 5 10 3

Input	Result
5 5 1 2 3 4 5 1 2 3 4 5	NO SUCH ELEMENTS

Answer:(penalty regime: 0 %)

```
n, m = map(int, input().split())
a = list(map(int, input().split()))
b = list(map(int, input().split()))

result = [x for x in a if x not in b] + [x for x in b if x not in a]

if result:
    print(*result)
    print(len(result))
else:
    print("NO SUCH ELEMENTS")
```


```
n, m = map(int, input().split())
a = list(map(int, input().split()))
b = list(map(int, input().split()))

result = [x for x in a if x not in b] + [x for x in b if x not in a]

if result:
    print(*result)
    print(len(result))
else:
    print("NO SUCH ELEMENTS")
```


Feedback

Input	Expected	Got
5 4 1 2 8 6 5 2 6 8 10	1 5 10 3	1 5 10 3

Input	Expected	Got
3 3 10 10 10 10 11 12	11 12 2	11 12 2
5 5 1 2 3 4 5	NO SUCH ELEMENTS	NO SUCH ELEMENTS
1 2 3 4 5		

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 4

Correct
Mark 1.00 out of 1.00
Flag question

Question text

There is a malfunctioning keyboard where some letter keys do not work. All other keys on the keyboard work properly.

Given a string text of words separated by a single space (no leading or trailing spaces) and a string brokenLetters of all distinct letter keys that are broken, return the number of words in text you can fully type using this keyboard.

Example 1:

Input: text = "hello world", brokenLetters = "ad"

Output:

1

Explanation: We cannot type "world" because the 'd' key is broken.

For example:

Input	Result
hello world ad	1
Faculty Upskilling in Python Programming ak	2

Answer:(penalty regime: 0 %)

```
text = input().lower()
brokenLetters = input().lower()

count = 0

for word in text.split():
    if all(letter not in brokenLetters for letter in word):
        count += 1
```

```
 9
10  print(count)
```

```
 1  text = input().lower()
 2  brokenLetters = input().lower()
 3
 4  count = 0
 5
 6  for word in text.split():
 7      if all(letter not in brokenLetters for letter in word):
 8          count += 1
 9
10  print(count)
```

Feedback

Input	Expected	Got
hello world ad	1	1
Welcome to REC e	1	1
Faculty Upskilling in Python Programming ak	2	2

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 5

Correct

Mark 1.00 out of 1.00
Flag question

Question text

The **DNA sequence** is composed of a series of nucleotides abbreviated as `'A'`, `'C'`, `'G'`, and `'T'`.

- For example, `"ACGAATTCCG"` is a **DNA sequence**.

When studying **DNA**, it is useful to identify repeated sequences within the DNA.

Given a string `s` that represents a **DNA sequence**, return all the **`10`-letter-long** sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in **any order**.

Example 1:

```
Input: s = "AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT"
Output: ["AAAAACCCCC","CCCCCAAAAA"]
```

Example 2:

```
Input: s = "AAAAAAAAAAAAA"
Output: ["AAAAAAAAAA"]
```

For example:

Input	Result
AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT	AAAAACCCCC CCCCCAAAAA

Answer:(penalty regime: 0 %)

```
s = input().strip()

seen = set()
repeated = []

for i in range(len(s) - 9):
    seq = s[i:i + 10]

    if seq in seen and seq not in repeated:
        repeated.append(seq)
    else:
        seen.add(seq)

for seq in repeated:
    print(seq)
```

```
s = input().strip()

seen = set()
```

```
repeated = []

for i in range(len(s) - 9):
    seq = s[i:i + 10]

    if seq in seen and seq not in repeated:
        repeated.append(seq)
    else:
        seen.add(seq)

for seq in repeated:
    print(seq)
```

Feedback

Input	Expected	Got
AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT	AAAAACCCCC CCCCCAAAAA	AAAAACCCCC CCCCCAAAAA
AAAAAAAAAAAAA	AAAAAAAAAA	AAAAAAAAAA

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 6

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Coders here is a simple task for you, Given string str. Your task is to check whether it is a binary string or not by using python set.

Examples:

Input: str = "01010101010"

Output: Yes

Input: str = "REC101"

Output: No

For example:

Input	Result
01010101010	Yes
010101 10101	No

Answer:(penalty regime: 0 %)

```
s = input()

if set(s) <= {'0', '1'}:
    print("Yes")
else:
    print("No")
```


```
s = input()

if set(s) <= {'0', '1'}:
    print("Yes")
else:
    print("No")
```


Feedback

Input	Expected	Got
01010101010	Yes	Yes
REC123	No	No
010101 10101	No	No

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 7


Correct
Mark 1.00 out of 1.00
Flag question

Question text

Given an array of strings `words`, return *the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below*.

In the **American keyboard**:

- the first row consists of the characters `"qwertyuiop"`,
- the second row consists of the characters `"asdfghjkl"`, and
- the third row consists of the characters `"zxcvbnm"`.



Example 1:

```
Input: words = ["Hello","Alaska","Dad","Peace"]
Output: ["Alaska","Dad"]
```

Example 2:

```
Input: words = ["omk"]
Output: []
```

Example 3:

```
Input: words = ["adsdf","sfd"]
Output: ["adsdf","sfd"]
```

For example:

Input	Result
4 Hello Alaska Dad Peace	Alaska Dad
2 adsfd afd	adsfd afd

Answer:(penalty regime: 0 %)

```
n = int(input())
words = [input().strip() for _ in range(n)]

row1 = set("qwertyuiop")
row2 = set("asdfghjkl")
row3 = set("zxcvbnm")

result = []

for word in words:
    letters = set(word.lower())

    if letters <= row1 or letters <= row2 or letters <= row3:
        result.append(word)

if result:
    print(*result, sep="\n")
else:
    print("No words")
```


```
n = int(input())
words = [input().strip() for _ in range(n)]

row1 = set("qwertyuiop")
row2 = set("asdfghjkl")
row3 = set("zxcvbnm")

result = []

for word in words:
    letters = set(word.lower())

    if letters <= row1 or letters <= row2 or letters <= row3:
        result.append(word)

if result:
    print(*result, sep="\n")
else:
```

```
19      print("No words")
```

Feedback

Input	Expected	Got
4 Hello Alaska Dad Peace	Alaska Dad	Alaska Dad
1 omk	No words	No words
2 adsfd afd	adsfd afd	adsfd afd

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 8

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Given a tuple and a positive integer k, the task is to find the count of distinct pairs in the tuple whose sum is equal to **K**.

Examples:

Input: t = (5, 6, 5, 7, 7, 8), K = 13
Output: 2
Explanation:
Pairs with sum K(= 13) are {(5, 8), (6, 7), (6, 7)}.
Therefore, distinct pairs with sum K(= 13) are { (5, 8), (6, 7) }.
Therefore, the required output is 2.

For example:

Input	Result
1,2,1,2,5 3	1

Input	Result
1,2 0	0

Answer:(penalty regime: 0 %)

```
t = tuple(map(int, input().replace(',', ' ').split()))
k = int(input())

seen = set()
pairs = set()

for num in t:
    complement = k - num
    if complement in seen:
        pairs.add(tuple(sorted((num, complement))))
    seen.add(num)

print(len(pairs))
```


```
t = tuple(map(int, input().replace(',', ' ').split()))
k = int(input())

seen = set()
pairs = set()

for num in t:
    complement = k - num
    if complement in seen:
        pairs.add(tuple(sorted((num, complement))))
    seen.add(num)

print(len(pairs))
```


Feedback

Input	Expected	Got
5,6,5,7,7,8 13	2	2
1,2,1,2,5 3	1	1

Input	Expected	Got
1,2 0	0	0

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 9

Correct
Mark 1.00 out of 1.00
Flag question

Question text

You are given an integer tuple `nums` containing distinct numbers. Your task is to perform a sequence of operations on this tuple until it becomes empty. The operations are defined as follows:

1. If the first element of the tuple has the smallest value in the entire tuple, remove it.
2. Otherwise, move the first element to the end of the tuple.

You need to return an integer denoting the number of operations required to make the tuple empty.

Constraints

- The input tuple `nums` contains distinct integers.
- The operations must be performed using tuples and sets to maintain immutability and efficiency.
- Your function should accept the tuple `nums` as input and return the total number of operations as an integer.

Example:

Input: nums = (3, 4, -1)
Output: 5

Explanation:
Operation 1: [3, 4, -1] -> First element is not the smallest, move to the end -> [4, -1, 3]
Operation 2: [4, -1, 3] -> First element is not the smallest, move to the end -> [-1, 3, 4]
Operation 3: [-1, 3, 4] -> First element is the smallest, remove it -> [3, 4]
Operation 4: [3, 4] -> First element is the smallest, remove it -> [4]
Operation 5: [4] -> First element is the smallest, remove it -> []
Total operations: 5

For example:

Test	Result
`print(count_operations((3, 4, -1)))`	5

Answer:(penalty regime: 0 %)
Reset answer

```
def count_operations(nums):
    nums = tuple(nums)
    operations = 0

    while nums:
        if nums[0] == min(nums):
```

```
            nums = nums[1:]
        else:
            nums = nums[1:] + (nums[0],)

        operations += 1

    return operations
```

```
def count_operations(nums):
    nums = tuple(nums)
    operations = 0

    while nums:
        if nums[0] == min(nums):
            nums = nums[1:]
        else:
            nums = nums[1:] + (nums[0],)

        operations += 1

    return operations
```

Feedback

Test	Expected	Got
`print(count_operations((3, 4, -1)))`	5	5
`print(count_operations((1, 2, 3, 4, 5)))`	5	5
`print(count_operations((5, 4, 3, 2, 1)))`	15	15
`print(count_operations((42, )))`	1	1
`print(count_operations((-2, 3, -5, 4, 1)))`	11	11

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 10

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Check if a set is a subset of another set.

Example:

Sample Input1:

mango apple

mango orange

mango

output1:

yes

set3 is subset of set1 and set2

```
input2:

mango orange

banana orange

grapes

output2:
```

no

For example:

Test	Input	Result
1	mango apple mango orange mango	yes set3 is subset of set1 and set2
2	mango orange banana orange grapes	No

Answer:(penalty regime: 0 %)

```
set1 = set(input().split())
set2 = set(input().split())
set3 = set(input().split())

if set3.issubset(set1) and set3.issubset(set2):
```

```
if set3.issubset(set1) and set3.issubset(set2):
    print("yes")
    print("set3 is subset of set1 and set2")
else:
    print("No")
```

```
set1 = set(input().split())
set2 = set(input().split())
set3 = set(input().split())

if set3.issubset(set1) and set3.issubset(set2):
    print("yes")
    print("set3 is subset of set1 and set2")
else:
    print("No")
```

Feedback

Test	Input	Expected	Got
1	mango apple mango orange mango	yes set3 is subset of set1 and set2	yes set3 is subset of set1 and set2
2	mango orange banana orange grapes	No	No

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.
Finish review

Blocks

Skip Quiz navigation

Quiz navigation

Question 1 This page Question 2 This page Question 3 This page Question 4 This page Question 5 This page Question 6 This page Question 7 This page Question 8 This page Question 9 This page Question 10 This page
Show one page at a timeFinish review

Blocks

CS23336/GE23231/GE23233-IPP/PUP/PSPP

Status	Finished
Started	Thursday, 29 October 2026, 10:53 PM
Completed	Thursday, 29 October 2026, 10:59 PM
Duration	5 mins 51 secs
Grade	**15.00** out of 15.00 (**100**%)

Question 1

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What is the output of the given below program?

my_t1 = (1, 2, 3, 4)

my_t1.append((5, 6, 7))

print(len(my_t1))

Question 1 Answer

a.

Error

b.

5

c.

1

d.

2

Question 2

Correct
Mark 1.00 out of 1.00
Flag question

Question text

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

Question 2 Answer

a.

(16,17,18,19)

b.

(25,19,18,17)

c.

Error

d.

(16,17,18)

Question 3

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2
```

```
print(set3)
```

Question 3 Answer

a.

{2,5,3,1}

b.

{2,5,1}

c.

{}

d.

{3}

Question 4

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Which of the following options will not result in an error when performed on tuples in Python where tupl= (5,2,7,0,3)?

Question 4 Answer

a.

tupl.sort()

b.

tupl[1]=2

c.

tupl1=tupl+tupl

d.

tupl.append(2)

Question 5

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

Question 5 Answer

a.

(30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80)

b.

(30, 40, 50) (10, 20, 30, 40)

c.

(30, 40, 50)(40, 50, 60, 70, 80)

d.

(10, 20, 30, 40) (40, 50, 60, 70, 80)

Question 6

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Choose the correct option.

Question 6 Answer

a.

In Python, a tuple can contain only integers as its elements.

b.

In Python, a tuple can contain only strings as its elements.

c.

In Python, a tuple can contain both integers and strings as its elements.

d.

In Python, a tuple can contain either string or integer but not both at a time.

Question 7

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Write the Output of the following Code?

t = (15,83,83,52,60,45,52,85,100)

print(min(t)+max(t)+t.count(52))

Question 7 Answer

a.

Error

b.

2

c.

100

d.

117

Question 8

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

Question 8 Answer

a.

Error

b.

{‘rec’, 1, (‘cse’, ‘ece’),True}

c.

{‘rec’, 1, (‘cse’, ‘ece’)}

d.

{‘rec’, True, (‘cse’, ‘ece’)}

Question 9

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

Question 9 Answer

a.

['30', '8', '3', '2']

b.

['2', '3', '30', '8']

c.

['8', '30', '3', '2']

d.

['2', '3', '8', '30']

Question 10

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

Question 10 Answer

a.

{1,3,2}

b.

{4}

c.

{2}

d.

{1,3,4}

Question 11

Correct
Mark 1.00 out of 1.00
Flag question

Question text

A python tuple can be created without using any parentheses. (True/False)

Question 11 Answer

a.

False

b.

True

Question 12

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What will be printed when the following code executes?

```
a = ("Python Programming")

print type(a)
```

Question 12 Answer

a.

<class 'str'>

b.

<class 'int'>

c.

<class 'tuple'>

d.

str

Question 13

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

Question 13 Answer

a.

False

True

b.

False

False

c.

True

False

d.

True

True

Question 14

Correct
Mark 1.00 out of 1.00
Flag question

Question text

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)

>>>[t[i] for i in range(0, len(t), 2)]
```

Question 14 Answer

a.
[1, 2, 4, 3, 8, 9]

b.

(1, 4, 8)

c.

[2, 3, 9]

d.

[1, 4, 8]

Question 15

Correct
Mark 1.00 out of 1.00
Flag question

Question text

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

Question 15 Answer

a.

(1,2,3)(4,5,6)

b.

(1,2,3,3,2,1)

c.

(1,2,3,4,5,6)

d.

Error

Finish review

Blocks

Skip Quiz navigation

Quiz navigation

Question 1 This page Question 2 This page Question 3 This page Question 4 This page Question 5 This page Question 6 This page Question 7 This page Question 8 This page Question 9 This page Question 10 This page Question 11 This page Question 12 This page Question 13 This page Question 14 This page Question 15 This page
Show one page at a timeFinish review

Blocks