



From: JM

Date: 2016-08-09

To: KSL450

MBAXPRTU (71)

CONFXXXX.KSL

Name,Input,Level,6x(In,Out),Gain,Offs,Type,Addr,Chan,Stat
"1",0,0,0,0,0,0,0,0,0,0,0,100000,100000,.001,0,71,"1:1",1,0

Format of one comma separated line:

<i>Name</i>	<i>Description</i>
A) Name (Comment)	'Name or description
B) Input	'Reserved = 0
C) Level	'Reserved = 0
D-O) Input,Press,6x(In,Out)	'Calibration Data
P) Gain	'Gain
Q) Offs	'Offset
R) Type	'DAU Type = 71
S) Addr	'DAU Address is a list of ":" separated items Item 1 : Block number (consecutive addresses inside a block!) Item 2 : Slave Address Read Holding Registers (FC Hex 03) Only
T) Chan	'DAU Channel number, register address
U) Stat	'Input status

ONLIXXXX.DAT

Format of one comma separated line:

"1",5,1,1,0,71,"1:1",11,"",0

<i>Name</i>	<i>Description</i>
A) Name (Comment)	'Name or description
B) Output Data	'Type of data for output
C) Index for B	'Index for the output
D) Gain	'Gain
E) Offs	'Offset
F) Type	'OOU Type = 71
G) Addr	'OOU Address is a list of ":" separated items Item 1 : Block number (consecutive addresses inside a block!) Item 2 : Slave Address Preset Multiple Registers (FC Hex 10) Only

H) Chan
I) Output String
J) Stat

'OOU Channel number, register address
'Comment
'Output status