



Maridive 701

Anchor Handling Tug Supply DP2 / FiFi 1 Vessel.



MAIN SPECIFICATIONS

Registration:

Flag..... Belize
Port of Registry..... Belize
Owners..... Maridive & Oil Services
Year Built..... 2010
Class ABS "+A1 (E) Offshore Support & Firefighting Vessel Class 1 + AMS + DPS-2".
Call Sign V3NW5

Principal Dimensions:

Length Overall..... 70.70 M.
Breadth..... 16.00 M.
Depth..... 7.20 M.
Draft..... 6.20 M.
G.R.T / N.R.T..... 2379 / 713 M.

General:

Vessel is built to ABS, Class "+A1 (E) Offshore Support & Fire-fighting Vessel Class 1 + AMS + DPS-2". Designed for servicing Oil drilling rigs, Semi-submersible and jack up rigs, production platforms having twin Controlable Pitch propellers in Kort nozzles, Twin rudders and two Stern Thruster and Two bow thrust units. Vessel has a horse power of total 10800 BHP, and a Bollard Pull of 149.16 MT. Vessel is equipped with Dynamic Positioning System Class 2. And fitted with Fire Fighting Class 1 System.

Cargo Capacity:

Dead Weight 2200 Tons
Deck Cargo..... 800 Tons
Clear deck space..... 450 m²
Deck strength 5.5 Ton/m²
Liquid mud..... 495 Cu m
Bulk cement..... 9600 Cu.ft.
Drill water /Ballast 676 Cu.m
Potable Water..... 655 Cu.m
Fuel Oil..... 870 Cu.m
Rig Chain Locker..... 200 Cu.m

MARIDIVE & OIL SERVICES (S.A.E)

CAIRO

37, Cornish El Nil, Maadi
Tel: 23585204 (10 lines)
Fax: 23581160
Email: maridive@moscairo.com

ALEXANDRIA

10 Ahmed Yehia St Gleem 21411
Tel: 5852899
Fax: 583 4668
Email: maridive@mosalex.com

PORT SAID

16 El Gomhoria St . 42311
Shaher Group Building
Tel: 334134 – 221771
Fax: 23 6436

ABU DHABI

Al Kheily Bldg, Office No. 2
Behind Regency Hotel
Tourist Club Area
Tel: 2-671 2205
Fax: 2 671 2767
Email: maridive@emirates.net.ae

Accommodation: Fully A/C for hot & Cold climate

Total Berths: = 50 men

Walk – in Freezer / Refrigerator :

Refrigerator 15 Cu.m.
Freezer 15 Cu.m.

Navigation Equipment :

Radar 2 Furuno,
SSB Raytheon,
Gyro Compass Anschutz,
Depth Meter Anschutz,
Autopilot Kongsberg,
GPS Furuno,
GMDSS Koden
2VHF Furuno,
Navtex Furuno,

Anchor Handling & Towing Winch:

1 Electro-hydraulic Double Drum Waterfall type for Anchor Handling and Towing winch. Line Pull 300 Ton. Brake Holding 450 Ton.

Tow wire:..... 1400 m x 76mm dia.
A/H wire: 220 m x 76mm dia..
Towing Pins :..... one set hydraulic 160T SWL.
Shark Jaws One retractable unit 300T SWL.

Deck Equipment:

Capstan: 2 x 10 Tons
Tugger Winch 2 x 10 ton for cargo shifting.
Anchors 2 HHP stockless anchors,
1980 Kg each.

Stern Roller: 6m X 2.5m (SWL 450T)

Deck Crane: 5 Tons SWL @ 17 m Radius.

Main Engines:

2MAK 8 M 32C (2x5400 BHP).Total **10800 BHP**

Auxiliaries:

2xCAT Diesel gen. each 580 KW (Cat 3412)
Two 2000 Kw shaft alternators (AVK)
1xCAT Emergency gen. 95 KW (Cat C4.4)

Bow & Stern Thruster Units:

2 Transverse bow thrusters each 750 HP
2 Transverse stern thrusters each 750 HP

Cargo Pumps :

Fuel 150 Cu.m/hr @ 75m head
Potable Water..... 150 Cu.m/hr @ 80m head
Drill Water 150 Cu.m/hr @ 80m head
Bulk Compressor. 2x50 T/hr/50m head@6 bar
Liquid mud..... 2X75 Cu.m/hr@ 75m head

Fire Fighting Class 1 System:

2 FiFi monitors one (foam + water) each 1200m³/hr at 160m throw, effective height 45m.
2 seawater pumps each 1500 cu.m/hr at 14 bar m head
Foam tank 11.4 Cu.m

Bollard Pull..... 149.16 Metric Tons.

Speed : 14kt ballast condition, 12 kt service speed.

DP System class 2:

The vessel is fitted DP System class 2 certified by ABS class notation, implemented by Inmarsat fleet 77 for DGPS position correction.

Anti-Pollution:

2 Spray Booms, 8 m long each Booms fitted with 6 nozzles,. Dispersant tank capacity 20 Cu.m

Fresh water generator :

type: a fully automatic reverse osmosis seawater desalinator.
capacity: 2775 gallons per day (10 cu. meters per day)

