

## True bearings



- 1
- |   |        |   |        |   |          |   |          |
|---|--------|---|--------|---|----------|---|----------|
| a | 225° T | b | 315° T | c | 292.5° T | d | 157.5° T |
| e | 045° T | f | 135° T |   |          |   |          |

 2 090° T

 3 270° T

 4

|   |        |   |        |   |        |   |        |
|---|--------|---|--------|---|--------|---|--------|
| a | 035° T | b | 221° T | c | 320° T | d | 125° T |
|---|--------|---|--------|---|--------|---|--------|

5 319° T

6 053° T

7 132° T

8 221° T

9

|   |    |   |    |   |     |   |    |
|---|----|---|----|---|-----|---|----|
| a | No | b | No | c | Yes | d | No |
|---|----|---|----|---|-----|---|----|

10

|   |    |   |    |   |     |   |    |
|---|----|---|----|---|-----|---|----|
| a | No | b | No | c | Yes | d | No |
|---|----|---|----|---|-----|---|----|

11 *NE*

---

## Applications

12  $a = 62^\circ$

13 231° T

14 305° T

15

|   |       |   |          |
|---|-------|---|----------|
| a | 58.2° | b | 100.2° T |
|---|-------|---|----------|



16

a  $x = 15.1$

b  $y = 13.1$

17  $d = 2130$

18  $w = 90.1 \text{ km}$

19

a  $65^\circ$

b  $b = 5.0 \text{ km}$

c  $d = 11.8 \text{ km}$

20  $d = 22.3 \text{ m}$

21

a  $b = 227.8^\circ \text{T}$

b  $d = 334.9 \text{ m}$

22

a  $\angle BSP 90^\circ$

b  $BS = 750.3 \text{ m}$

c  $SP = 525.4 \text{ m}$

d  $2191.7 \text{ m}$