In [1]:
```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
%matplotlib inline
```

In [2]:
```
df=pd.read_csv('Mall_Customers.csv')
```

In [3]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 200 entries, 0 to 199
Data columns (total 5 columns):
 #   Column                  Non-Null Count  Dtype 
---  ------                  --------------  ----- 
 0   CustomerID              200 non-null    int64 
 1   Gender                  200 non-null    object
 2   Age                     200 non-null    int64 
 3   Annual Income (k$)      200 non-null    int64 
 4   Spending Score (1-100)  200 non-null    int64 
dtypes: int64(4), object(1)
memory usage: 7.9+ KB
```

In [4]:
```
df.head()
```

Out[4]:

	CustomerID	Gender	Age	Annual Income (k$)	Spending Score (1-100)
0	1	Male	19	15	39
1	2	Male	21	15	81
2	3	Female	20	16	6
3	4	Female	23	16	77
4	5	Female	31	17	40

```
A value is trying to be set on a copy of a slice from a DataFrame.
Try using .loc[row_indexer,col_indexer] = value instead

See the caveats in the documentation: https://pandas.pydata.org/pandas-do
s/stable/user_guide/indexing.html#returning-a-view-versus-a-copy (https:/
pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a
view-versus-a-copy)
  Final['label']=model.predict(features)
```

Out[8]:

	Annual Income (k$)	Spending Score (1-100)	label
0	15	39	4
1	15	81	2
2	16	6	4
3	16	77	2
4	17	40	4