

SOP: TECHNICAL SUPPORT TROUBLESHOOTING

Document ID	SOP-03
Version	2.0
Effective Date	10/2/2026
Department	Call Center Operations

Applies to: All Tier 1 agents. Principle: Diagnose → Resolve → Escalate. Do not escalate without completing all Tier 1 steps.

Steps

Step 1: Open Call & Verify Identity

Precondition	Call connected.
Action	Deliver greeting, recording notification, and 3-of-5 verification.
Output	Customer verified.
Policy Ref	CS-RULE-001, CS-RULE-002, CS-RULE-004

Step 2: Identify & Confirm the Issue

Precondition	Verification complete.
Action	Ask: 'Are you calling about mobile or home internet?' 'Is this affecting all devices or just one?' 'Was it sudden or gradual?' 'Any recent changes?' Acknowledge with A.C.E.S. before starting diagnostics.
Output	Issue classified: mobile signal / slow internet / no internet / call quality / VoIP.
Policy Ref	CS-RULE-011

Step 3: Check Account Status & Outage Map

Precondition	Issue classified.
Action	Verify in CRM: account is Active (not suspended). Check area outage map for customer's address. Check for open existing ticket on the same issue. If regional outage confirmed: inform customer, provide ETA from Network Ops ticket, offer callback when service is restored. Do not proceed with device-level troubleshooting during a confirmed outage.
Output	Account status confirmed. Outage ruled out or acted on.
Policy Ref	KB-PROD-01 Section 5

Step 4: Execute Diagnostic Path

Precondition	No active outage. Account confirmed active.
--------------	---

Action	Follow the correct path based on issue type. Complete all steps before triggering escalation. Paths A–E below.
Output	Tier 1 resolution achieved, or escalation trigger met.
Policy Ref	KB-PROD-01 Section 5

Path A — No Mobile Signal

1. Confirm Airplane Mode is OFF.
2. Restart the device completely.
3. Reseat SIM card (remove and reinsert).
4. Toggle Airplane Mode ON for 10 seconds, then OFF to force network search.

ESCALATE to Tier 2 if: device shows 'Invalid SIM' or 'Emergency Calls Only' after SIM reseat.

Path B — Slow Home Internet

1. Run speed test (hardwired ethernet only — WiFi tests not valid for refund eligibility).
2. Compare result to plan speed. Acceptable range: within 20% of advertised speed.
3. Ask number of connected devices; check for background downloads or cloud backups.
4. Speed good at router but slow on device → WiFi coverage issue; suggest 5 GHz band or wired connection.
5. Speed slow at router → power cycle modem/router (unplug 30 seconds, replug).

ESCALATE to Tier 2 if: speed consistently below 50% of plan after reboot.

Path C — WiFi Connected but No Internet

1. Check modem indicator lights: WAN/Internet light must be solid green or white.
2. If WAN light is red or blinking: check coax/fiber cable is firmly connected at both ends.
3. Unplug modem power for 60 seconds, then replug.
4. Ask customer to 'Forget Network' on device and rejoin with password.

ESCALATE to Tier 2 if: red WAN light persists after full reboot (technician likely required).

Path D — Cannot Make or Receive Calls (Mobile)

1. Confirm Do Not Disturb is OFF.
2. Check call forwarding is not sending calls directly to voicemail.
3. Disable WiFi Calling temporarily to test on cellular network only.
4. Prompt customer: Settings → General → About → update Carrier Settings.

ESCALATE to Tier 2 if: 'Call Failed' error or fast busy signal persists.

Path E — No VoIP Dial Tone

1. Confirm home internet connection is active (VoIP requires broadband).
2. Check Battery Backup Unit (BBU) status if power was recently interrupted.
3. Reboot router/modem.

IMPORTANT: Inform customer that VoIP does not function during power or internet outages without a BBU installed. (KB-PROD-01 Section 6.2)

ESCALATE to Tier 2 if: BBU failure suspected or line fault indicated.

Step 5: Confirm Resolution

Precondition	Diagnostic steps complete.
---------------------	----------------------------

Action	Ask customer to test service in real time while still on the call: 'Can you try loading a webpage now?' or 'Can you try placing a test call?' Do not close the case until customer confirms resolution or a ticket is created.
Output	Issue resolved, or ticket opened.
Policy Ref	CS-RULE-018

Step 6: Explain Root Cause

Precondition	Resolution confirmed.
Action	Explain why the issue occurred. Example: 'The modem needed a power cycle to refresh its connection to the network.' This builds trust and reduces repeat calls.
Output	Root cause communicated to customer.
Policy Ref	CS-RULE-018

Step 7: Document & Close

Precondition	Resolution complete.
Action	Log case notes within 5 minutes: issue type, diagnostic path followed, steps taken, resolution status, escalation ticket number if applicable. Provide case reference number and offer post-call survey.
Output	Case notes saved. Call closed.
Policy Ref	CS-RULE-020, CS-RULE-021, CS-RULE-022

Key Rules

- Always check for regional outage before device-level troubleshooting — saves time for both agent and customer.
- Factory reset (pinhole 15 seconds) erases all custom WiFi settings. Only recommend as last resort and warn customer explicitly.
- Speed tests must be hardwired to be valid for refund eligibility. (FIN-RULE-003)
- International roaming requires activation at both device AND account level. Verify both before troubleshooting.