



Started on	Sunday, 30 August 2026, 10:03 PM
State	Finished
Completed on	Sunday, 30 August 2026, 10:04 PM
Time taken	55 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of $arr[i] * i$, where i is the index of the element ($i = 0, 1, 2, \dots, N$). Write an algorithm based on Greedy technique with a Complexity $O(n \log n)$.

Input Format:

First line specifies the number of elements- n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int compare(const void *a, const void *b)
5  {
6      return (*(int *)a - *(int *)b);
7  }
8
9  int main()
10 {
11     int n;
12     scanf("%d", &n);
13
14     int a[n];
15
16     for (int i = 0; i < n; i++)
17         scanf("%d", &a[i]);
18
19     qsort(a, n, sizeof(int), compare);
20
21     long long sum = 0;
22
23     for (int i = 0; i < n; i++)
24     {
25         sum += (long long)a[i] * i;
26     }
27
28     printf("%lld", sum);
29
30     return 0;
31 }
```

	Input	Expected	Got	
✓	5 2 5 3 4 0	40	40	✓

	Input	Expected	Got	
✓	10 2 2 2 4 4 3 3 5 5 5	191	191	✓
✓	2 45 3	45	45	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)