How to review DIALux lux levels and uniformity on a UAE project



Start with the room reference

Commercial lighting consultants in Dubai can resolve a surprising number of discrepancies by asking which task, working-plane height and operating scene each DIALux row represents.

[AI IMAGE PROMPT: Photorealistic architectural rendering of consultant comparing a reception counter section with a working-plane overlay on a monitor, luxury modern interior in Dubai, warm 3000K accent lighting, cinematic lighting, 8k resolution, Unreal Engine 5 render style --ar 16:9]

A reception desk, a vertical display and the floor beside them need different calculation surfaces because illuminance depends on the direction of the receiving plane.

[AI IMAGE PROMPT: Photorealistic architectural rendering of one reception counter with horizontal writing surface, upright signage and adjacent floor clearly visible, luxury modern interior in Dubai, warm 3000K accent lighting, cinematic lighting, 8k resolution, Unreal Engine 5 render style --ar 16:9]

How to review DIALux lux levels and uniformity on a UAE project



Read the darkest point

Suppose an office task area averages 500 lx with a minimum of 250 lx: its minimum-to-average uniformity is 0.50, so it would miss an illustrative project target of 0.60 despite meeting a 500 lx average.

[AI IMAGE PROMPT: Photorealistic architectural rendering of office workstations with a shaded perimeter desk and lux meter under the shelf, avoid fabricated diagram text, luxury modern interior in Dubai, warm 3000K accent lighting, cinematic lighting, 8k resolution, Unreal Engine 5 render style --ar 16:9]

Before adding fittings, inspect the grid point in section for an overhead bulkhead, tall partition or incorrect luminaire orientation.

[AI IMAGE PROMPT: Photorealistic architectural rendering of sectional perspective of a tall acoustic screen cutting light off one desktop, luxury modern interior in Dubai, warm 3000K accent lighting, cinematic lighting, 8k resolution, Unreal Engine 5 render style --ar 16:9]

Replacing a narrow-beam optic with a wider distribution may lift the minimum between fittings, but rerun the perimeter and glare checks before accepting the change.

[AI IMAGE PROMPT: Photorealistic architectural rendering of pair of removable narrow and wide beam lenses beside overlapping light pools on desks, luxury modern interior in Dubai, warm 3000K accent lighting, cinematic lighting, 8k resolution, Unreal Engine 5 render style --ar 16:9]

How to review DIALux lux levels and uniformity on a UAE project



Check watts and maintained output separately

For a Masdar City office seeking sustainable lighting solutions, a 600 W installed lighting load across 100 square metres gives an illustrative 6 W/m², with the applicable allowance taken from the approved project brief.

[AI IMAGE PROMPT: Photorealistic architectural rendering of sun-shaded office floor model with a lighting circuit schedule and input power meter, luxury modern interior in Dubai, warm 3000K accent lighting, cinematic lighting, 8k resolution, Unreal Engine 5 render style --ar 16:9]

Compare the proposed system watts and photometric file at the specified drive current, then document the maintenance factor and cleaning interval used for maintained lux.

[AI IMAGE PROMPT: Photorealistic architectural rendering of labelled photometric sample on a bench beside a driver and a maintenance log with indistinct writing, luxury modern interior in Dubai, warm 3000K accent lighting, cinematic lighting, 8k resolution, Unreal Engine 5 render style --ar 16:9]

In the OMEGALUX Lighting Guide, upload the text-based report and compare every Light scene 1 working plane across continuation pages, checking repeated room names against their storey and index.

[AI IMAGE PROMPT: Photorealistic architectural rendering of architect reviewing a multipage working-plane schedule with storey tabs and highlighted room rows, luxury modern interior in Dubai, warm 3000K accent lighting, cinematic lighting, 8k resolution, Unreal Engine 5 render style --ar 16:9]