

Your Code

```
1 #include <stdio.h>
2
3 int linearSearch(int arr[], int n, int key) {
4     for(int i = 0; i < n; i++) {
5         if(arr[i] == key)
6             return i;
7     }
8     return -1;
9 }
10
11 int main() {
12     int arr[] = {5, 3, 8, 1, 9};
13     int n = 5;
14     int key = 8;
15
16     int result = linearSearch(arr, n, key);
17
18     if(result != -1)
19         printf("Element found at index %d\n", result);
20     else
21         printf("Element not found\n");
22
23     return 0;
24 }
```

Input

stdin input

Output

Element found at index 2

your Code

```
1 #include <stdio.h>
2 int main() {
3     int arr[5] = {10,20,30,40,50};
4     for(int i=0;i<5;i++)
5         printf("%d ",arr[i]);
6     return 0;
7 }
```

input

stdin input

Output

10 20 30 40 50

```

1#include <stdio.h>
2#include <stdlib.h>
3
4struct Node {
5    int data;
6    struct Node *next;
7};
8
9void reversedisplay(struct Node *head)
10{
11    if (head == NULL)
12        return;
13
14    reversedisplay(head->next);
15    printf("%d ", head->data);
16}
17
18/* Example usage */
19int main() {
20    struct Node *head = NULL, *tail = NULL;
21
22    int vals[] = {10, 20, 30, 40};
23    for (int i = 0; i < 4; i++) {
24        struct Node *node = (struct Node *)malloc(sizeof(struct Node));
25        node->data = vals[i];
26        node->next = NULL;
27

```

stdin input

Output

40 30 20 10