CS23336/GE23231/GE23233-PP/PL/PP/SPP

Quiz navigation



Show one page at a time

Finish review

Started on Tuesday, 14 August 2018, 3:19 PM
State Finished
Completed Tuesday, 14 August 2018, 4:00 PM
Time taken 40 mins 41 secs
Grade 90.00 out of 10.00 (900%)

Question 1
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

ALL5LY

We, the ALL5LY handling programming lab for you to very strict. Your seniors have told you that she will not allow you to submit the program with compilation errors and she will not accept the program if you do not follow the rules. She is very much concerned about the time, so they requested the program should be executed in one test case only and the execution of the program should not be allowed time is wasted a lot given the number of problems given last week and the number of problems solved by you in this week.

Input Format:

Input consists of 3 integers.

The first integer corresponds to the number of problems given and the second integer corresponds to the number of problems solved.

Output Format:

Output consists of the string "Yet" or "GoT"

Sample Input and Output:

```
4
3
GoT
```

For example:

Input	Result
4 3	GoT

Answer: (penalty regime: 0 %)

```
N=int(input())
M=int(input())
if N-M<=1:
    print("GoT")
else:
    print("Yet")
```

Reset answer

Question 2
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

Input	Expected	Got	
3 4 5	Equilateral Triangle	Equilateral Triangle	✓
4 4 4	Equilateral Triangle	Equilateral Triangle	✓
5 3 4	Scalene Triangle	Scalene Triangle	✓

Passed all tests! ✓

Finish review

A triangle can be classified based on the lengths of its sides as equilateral, isosceles or scalene. All three sides of an equilateral triangle are of the same length. An isosceles triangle has two sides of the same length. Finally, all three sides of a scalene triangle are of different lengths. Write a program that reads the lengths of the three sides of a triangle from the user. Then display a message that states the triangle's classification.

Sample Input 1

```
60
60
60
```

Sample Output 1

```
That's a equilateral triangle
```

Sample Input 2

```
4
4
5
```

Sample Output 2

```
That's a isosceles triangle
```

Sample Input 3

```
3
4
5
```

Sample Output 3

```
That's a scalene triangle
```

For example:

Input	Result
60 60 60	That's a equilateral triangle
4 4 5	That's a isosceles triangle
3 4 5	That's a scalene triangle

Answer: (penalty regime: 0 %)

```
a=int(input())
b=int(input())
c=int(input())
if(a==b and b==c and a==c):
    print("That's a equilateral triangle")
elif(a==b or b==c or a==c):
    print("That's a isosceles triangle")
else:
    print("That's a scalene triangle")
```

Reset answer

Input	Expected	Got	
60 60 60	That's a equilateral triangle	That's a equilateral triangle	✓
4 4 5	That's a isosceles triangle	That's a isosceles triangle	✓
3 4 5	That's a scalene triangle	That's a scalene triangle	✓
5 5 8	That's a isosceles triangle	That's a isosceles triangle	✓
3 4 5	That's a equilateral triangle	That's a equilateral triangle	✓

Passed all tests! ✓

Finish review

Question 3
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

Most years have 365 days. However, the time required for the Earth to orbit the Sun is actually slightly more than that. As a result, an additional day, referred to as a leap day, is included in some years to correct for this difference. Such years are referred to as leap years. The rules for determining whether or not a year is a leap year follow:

- Years that are multiples of 400 are leap years.
- Of the remaining years, any year that is divisible by 4 is a leap year.
- All other years are not leap years.

Write a program that reads a year from the user and displays a message indicating whether or not it is a leap year.

Sample Input 1

```
1900
```

Sample Output 1

```
1900 is not a leap year.
```

Sample Input 2

```
2000
```

Sample Output 2

```
2000 is a leap year.
```

For example:

Input	Result
1900	1900 is not a leap year.

Answer: (penalty regime: 0 %)

```
y=int(input())
if(y%400==0 or y%4==0 and y%100!=0):
    print(y," is a leap year.")
else:
    print(y," is not a leap year.")
```

Reset answer

Input	Expected	Got	
1900	1900 is not a leap year.	1900 is not a leap year.	✓
2000	2000 is a leap year.	2000 is a leap year.	✓
2100	2100 is not a leap year.	2100 is not a leap year.	✓
2018	2018 is not a leap year.	2018 is not a leap year.	✓

Passed all tests! ✓

Finish review

Question 4
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

Write a program that accepts 5 inputs and returns the count of how many of those 5 are odd.

For example:

If the five inputs are 5, 12, 19, 8, and 15, there are three odd numbers (5, 19 and 15). So, the program must return 3.

Another example:

If the five inputs are 10, 12, 18, 8, and 20, there are no odd numbers (0 such 8). So, the program must return 0.

Observe that zero is considered an even number.

For example:

Input	Result
5 12 19 8 15	3
10 12 18 8 20	0

Answer: (penalty regime: 0 %)

```
count=0
for i in range(5):
    n=int(input())
    if(n%2!=0):
        count+=1
print(count)
```

Reset answer

Input	Expected	Got	
5 12 19 8 15	3	3	✓
10 12 18 8 20	0	0	✓
1 2 3 4 5	3	3	✓

Passed all tests! ✓

Finish review

Question 5
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

Write a Python program that accepts three parameters. The first parameter is an integer. The second is one of the following: addition, subtraction, or multiplication. The third parameter will also be an integer.

The function should perform a calculation and return the results. For example, if the function is passed 4 and 6, it should return the following:

Sample Input Format:

```
4
*
6
```

Sample Output Format:

```
24
```

Answer: (penalty regime: 0 %)

```
def calc(a,b):
    a = 5
    b = 10
def add(a,b):
    print(a+b)
def mul(a,b):
    print(a*b)
def div(a,b):
    print(a/b)
def sub(a,b):
    print(a-b)
a=int(input())
op=input()
b=int(input())
if op=="+":
    add(a,b)
elif op=="*":
    mul(a,b)
elif op=="/":
    div(a,b)
elif op=="-":
    sub(a,b)
```

Reset answer

Input	Expected	Got	
4 * 6	24	24	✓
10 - 5	5	5	✓
5 + 5	10	10	✓
100 / 100	1.0	1.0	✓
5.5 + 4.5	10.0	10.0	✓

Passed all tests! ✓

Finish review

Question 6
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

A certain type of steel is used to test and grid grade according to the following conditions.

1. Hardness of the steel must be greater than 50.
2. Carbon content of the steel must be less than 0.7
3. Tensile strength must be greater than 5600.

The grades awarded are as follows:

- Grade is 10 if all three conditions are met
- Grade is 9 if conditions (2) and (3) are met
- Grade is 8 if conditions (1) and (3) are met
- Grade is 7 if conditions (1) and (2) are met
- Grade is 6 if only one condition is met
- Grade is 5 if none of the three conditions are met

Write a program to print the grade of the steel, based on the values of hardness, carbon content and tensile strength of the steel, given by the user.

Input:

```
50
0.6
5601
```

Output:

```
10
```

Answer: (penalty regime: 0 %)

```
h=int(input())
c=float(input())
t=int(input())
if h>50 and c<0.7 and t>5600:
    print("10")
elif h>50 and c<0.7 or t>5600:
    print("9")
elif h>50 and c<0.7 or t>5600:
    print("8")
elif h>50 and c<0.7 or t>5600:
    print("7")
else:
    print("5")
```

Reset answer

Input	Expected	Got	
50 0.6 5601	10	10	✓
50 0.6 5600	9	9	✓
50 0.7 5600	5	5	✓

Passed all tests! ✓

Finish review

Question 7
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

Given an integer, N, count whether in this given number can be made a perfect square after adding 1 to it.

Input Format

Single integer input

Output Format

Output 1 or 0

Example Input

24

Output

1

Example Input

80

Output

0

For example:

Input	Result
24	1

Answer: (penalty regime: 0 %)

```
n=int(input())
if((n+1)**0.5==int((n+1)**0.5)):
    print("1")
else:
    print("0")
```

Reset answer

Input	Expected	Got	
24	1	1	✓
80	0	0	✓
99	1	1	✓

Passed all tests! ✓

Finish review

Question 8
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

The Chinese zodiac assigns animals to years in a 12 year cycle. Over 10 years is shown in the table below. The pattern repeats every 12 years, with 2020 being another year of the Dragon, and 1900 being another year of the rat.

Year Animal
2000 Dragon
2001 Snake
2002 Horse
2003 Sheep
2004 Monkey
2005 Rooster
2006 Dog
2007 Pig
2008 Rat
2009 Ox
2010 Tiger

Write a program that reads a year from the user and displays the animal associated with that year. Your program should work correctly for any year greater than or equal to zero, not just the ones listed in the table.

Sample Input 1

```
2000
```

Sample Output 1

```
2000 is the year of the Tiger.
```

Sample Input 2

```
2001
```

Sample Output 2

```
2001 is the year of the Rat.
```

Answer: (penalty regime: 0 %)

```
year=int(input())
if year%12==0:
    print(year,"is the year of the Dragon.")
elif year%12==1:
    print(year,"is the year of the Snake.")
elif year%12==2:
    print(year,"is the year of the Horse.")
elif year%12==3:
    print(year,"is the year of the Sheep.")
elif year%12==4:
    print(year,"is the year of the Monkey.")
elif year%12==5:
    print(year,"is the year of the Rooster.")
elif year%12==6:
    print(year,"is the year of the Dog.")
elif year%12==7:
    print(year,"is the year of the Pig.")
elif year%12==8:
    print(year,"is the year of the Rat.")
elif year%12==9:
    print(year,"is the year of the Ox.")
elif year%12==10:
    print(year,"is the year of the Tiger.")
elif year%12==11:
    print(year,"is the year of the Rabbit.")
```

Reset answer

Input	Expected	Got	
2000	2000 is the year of the Tiger.	2000 is the year of the Tiger.	✓
2001	2001 is the year of the Rat.	2001 is the year of the Rat.	✓

Passed all tests! ✓

Finish review

Question 9
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

Write a program to determine the type of each character the user's terrific number in the train is given.

Input Format:

Input consists of a single integer. Assume that the range of input is between 0 and 75.

Output Format:

Output contains one single string. (Upper or Middle or Lower or Dot) Lower or Dot (Upper)

Sample Input 1:

```
0
```

Sample Output 1:

```
Lower Dot
```

Answer: (penalty regime: 0 %)

```
n=int(input())
if n in [0,1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,24,25]:
    print("Lower Dot")
elif n in [26,27,28,29,30,31,32,33,34,35,36,37,38,39,40,41,42,43,44,45,46,47,48,49,50,51]:
    print("Upper Dot")
elif n in [52,53,54,55,56,57,58,59,60,61]:
    print("Middle Dot")
else:
    print("Dot (Upper Dot)")
```

Reset answer

Input	Expected	Got	
0	Lower Dot	Lower Dot	✓
1	Lower Dot	Lower Dot	✓
26	Upper Dot	Upper Dot	✓
52	Middle Dot	Middle Dot	✓
75	Dot (Upper Dot)	Dot (Upper Dot)	✓

Passed all tests! ✓

Finish review

Question 10
Correct
Mark 100.00 out of 100.00
Flag question
Edit question

Write a program to calculate and print the Electricity bill where the unit consumed by the user is given from test case. It prints the total amount the customer has to pay. The charges are as follows

Unit Charges (Rs)

upto 199 @1.20

200 and above but less than 400 @1.50

400 and above but less than 600 @1.80

600 and above @2.00

If bill exceeds Rs.400 then a surcharge of 15% will be charged and the minimum bill should be of Rs.100/-

Sample Test Cases

Test Case 1

Input

50

Output

100.00

Test Case 2

Input

300

Output

517.50

For example:

Input	Result
100.00	120.00
500	1035.00

Answer: (penalty regime: 0 %)

```
n=float(input())
p=0

if(n<199):
    p=n*1.20
elif(200<=n<400):
    p=n*1.50
elif(400<=n<600):
    p=n*1.80
elif(600<=n):
    p=n*2.00


if(p>100):
    if(p>400):
        p=p*0.15+p
else:
    p=100

print(p)
```

	Input	Expected	Got	
✓	50	100.00	100	✓
✓	100.00	120.00	120.0	✓
✓	500	1035.00	1035.0	✓
✓	700	1610.00	1610.0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Finish review