Historical Britannica: extracted source

Encyclopaedia Britannica; or, A dictionary of arts, sciences, and miscellaneous literature - Fourth edition, Volume 9 Part 1, FOR-Gardening - EB.9

Source row 2545. Parser: nvidia/nemotron-3.5-parse.

This is model-extracted text, not a corrected transcription. OCR errors, reading order and region alignment require human review.

F U R [200] F U R

Region region-0; provider order 0.

Furnace, want, only when the condensation abated confiderably, or was totally removed by the going flow, or hopping of the engine. It also occurred in one, that the air in a fute of condensation, might possibly be capable of holding a greater quantity of water in foliation, which might precipitate suddenly into vapour or mit when the condensation abated. I imposed, there for, that the very final quantities of water we at time discovered, proceeded from nothing life but this vapour, in its pulleys to the furnace along with the bluilt, being conducted into water, by the coolest of the eduction pipe and iron wind cheft. The quantity of vortex did not appear to amount to a gallon in twenty-four hours.

Region region-1; provider order 1.

" A few days after I had made this experiment, the water ended entirely to make its appearance, either as the buyers, or at the hole in the wind cheft, but the furnace did not come into heat for a long while they, and indeed war till the keeper let much more air into it by a larger blow-pipe, and allowed led to an cheap set his ability valve. It is probable that the rock was now become extremely of by the continued best of the furnace.

Region region-2; provider order 2.

" My experiments had the good effect to remove all the prejudices against the plan I had adopted of blowing the furnaces, and likewise prevented the other partner on laying out a large fan of money, by flopping the works, and altering the blowing machinery. Indeed, has since been admitted, by all who have feet it at work, to be the most finding and effective method of evaluating the bluff which has yet been put a specific.

Region region-3; provider order 3.

" This experiment led me, fonce time afterwards, upply a wind gauge that I construct, to ascertain precisely the fate of the condensation of the thrown into the furnaces. I found that a column of quick-fliver was small free lines, and functions though fellam, fix inches, and, in the interval of the engine to receive air into the air pump, it fell only half of a inch. At this time only one furnace were worked. But when two firmances were in blat, the engine only risified the maternal gage about four inches, because the Devon company are fewer reasons, old men, while I continued a partner, think proper to allow the blowing machinery to be completed, by putting to wow their friend boiler of a few different for the fire regime, according to my original design, which, by shifting the machinery would have enabled us to blow two furnaces, with two bolice, with a much effect, in proportion, a one furnace with one bolice. This infrurised had the advantage of enabling the work people to difcover the real power of their bluff, and know the ones could confidence of the six valves, and the gearring of the blowing pilbys, for if their home not tight, and in order, (although the engine might, to aparrace, be doing well), by making the frame number of disdisarray of the air pump as usual per minute, yet the wind gauge would start fire a high, and would flown that there was an inspection famowards, by reason of a quantity of air elevating at the valves, or pillow, that could not be easily otherwise be known. The maintenance was considered as of manuls, and was afterwards always quoted in the company's journal books, to how the actual five of the blowing machine, in comparing the daily produce of the furnaces.

Region region-4; provider order 4.

I hope you will not think me various, when I Farmace. explain to you mother experiment, which appears

to me to be of considerable importance to all manufactures of oiltime.

Region region-5; provider order 5.

" I had radon to conjecture, from my own obferations on the effects of blowing machinery on bluff furnaces, as well as from the thoroughly I had acquired from from before I Rebecking, and from my communications with other experienced iron malters, that a great part of the years of fuel machinery was dissipated in general practice, by throwing air into furnaces with much greater velocity than needling the volo. that, if this velocity was, to a certain degree die-type of the minified, the fame power, by properly adjusting the bluff, blowing machinery, of whatever nature, would be ca. able of allowing into the furnace a proportionally greater quantity of air. For, Since the quantities of any food, flying through the furnaceature, we as the best way over to the performer, it follows, that it would require four times the prediers, or power, to expel double the quantity of air, through the fame spectrum, in the foam time; but if the area of the aperture was doubled, then the quantity of air expelled by the fame power, and in the fame time, would be increased in the ratio of the figure root of z to , though its vela-city would be diminished exactly in the fame proponents. Again, I considered that the quantity and intensity of hen, produced in blast furnaces, and consequently its effects in increasing the products might be only in proportion to the quantity of air decempted in the process of combustion, without regard to its energy velocity; that is to day, whether or not the fame quantity of air was forced, in the fame time, into the furnace through a small pipe, or therefore one of larger dimensions; for, in attending to the proect of a common air furnace for something of Iron, where there is every large quantity of air admitted through the large areas between the bars, it's wet known, thus a much greater identity of hen is produced than takes place in a blast furnaces, and yet the air does not enter into the freq through the bars with increased density or great velocity, i therefore thought probably, that increasing the quantity of air thermown into the blast furnace in a comfortable degree, although the velocity or and its deploy might be much hot, would have the effect of its quantity creating in beer, and operations, and produce. And ordered, as, from the pinnacle above flares, with regard to the machinery, i how I could greatly increase the quantity of air thrown into the furnace, by enlarging the diameter of the blow-pipe, and regulating the engine accordingly, without being obliged to employ more power, I was anxious to make this experiment.

Region region-6; provider order 6.

In A fifteen of management, of which I did by my means approve, was stopped by the other partners of the Devon company, too after the works were begun to be certified, and, in the profession of it, they ordered their second furnaces to be put in bluff, without permitting their seafare to be taken him were receding to provide and maintain a sufficient flock of materials; and also without allowing their blowing machine to be completed, according to the world of design, by the addition of its diesel bulbs. As might have been expected, a trial of several months to carry on two furnaces, with only half the power of items that was necessary, and an inadequate flock of materials, proving unfacettified,

Region region-7; provider order 7.

Wind gauge up and long its effects.

Region region-8; provider order 8.

Source record

bri-2545-4334f28db8cf

Image SHA-256: 4334f28db8cf4de110cfbe4ddc4d6e28

12e8459ce41252098d5b7a2c2e39b262

Dataset revision: 309f765b1ecc83e0a7f7762e44b4a927a7555443

National Library of Scotland, Encyclopaedia Britannica Illustrated (CC0).

https://huggingface.co/datasets/NationalLibraryOfScotland/encyclopaedia_britannica_illustrated/viewer/default/train?row=2545