

Ex: No. 08a
date :- 25/10/25

A Python Program to Implement Ada Boosting

Aim:-

To implement a python program for Ada Boosting.

Algorithm:-

Step 1:- Import Necessary Libraries

Import numpy as np

Step 2:- Load and prepare Data

Step 3:- Initialize parameters

Step 4:- Train weak classifiers

Step 5:- Make prediction

Step 6:- Evaluate the model

Program:-

```
import numpy numpy as np
import pandas as pd
from sklearn.tree import DecisionTreeClassifier
from sklearn.model_selection import train_test_split
from sklearn.metrics import accuracy_score
```

Step 2: Load and Prepare Data

```
data = pd.DataFrame({
```

```
    'x1': [2, 3, 4, 5, 6, 6, 7, 9, 9],
```

```
    'x2': [5, 3, 6, 8, 1, 9, 5, 8, 9, 2]
```

```
    'label': [1, 1, 0, 1, 0, 1, 0, 1, 0, 0]
```

```
})
```

```
x = data[['x1', 'x2']].values
```

```
y = data['label'].values
```


Handwritten notes on the left margin of the top page.

	X1	X2	label	weights
6	6	5	0	0.1
6	6	5	0	0.1
0	1	5	1	0.1
6	6	5	0	0.1
7	7	8	1	0.1
5	6	9	1	0.1
1	2	3	1	0.1
8	9	9	0	0.1
4	5	1	0	0.1
6	6	5	0	0.1

Handwritten notes on the right margin of the top page.

Handwritten notes on the right margin of the top page.

Handwritten notes at the bottom of the top page.



Handwritten notes on the right margin of the bottom page.

Handwritten notes on the left margin of the bottom page.

	X1	X2	label	weights
1	2	3	1	0.1
6	6	5	0	0.1
5	6	9	1	0.1
1	2	3	1	0.1
5	6	9	1	0.1
8	9	9	0	0.1
8	9	9	0	0.1
8	9	9	0	0.1
5	6	9	1	0.1
8	9	9	0	0.1

Handwritten notes on the right margin of the bottom page.

Handwritten notes at the top of the page, including "2018/12/28" and "Machine Learning" written upside down.

	X1	X2	label	weights	y_pred
6	6	5	0	0.1	0
6	6	5	0	0.1	0
0	1	5	1	0.1	1
6	6	5	0	0.1	0
7	7	8	1	0.1	0
5	6	9	1	0.1	0
1	2	3	1	0.1	1
8	9	9	0	0.1	0
4	5	1	0	0.1	0
6	6	5	0	0.1	0

	X1	X2	label	weights	y_pred	updated_weights
6	6	5	0	0.1	0	0.033622
6	6	5	0	0.1	0	0.033622
0	1	5	1	0.1	1	0.033622
6	6	5	0	0.1	0	0.033622
7	7	8	1	0.1	0	0.297427
5	6	9	1	0.1	0	0.297427
1	2	3	1	0.1	1	0.033622
8	9	9	0	0.1	0	0.033622
4	5	1	0	0.1	0	0.033622
6	6	5	0	0.1	0	0.033622

X1	X2	label	weights	y_pred	normalized_weights	current_loss	updated_loss
6	6	5	0	0	0.000000	0.000000	0.000000
6	6	5	0	0	0.000000	0.000000	0.000000
0	1	5	1	1	0.000000	0.000000	0.000000
6	6	5	0	0	0.000000	0.000000	0.000000
7	7	8	1	0	0.000000	0.000000	0.000000
5	6	9	1	0	0.000000	0.000000	0.000000
1	2	3	1	1	0.000000	0.000000	0.000000
8	9	9	0	0	0.000000	0.000000	0.000000
4	5	1	0	0	0.000000	0.000000	0.000000
6	6	5	0	0	0.000000	0.000000	0.000000

Handwritten notes at the bottom of the page, including "Machine Learning" and "2018/12/28" written upside down.

```

# Convert y into {-1, +1} form for AdaBoost
y_transformed = np.where(y == -1, 1, -1)
x_transformed = x, test_size = 0.3, random_state = 42)

# Step 3: Initialise parameters
n_estimators = 5
n_samples = x_train.shape[0]
weights = np.ones(n_samples) / n_samples
classifiers = []
alphas = []

# Step 4: Train weak classifiers
for i in range(n_estimators):
    clf = DecisionTreeClassifier(max_depth=1)
    clf.fit(x_train, y_train, sample_weight=weights)
    y_pred = clf.predict(x_train)

# Calculate weighted error
err = np.sum(weights * (y_train != y_pred)) /
    np.sum(weights)
    if err == 0:
        err = 1e-10

# Compute alpha
alpha = 0.5 * np.log((1 - err) / err)


# Update weights
weights = weights * np.exp(-alpha * y_train * y_pred)
weights /= np.sum(weights) # normalise

classifiers.append(clf)
alphas.append(alpha)

# Step 5: Make prediction
def predict(x):
    final_score = np.zeros(x.shape[0])
    for clf, alpha in zip(classifiers, alphas):

```

`Test(0.5, 0.75, 'x[0] <= 3.5 | gini = 0.48 | samples = 10 | value = [5, 5]`
`Test(0.25, 0.75, 'gini = 0 | samples = 2 | value = [2, 0]`
`Test(0.75, 0.25, 'gini = 0.375 | samples = 8 | value = [3, 5]`



$$V(\text{node} - p) = |p - p'| \times \text{weight} \times \text{samples} \times \text{value}$$

$$(p - p') \times (1 - p) \times \text{weight} \times \text{samples} \times \text{value}$$

$$(p - p') \times p \times \text{weight} \times \text{samples} \times \text{value}$$

$$\text{weight} \times \text{samples} \times \text{value} \times (p - p')$$

$$\text{weight} \times \text{samples} \times \text{value} \times (1 - p)$$

$$\text{weight} \times \text{samples} \times \text{value} \times p$$

$$\text{weight} \times \text{samples} \times \text{value} \times (1 - p)$$

$$\text{weight} \times \text{samples} \times \text{value} \times p$$

$$\text{weight} \times \text{samples} \times \text{value} \times (1 - p)$$

$$\text{weight} \times \text{samples} \times \text{value} \times p$$

```
preds = clf.predict(x)
final_score = alpha * preds
return np.sign(final_score)

y_pred_test = predict(x_test)

# Step 6: Evaluate Model
acc = accuracy_score(y_test, y_pred_test)

# Step 7: Output Results
print("Final Accuracy on Test Set:", acc)
print("Classifier weights (alphas):", alphas).
```

Result:-

Thus the python program to implement ~~Adaboost~~ has been successfully executed.