

Cisco Packet Tracer

File Edit Options View Tools Extensions Help

Logical Physical x: 998, y: 87

Stimulating Multimedia Media Network in Cisco packet tracer

PC-PT Host 1

Printer-PT Printer0

2960-24TT Switch0

PC-PT PC1

PC-PT PC2

Host 1

Physical Config Desktop Programming Attributes

Command Prompt

```
C:\>
C:\>ipconfig 172.16.0.2

Pinging 172.16.0.2 with 32 bytes of data:

Reply from 172.16.0.2: bytes=32 time=1ms TTL=128
Reply from 172.16.0.2: bytes=32 time=3ms TTL=128
Reply from 172.16.0.2: bytes=32 time=1ms TTL=128
Reply from 172.16.0.2: bytes=32 time=3ms TTL=128

Ping statistics for 172.16.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 3ms, Average = 1ms

C:\>ipconfig 172.16.0.1

Pinging 172.16.0.1 with 32 bytes of data:

Reply from 172.16.0.1: bytes=32 time=6ms TTL=128
Reply from 172.16.0.1: bytes=32 time=1ms TTL=128
Reply from 172.16.0.1: bytes=32 time=1ms TTL=128
Reply from 172.16.0.1: bytes=32 time=1ms TTL=128

Ping statistics for 172.16.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
```

Time: 24:36:53

Realtime Simulation

Activate Windows
Go to Settings to activate Windows.

Automatically Choose Connection Type

Type here to search

25°C Mostly clear 00:16 29-01-2023