88
Pass

Malayambakam jyothi

PDF generated at: 4 Mar 2026 13:01:20 UTC

View this report on HackerRank

Score

88% • 154.0 / 175
scored in eClerx - Java Coding Test - 3+ Years New in 19 min 45 sec on 4 Mar 2026 18:09:43 IST

Candidate Information

Email	malayambakamjyothi03@gmail.com
Test	eClerx - Java Coding Test - 3+ Years New
Candidate Packet	View
Taken on	4 Mar 2026 18:09:43 IST
Time taken	19 min 45 sec/ 90 min
Work Experience	> 5 years
Invited by	Vipul
Invited on	4 Mar 2026 15:23:09 IST

Skill Distribution

No.	Skill	Score
1	Spring Boot Advanced	100%

2	Spring Boot Intermediate	66%
3	Problem Solving Intermediate	78%
4	Java Intermediate	100%

Tags Distribution

Spring Boot	80%	Hard	100%
TDD	100%	Spring	0%
JPA	0%	Spring Data	0%
Transactional	0%	Medium	87%
Exception Handling	100%	Aspect-Oriented Programming	100%
Pointers	78%	Greedy	100%
Sorting	100%	Java	100%

Questions

Spring Boot (Advanced) • 20 / 25

No.	Question	Skill	Score	Code Quality	Time Taken	Status
1	Cracker Multiple Choice	Spring Boot (Advanced)	5/5	-	52 sec	✓

2	Output Multiple Choice	Spring Boot (Advanced)	5/5	-	29 sec	✓
3	Spring Data Transactional Multiple Choice	Spring Boot (Intermediate)	0/5	-	1 min 29 sec	✗
4	CSRF Multiple Choice	Spring Boot (Intermediate)	5/5	-	1 min 12 sec	✓
5	Predict the Output Multiple Choice	Spring Boot (Intermediate)	5/5	-	1 min 10 sec	✓

Problem Solving (Intermediate) • 59 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status
6	Quiz Competition Coding	Problem Solving (Intermediate)	59/75	-	6 min 24 sec	✓

Java (Intermediate) • 75 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status
7	Java: DataVille's Optimal Storage Coding	Java (Intermediate)	75/75	-	7 min 23 sec	✓

Candidate Feedback

good

1. Cracker

Correct

Multiple Choice | Spring Boot | Hard

Question description

Cracker.java

```
@Component
public class Cracker {
    public void startCracking(){
        System.out.println("Cracking...");
    }
    public void stopCracking(){
        System.out.println("Cracking Stopped!");
    }
}
```

CrackerService.java

```
@Service
public class CrackerService {

    @Autowired
    Cracker cracker;
    public void workWithNewCracker() {
        cracker.stopCracking();
        cracker = new Cracker();
    }
    public void startWorking() {
        cracker.startCracking();
    }
}
```

CrackerWorker.java

```
@Service
public class CrackerWorker {

    @Autowired
    CrackerService crackerService;

    public void startWorking() {
        crackerService.startWorking();
        crackerService.workWithNewCracker();
        crackerService = new CrackerService();
        crackerService.startWorking();
    }
}
```

Consider these classes are managed in Spring Boot. What happens when 'crackerWorker.startWorking()' is called in the Spring context?

Interviewer guidelines

CrackerService in CrackerWorker will work perfectly until it's replaced with new CrackerService. When that happens it just replace existing injected bean with empty pojo. Which doesn't have it's cracker object so when it's startWorking method is called it will try to execute null cracker attributes startWorking method and NullPointerException will arise.

Candidate's Solution

Options: (Expected answer indicated with a tick)

- "Cracking..." "Cracking Stopped!" will be written to console

- "Cracking..." "Cracking Stopped!" "Cracking..." will be written to console

"Cracking..." "Cracking Stopped!" NullPointerException will be thrown

None of above

No comments.

2. Output

Correct

Multiple Choice | Hard | Spring Boot | TDD

Question description

What will happen to the output file?

```
@SpringBootTest
public class LogTest
{
   File log;
   FileWriter logWriter;

   @Autowired
   SomeClassToTest someClassToTest;

   @Before
   public void init()
   {
     log = new File("log.txt");
     logWriter = new FileWriter(log);
   }

   @After
   public void teardown()
   {
      log.delete();
```

```
    }

    @Test
    public void test1()
    {
        logWriter.write("Entered Test 1");
        assertTrue(someClassToTest.someMethod());
    }

    @Test
    public void test2()
    {
        logWriter.write("Entered Test 2");
        assertTrue(someClassToTest.otherMethod());
    }
}
```

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ The output file is not created.
- ○ The output file is created but not deleted.
- ● **The output file is created and eventually deleted.** ✓
- ○ The create and delete blocks will not be executed.

No comments.

3. Spring Data Transactional

Incorrect

Multiple Choice | Spring | Spring Boot | JPA | Spring Data | Transactional | Medium

Question description

Given the following code, what happens when *StudentRepsitoryTest* runs?

Lesson.java

```
@Entity
public class Lesson {
   @Id
   private Long id;
   private String name;
   private Integer courseLength;
   private Integer courseLevel;
   @JsonBackReference
   @ManyToOne(fetch = FetchType.LAZY)
   @JoinColumn(name = "student_id")
   private Student student;
   private boolean inProgress;
   //getter & setters
}
```

Student.java

```
@Entity
public class Student {
   @Id
   private Long id;
   private String name;
   private String surname;
   @JsonManagedReference
   @OneToMany(mappedBy = "student", fetch = FetchType.EAGER, cascade = {CascadeType.PERSIST,
CascadeType.REFRESH})
   private List<Lesson> lessons;
   //getter & setters
}
```

StudentRepository.java

```
@Repository
public interface StudentRepository extends JpaRepository<Student, Long>{
    //Y
    Optional<Student> findById(Long id);
}
```

LessonRepository.java

```
@Repository
public interface LessonRepository extends JpaRepository<Lesson, Long> {
}
```

StudentService.java

```
@Service
public class StudentService{
    private StudentRepository studentRepository;
    public StudentService(StudentRepository studentRepository, LessonRepository lessonRepository)
{
        this.studentRepository = studentRepository;
        this.lessonRepository = lessonRepository;
    }

    public void save(Student student) {
        studentRepository.save(student);
    }

    //other crud metods

    //X
    public void deleteStudentWithLessons(Long id) throws SQLException {
        Student student =
                studentRepository.findById(id).orElseThrow(() -> new RuntimeException("Student not foun
d"));
        List<Lesson> lessons = student.getLessons();
        lessons.stream().forEach(lesson -> lesson.setStudent(null));
        studentRepository.delete(student);
```

```
        boolean inProgress =lessons.stream()
                .map(Lesson::isInProgress)
                .filter(progress -> progress == true)
                .findFirst()
                .orElseGet(() -> false);
        if (inProgress) {
            throw new SQLException("Cannot delete all Lessons. There are lessons in progress state");
        }
        lessonRepository.deleteAll(lessons);
    }
}
```

StudentRepositoryTest.java

```
@SpringBootTest
class StudentRepositoryTest {
    @Autowired
    StudentRepository studentRepository;
    @Autowired
    StudentService studentService;
    @Autowired
    LessonRepository lessonRepository;
    Student student;
    @BeforeEach
    public void init() {
        student = Student.builder().name("Jorn").surname("Deynhoven").build();
        studentRepository.save(student);
        lessonRepository.saveAll(List.of(
                Lesson.builder().name("Music").courseLength(10).student(student).courseLevel(123).build
(),
                Lesson.builder().name("Art").courseLength(20).courseLevel(123).student(student).build(),
                Lesson.builder().name("Trance").courseLength(30).courseLevel(123).student(student).inPro
gress(true).build()
        ));
    }
    @Test
    void deleteStudentWithLessonsTest() throws SQLException {
        studentService.deleteStudentWithLessons(student.getId());
    }
}
```

Interviewer guidelines

Candidate has to know how to use spring data in any spring application which uses spring data. If an entity wanted to remove from database without removing the child attributes, then first relation between them should be removed. Without doing this, spring will throw DataIntegrityViolationException to keep database consistent. To achive that without changing existing code, we need to annotate deleteStudentWithLessons(Long id) method with @Transactional annotation. With this spring will update the database states of child entities. In this case it will update Lesson attributes to have student as null. Then student will be removed in the next line.

After this there is a inProgress check for existing lessons. it will throw SQLException which is a checked exception. @Transactional annotation in default only rolls back for unchecked exception such as RuntimeException. So all changes will be reflected to database.

Option A and E is right. More info can be found in https://docs.spring.io/spring-framework/docs/current/javadoc-api/org/springframework/transaction/annotation/Transactional.html

Candidate's Solution

Options: (Expected answer indicated with a tick)

- [x] It will try to delete the student then the DataIntegrityViolationException will be thrown.
- [x] It will delete the student successfully then an SQLException will be thrown with the message "Cannot delete all Lessons. There are lessons in progress state".
- [x] If @Transactional annotation is put in place of X (StudentServer.java), after saving the student and lessons, it will update lessons and remove the student. Then it will throw an SQLException and all database changes will be rolled back.

- [ ] It will throw a RuntimeException with the message "Student not found".

- [ ] If @Transactional annotation is put in place of X (StudentServer.java), after saving the student and lessons, it will update lessons and remove the student. Then it will throw an SQLException.

No comments.

4. CSRF

Correct

Multiple Choice | Spring Boot | Medium

Question description

Which Java Spring-based code segment correctly configures CSRF?

Interviewer guidelines

CSRF Protection makes sure that server is not bombarded with unwanted calls. Spring Security enables some features by default like CSRF and Form based authentication.

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ( ) private void manage(HttpSecurity http) {   http.csrf().allowed() }

private void manage(HttpSecurity http) {   http.csrf() }

private void manage(HttpSecurity http) {   http.csrf().enable() }

** None of the above. CSRF is configured by default when Spring Security Dependency is added. **

No comments.

5. Predict the Output

Correct

Multiple Choice | Medium | Exception Handling | Spring Boot | Aspect-Oriented Programming

Question description

Consider the following Snippet and predict the output.

The following API is triggered: http://localhost:8080/add/employee?eId=123&fName=Ravi&lastName=Shekhar

```
@Autowired
private EService eService;

@RequestMapping(value = "/add/employee", method = RequestMethod.GET)
public com.model.Employee add(@RequestParam("eId") String eId, @RequestParam("fName") Strin
g fName, @RequestParam("lastName") String lastName)
{
   return eService.createEmployee(eId, fName, lastName);
}
```

```
@Aspect
@Component
public class EServiceAspect
{
   @After(value = "execution(* com.random.service.EService.*(..)) && args(eId, fName, lastName)")
   public void afterAdvice(JoinPoint joinPoint, String eId, String fName, String lastName) {
      System.out.println("After method:" + joinPoint.getSignature());
      System.out.println("Creating Employee with first name - " + fName+ ", second name - " + lastNa
me+ " and id - " + eId);
   }
}
```

Candidate's Solution

Options: (Expected answer indicated with a tick)

- [x] ** After method : com.test.model.Employee addEmployee(String,String,String) Creating Employee with first name - Ravi , second name - Shekhar and id - 123   **
- [ ] After method : com.test.model.Employee addEmployee(string,string,string) Creating Employee with first name - Ravi , second name - Shekhar and id - 123
- [ ] After method : com.test.model.Employee addEmployee(empId,firstName,secondName) Creating Employee with first name - Ravi , second name - Shekhar and id - 123

After method : com.test.model.Employee addEmployee(String,String,String)
Creating Employee with first name - Shekhar, second name - Ravi and id - 123

No comments.

6. Quiz Competition

Partially correct

Coding Medium Pointers

Question description

A class has students with various talents, each represented by an integer from 1 to *talentsCount*. You need to form teams for a quiz competition, where each team must have at least one member with each talent.

Teams must be formed from consecutive students in the array. For each possible starting position, determine the minimum number of students needed to form a valid team. If it is not possible to form a team with all talents from a particular starting position, return -1 for that position.

Example

talentsCount = 3
talent = [1, 2, 3, 2, 1]

- Starting at position 1: [1, 2, 3] includes all talents, minimum size = 3
- Starting at position 2: [2, 3, 2, 1] is the smallest subarray with all talents, minimum size = 4
- Starting at position 3: [3, 2, 1] includes all talents, minimum size = 3
- Starting at positions 4 and 5: Cannot form a team with all talents, return -1

The result is [3, 4, 3, -1, -1].

Function Description

Complete the function *teamSize* in the editor with the following parameter(s):

int talent[n]: the students' talents

int talentsCount : the number of talents represented numbered from 1 to *talentsCount*

Returns

int[n]: at each index, the minimum size subarray required, or -1 if an appropriate subarray does not exist

Constraints

- $1 \le n, talentsCount \le 10^5$
- $1 \le talent[i] \le talentsCount$

▼ INPUT FORMAT FOR CUSTOM TESTING

The first line contains an integer, *n*, the number of elements in *talent*.

Each line *i* of the *n* subsequent lines (where $0 \le i < n$) contains an integer, *talent[i]*.

The next line contains the integer *talentCount*.

▼ SAMPLE CASE 0

Sample Input For Custom Testing

```
STDIN   Function
-----   --------
8       talent[] size n = 8
1       talent = [1, 1, 2, 2, 3, 1, 3, 2]
1
2
2
3
1
3
2
3       talentsCount = 3
```

Sample Output

```
5
4
4
3
4
```

```
3
-1
-1
```

Explanation

The shortest subarrays for each position:

Beginning at the first position: [1, 1, 2, 2, 3] (length 5)

Second position: [1, 2, 2, 3] (length 4)

Third position: [2, 2, 3, 1] (length 4)

Fourth position: [2, 3, 1] (length 3)

Fifth position: [3, 1, 3, 2] (length 4)

Sixth position: [1, 3, 2] (length 3)

No further subarrays will have 3 elements.

▼ SAMPLE CASE 1

Sample Input For Custom Testing

```
STDIN   Function
-----   --------
5       talent[] size n = 5
1       talent = [1, 1, 1, 1, 1]
1
1
1
1
1       talentsCount = 1
```

Sample Output

```
1
1
1
1
1
```

Explanation

Since there is only 1 type of talent, any 1 person can form a team.

▼ SAMPLE CASE 2

Sample Input For Custom Testing

```
STDIN   Function
-----   --------
9       talent[] size n = 9
7       talent = [7, 5, 3, 4, 6, 1, 7, 2, 4]
5
3
4
6
1
7
2
4
7       talentsCount  7
```

Sample Output

```
8
7
-1
-1
-1
-1
-1
-1
-1
```

Explanation

There have to be at least *7* elements in any subarray to have one from each talent. The shortest subarrays at each position are:

Beginning at the first position: [7, 5, 3, 4, 6, 1, 7, 2] (length 8)

Second position: [5, 3, 4, 6, 1, 7, 2] (length 7)

No further subarrays will have 7 elements.

Interviewer guidelines

▼ SOLUTION

This can be solved using two-pointer technique. For a particular left index (L), we move the right index (R) forward until we have k distinct elements, then once we get it, we can move L forward. Each element will be traversed at most two times.

Time Complexity: O(n) or O(nLogn) (with set/map).

C++ Solution:

```
int f[100005];

vector<int> teamSize(vector<int> talent, int talentsCount) {
    int k = talentsCount;
    int n = talent.size();
    assert(n>=1&&n<=100000);
    assert(k>=1&&k<=n);
    for(int i=0;i<n;i++)
    {
        assert(talent[i]<=k&&talent[i]>=1);
    }
    int cnt = 0;
    int j = 0;
    vector<int> ans(n);
    for(int i=0;i<n;i++)
    {
        int x = talent[i];
        f[x]++;
        if(f[x]==1)
            cnt++;
        while(cnt==k&&j<=i)
        {
            ans[j] = i - j + 1;
            int y = talent[j];
            f[y]--;
            if(f[y]==0)
                cnt--;
            j++;
        }
    }
    while(j<n)
        ans[j++] = -1;
    return ans;
}
```

Candidate's Solution

Language used: **Java 8**

```java
import java.io.*;
import java.math.*;
import java.security.*;
import java.text.*;
import java.util.*;
import java.util.concurrent.*;
import java.util.function.*;
import java.util.regex.*;
import java.util.stream.*;
import static java.util.stream.Collectors.joining;
import static java.util.stream.Collectors.toList;



class Result {

    /*
     * Complete the 'teamSize' function below.
     *
     * The function is expected to return an INTEGER_ARRAY.
     * The function accepts following parameters:
     *  1. INTEGER_ARRAY talent
     *  2. INTEGER talentsCount
     */

    public static List<Integer> teamSize(List<Integer> talent, int talentsCount) {
    // Write your code here
    int n = talent.size();;
    List<Integer> result = new ArrayList<>();
    for(int i=0;i<n;i++){
        int[] freq = new int[talentsCount+1];
        int found =0;
        int minSize=-1;
        for(int j=i;j<n;j++){
            int val= talent.get(j);
            if(val>=1&& val<=talentsCount){
                if(freq[val]==0){
                    found++;
                }
                freq[val]++;
            }
            if(found==talentsCount){
                minSize = j-i+1;
                break;
            }
```

```
        }
        result.add(minSize);
    }
    return result;

    }

}

public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int talentCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> talent = IntStream.range(0, talentCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int talentsCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> result = Result.teamSize(talent, talentsCount);

        bufferedWriter.write(
            result.stream()
                .map(Object::toString)
                .collect(joining("\n"))
            + "\n"
        );

        bufferedReader.close();
        bufferedWriter.close();
    }
}
```

88

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
TestCase 0	Easy	Sample	Success	1	0.1111 sec	30.1 KB
TestCase 1	Easy	Sample	Success	1	0.117 sec	29.9 KB
TestCase 2	Easy	Sample	Success	1	0.119 sec	30.6 KB
TestCase 3	Easy	Hidden	Success	3	0.1861 sec	42.7 KB
TestCase 4	Easy	Hidden	Success	3	0.2481 sec	42.7 KB
TestCase 5	Easy	Hidden	Success	3	0.2333 sec	43.6 KB
TestCase 6	Easy	Hidden	Success	8	1.8488 sec	183 KB
TestCase 7	Easy	Hidden	Success	8	1.8272 sec	183 KB
TestCase 8	Easy	Hidden	Success	8	1.9122 sec	183 KB

TestCase 9	Easy	Hidden	Success	8	1.8874 sec	183 KB
TestCase 10	Easy	Hidden	Success	8	2.787 sec	210 KB
TestCase 11	Easy	Hidden	Terminated due to timeout	0	4.029 sec	209 KB
TestCase 12	Easy	Hidden	Terminated due to timeout	0	4.0262 sec	210 KB
TestCase 13	Easy	Hidden	Success	7	2.8372 sec	210 KB

No comments.

7. Java: DataVille's Optimal Storage

Correct

Coding Greedy Sorting Medium Java

Question description

In the digital city of DataVille, efficient data management is critical. The city's database is represented as a binary array, *databaseStorage*, containing *n* bits of data. Each bit represents one of two types of data:

- Standard data: Represented by 0.
- Priority data: Represented by 1.

To optimize efficiency during peak operational hours, the number of transitions between 0s and 1s in the array must be minimized. Transitions are points in the array where adjacent elements differ (e.g., a 0 followed by a 1 or a 1 followed by a 0).

Operations:

- You can swap any two bits in the array as many times as you like.

The goal is to rearrange the bits to minimize transitions with the minimum number of swaps.

Example

Consider that *databaseStorage* = [1, 0, 1, 0, 1]. One optimal strategy is to swap *databaseStorage[0]* and *databaseStorage[3]*. After performing this operation, the array is [**0**, 0, 1, **1**, 1], which requires only one transition between *databaseStorage[1]* and *databaseStorage[2]*. This requires only 1 swap, so the return value is 1.

Function Description

Complete the function g*etOptimalStorage* in the editor below.

Function Parameters

int databaseStorage[n]: the current organization of the database's storage, with 0s for standard data and 1s for priority data

Returns

int: the minimum number of operations required to minimize transitions between 0s and 1s

Constraints

- $2 \le n \le 10^5$
- *databaseStorage[i]* $\in$ {0, 1}

▼ INPUT FORMAT FOR CUSTOM TESTING

The first line contains an integer, *n,* the size of *databaseStorage*.
Each of the next lines contains an integer, *databaseStorage[i].*

▼ SAMPLE CASE 0

Sample Input 0

```
STDIN       FUNCTION
-----       --------
7           databaseStorage[] size n = 7
1           databaseStorage = [1, 0, 1, 1, 0, 0, 1]
0
1
1
```

```
0
0
1
```

Sample Output 0

```
1
```

Explanation

One optimal strategy is to swap *databaseStorage[1]* (which is 0) with *databaseStorage[6]* (which is 1). After performing this operation, the array becomes [1, **1**, 1, 1, 0, 0, **0**]. This solution requires only 1 swap, so the output is 1.

▼ SAMPLE CASE 1

Sample Input 1

```
STDIN     FUNCTION
-----     --------
9         databaseStorage[] size n = 9
1         databaseStorage = [1, 0, 0, 1, 1, 0, 0, 0, 1]
0
0
1
1
0
0
0
1
```

Sample Output 1

```
2
```

Explanation

One optimal strategy of operations is:

1. Swap *databaseStorage*[1] and *databaseStorage*[8]. After performing this operation, the array becomes [1, **1**, 0, 1, 1, 0, 0, 0, **0**].
2. Swap *databaseStorage*[2] and *databaseStorage*[4]. After performing this operation, the array becomes [1, 1, **1**, 1, **0**, 0, 0, 0, 0].

Now there is only one transition. The minimum number of swaps is 2.

Interviewer guidelines

▼ SOLUTION

The solution is to count the number of 0s and 1s in the array. Then, we count the number of 0s and 1s that are out of place. The answer is the minimum of the two counts.

```
class Result {

    /*
     * Complete the 'getOptimalStorage' function below.
     *
     * The function is expected to return an INTEGER.
     * The function accepts INTEGER_ARRAY databaseStorage as parameter.
     */

    public static int getOptimalStorage(List<Integer> databaseStorage) {
        int zeros = 0, ones = 0;

        for (int brick : databaseStorage) {
            if (brick == 0) {
                zeros++;
            } else {
                ones++;
            }
        }

        int startZero = 0, startOne = 0;

        for (int i = 0; i < ones; ++i) {
            if (databaseStorage.get(i) != 1) {
                startOne++;
            }
        }

        for (int i = 0; i < zeros; ++i) {
            if (databaseStorage.get(i) != 0) {
                startZero++;
            }
        }

        return Math.min(startZero, startOne);
    }
```

```
}
```

▼ COMPLEXITY

Time Complexity - O(n)

To traverse over the array, we use a loop that runs n times. The complexity is O(n).

Space Complexity - O(1)

We use only 2 variables, hence the space complexity is O(1).

Candidate's Solution

Language used: **Java 8**

```
import java.io.*;
import java.math.*;
import java.security.*;
import java.text.*;
import java.util.*;
import java.util.concurrent.*;
import java.util.function.*;
import java.util.regex.*;
import java.util.stream.*;
import static java.util.stream.Collectors.joining;
import static java.util.stream.Collectors.toList;


class Result {

    /*
     * Complete the 'getOptimalStorage' function below.
     *
     * The function is expected to return an INTEGER.
     * The function accepts INTEGER_ARRAY databaseStorage as parameter.
     */

    public static int getOptimalStorage(List<Integer> databaseStorage) {
        int n= databaseStorage.size();
        int count0=0,count1=0;
        for(int v: databaseStorage){
            if(v==0) count0++;
            else count1++;
```

```
        }
        int mismatch1=0;
        for(int i=0;i<count0;i++){
            if(databaseStorage.get(i)!=0)mismatch1++;
        }
        int mismatch2=0;
        for(int i=0;i<count1;i++){
            if(databaseStorage.get(i)!=1) mismatch2++;
        }
        return Math.min(mismatch1,mismatch2);

    }

}

public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int databaseStorageCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> databaseStorage = IntStream.range(0, databaseStorageCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int result = Result.getOptimalStorage(databaseStorage);

        bufferedWriter.write(String.valueOf(result));
        bufferedWriter.newLine();

        bufferedReader.close();
        bufferedWriter.close();
    }
}
```

72

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
TestCase 0	Easy	Sample	Success	1	0.1129 sec	30.3 KB
TestCase 1	Easy	Sample	Success	1	0.1152 sec	30 KB
TestCase 2	Easy	Sample	Success	1	0.1141 sec	29.9 KB
TestCase 3	Easy	Hidden	Success	3	0.1162 sec	30.4 KB
TestCase 4	Easy	Hidden	Success	3	0.1077 sec	30.5 KB
TestCase 5	Easy	Hidden	Success	3	0.1177 sec	30.6 KB
TestCase 6	Easy	Hidden	Success	4	0.1105 sec	30 KB
TestCase 7	Easy	Hidden	Success	4	0.1205 sec	30.1 KB
TestCase 8	Easy	Hidden	Success	5	0.1145 sec	30.4 KB
TestCase 9	Easy	Hidden	Success	5	0.1064 sec	30.3 KB
TestCase 10	Easy	Hidden	Success	5	0.0974 sec	30.3 KB
TestCase 11	Medium	Hidden	Success	7	0.133 sec	31 KB

TestCase 12	Medium	Hidden	Success	8	0.1393 sec	31.5 KB
TestCase 13	Hard	Hidden	Success	10	0.119 sec	31.4 KB
TestCase 14	Hard	Hidden	Success	15	0.2651 sec	53.6 KB

No comments.