98.6
Pass

Mukund

PDF generated at: 12 Feb 2026 16:18:13 UTC

View this report on HackerRank

Score

98.6% • 172.5 / 175
scored in eClerx - Java Coding Test - 3+ Years New in 42 min 19 sec on 12 Feb 2026 21:03:39 IST

Candidate Information

Email	mukundsuvarnakar97@gmail.com
Test	eClerx - Java Coding Test - 3+ Years New
Candidate Packet	View
Taken on	12 Feb 2026 21:03:39 IST
Time taken	42 min 19 sec/ 90 min
Work Experience	4 years
Invited by	Vipul
Invited on	12 Feb 2026 16:15:11 IST

Skill Distribution

No.	Skill	Score
1	Spring Boot Advanced	100%

2	Spring Boot Intermediate	87%
3	Problem Solving Intermediate	100%
4	Java Intermediate	100%

Tags Distribution

Spring Boot	87%	Hard	100%
Spring	83%	JPA	50%
Spring Data	50%	Transactional	50%
Medium	98%	Application Properties Annotations	100%
Implementation	100%	Arrays	100%
Algorithms	100%	Problem Solving	100%
Greedy	100%	Java	100%

Questions

Spring Boot (Advanced) • 22.5 / 25

No.	Question	Skill	Score	Code Quality	Time Taken	Status
1	Specification Multiple Choice	Spring Boot (Advanced)	5/5	-	38 sec	✓

2	Spring Data Transactional Multiple Choice	Spring Boot (Intermediate)	2.5/5	-	2 min 38 sec	
3	Configuration Properties Multiple Choice	Spring Boot (Intermediate)	5/5	-	1 min 53 sec	
4	Spring Scopes Multiple Choice	Spring Boot (Intermediate)	5/5	-	50 sec	
5	CSRF Multiple Choice	Spring Boot (Intermediate)	5/5	-	1 min 7 sec	

Problem Solving (Intermediate) • 75 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status
6	Wind Farms Coding	Problem Solving (Intermediate)	75/75	-	20 min 14 sec	

Java (Intermediate) • 75 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status
7	Java: Optimized Sequential Video Watching Coding	Java (Intermediate)	75/75	-	14 min 30 sec	

1. Specification

Correct

Multiple Choice | Spring Boot | Hard

Question description

Which of the following options can be used for dynamic jpa queries with spring-data-jpa repositories?

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ PreparedStatement
- ● Specification ✓
- ○ Criteria
- ○ Query

No comments.

2. Spring Data Transactional

Partially correct

Multiple Choice | Spring | Spring Boot | JPA | Spring Data | Transactional | Medium

Question description

Given the following code, what happens when *StudentRepsitoryTest* runs?

Lesson.java

```
@Entity
public class Lesson {
   @Id
   private Long id;
   private String name;
   private Integer courseLength;
   private Integer courseLevel;
   @JsonBackReference
   @ManyToOne(fetch = FetchType.LAZY)
   @JoinColumn(name = "student_id")
   private Student student;
   private boolean inProgress;
   //getter & setters
}
```

Student.java

```
@Entity
public class Student {
   @Id
   private Long id;
   private String name;
   private String surname;
   @JsonManagedReference
   @OneToMany(mappedBy = "student", fetch = FetchType.EAGER, cascade = {CascadeType.PERSIST,
CascadeType.REFRESH})
   private List<Lesson> lessons;
   //getter & setters
}
```

StudentRepository.java

```
@Repository
public interface StudentRepository extends JpaRepository<Student, Long>{
   //Y
   Optional<Student> findById(Long id);
}
```

LessonRepository.java

```
@Repository
public interface LessonRepository extends JpaRepository<Lesson, Long> {
}
```

StudentService.java

```
@Service
public class StudentService{
    private StudentRepository studentRepository;
    public StudentService(StudentRepository studentRepository, LessonRepository lessonRepository)
{
        this.studentRepository = studentRepository;
        this.lessonRepository = lessonRepository;
    }

    public void save(Student student) {
        studentRepository.save(student);
    }

    //other crud metods

    //X
    public void deleteStudentWithLessons(Long id) throws SQLException {
        Student student =
                studentRepository.findById(id).orElseThrow(() -> new RuntimeException("Student not foun
d"));
        List<Lesson> lessons = student.getLessons();
        lessons.stream().forEach(lesson -> lesson.setStudent(null));
        studentRepository.delete(student);

        boolean inProgress =lessons.stream()
                .map(Lesson::isInProgress)
                .filter(progress -> progress == true)
                .findFirst()
                .orElseGet(() -> false);
        if (inProgress) {
            throw new SQLException("Cannot delete all Lessons. There are lessons in progress state");
        }
        lessonRepository.deleteAll(lessons);
```

```
    }
}
```

StudentRepositoryTest.java

```
@SpringBootTest
class StudentRepositoryTest {
    @Autowired
    StudentRepository studentRepository;
    @Autowired
    StudentService studentService;
    @Autowired
    LessonRepository lessonRepository;
    Student student;
    @BeforeEach
    public void init() {
        student = Student.builder().name("Jorn").surname("Deynhoven").build();
        studentRepository.save(student);
        lessonRepository.saveAll(List.of(
                Lesson.builder().name("Music").courseLength(10).student(student).courseLevel(123).build
(),
                Lesson.builder().name("Art").courseLength(20).courseLevel(123).student(student).build(),
                Lesson.builder().name("Trance").courseLength(30).courseLevel(123).student(student).inPro
gress(true).build()
        ));
    }
    @Test
    void deleteStudentWithLessonsTest() throws SQLException {
        studentService.deleteStudentWithLessons(student.getId());
    }
}
```

Interviewer guidelines

Candidate has to know how to use spring data in any spring application which uses spring data. If an entity wanted to remove from database without removing the child attributes, then first relation between them should be removed. Without doing this, spring will throw DataIntegrityViolationException to keep database consistent. To achive that without changing existing code, we need to annotate deleteStudentWithLessons(Long id) method with @Transactional annotation. With this spring will update the database states of child entities. In this case it will update Lesson attributes to have

student as null. Then student will be removed in the next line.

After this there is a inProgress check for existing lessons. it will throw SQLException which is a checked exception. @Transactional annotation in default only rolls back for unchecked exception such as RuntimeException. So all changes will be reflected to database.

Option A and E is right. More info can be found in https://docs.spring.io/spring-framework/docs/current/javadoc-api/org/springframework/transaction/annotation/Transactional.html

Candidate's Solution

Options: (Expected answer indicated with a tick)

- [x] ** It will try to delete the student then the DataIntegrityViolationException will be thrown. **
- [ ] It will delete the student successfully then an SQLException will be thrown with the message "Cannot delete all Lessons. There are lessons in progress state".
- [ ] If @Transactional annotation is put in place of X (StudentServer.java), after saving the student and lessons, it will update lessons and remove the student. Then it will throw an SQLException and all database changes will be rolled back.
- [ ] It will throw a RuntimeException with the message "Student not found".

- [ ] If @Transactional annotation is put in place of X (StudentServer.java), after saving the student and lessons, it will update lessons and remove the student. Then it will throw an SQLException.

No comments.

3. Configuration Properties

Correct

Multiple Choice | Spring | Spring Boot | Application Properties Annotations | Medium

Question description

An *application.properties* file contains the following properties:

```
app.prop1 = value1
app.prop2 = value2
```

You decided to create a class to hold this configuration. To protect it, the class is defined as final.

```
@Configuration
@ConfigurationProperties(prefix = "app")
public final class AppConfiguration {
  String prop1;
  String prop2;

  public String getProp1() {
    return prop1;
  }

  public void setProp1(String prop1) {
    this.prop1 = prop1;
  }
```

```
  public String getProp2() {
    return prop2;
  }

  public void setProp2(String prop2) {
    this.prop2 = prop2;
  }
}
```

What is the result of running the Spring application with this class?

Interviewer guidelines

Spring creates dynamic proxies for classes annotated with `@Configuration` classes. Spring uses CGLIB to extend your class to create proxy. Hence, configuration classes cannot be final. When running the code Spring throws `BeanDefinitionParsingException` and this is the correct option.

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ The application runs, the configuration bean is created. and the properties are initialized correctly (prop1=value1, prop2=value2).
- ○ The application runs, and a configuration bean is created, but properties are set to null (prop1=null, prop2=null).
- ● ** A BeanDefinitionParsingException is thrown because the @Configuration bean cannot be marked as final. ** ✓

An IllegalStateException is thrown because the @Configuration bean cannot have an @ConfigurationProperties annotation.

A NoSuchMethodException is thrown because the @Configuration bean needs a default constructor.

No comments.

4. Spring Scopes

Correct

Multiple Choice | Medium | Spring

Question description

Which of the following statements is/are true about @Scope("request") and @Scope("prototype") annotations?

Candidate's Solution

Options: (Expected answer indicated with a tick)

- [x] Both are used to define the scope of spring beans.
- [x] @Scope(“request”) creates a bean instance for a single HTTP request.
- [x] @RequestScope can be used instead of @Scope(“request”).

@Scope("prototype") will return a different instance every time it is requested from the container.

No comments.

5. CSRF

Correct

Multiple Choice | Spring Boot | Medium

Question description

Which Java Spring-based code segment correctly configures CSRF?

Interviewer guidelines

CSRF Protection makes sure that server is not bombarded with unwanted calls. Spring Security enables some features by default like CSRF and Form based authentication.

Candidate's Solution

Options: (Expected answer indicated with a tick)

- private void manage(HttpSecurity http) {   http.csrf().allowed() }

- private void manage(HttpSecurity http) {   http.csrf() }

private void manage(HttpSecurity http) {   http.csrf().enable() }

None of the above. CSRF is configured by default when Spring Security Dependency is added.

No comments.

6. Wind Farms

Correct

Coding | Implementation | Medium | Arrays | Algorithms | Problem Solving

Question description

An energy company needs to place a control center to manage a distributed wind farm. Your task is to determine the optimal location for the control center that minimizes the total connection cost.

For each wind farm *i*:

- The farm is located at coordinates *(x[i], y[i])*
- The control center is at coordinates *(cx, cy)*
- The distance is calculated as *|x[i] - cx| + |y[i] - cy|*
- The connection cost is *premium[i] * distance*

Example

x = [1, 3, 2, 4]
y = [1, 2, 3, 4]
premium = [1, 3, 2, 4]



The optimal location is at position [3, 3], resulting in:

Farm #	Location	Distance	Premium	Cost
0	(1, 1)	|1 - 3| + |1 - 3| = 4	1	4 * 1 = 4

1	(3, 2)	|3 - 3| + |2 - 3| = 1	3	1 * 3 = 3
2	(2, 3)	|2 - 3| + |3 - 3| = 1	2	1 * 2 = 2
3	(4, 4)	|4 - 3| + |4 - 3| = 2	4	2 * 4 = 8

The total connection cost is 17, which is the minimum possible.

Function Description

Complete the function *windFarms* in the editor with the following parameter(s):

int premium[n]: the distance multiplier for the cost to connect
int x[n]: *x* coordinates of the wind farms
int y[n]: *y* coordinates of the wind farms

Returns

int: the minimum cost to connect the wind farms

Constraints

- $1 \le n \le 10^3$
- $1 \le x[i], y[i] \le 10^4$
- $1 \le premium[i] \le 50$

▼ INPUT FORMAT FOR CUSTOM TESTING

The first line contains an integer *n*, the size of the array *premium*.
The next *n* lines each contain an element, *premium[i],* where 0 ≤ i < n.
The next line contains an integer *n*, the size of *x[]*.
The next *n* lines each contain an element, *x[i]*.
The next line contains an integer *n*, the size of *y[]*.
The next *n* lines each contain an element, *y[i]*.

Note: *n* is the same value in each instance.

▼ SAMPLE CASE 0

Sample Input 0

```
STDIN    Function
-----    --------
3    →  premium[] size n = 3
1    →  premium = [1, 1, 1]
1
1
3    →  x[] size n = 3
2    →  x = [2, 3, 5]
3
5
3    →  y[] size n = 3
1    →  y = [1, 1, 1]
1
1
```

Sample Output 0

```
3
```

Explanation 0



Locate the controller at farm 1.

Farm #	Location	Distance	Premium	Cost
0	(1, 1)	|1 - 3| + |1 - 1| = 1	1	1 * 1 = 1
1	(3, 1)	|3 - 3| + |1 - 1| = 0	1	0 * 1 = 0

2	(5, 1)	|5 - 3| + |1 - 1| = 2	1	2 * 1 = 2

▼ SAMPLE CASE 1

Sample Input 1

```
STDIN    Function
-----    --------
2    →  premium[] size n = 2
1    →  premium = [1, 10]
10
2    →  x[] size n = 2
1    →  x = [1, 2]
2
2    →  y[] size n = 2
1    →  y = [1, 2]
2
```

Sample Output 1

```
2
```

Explanation 1



The sum of the distances to a center at (1, 1), (1, 2), (2, 2), or (2, 1) is 2. Since the premium to connect farm 1 is 10, it is best to locate at position (2, 2) for a cost of 2 * 1 + 0 * 10 = 2.

▼ SAMPLE CASE 2

Sample Input 2

```
STDIN    Function
-----    --------
3    →  premium[] size n = 3
1    →  premium = [1, 1, 1]
1
1
3    →  x[] size n = 3
5    →  x = [5, 2, 3]
2
3
3    →  y[] size n = 3
3    →  y = [3, 4, 7]
4
7
```

Sample Output 2

```
7
```

Explanation 2



The optimal location is (3, 4) for a cost of 3 + 1 + 3 = 7.

Interviewer guidelines

▼ SOLUTION

Skills: Loops and counters, I/O

The cost can be calculated for x and y coordinates separately. The function examines each possible x and y coordinate for the control center separately (from 1 to 10000), computes the total cost of connecting all farms for each possible coordinate, and captures the minimum cost found. The ultimate minimum cost is the summation of these minimum costs for x and y coordinates separately.

Optimal Solution

```
def windFarms(premium, x, y):
    minCostX = 10**10
    n = len(x)

    for cx in range(1, 10001):
        cost = 0
        for i in range(n):
            cost += premium[i] * abs(cx - x[i])

        minCostX = min(minCostX, cost)

    minCostY = 10**10
    for cy in range(1, 10001):
        cost = 0
        for i in range(n):
            cost += premium[i] * abs(cy - y[i])

        minCostY = min(minCostY, cost)

    return minCostX + minCostY
```

▼ **COMPLEXITY ANALYSIS**

Time Complexity - O(n)

The universe of x and y values are tested against 10000 values.

Space Complexity - O(1)

Constant space is required regardless of n.

Candidate's Solution

Language used: **Java 8**

```java
import java.io.*;
import java.math.*;
import java.security.*;
import java.text.*;
import java.util.*;
import java.util.concurrent.*;
import java.util.function.*;
import java.util.regex.*;
import java.util.stream.*;
import static java.util.stream.Collectors.joining;
import static java.util.stream.Collectors.toList;


class Result {

    /*
     * Complete the 'windFarms' function below.
     *
     * The function is expected to return an INTEGER.
     * The function accepts following parameters:
     *  1. INTEGER_ARRAY premium
     *  2. INTEGER_ARRAY x
     *  3. INTEGER_ARRAY y
     */

    public static int windFarms(List<Integer> premium, List<Integer> x, List<Integer> y) {
    // Write your code here
    int cx=weightedMedium(x,premium);
    int cy=weightedMedium(y,premium);

    long cost=0;

    for(int i=0;i<x.size();i++)
    {
        cost +=(long)premium.get(i)* (Math.abs(x.get(i)-cx)+Math.abs(y.get(i)-cy));
    }

    return (int) cost;


    }
```

```java

    private static int weightedMedium(List<Integer> coord,List<Integer> weight)
    {
        int n=coord.size();
        List<int[]> list=new ArrayList<>();
        for(int i=0;i<n;i++)
        {
            list.add(new int[]{coord.get(i),weight.get(i)});
        }

        list.sort(Comparator.comparingInt(a-> a[0]));

        int total=weight.stream().mapToInt(i->i).sum();

        int sum=0;

        for(int[] p:list)
        {
            sum +=p[1];
            if(sum*2 >=total)
            {
                return p[0];
            }
        }

        return 0;

    }

}

public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int premiumCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> premium = IntStream.range(0, premiumCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
```

```
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int xCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> x = IntStream.range(0, xCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int yCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> y = IntStream.range(0, yCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int result = Result.windFarms(premium, x, y);

        bufferedWriter.write(String.valueOf(result));
        bufferedWriter.newLine();

        bufferedReader.close();
        bufferedWriter.close();
    }
}

```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
TestCase 0	Easy	Sample	Success	1	0.1301 sec	31.1 KB
TestCase 1	Easy	Sample	Success	1	0.1336 sec	32.1 KB
TestCase 2	Easy	Sample	Success	1	0.1203 sec	31.8 KB
TestCase 3	Easy	Sample	Success	2	0.118 sec	32.3 KB
TestCase 4	Easy	Hidden	Success	2	0.1293 sec	32.1 KB
TestCase 5	Easy	Hidden	Success	2	0.1215 sec	32 KB
TestCase 6	Medium	Sample	Success	6	0.1164 sec	32.5 KB
TestCase 7	Medium	Hidden	Success	6	0.1369 sec	32.5 KB
TestCase 8	Medium	Hidden	Success	6	0.1358 sec	32.5 KB
TestCase 9	Hard	Hidden	Success	12	0.1419 sec	34.9 KB
TestCase 10	Hard	Hidden	Success	12	0.1368 sec	36 KB
TestCase 11	Hard	Hidden	Success	12	0.1551 sec	34.8 KB

TestCase 12	Hard	Hidden	Success	12	0.1542 sec	35.4 KB

No comments.

7. Java: Optimized Sequential Video Watching

Correct

Coding Medium Greedy Java

Question description

A learner is given a sequential playlist of *n* videos to enhance their knowledge. Implement a function to calculate the minimum time required to complete a total of *m* viewings while adhering to the platform's constraints.

System Constraints

- Sequential Viewing:
  - The learner must watch videos in the order they appear in the playlist.
  - To watch a video at index *i*, the learner must first watch all videos from index 0 to *i-1* at least once.
- Initial Full Viewing:
  - To view any video at index *i* for the first time, the learner must spend *firstWatch[i] + repeatWatch[i]* minutes. This ensures a complete understanding of the video.
- Subsequent Viewings:
  - For subsequent viewings of a video at index *i*, the learner spends only *repeatWatch[i]* minutes.
  - At any time, they can rewatch any video they have already watched.
- Minimum Total Watch Count:
  - The learner must achieve at least *m* total viewings across all videos.
  - Videos can be rewatched as desired, and not all videos need to be watched equally.

Return the minimum time required to complete *m* viewings of videos while following these constraints.

Example

If $n = 4$, $m = 4$, *firstWatch* = [1, 5, 9, 11], and *repeatWatch* = [2, 7, 10, 11], the optimal strategy is as follows:

- The learner watches the 0th video for the first time, spending *firstWatch*[0] + *repeatWatch*[0] = 1 + 2 = 3 minutes.
- The learner then rewatches the 0th video 3 more times in, spending *repeatWatch*[0]*3 = 2 * 3 = 6 minutes.
- The learner has successfully completed 4 viewings. Thus, the total time required is 3 + 6 = 9 minutes, and 9 is returned.

Function Description

Complete the function *findMinMinutes* in the editor below.

Function Parameters

int m: the total number of video viewings to complete

int firstWatch[n]: the minutes required to watch each video the first time

int repeatWatch[n]: the minutes required to rewatch each video

Returns

long: the minimum minutes required for the learner to reach their target number of viewings

Constraints

- $1 \le n \le 10^5$
- $1 \le m \le 10^9$
- $1 \le firstWatch[i], repeatWatch[i] \le 10^9$

▼ INPUT FORMAT FOR CUSTOM TESTING

The first line contains an integer, *m*.
The next line contains an integer, *n,* the size of *firstWatch*.
Each of the next *n* lines contains an integer, *firstWatch[i]*.
The next line contains an integer, *n,* the size of *repeatWatch*.
Each of the next *n* lines contains an integer, *repeatWatch[i]*.

▼ SAMPLE CASE 0

Sample Input 0

```
STDIN    FUNCTION
-----    --------
5        m = 5
3        firstWatch[] size n = 3
6        firstWatch = [6, 8, 9]
8
9
3        repeatWatch[] size n = 3
4        repeatWatch = [4, 2, 10]
2
10
```

Sample Output 0

```
26
```

Explanation

The goal is to complete 5 viewings. One optimal strategy is:

- The learner watches the 0th video for the first time, so the time required is *firstWatch*[0] + *repeatWatch*[0] = 6 + 4 = 10 minutes.
- The learner watches the 1st video for the first time, so the time required is *firstWatch*[1] + *repeatWatch*[1] = 8 + 2 = 10 minutes.
- The learner then rewatches the 1st video 3 times. So the time taken = *repeatWatch*[1]*3 = 2 * 3 = 6 minutes.
- The total time required to complete 5 video viewings is 10 + 10 + 6 = 26 minutes.

▼ SAMPLE CASE 1

Sample Input 1

```
STDIN     FUNCTION
-----     --------
6         m = 6
5         firstWatch[] size n = 5
2         firstWatch = [2, 3, 7, 8, 4]
3
7
8
4
5         repeatWatch[] size n = 5
3         repeatWatch = [3, 6, 8, 7, 6]
6
8
```

```
7
6
```

Sample Output 1

```
20
```

Explanation

The goal is to complete 6 viewings. One optimal strategy is:

- The learner watches the 0th video for the first time in *firstWatch*[0] + *repeatWatch[0]* = 2 + 3 = 5 minutes.
- The learner then rewatches the 0th video 5 times in *repeatWatch[0]**5 = 3 * 5 = 15 minutes.
- The total time required to complete 6 viewings is 5 + 15 = 20 minutes.

Interviewer guidelines

▼ SOLUTION

Description

The greedy solution suggests that, at any given index, if the time to watch the video is less than at any other index between i+1 and n, the minimum total time will be the sum of the watch time up to index i-1, plus the repeat time of the ith video multiplied by (m-i).

Solution

```
class Result {

    /*
     * Complete the 'findMinMinutes' function below.
     *
     * The function is expected to return a LONG_INTEGER.
     * The function accepts following parameters:
     *  1. INTEGER m
     *  2. INTEGER_ARRAY firstWatch
     *  3. INTEGER_ARRAY repeatWatch
     */

    public static long findMinMinutes(int m, List<Integer> firstWatch, List<Integer> repeatWatch) {
        long minMinutes = Long.MAX_VALUE;
        long cur = 0;
        int n = firstWatch.size();

        for (int i = 0; i < Math.min(n,m); i++) {
            int a = firstWatch.get(i);
```

```
            int b = repeatWatch.get(i);

            minMinutes = Math.min(minMinutes, cur + ((long) (m - i) * b) + a);

            cur += a + b;
        }
        return minMinutes;
    }

}
```

▼ COMPLEXITY

Time Complexity - O(n)

The algorithm iterates through each number in *firstWatch* and *repeatWatch* exactly once, performing constant-time checks and arithmetic operations in each iteration. Thus, the time complexity is O(n), where *n* is the length of *firstWatch*.

Space Complexity - O(1)

Space usage is constant, only utilizing a fixed number of variables (*mn, cur,* etc.) that do not scale with the length of *firstWatch*. Therefore, the space complexity is O(1).

Candidate's Solution

Language used: **Java 8**

```
import java.io.*;
import java.math.*;
import java.security.*;
import java.text.*;
import java.util.*;
import java.util.concurrent.*;
import java.util.function.*;
import java.util.regex.*;
import java.util.stream.*;
import static java.util.stream.Collectors.joining;
import static java.util.stream.Collectors.toList;


import java.io.*;
import java.math.*;
import java.security.*;
import java.text.*;
import java.util.*;
```

```java
import java.util.concurrent.*;
import java.util.function.*;
import java.util.regex.*;
import java.util.stream.*;

import javax.swing.text.View;

import static java.util.stream.Collectors.joining;
import static java.util.stream.Collectors.toList;



class Result {

    /*
     * Complete the 'findMinMinutes' function below.
     *
     * The function is expected to return a LONG_INTEGER.
     * The function accepts following parameters:
     *  1. INTEGER m
     *  2. INTEGER_ARRAY firstWatch
     *  3. INTEGER_ARRAY repeatWatch
     */

    public static long findMinMinutes(int m, List<Integer> firstWatch, List<Integer> repeatWatch) {

        long totalTime=0;
        long view=0;
        long ans=Long.MAX_VALUE;
        int minRepeat=Integer.MAX_VALUE;

        for(int i=0;i<firstWatch.size();i++)
        {
            totalTime +=firstWatch.get(i) +repeatWatch.get(i);
            view++;
            minRepeat=Math.min(minRepeat, repeatWatch.get(i));

            if(view <=m)
            {
                long total=totalTime+ (long)(m-view)* minRepeat;
                ans = Math.min(ans, total);
            // }else{
            //     long extra=(m-view)* (long)minRepeat;
            //     ans=Math.min(ans, totalTime* extra);
            // }
```

```
            }
        }
        return ans;
    }

}

public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int m = Integer.parseInt(bufferedReader.readLine().trim());

        int firstWatchCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> firstWatch = IntStream.range(0, firstWatchCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int repeatWatchCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> repeatWatch = IntStream.range(0, repeatWatchCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

```

```
        long result = Result.findMinMinutes(m, firstWatch, repeatWatch);

        bufferedWriter.write(String.valueOf(result));
        bufferedWriter.newLine();

        bufferedReader.close();
        bufferedWriter.close();
    }
}

public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int m = Integer.parseInt(bufferedReader.readLine().trim());

        int firstWatchCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> firstWatch = IntStream.range(0, firstWatchCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int repeatWatchCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> repeatWatch = IntStream.range(0, repeatWatchCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
```

```
            .map(Integer::parseInt)
            .collect(toList());

        long result = Result.findMinMinutes(m, firstWatch, repeatWatch);

        bufferedWriter.write(String.valueOf(result));
        bufferedWriter.newLine();

        bufferedReader.close();
        bufferedWriter.close();
    }
}

```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
Testcase 2	Easy	Sample	Success	1	0.1079 sec	31.9 KB
Testcase 0	Easy	Sample	Success	1	0.1059 sec	31.3 KB
Testcase 1	Easy	Sample	Success	1	0.1332 sec	31.8 KB
Testcase 3	Easy	Hidden	Success	4	0.1148 sec	31.9 KB
Testcase 4	Easy	Hidden	Success	4	0.1458 sec	31.8 KB
Testcase 5	Easy	Hidden	Success	4	0.1975 sec	35.8 KB
Testcase 6	Medium	Hidden	Success	5	0.3717 sec	91.8 KB
Testcase 7	Medium	Hidden	Success	5	0.5319 sec	175 KB

Testcase 8	Medium	Hidden	Success	5	0.5911 sec	177 KB
Testcase 9	Medium	Hidden	Success	5	0.4872 sec	175 KB
Testcase 10	Medium	Hidden	Success	5	0.4918 sec	176 KB
Testcase 11	Medium	Hidden	Success	5	0.4629 sec	164 KB
Testcase 12	Hard	Hidden	Success	10	0.3353 sec	96.1 KB
Testcase 13	Hard	Hidden	Success	10	0.4187 sec	165 KB
Testcase 14	Hard	Hidden	Success	10	0.1187 sec	31.5 KB

No comments.