97.1
Pass

Priyanka Choure

PDF generated at: 16 Feb 2026 11:48:19 UTC

View this report on HackerRank

Score

97.1% • 170.0 / 175
scored in eClerx - Java Coding Test - 3+ Years New in 35 min 12 sec on 16 Feb 2026 15:46:34 IST

Candidate Information

Email	priyankachoure122496@gmail.com
Test	eClerx - Java Coding Test - 3+ Years New
Candidate Packet	View
Taken on	16 Feb 2026 15:46:34 IST
Time taken	35 min 12 sec/ 90 min
Work Experience	> 5 years
Invited by	Nancy
Invited on	13 Feb 2026 10:48:59 IST

Skill Distribution

No.	Skill	Score
1	Spring Boot Advanced	100%

2	Spring Boot Intermediate	66%
3	Problem Solving Intermediate	100%
4	Java Intermediate	100%

Tags Distribution

Spring Boot	80%	Hard	100%
TDD	100%	Medium	96%
Exception Handling	0%	Aspect-Oriented Programming	0%
Pointers	100%	Java	100%
Multithreading	100%	Interfaces	100%
OOP	100%		

Questions

Spring Boot (Advanced) • 20 / 25

No.	Question	Skill	Score	Code Quality	Time Taken	Status
1	Specification Multiple Choice	Spring Boot (Advanced)	5/5	-	1 min 32 sec	✓

2	Response Multiple Choice	Spring Boot (Advanced)	5/5	-	3 min	✓
3	Endpoint Security Multiple Choice	Spring Boot (Intermediate)	5/5	-	51 sec	✓
4	CSRF Multiple Choice	Spring Boot (Intermediate)	5/5	-	1 min 56 sec	✓
5	Predict the Output Multiple Choice	Spring Boot (Intermediate)	0/5	-	3 min 49 sec	✗

Problem Solving (Intermediate) • 75 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status
6	Quiz Competition Coding	Problem Solving (Intermediate)	75/75	-	12 min 11 sec	✓

Java (Intermediate) • 75 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status
7	Java: Safe Cracking Coding	Java (Intermediate)	75/75	-	11 min 17 sec	✓

1. Specification

Correct

Multiple Choice | Spring Boot | Hard

Question description

Which of the following options can be used for dynamic jpa queries with spring-data-jpa repositories?

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ PreparedStatement
- ● Specification ✓
- ○ Criteria
- ○ Query

No comments.

2. Response

Correct

Multiple Choice | Hard | Spring Boot | TDD

Question description

Which response will cause the following test case to fail?

```
@Test
   @DisplayName("Filter Price Check 3")
   public void FilterPriceCheck3() throws Exception {
      mockMvc.perform(get("/filter/price/150/500"))
            .andDo(print())
            .andExpect(jsonPath("$[*].product", containsInAnyOrder("Product 1", "Product 2" , "Produc
t 5")))
   }
```

Candidate's Solution

Options: (Expected answer indicated with a tick)

- [ ] [{"product" : "Product 5"} , {"product" : "Product 1"}, {"product" : "Product 2"}]
- [ ] [{"product" : "Product 5"} , {"product" : "Product 2"}, {"product" : "Product 1"}]
- [ ] [{"product" : "Product 1"} , {"product" : "Product 2"}, {"product" : "Product 5"}]
- [x] **[{"product" : "product 5"} , {"product" : "product 2"}, {"product" : "product 1"}]**

No comments.

3. Endpoint Security

Correct

Multiple Choice | Spring Boot | Medium

Question description

In Spring Boot Security, the option to enable secure endpoints with @PreAuthorize annotation is:

Interviewer guidelines

@EnableGlobalMethodSecurity by default doesn't enable this feature. To enable this prePostEnabled=true value must be set

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ Configuration class annotated with @EnableGlobalMethodSecurity
- ○ Configuration class annotated with @EnableGlobalMethodSecurity(securedEnabled = true)
- ● **Configuration class annotated with @EnableGlobalMethodSecurity(prePostEnabled = true)** ✓
- ○ None above

No comments.

4. CSRF

Correct

Multiple Choice | Spring Boot | Medium

Question description

Which Java Spring-based code segment correctly configures CSRF?

Interviewer guidelines

CSRF Protection makes sure that server is not bombarded with unwanted calls. Spring Security enables some features by default like CSRF and Form based authentication.

Candidate's Solution

Options: (Expected answer indicated with a tick)

- private void manage(HttpSecurity http) {   http.csrf().allowed() }
- private void manage(HttpSecurity http) {   http.csrf() }
- private void manage(HttpSecurity http) {   http.csrf().enable() }
- ✓ ** None of the above. CSRF is configured by default when Spring Security Dependency is added. **

No comments.

5. Predict the Output

Incorrect

Multiple Choice | Medium | Exception Handling | Spring Boot | Aspect-Oriented Programming

Question description

Consider the following Snippet and predict the output.

The following API is triggered: http://localhost:8080/add/employee?eId=123&fName=Ravi&lastName=Shekhar

```
@Autowired
private EService eService;

@RequestMapping(value = "/add/employee", method = RequestMethod.GET)
public com.model.Employee add(@RequestParam("eId") String eId, @RequestParam("fName") Strin
g fName, @RequestParam("lastName") String lastName)
{
   return eService.createEmployee(eId, fName, lastName);
}

@Aspect
@Component
public class EServiceAspect
{
   @After(value = "execution(* com.random.service.EService.*(..)) && args(eId, fName, lastName)")
   public void afterAdvice(JoinPoint joinPoint, String eId, String fName, String lastName) {
      System.out.println("After method:" + joinPoint.getSignature());
      System.out.println("Creating Employee with first name - " + fName+ ", second name - " + lastNa
me+ " and id - " + eId);
   }
}
```

Candidate's Solution

Options: (Expected answer indicated with a tick)

After method : com.test.model.Employee addEmployee(String,String,String) Creating Employee with first name - Ravi , second name - Shekhar and id - 123

** After method : com.test.model.Employee addEmployee(string,string,string) Creating Employee with first name - Ravi , second name - Shekhar and id - 123   **

After method : com.test.model.Employee addEmployee(empId,firstName,secondName) Creating Employee with first name - Ravi , second name - Shekhar and id - 123

After method : com.test.model.Employee addEmployee(String,String,String) Creating Employee with first name - Shekhar, second name - Ravi and id - 123

No comments.

6. Quiz Competition

Correct

Coding Medium Pointers

Question description

A class has students with various talents, each represented by an integer from 1 to *talentsCount*. You need to form teams for a quiz competition, where each team must have at least one member with each talent.

Teams must be formed from consecutive students in the array. For each possible starting position, determine the minimum number of students needed to form a valid team. If it is not possible to form a team with all talents from a particular starting position, return -1 for that position.

Example

talentsCount = 3

talent = [1, 2, 3, 2, 1]

- Starting at position 1: [1, 2, 3] includes all talents, minimum size = 3
- Starting at position 2: [2, 3, 2, 1] is the smallest subarray with all talents, minimum size = 4
- Starting at position 3: [3, 2, 1] includes all talents, minimum size = 3
- Starting at positions 4 and 5: Cannot form a team with all talents, return -1

The result is [3, 4, 3, -1, -1].

Function Description

Complete the function *teamSize* in the editor with the following parameter(s):

int talent[n]: the students' talents

int talentsCount : the number of talents represented numbered from 1 to *talentsCount*

Returns

int[n]: at each index, the minimum size subarray required, or -1 if an appropriate subarray does not exist

Constraints

- $1 \le n, talentsCount \le 10^5$
- $1 \le talent[i] \le talentsCount$

▼ INPUT FORMAT FOR CUSTOM TESTING

The first line contains an integer, *n*, the number of elements in *talent*.

Each line *i* of the *n* subsequent lines (where $0 \le i < n$) contains an integer, *talent[i]*.

The next line contains the integer *talentCount*.

▼ SAMPLE CASE 0

Sample Input For Custom Testing

```
STDIN   Function
-----   --------
8       talent[] size n = 8
1       talent = [1, 1, 2, 2, 3, 1, 3, 2]
1
2
2
3
1
3
2
3       talentsCount = 3
```

Sample Output

```
5
4
4
3
4
3
-1
-1
```

Explanation

The shortest subarrays for each position:

Beginning at the first position: [1, 1, 2, 2, 3] (length 5)

Second position: [1, 2, 2, 3] (length 4)

Third position: [2, 2, 3, 1] (length 4)

Fourth position: [2, 3, 1] (length 3)

Fifth position: [3, 1, 3, 2] (length 4)

Sixth position: [1, 3, 2] (length 3)

No further subarrays will have 3 elements.

▼ SAMPLE CASE 1

Sample Input For Custom Testing

```
STDIN   Function
-----   --------
5       talent[] size n = 5
1       talent = [1, 1, 1, 1, 1]
```

```
1
1
1
1
1      talentsCount = 1
```

Sample Output

```
1
1
1
1
1
```

Explanation

Since there is only 1 type of talent, any 1 person can form a team.

▼ SAMPLE CASE 2

Sample Input For Custom Testing

```
STDIN   Function
-----   --------
9       talent[] size n = 9
7       talent = [7, 5, 3, 4, 6, 1, 7, 2, 4]
5
3
4
6
1
7
2
4
7       talentsCount  7
```

Sample Output

```
8
7
-1
-1
-1
-1
-1
-1
-1
```

Explanation

There have to be at least *7* elements in any subarray to have one from each talent. The shortest subarrays at each position are:

Beginning at the first position: [7, 5, 3, 4, 6, 1, 7, 2] (length 8)

Second position: [5, 3, 4, 6, 1, 7, 2] (length 7)

No further subarrays will have 7 elements.

Interviewer guidelines

▼ SOLUTION

This can be solved using two-pointer technique. For a particular left index (L), we move the right index (R) forward until we have k distinct elements, then once we get it, we can move L forward. Each element will be traversed at most two times.

Time Complexity: O(n) or O(nLogn) (with set/map).

C++ Solution:

```
int f[100005];

vector<int> teamSize(vector<int> talent, int talentsCount) {
    int k = talentsCount;
    int n = talent.size();
    assert(n>=1&&n<=100000);
    assert(k>=1&&k<=n);
    for(int i=0;i<n;i++)
    {
        assert(talent[i]<=k&&talent[i]>=1);
    }
    int cnt = 0;
    int j = 0;
    vector<int> ans(n);
    for(int i=0;i<n;i++)
    {
        int x = talent[i];
        f[x]++;
        if(f[x]==1)
            cnt++;
```

```
        while(cnt==k&&j<=i)
        {
            ans[j] = i - j + 1;
            int y = talent[j];
            f[y]--;
            if(f[y]==0)
                cnt--;
            j++;
        }
    }
    while(j<n)
        ans[j++] = -1;
    return ans;
}
```

Candidate's Solution

Language used: **Java 8**

```
import java.io.*;
import java.math.*;
import java.security.*;
import java.text.*;
import java.util.*;
import java.util.concurrent.*;
import java.util.function.*;
import java.util.regex.*;
import java.util.stream.*;
import static java.util.stream.Collectors.joining;
import static java.util.stream.Collectors.toList;


class Result {

    /*
     * Complete the 'teamSize' function below.
     *
     * The function is expected to return an INTEGER_ARRAY.
     * The function accepts following parameters:
     *  1. INTEGER_ARRAY talent
     *  2. INTEGER talentsCount
     */

```

```java
    public static List<Integer> teamSize(List<Integer> talent, int talentsCount) {
    // Write your code here
    int n = talent.size();
    List<Integer> result = new ArrayList<>(Collections.nCopies(n, -1));

    int[] freq = new int[talentsCount+1];
    int distinct=0;
    int right =0;

    for(int left =0; left <n; left++)
    {
        while(right<n && distinct < talentsCount)
        {
            int t = talent.get(right);
            if(freq[t] == 0){ distinct++; }

            freq[t]++;
            right++;
        }

        if(distinct == talentsCount){
            result.set(left, right-left);
        }
        else{
            break;
        }
        int removeTalent = talent.get(left);
        freq[removeTalent]--;

        if(freq[removeTalent] == 0){
            distinct--;
        }
    }

    return result;

    }

}

public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
```

```
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int talentCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> talent = IntStream.range(0, talentCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int talentsCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> result = Result.teamSize(talent, talentsCount);

        bufferedWriter.write(
            result.stream()
                .map(Object::toString)
                .collect(joining("\n"))
            + "\n"
        );

        bufferedReader.close();
        bufferedWriter.close();
    }
}

```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
TestCase 0	Easy	Sample	Success	1	0.1057 sec	31.9 KB
TestCase 1	Easy	Sample	Success	1	0.16 sec	31.8 KB

TestCase 2	Easy	Sample	Success	1	0.1032 sec	31.8 KB
TestCase 3	Easy	Hidden	Success	3	0.1544 sec	39.1 KB
TestCase 4	Easy	Hidden	Success	3	0.2508 sec	39.5 KB
TestCase 5	Easy	Hidden	Success	3	0.1676 sec	39 KB
TestCase 6	Easy	Hidden	Success	8	0.3813 sec	115 KB
TestCase 7	Easy	Hidden	Success	8	0.3436 sec	113 KB
TestCase 8	Easy	Hidden	Success	8	0.42 sec	114 KB
TestCase 9	Easy	Hidden	Success	8	0.3997 sec	113 KB
TestCase 10	Easy	Hidden	Success	8	0.3825 sec	94.3 KB
TestCase 11	Easy	Hidden	Success	8	0.4298 sec	116 KB
TestCase 12	Easy	Hidden	Success	8	0.3233 sec	108 KB
TestCase 13	Easy	Hidden	Success	7	0.3565 sec	79.3 KB

No comments.

7. Java: Safe Cracking

Correct

Coding Medium Java Multithreading Interfaces OOP

Question description

Implement a *SafeCracking* class that executes a sequence of operations to rob a bank vault. The class should coordinate with an *IActions* interface to perform the robbery in the correct order.

Your implementation must follow a specific sequence of operations:

1. First, unlock the vault door.
2. Then, simultaneously determine the safe deposit box number and hack its PIN.
3. Finally, open the safe deposit box using the obtained information.

Method to Implement

```
void rob(IActions actions)
```

This method should coordinate with the provided *IActions* object to execute the following steps in order:

1. Call *unlockTheDoor()* to get the door passcode string.
2. Concurrently call both:
   - *hackSecretPin(passcodeOfDoor)* to get the safe deposit box PIN
   - *figureOutSafeDepositBoxNumber(passcodeOfDoor)* to get the safe deposit box number
3. Call *openSafeDepositLock(safeDepositBoxNumber, safetyDepositBoxPin)* to complete the robbery.

Note: The concurrent operations in step 2 are critical for the time-sensitive nature of the robbery scenario.

Example

The system will validate your implementation by checking if the operations are called in the correct order with the proper parameters. A successful implementation will output:

```
true
```

This indicates that all operations were performed correctly, and the robbery was successful. If the operations are performed in the wrong order or with incorrect parameters, the output will be *false*.

Constraints

- *1* ≤ lengths of *passcodeOfDoor*, *safeDespositBoxNumber, safetyDepositBoxPin ≤ 10*

▼ INPUT FORMAT FOR CUSTOM TESTING

There is no input passed from stdin.

▼ SAMPLE CASE 0

Sample Output

```
true
```

Explanation

- stdout shows *true* if it is a successful robbery otherwise, it shows *false.*

Interviewer guidelines

Java 8 and Java 15 Solution

```
class SafeCracking {
    public void rob(IActions actions) throws InterruptedException, ExecutionException{
        ExecutorService threadPool = Executors.newFixedThreadPool(2);
        String passcodeOfDoor = actions.unlockTheDoor();
        Future<String> hackSecretPinTask = threadPool.submit(() -> actions.hackSecretPin(passcodeOf
Door));
        Future<String> figureOutSafeDepositBoxNumberTask = threadPool.submit(() -> actions.figureO
utSafeDepositBoxNumber(passcodeOfDoor));

        String safeDespositBoxNumber = figureOutSafeDepositBoxNumberTask.get();
        String safeDepositBoxPin = hackSecretPinTask.get();

        actions.openSafeDepositLock(safeDespositBoxNumber, safeDepositBoxPin);
        threadPool.shutdown();
    }
}
```

Candidate's Solution

Language used: **Java 8**

```java
import java.io.*;
import java.util.*;
import java.util.concurrent.ExecutionException;
import java.util.concurrent.ExecutorService;
import java.util.concurrent.Executors;
import java.util.concurrent.Future;

interface IActions{
    public String unlockTheDoor();
    public String hackSecretPin(final String passcodeOfDoor) throws InterruptedException, ExecutionException;
    public String figureOutSafeDepositBoxNumber(final String passcodeOfDoor) throws InterruptedException, ExecutionException;
    public void openSafeDepositLock(final String safetyDespositBoxNumber, final String safetyDepositBoxPin);
    public boolean getRobberyVerdict();
}


class SafeCracking {
    public void rob(IActions actions) throws InterruptedException, ExecutionException{

        String passCodeOfDoor = actions.unlockTheDoor();
        ExecutorService executor = Executors.newFixedThreadPool(2);

        Future<String> pinFuture = executor.submit(() -> actions.hackSecretPin(passCodeOfDoor));

        Future<String> boxNumberFuture = executor.submit(() -> actions.figureOutSafeDepositBoxNumber(passCodeOfDoor));

        String safetyDepositBoxPin =pinFuture.get();
        String safetyDepositeBoxNumber = boxNumberFuture.get();

        executor.shutdown();

        actions.openSafeDepositLock(safetyDepositeBoxNumber, safetyDepositBoxPin);
    }
}
public class Solution {
    public static void main(String[] args) throws InterruptedException, ExecutionException{
         IActions actions = Actions.actions;
         new SafeCracking().rob(actions);
```

```
        System.out.println(actions.getRobberyVerdict());
    }
}

class Actions implements IActions{
    public static IActions actions = new Actions();

    private String passcodeOfDoor;
    private String safetyBoxNumber;
    private String pinOfSafetyBox;

    private String passedPasscodeOfDoor;
    private String passedSafetyBoxNumber;
    private String passedPinOfSafetyBox;

    private Actions() {
        this.passcodeOfDoor = randomStringGenerator(10);
        this.safetyBoxNumber = randomStringGenerator(10);
        this.pinOfSafetyBox = randomStringGenerator(10);
    }

    private String randomStringGenerator(int targetStringLength) {
        int leftLimit = 48; // numeral '0'
        int rightLimit = 122; // letter 'z'
        Random random = new Random();

        String generatedString = random.ints(leftLimit, rightLimit + 1)
            .filter(i -> (i <= 57 || i >= 65) && (i <= 90 || i >= 97))
            .limit(targetStringLength)
            .collect(StringBuilder::new, StringBuilder::appendCodePoint, StringBuilder::append)
            .toString();

        return generatedString;
    }

    public boolean getRobberyVerdict(){
        return (passcodeOfDoor == passedPasscodeOfDoor) && (pinOfSafetyBox == passedPinOfSafetyBox)
            && (safetyBoxNumber == passedSafetyBoxNumber);
    }

    public String unlockTheDoor() {
        return this.passcodeOfDoor;
    }

```

```
    public String hackSecretPin(final String passcodeOfDoor) throws InterruptedException, ExecutionException {
        this.passedPasscodeOfDoor = passcodeOfDoor;
        Thread.sleep(2000);
        return this.pinOfSafetyBox;
    }

    public  String figureOutSafeDepositBoxNumber(final String passcodeOfDoor) throws InterruptedException, ExecutionException {
        Thread.sleep(2000);
        return this.safetyBoxNumber;
    }

    public void openSafeDepositLock(final String safetyDespositBoxNumber, final String safetyDepositBoxPin) {
        this.passedSafetyBoxNumber = safetyDespositBoxNumber;
        this.passedPinOfSafetyBox = safetyDepositBoxPin;
    }
}
```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
Testcase 0	Easy	Sample	Success	1	2.1452 sec	31.6 KB
Testcase 1	Hard	Hidden	Success	74	2.1283 sec	32 KB

No comments.