87.1
Pass

Akshay Sharma

PDF generated at: 18 Feb 2026 05:31:00 UTC

View this report on HackerRank

Score

87.1% • 152.5 / 175
scored in eClerx - Java Coding Test - 3+ Years New in 45 min 43 sec on 18 Feb 2026 10:13:02 IST

Candidate Information

Email	akshaysharma2aug1997@gmail.com
Test	eClerx - Java Coding Test - 3+ Years New
Candidate Packet	View
Taken on	18 Feb 2026 10:13:02 IST
Time taken	45 min 43 sec/ 90 min
Work Experience	5 years
Invited by	Vipul
Invited on	18 Feb 2026 09:02:35 IST

Skill Distribution

No.	Skill	Score
1	Spring Boot Advanced	0%

2	Spring Boot Intermediate	12%
3	Problem Solving Intermediate	100%
4	Java Intermediate	100%

Tags Distribution

Spring Boot	0%	Hard	0%
Spring	16%	JPA	0%
Spring Data	0%	Transactional	0%
Medium	89%	Application Properties Annotations	0%
Exception Handling	0%	Aspect-Oriented Programming	0%
Pointers	100%	Java	100%
Multithreading	100%	Interfaces	100%
OOP	100%		

Questions

Spring Boot (Advanced) • 2.5 / 25

No.	Question	Skill	Score	Code Quality	Time Taken	Status

1	Determine the Output Multiple Choice	Spring Boot (Advanced)	0/5	-	59 sec	⊗
2	Spring Data Transactional Multiple Choice	Spring Boot (Intermediate)	0/5	-	33 sec	⊗
3	Configuration Properties Multiple Choice	Spring Boot (Intermediate)	0/5	-	14 sec	⊗
4	Spring Scopes Multiple Choice	Spring Boot (Intermediate)	2.5/5	-	19 sec	✓
5	Predict the Output Multiple Choice	Spring Boot (Intermediate)	0/5	-	10 sec	⊗

Problem Solving (Intermediate) • 75 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status
6	Quiz Competition Coding	Problem Solving (Intermediate)	75/75	-	19 min 34 sec	✓

Java (Intermediate) • 75 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status

7	Java: Safe Cracking Coding	Java (Intermediate)	75/75	-	23 min 28 sec	

1. Determine the Output

Incorrect

Multiple Choice | Spring Boot | Hard

Question description

SpringQuestionApplication.java

```
package com.hackerrank.spring;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
@SpringBootApplication
public class SpringQuestionsApplication {
   public static void main(String[] args) {
      SpringApplication.run(SpringQuestionsApplication.class, args);
   }
}
```

Lie.java

```
package com.hackerrank;
import org.springframework.boot.CommandLineRunner;
import org.springframework.stereotype.Component;
@Component
public class Lie implements CommandLineRunner {
   @Override
   public void run(String... args) throws Exception {
      System.out.println("Truth is behind the lies");
      System.out.println("This is working perfectly");
      throw new Exception("Does this work?");
   }
}
```

Truth.java

```
package com.hackerrank.spring.reality;

import org.springframework.boot.CommandLineRunner;
import org.springframework.stereotype.Component;

@Component
public class Truth implements CommandLineRunner {
    @Override
    public void run(String... args) throws Exception {
        System.out.println("Truth is in your eyes");
    }
}
```

What will be printed on the console when the "SpringBootApplication" class is executed?

Interviewer guidelines

Correct Answer:

Option [A] – "Truth is in your eyes"

Explanation: Spring Boot scans only the package of the `@SpringBootApplication` class and its subpackages. `Truth` is under a subpackage and runs. `Lie` is in a parent package, so it is **not scanned** and its runner does not execute.

Incorrect Answers:

Option [B] – Multiple prints + exceptions

Explanation: `Lie` never runs, so its prints and exception do not occur.

Option [C] – Prints from Lie only

Explanation: `Truth` is discovered and executed; `Lie` is not.

Option [D] – Prints from Lie, then Truth

Explanation: `Lie` is outside the scan path and never executed.

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ Truth is in your eyes ✓

- [x] Truth is in your eyes Truth is behind the lies This is working perfectly And exception occurs and application stops
- [ ] Truth is behind the lies This is working perfectly And exception occurs and application stops
- [ ] Truth is behind the lies This is working perfectly And exception occurs containing “Does this work?” Truth is in your eyes

No comments.

2. Spring Data Transactional

Incorrect

Multiple Choice | Spring | Spring Boot | JPA | Spring Data | Transactional | Medium

Question description

Given the following code, what happens when *StudentRepsitoryTest* runs?

Lesson.java

```
@Entity
public class Lesson {
    @Id
    private Long id;
    private String name;
    private Integer courseLength;
    private Integer courseLevel;
    @JsonBackReference
    @ManyToOne(fetch = FetchType.LAZY)
    @JoinColumn(name = "student_id")
    private Student student;
```

```
    private boolean inProgress;
    //getter & setters
}
```

Student.java

```
@Entity
public class Student {
    @Id
    private Long id;
    private String name;
    private String surname;
    @JsonManagedReference
    @OneToMany(mappedBy = "student", fetch = FetchType.EAGER, cascade = {CascadeType.PERSIST,
CascadeType.REFRESH})
    private List<Lesson> lessons;
    //getter & setters
}
```

StudentRepository.java

```
@Repository
public interface StudentRepository extends JpaRepository<Student, Long>{
    //Y
    Optional<Student> findById(Long id);
}
```

LessonRepository.java

```
@Repository
public interface LessonRepository extends JpaRepository<Lesson, Long> {
}
```

StudentService.java

```
@Service
public class StudentService{
    private StudentRepository studentRepository;
    public StudentService(StudentRepository studentRepository, LessonRepository lessonRepository)
{
        this.studentRepository = studentRepository;
        this.lessonRepository = lessonRepository;
    }

    public void save(Student student) {
        studentRepository.save(student);
    }

    //other crud metods

    //X
    public void deleteStudentWithLessons(Long id) throws SQLException {
        Student student =
                studentRepository.findById(id).orElseThrow(() -> new RuntimeException("Student not foun
d"));
        List<Lesson> lessons = student.getLessons();
        lessons.stream().forEach(lesson -> lesson.setStudent(null));
        studentRepository.delete(student);

        boolean inProgress =lessons.stream()
                .map(Lesson::isInProgress)
                .filter(progress -> progress == true)
                .findFirst()
                .orElseGet(() -> false);
        if (inProgress) {
            throw new SQLException("Cannot delete all Lessons. There are lessons in progress state");
        }
        lessonRepository.deleteAll(lessons);
    }
}
```

StudentRepositoryTest.java

```
@SpringBootTest
class StudentRepositoryTest {
    @Autowired
    StudentRepository studentRepository;
    @Autowired
```

```
    StudentService studentService;
    @Autowired
    LessonRepository lessonRepository;
    Student student;
    @BeforeEach
    public void init() {
        student = Student.builder().name("Jorn").surname("Deynhoven").build();
        studentRepository.save(student);
        lessonRepository.saveAll(List.of(
                Lesson.builder().name("Music").courseLength(10).student(student).courseLevel(123).build
(),
                Lesson.builder().name("Art").courseLength(20).courseLevel(123).student(student).build(),
                Lesson.builder().name("Trance").courseLength(30).courseLevel(123).student(student).inPro
gress(true).build()
        ));
    }
    @Test
    void deleteStudentWithLessonsTest() throws SQLException {
        studentService.deleteStudentWithLessons(student.getId());
    }
}
```

Interviewer guidelines

Candidate has to know how to use spring data in any spring application which uses spring data. If an entity wanted to remove from database without removing the child attributes, then first relation between them should be removed. Without doing this, spring will throw DataIntegrityViolationException to keep database consistent. To achive that without changing existing code, we need to annotate deleteStudentWithLessons(Long id) method with @Transactional annotation. With this spring will update the database states of child entities. In this case it will update Lesson attributes to have student as null. Then student will be removed in the next line.

After this there is a inProgress check for existing lessons. it will throw SQLException which is a checked exception. @Transactional annotation in default only rolls back for unchecked exception such as RuntimeException. So all changes will be reflected to database.

Option A and E is right. More info can be found in https://docs.spring.io/spring-framework/docs/current/javadoc-api/org/springframework/transaction/annotation/Transactional.html

Candidate's Solution

Options: (Expected answer indicated with a tick)

- [ ] It will try to delete the student then the DataIntegrityViolationException will be thrown.
- [x] It will delete the student successfully then an SQLException will be thrown with the message "Cannot delete all Lessons. There are lessons in progress state".
- [x] If @Transactional annotation is put in place of X (StudentServer.java), after saving the student and lessons, it will update lessons and remove the student. Then it will throw an SQLException and all database changes will be rolled back.
- [ ] It will throw a RuntimeException with the message "Student not found".
- [x] If @Transactional annotation is put in place of X (StudentServer.java), after saving the student and lessons, it will update lessons and remove the student. Then it will throw an SQLException.

No comments.

3. Configuration Properties

Incorrect

Multiple Choice | Spring | Spring Boot | Application Properties Annotations | Medium

Question description

An *application.properties* file contains the following properties:

```
app.prop1 = value1
app.prop2 = value2
```

You decided to create a class to hold this configuration. To protect it, the class is defined as final.

```
@Configuration
@ConfigurationProperties(prefix = "app")
public final class AppConfiguration {
  String prop1;
  String prop2;

  public String getProp1() {
    return prop1;
  }

  public void setProp1(String prop1) {
    this.prop1 = prop1;
  }

  public String getProp2() {
    return prop2;
  }

  public void setProp2(String prop2) {
    this.prop2 = prop2;
  }
}
```

What is the result of running the Spring application with this class?

Interviewer guidelines

Spring creates dynamic proxies for classes annotated with `@Configuration` classes. Spring uses CGLIB to extend your class to create proxy. Hence, configuration classes cannot be final. When running the code Spring throws `BeanDefinitionParsingException` and this is the correct option.

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ The application runs, the configuration bean is created. and the properties are initialized correctly (prop1=value1, prop2=value2).
- ○ The application runs, and a configuration bean is created, but properties are set to null (prop1=null, prop2=null).
- ○ A BeanDefinitionParsingException is thrown because the @Configuration bean cannot be marked as final.
- ● ** An IllegalStateException is thrown because the @Configuration bean cannot have an @ConfigurationProperties annotation. **
- ○ A NoSuchMethodException is thrown because the @Configuration bean needs a default constructor.

No comments.

4. Spring Scopes

Partially correct

Multiple Choice | Medium | Spring

Question description

Which of the following statements is/are true about @Scope("request") and @Scope("prototype") annotations?

Candidate's Solution

Options: (Expected answer indicated with a tick)

- [ ] Both are used to define the scope of spring beans.
- [x] **@Scope("request") creates a bean instance for a single HTTP request.**
- [x] **@RequestScope can be used instead of @Scope("request").**
- [ ] @Scope("prototype") will return a different instance every time it is requested from the container.

No comments.

---

5. Predict the Output

Incorrect

Multiple Choice | Medium | Exception Handling | Spring Boot | Aspect-Oriented Programming

Question description

Consider the following Snippet and predict the output.

The following API is triggered: http://localhost:8080/add/employee?eId=123&fName=Ravi&lastName=Shekhar

```
@Autowired
private EService eService;

@RequestMapping(value = "/add/employee", method = RequestMethod.GET)
public com.model.Employee add(@RequestParam("eId") String eId, @RequestParam("fName") Strin
g fName, @RequestParam("lastName") String lastName)
{
   return eService.createEmployee(eId, fName, lastName);
}

@Aspect
@Component
public class EServiceAspect
{
   @After(value = "execution(* com.random.service.EService.*(..)) && args(eId, fName, lastName)")
   public void afterAdvice(JoinPoint joinPoint, String eId, String fName, String lastName) {
      System.out.println("After method:" + joinPoint.getSignature());
      System.out.println("Creating Employee with first name - " + fName+ ", second name - " + lastNa
me+ " and id - " + eId);
   }
}
```

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ After method : com.test.model.Employee addEmployee(String,String,String)
  Creating Employee with first name - Ravi , second name - Shekhar and id - 123

- ● After method : com.test.model.Employee addEmployee(string,string,string)
  Creating Employee with first name - Ravi , second name - Shekhar and id - 123

After method : com.test.model.Employee addEmployee(empId,firstName,secondName) Creating Employee with first name - Ravi , second name - Shekhar and id - 123

After method : com.test.model.Employee addEmployee(String,String,String) Creating Employee with first name - Shekhar, second name - Ravi and id - 123

No comments.

6. Quiz Competition

Correct

Coding Medium Pointers

Question description

A class has students with various talents, each represented by an integer from 1 to *talentsCount*. You need to form teams for a quiz competition, where each team must have at least one member with each talent.

Teams must be formed from consecutive students in the array. For each possible starting position, determine the minimum number of students needed to form a valid team. If it is not possible to form a team with all talents from a particular starting position, return -1 for that position.

Example

talentsCount = 3

talent = [1, 2, 3, 2, 1]

- Starting at position 1: [1, 2, 3] includes all talents, minimum size = 3

- Starting at position 2: [2, 3, 2, 1] is the smallest subarray with all talents, minimum size = 4
- Starting at position 3: [3, 2, 1] includes all talents, minimum size = 3
- Starting at positions 4 and 5: Cannot form a team with all talents, return -1

The result is [3, 4, 3, -1, -1].

Function Description

Complete the function *teamSize* in the editor with the following parameter(s):

int talent[n]: the students' talents

int talentsCount : the number of talents represented numbered from 1 to *talentsCount*

Returns

int[n]: at each index, the minimum size subarray required, or -1 if an appropriate subarray does not exist

Constraints

- $1 \le n, talentsCount \le 10^5$
- $1 \le talent[i] \le talentsCount$

▼ INPUT FORMAT FOR CUSTOM TESTING

The first line contains an integer, *n*, the number of elements in *talent*.

Each line *i* of the *n* subsequent lines (where $0 \le i < n$) contains an integer, *talent[i]*.

The next line contains the integer *talentCount*.

▼ SAMPLE CASE 0

Sample Input For Custom Testing

```
STDIN   Function
-----   --------
8       talent[] size n = 8
1       talent = [1, 1, 2, 2, 3, 1, 3, 2]
1
2
2
3
1
3
```

```
2
3      talentsCount = 3
```

Sample Output

```
5
4
4
3
4
3
-1
-1
```

Explanation

The shortest subarrays for each position:

Beginning at the first position: [1, 1, 2, 2, 3] (length 5)

Second position: [1, 2, 2, 3] (length 4)

Third position: [2, 2, 3, 1] (length 4)

Fourth position: [2, 3, 1] (length 3)

Fifth position: [3, 1, 3, 2] (length 4)

Sixth position: [1, 3, 2] (length 3)

No further subarrays will have 3 elements.

▼ SAMPLE CASE 1

Sample Input For Custom Testing

```
STDIN   Function
-----   --------
5       talent[] size n = 5
1       talent = [1, 1, 1, 1, 1]
1
1
1
1
1       talentsCount = 1
```

Sample Output

```
1
1
1
```

```
1
1
```

Explanation

Since there is only 1 type of talent, any 1 person can form a team.

▼ SAMPLE CASE 2

Sample Input For Custom Testing

```
STDIN   Function
-----   --------
9       talent[] size n = 9
7       talent = [7, 5, 3, 4, 6, 1, 7, 2, 4]
5
3
4
6
1
7
2
4
7       talentsCount  7
```

Sample Output

```
8
7
-1
-1
-1
-1
-1
-1
-1
```

Explanation

There have to be at least *7* elements in any subarray to have one from each talent. The shortest subarrays at each position are:

Beginning at the first position: [7, 5, 3, 4, 6, 1, 7, 2] (length 8)

Second position: [5, 3, 4, 6, 1, 7, 2] (length 7)

No further subarrays will have 7 elements.

Interviewer guidelines

▼ SOLUTION

This can be solved using two-pointer technique. For a particular left index (L), we move the right index (R) forward until we have k distinct elements, then once we get it, we can move L forward. Each element will be traversed at most two times.

Time Complexity: O(n) or O(nLogn) (with set/map).

C++ Solution:

```
int f[100005];

vector<int> teamSize(vector<int> talent, int talentsCount) {
    int k = talentsCount;
    int n = talent.size();
    assert(n>=1&&n<=100000);
    assert(k>=1&&k<=n);
    for(int i=0;i<n;i++)
    {
        assert(talent[i]<=k&&talent[i]>=1);
    }
    int cnt = 0;
    int j = 0;
    vector<int> ans(n);
    for(int i=0;i<n;i++)
    {
        int x = talent[i];
        f[x]++;
        if(f[x]==1)
            cnt++;
        while(cnt==k&&j<=i)
        {
            ans[j] = i - j + 1;
            int y = talent[j];
            f[y]--;
            if(f[y]==0)
                cnt--;
            j++;
        }
    }
    while(j<n)
```

```
        ans[j++] = -1;
    return ans;
}
```

Candidate's Solution

Language used: **Java 17**

```java
import java.io.*;
import java.math.*;
import java.security.*;
import java.text.*;
import java.util.*;
import java.util.concurrent.*;
import java.util.function.*;
import java.util.regex.*;
import java.util.stream.*;
import static java.util.stream.Collectors.joining;
import static java.util.stream.Collectors.toList;


class Result {

    /*
     * Complete the 'teamSize' function below.
     *
     * The function is expected to return an INTEGER_ARRAY.
     * The function accepts following parameters:
     *  1. INTEGER_ARRAY talent
     *  2. INTEGER talentsCount
     */

    public static List<Integer> teamSize(List<Integer> talent, int talentsCount) {
    // Write your code here
    List<Integer>result= new ArrayList<>();
    int n=talent.size();
    int[] counts = new int[talentsCount+1];
    int u=0,r=0;
    for(int l=0;l<n;l++){
        while(r<n && u<talentsCount ){
            int currnt=talent.get(r);
            if(currnt<=talentsCount){
                if(counts[currnt]==0){
```

```
                    u++;
                }
                counts[currnt]++;
            }
            r++;
        }
        if(u==talentsCount) result.add(r-l);
        else result.add(-1);
        int lt=talent.get(l);
    if(lt <= talentsCount){
     counts[lt]--;
     if(counts[lt]==0) u--;
    }
    }
    return result;

    }

}
public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int talentCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> talent = IntStream.range(0, talentCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int talentsCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> result = Result.teamSize(talent, talentsCount);

        bufferedWriter.write(
```

```
            result.stream()
                .map(Object::toString)
                .collect(joining("\n"))
            + "\n"
        );

        bufferedReader.close();
        bufferedWriter.close();
    }
}

```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
TestCase 0	Easy	Sample	Success	1	0.0488 sec	34 KB
TestCase 1	Easy	Sample	Success	1	0.0607 sec	34 KB
TestCase 2	Easy	Sample	Success	1	0.0569 sec	33.9 KB
TestCase 3	Easy	Hidden	Success	3	0.1046 sec	44.5 KB
TestCase 4	Easy	Hidden	Success	3	0.145 sec	45.1 KB
TestCase 5	Easy	Hidden	Success	3	0.1217 sec	44.9 KB
TestCase 6	Easy	Hidden	Success	8	0.3059 sec	63.1 KB
TestCase 7	Easy	Hidden	Success	8	0.4185 sec	62.4 KB
TestCase 8	Easy	Hidden	Success	8	0.3487 sec	63.1 KB

TestCase 9	Easy	Hidden	Success	8	0.4099 sec	62.8 KB
TestCase 10	Easy	Hidden	Success	8	0.4419 sec	67.2 KB
TestCase 11	Easy	Hidden	Success	8	0.4778 sec	64.3 KB
TestCase 12	Easy	Hidden	Success	8	0.4826 sec	70 KB
TestCase 13	Easy	Hidden	Success	7	0.3782 sec	66.8 KB

No comments.

7. Java: Safe Cracking

Correct

Coding Medium Java Multithreading Interfaces OOP

Question description

Implement a *SafeCracking* class that executes a sequence of operations to rob a bank vault. The class should coordinate with an *IActions* interface to perform the robbery in the correct order.

Your implementation must follow a specific sequence of operations:

1. First, unlock the vault door.
2. Then, simultaneously determine the safe deposit box number and hack its PIN.
3. Finally, open the safe deposit box using the obtained information.

Method to Implement

```
void rob(IActions actions)
```

This method should coordinate with the provided *IActions* object to execute the following steps in order:

1. Call *unlockTheDoor()* to get the door passcode string.
2. Concurrently call both:
   - *hackSecretPin(passcodeOfDoor)* to get the safe deposit box PIN
   - *figureOutSafeDepositBoxNumber(passcodeOfDoor)* to get the safe deposit box number
3. Call *openSafeDepositLock(safeDepositBoxNumber, safetyDepositBoxPin)* to complete the robbery.

Note: The concurrent operations in step 2 are critical for the time-sensitive nature of the robbery scenario.

Example

The system will validate your implementation by checking if the operations are called in the correct order with the proper parameters. A successful implementation will output:

```
true
```

This indicates that all operations were performed correctly, and the robbery was successful. If the operations are performed in the wrong order or with incorrect parameters, the output will be *false*.

Constraints

- *1* ≤ lengths of *passcodeOfDoor*, *safeDespositBoxNumber, safetyDepositBoxPin* ≤ *10*

▼ INPUT FORMAT FOR CUSTOM TESTING

There is no input passed from stdin.

▼ SAMPLE CASE 0

Sample Output

```
true
```

Explanation

- stdout shows *true* if it is a successful robbery otherwise, it shows *false.*

Interviewer guidelines

Java 8 and Java 15 Solution

```
class SafeCracking {
   public void rob(IActions actions) throws InterruptedException, ExecutionException{
      ExecutorService threadPool = Executors.newFixedThreadPool(2);
      String passcodeOfDoor = actions.unlockTheDoor();
      Future<String> hackSecretPinTask = threadPool.submit(() -> actions.hackSecretPin(passcodeOf
Door));
      Future<String> figureOutSafeDepositBoxNumberTask = threadPool.submit(() -> actions.figureO
utSafeDepositBoxNumber(passcodeOfDoor));

      String safeDespositBoxNumber = figureOutSafeDepositBoxNumberTask.get();
      String safeDepositBoxPin = hackSecretPinTask.get();

      actions.openSafeDepositLock(safeDespositBoxNumber, safeDepositBoxPin);
      threadPool.shutdown();
   }
}
```

Candidate's Solution

Language used: **Java 17**

```java
import java.io.*;
import java.util.*;
import java.util.concurrent.ExecutionException;
import java.util.concurrent.ExecutorService;
import java.util.concurrent.Executors;
import java.util.concurrent.Future;

interface IActions{
    public String unlockTheDoor();
    public String hackSecretPin(final String passcodeOfDoor) throws InterruptedException, ExecutionException;
    public String figureOutSafeDepositBoxNumber(final String passcodeOfDoor) throws InterruptedException, ExecutionException;
    public void openSafeDepositLock(final String safetyDespositBoxNumber, final String safetyDepositBoxPin);
    public boolean getRobberyVerdict();
}

class SafeCracking {
```

```
    public void rob(IActions actions) throws InterruptedException, ExecutionException{
        String doorCode = actions.unlockTheDoor();
       ExecutorService executor= Executors.newFixedThreadPool(2);
       try{
        Future<String>pFuture=executor.submit(()->actions.hackSecretPin(doorCode));
        Future<String> boxNumberFuture = executor.submit(()->actions.figureOutSafeDepositBoxNumber(doorCode));

        String pin=pFuture.get();
        String boxNumber=boxNumberFuture.get();



         actions.openSafeDepositLock(boxNumber, pin);
       }catch(InterruptedException | ExecutionException e){
         System.out.println("Heist faill"+e.getMessage());
       }finally{
        executor.shutdown();
       }

    }
}

public class Solution {
    public static void main(String[] args) throws InterruptedException, ExecutionException{
        IActions actions = Actions.actions;
        new SafeCracking().rob(actions);
        System.out.println(actions.getRobberyVerdict());
    }
}

class Actions implements IActions{
    public static IActions actions = new Actions();

    private String passcodeOfDoor;
    private String safetyBoxNumber;
    private String pinOfSafetyBox;

    private String passedPasscodeOfDoor;
    private String passedSafetyBoxNumber;
    private String passedPinOfSafetyBox;

    private Actions() {
```

```
        this.passcodeOfDoor = randomStringGenerator(10);
        this.safetyBoxNumber = randomStringGenerator(10);
        this.pinOfSafetyBox = randomStringGenerator(10);
    }

    private String randomStringGenerator(int targetStringLength) {
        int leftLimit = 48; // numeral '0'
        int rightLimit = 122; // letter 'z'
        Random random = new Random();

        String generatedString = random.ints(leftLimit, rightLimit + 1)
            .filter(i -> (i <= 57 || i >= 65) && (i <= 90 || i >= 97))
            .limit(targetStringLength)
            .collect(StringBuilder::new, StringBuilder::appendCodePoint, StringBuilder::append)
            .toString();

        return generatedString;
    }

    public boolean getRobberyVerdict(){
        return (passcodeOfDoor == passedPasscodeOfDoor) && (pinOfSafetyBox == passedPinOfSafetyBox)
            && (safetyBoxNumber == passedSafetyBoxNumber);
    }

    public String unlockTheDoor() {
        return this.passcodeOfDoor;
    }

    public String hackSecretPin(final String passcodeOfDoor) throws InterruptedException, ExecutionException {
        this.passedPasscodeOfDoor = passcodeOfDoor;
        Thread.sleep(2000);
        return this.pinOfSafetyBox;
    }

    public  String figureOutSafeDepositBoxNumber(final String passcodeOfDoor) throws InterruptedException, ExecutionException {
        Thread.sleep(2000);
        return this.safetyBoxNumber;
    }

    public void openSafeDepositLock(final String safetyDespositBoxNumber, final String safetyDepositBoxPin) {
        this.passedSafetyBoxNumber = safetyDespositBoxNumber;
```

```
        this.passedPinOfSafetyBox = safetyDepositBoxPin;
    }
}
```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
Testcase 0	Easy	Sample	Success	1	2.0524 sec	34.1 KB
Testcase 1	Hard	Hidden	Success	74	2.0992 sec	34.1 KB

No comments.