100
Pass

G Bhavesh

PDF generated at: 13 Feb 2026 11:18:49 UTC

View this report on HackerRank

Score

100% • 175.0 / 175
scored in eClerx - Java Coding Test - 3+ Years New in 75 min 3 sec on 13 Feb 2026 15:28:33 IST

Candidate Information

Email	gbhaveshtpt@gmail.com
Test	eClerx - Java Coding Test - 3+ Years New
Candidate Packet	View
Taken on	13 Feb 2026 15:28:33 IST
Time taken	75 min 3 sec/ 90 min
Work Experience	3 years
Invited by	Nancy
Invited on	12 Feb 2026 15:48:08 IST

Skill Distribution

No.	Skill	Score
1	Spring Boot Advanced	100%

2	Spring Boot Intermediate	100%
3	Problem Solving Intermediate	100%
4	Java Intermediate	100%

Tags Distribution

Spring Boot	100%	Hard	100%
Spring	100%	Application Properties Annotations	100%
Medium	100%	Exception Handling	100%
Aspect-Oriented Programming	100%	Implementation	100%
Arrays	100%	Algorithms	100%
Problem Solving	100%	Greedy	100%
Java	100%		

Questions

Spring Boot (Advanced) • 25 / 25

No.	Question	Skill	Score	Code Quality	Time Taken	Status
1	Specification Multiple Choice	Spring Boot (Advanced)	5/5	-	1 min 15 sec	✓

2	Configuration Properties Multiple Choice	Spring Boot (Intermediate)	5/5	-	1 min 19 sec	✓
3	Spring Scopes Multiple Choice	Spring Boot (Intermediate)	5/5	-	1 min 16 sec	✓
4	Endpoint Security Multiple Choice	Spring Boot (Intermediate)	5/5	-	55 sec	✓
5	Predict the Output Multiple Choice	Spring Boot (Intermediate)	5/5	-	3 min 57 sec	✓

Problem Solving (Intermediate) • 75 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status
6	Wind Farms Coding	Problem Solving (Intermediate)	75/75	-	42 min 27 sec	✓

Java (Intermediate) • 75 / 75

No.	Question	Skill	Score	Code Quality	Time Taken	Status
7	Java: Optimized Sequential Video Watching Coding	Java (Intermediate)	75/75	-	23 min 17 sec	✓

Candidate Feedback

good

1. Specification

Correct

Multiple Choice | Spring Boot | Hard

Question description

Which of the following options can be used for dynamic jpa queries with spring-data-jpa repositories?

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ PreparedStatement
- ● Specification ✓
- ○ Criteria
- ○ Query

No comments.

2. Configuration Properties

Correct

Multiple Choice | Spring | Spring Boot | Application Properties Annotations | Medium

Question description

An *application.properties* file contains the following properties:

```
app.prop1 = value1
app.prop2 = value2
```

You decided to create a class to hold this configuration. To protect it, the class is defined as final.

```
@Configuration
@ConfigurationProperties(prefix = "app")
public final class AppConfiguration {
  String prop1;
  String prop2;

  public String getProp1() {
    return prop1;
  }

  public void setProp1(String prop1) {
    this.prop1 = prop1;
  }

  public String getProp2() {
    return prop2;
  }

  public void setProp2(String prop2) {
    this.prop2 = prop2;
  }
}
```

What is the result of running the Spring application with this class?

Interviewer guidelines

Spring creates dynamic proxies for classes annotated with `@Configuration` classes. Spring uses CGLIB to extend your class to create proxy. Hence, configuration classes cannot be final. When running the code Spring throws `BeanDefinitionParsingException` and this is the correct option.

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ The application runs, the configuration bean is created. and the properties are initialized correctly (prop1=value1, prop2=value2).
- ○ The application runs, and a configuration bean is created, but properties are set to null (prop1=null, prop2=null).
- ● ** A BeanDefinitionParsingException is thrown because the @Configuration bean cannot be marked as final. ** ✓
- ○ An IllegalStateException is thrown because the @Configuration bean cannot have an @ConfigurationProperties annotation.
- ○ A NoSuchMethodException is thrown because the @Configuration bean needs a default constructor.

No comments.

3. Spring Scopes

Correct

Multiple Choice Medium Spring

Question description

Which of the following statements is/are true about @Scope("request") and @Scope("prototype") annotations?

Candidate's Solution

Options: (Expected answer indicated with a tick)

- [x] Both are used to define the scope of spring beans.
- [x] @Scope("request") creates a bean instance for a single HTTP request.
- [x] @RequestScope can be used instead of @Scope("request").
- [x] @Scope("prototype") will return a different instance every time it is requested from the container.

No comments.

---

4. Endpoint Security

Correct

Multiple Choice Spring Boot Medium

Question description

In Spring Boot Security, the option to enable secure endpoints with @PreAuthorize annotation is:

Interviewer guidelines

@EnableGlobalMethodSecurity by default doesn't enable this feature. To enable this prePostEnabled=true value must be set

Candidate's Solution

Options: (Expected answer indicated with a tick)

- ○ Configuration class annotated with @EnableGlobalMethodSecurity
- ○ Configuration class annotated with @EnableGlobalMethodSecurity(securedEnabled = true)
- ● **Configuration class annotated with @EnableGlobalMethodSecurity(prePostEnabled = true)** ✓
- ○ None above

No comments.

---

5. Predict the Output

Correct

Multiple Choice | Medium | Exception Handling | Spring Boot | Aspect-Oriented Programming

Question description

Consider the following Snippet and predict the output.

The following API is triggered: http://localhost:8080/add/employee?eId=123&fName=Ravi&lastName=Shekhar

```
@Autowired
private EService eService;

@RequestMapping(value = "/add/employee", method = RequestMethod.GET)
public com.model.Employee add(@RequestParam("eId") String eId, @RequestParam("fName") Strin
g fName, @RequestParam("lastName") String lastName)
{
   return eService.createEmployee(eId, fName, lastName);
}

@Aspect
@Component
public class EServiceAspect
{
   @After(value = "execution(* com.random.service.EService.*(..)) && args(eId, fName, lastName)")
   public void afterAdvice(JoinPoint joinPoint, String eId, String fName, String lastName) {
      System.out.println("After method:" + joinPoint.getSignature());
      System.out.println("Creating Employee with first name - " + fName+ ", second name - " + lastNa
me+ " and id - " + eId);
   }
}
```

Candidate's Solution

Options: (Expected answer indicated with a tick)

- [x] ** After method : com.test.model.Employee addEmployee(String,String,String) **
  ** Creating Employee with first name - Ravi , second name - Shekhar and id - 123 **
  **   **

- [ ] After method : com.test.model.Employee addEmployee(string,string,string)
  Creating Employee with first name - Ravi , second name - Shekhar and id - 123

After method : com.test.model.Employee addEmployee(empId,firstName,secondName) Creating Employee with first name - Ravi , second name - Shekhar and id - 123

After method : com.test.model.Employee addEmployee(String,String,String) Creating Employee with first name - Shekhar, second name - Ravi and id - 123

No comments.

6. Wind Farms

Correct

Coding | Implementation | Medium | Arrays | Algorithms | Problem Solving

Question description

An energy company needs to place a control center to manage a distributed wind farm. Your task is to determine the optimal location for the control center that minimizes the total connection cost.

For each wind farm *i*:

- The farm is located at coordinates *(x[i], y[i])*
- The control center is at coordinates *(cx, cy)*
- The distance is calculated as *|x[i] - cx| + |y[i] - cy|*
- The connection cost is *premium[i] * distance*

Example

x = [1, 3, 2, 4]

y = [1, 2, 3, 4]
premium = [1, 3, 2, 4]



The optimal location is at position [3, 3], resulting in:

Farm #	Location	Distance	Premium	Cost

0	(1, 1)	|1 - 3| + |1 - 3| = 4	1	4 * 1 = 4
1	(3, 2)	|3 - 3| + |2 - 3| = 1	3	1 * 3 = 3
2	(2, 3)	|2 - 3| + |3 - 3| = 1	2	1 * 2 = 2
3	(4, 4)	|4 - 3| + |4 - 3| = 2	4	2 * 4 = 8

The total connection cost is 17, which is the minimum possible.

Function Description

Complete the function *windFarms* in the editor with the following parameter(s):

int premium[n]: the distance multiplier for the cost to connect
int x[n]: *x* coordinates of the wind farms
int y[n]: *y* coordinates of the wind farms

Returns

int: the minimum cost to connect the wind farms

Constraints

- $1 \le n \le 10^3$
- $1 \le x[i], y[i] \le 10^4$
- $1 \le premium[i] \le 50$

▼ INPUT FORMAT FOR CUSTOM TESTING

The first line contains an integer *n*, the size of the array *premium*.
The next *n* lines each contain an element, *premium[i],* where $0 \le i < n$.
The next line contains an integer *n*, the size of *x[]*.
The next *n* lines each contain an element, *x[i]*.
The next line contains an integer *n*, the size of *y[]*.
The next *n* lines each contain an element, *y[i]*.

Note: *n* is the same value in each instance.

▼ SAMPLE CASE 0

Sample Input 0

```
STDIN    Function
-----    --------
3    →  premium[] size n = 3
1    →  premium = [1, 1, 1]
1
1
3    →  x[] size n = 3
2    →  x = [2, 3, 5]
3
5
3    →  y[] size n = 3
1    →  y = [1, 1, 1]
1
1
```

Sample Output 0

```
3
```

Explanation 0



Locate the controller at farm 1.

Farm #	Location	Distance	Premium	Cost
0	(1, 1)	|1 - 3| + |1 - 1| = 1	1	1 * 1 = 1
1	(3, 1)	|3 - 3| + |1 - 1| = 0	1	0 * 1 = 0

2	(5, 1)	|5 - 3| + |1 - 1| = 2	1	2 * 1 = 2

▼ SAMPLE CASE 1

Sample Input 1

```
STDIN    Function
-----    --------
2    →  premium[] size n = 2
1    →  premium = [1, 10]
10
2    →  x[] size n = 2
1    →  x = [1, 2]
2
2    →  y[] size n = 2
1    →  y = [1, 2]
2
```

Sample Output 1

```
2
```

Explanation 1



The sum of the distances to a center at (1, 1), (1, 2), (2, 2), or (2, 1) is 2. Since the premium to connect farm 1 is 10, it is best to locate at position (2, 2) for a cost of 2 * 1 + 0 * 10 = 2.

▼ SAMPLE CASE 2

Sample Input 2

```
STDIN    Function
-----    --------
3    →  premium[] size n = 3
1    →  premium = [1, 1, 1]
1
1
3    →  x[] size n = 3
5    →  x = [5, 2, 3]
2
3
3    →  y[] size n = 3
3    →  y = [3, 4, 7]
4
7
```

Sample Output 2

```
7
```

Explanation 2



The optimal location is (3, 4) for a cost of 3 + 1 + 3 = 7.

Interviewer guidelines

▼ SOLUTION

Skills: Loops and counters, I/O

The cost can be calculated for x and y coordinates separately. The function examines each possible x and y coordinate for the control center separately (from 1 to 10000), computes the total cost of connecting all farms for each possible coordinate, and captures the minimum cost found. The ultimate minimum cost is the summation of these minimum costs for x and y coordinates separately.

Optimal Solution

```
def windFarms(premium, x, y):
    minCostX = 10**10
    n = len(x)

    for cx in range(1, 10001):
        cost = 0
        for i in range(n):
            cost += premium[i] * abs(cx - x[i])

        minCostX = min(minCostX, cost)

    minCostY = 10**10
    for cy in range(1, 10001):
        cost = 0
        for i in range(n):
            cost += premium[i] * abs(cy - y[i])

        minCostY = min(minCostY, cost)

    return minCostX + minCostY
```

▼ **COMPLEXITY ANALYSIS**

Time Complexity - O(n)

The universe of x and y values are tested against 10000 values.

Space Complexity - O(1)

Constant space is required regardless of n.

Candidate's Solution

Language used: **Java 21**

```java
import java.io.*;
import java.math.*;
import java.security.*;
import java.text.*;
import java.util.*;
import java.util.concurrent.*;
import java.util.function.*;
import java.util.regex.*;
import java.util.stream.*;
import static java.util.stream.Collectors.joining;
import static java.util.stream.Collectors.toList;


class Result {

    /*
     * Complete the 'windFarms' function below.
     *
     * The function is expected to return an INTEGER.
     * The function accepts following parameters:
     *  1. INTEGER_ARRAY premium
     *  2. INTEGER_ARRAY x
     *  3. INTEGER_ARRAY y
     */

    public static int windFarms(List<Integer> premium, List<Integer> x, List<Integer> y) {
    // Write your code here
        int cx = findWeightedMedian(x,premium);
        int cy = findWeightedMedian(y, premium);
        long totalCost=0;

        for(int i=0;i<x.size();i++){
            long distance = Math.abs(x.get(i)-cx)+Math.abs(y.get(i)-cy);
            totalCost += premium.get(i)*distance;
        }

        return (int) totalCost;

    }

    private static int findWeightedMedian(List<Integer> x, List<Integer> premium){
        int n = x.size();
```

```
        List<Integer> test = new ArrayList<>();
        for(int i=0;i<n;i++){
            test.add(i);
        }

        Collections.sort(test, (a, b) -> x.get(a) - x.get(b));
        int totalWeight = 0;
        for(int w : premium){
            totalWeight += w;
        }

        long runningWeight = 0;
        for(int index : test){
            runningWeight += premium.get(index);

            if(runningWeight*2 >= totalWeight){
                return x.get(index);
            }
        }

        return x.get(test.get(n-1));
    }

}
public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int premiumCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> premium = IntStream.range(0, premiumCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

```

```
        int xCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> x = IntStream.range(0, xCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int yCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> y = IntStream.range(0, yCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        int result = Result.windFarms(premium, x, y);

        bufferedWriter.write(String.valueOf(result));
        bufferedWriter.newLine();

        bufferedReader.close();
        bufferedWriter.close();
    }
}

```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
TestCase 0	Easy	Sample	Success	1	0.0565 sec	37.4 KB

TestCase 1	Easy	Sample	Success	1	0.0632 sec	37.6 KB
TestCase 2	Easy	Sample	Success	1	0.0613 sec	37.6 KB
TestCase 3	Easy	Sample	Success	2	0.0566 sec	37.5 KB
TestCase 4	Easy	Hidden	Success	2	0.051 sec	37.4 KB
TestCase 5	Easy	Hidden	Success	2	0.0585 sec	37.3 KB
TestCase 6	Medium	Sample	Success	6	0.0588 sec	38.2 KB
TestCase 7	Medium	Hidden	Success	6	0.0634 sec	38.1 KB
TestCase 8	Medium	Hidden	Success	6	0.0598 sec	38.4 KB
TestCase 9	Hard	Hidden	Success	12	0.0841 sec	44.2 KB
TestCase 10	Hard	Hidden	Success	12	0.0895 sec	43.7 KB
TestCase 11	Hard	Hidden	Success	12	0.0938 sec	43.5 KB
TestCase 12	Hard	Hidden	Success	12	0.0774 sec	44.1 KB

No comments.

7. Java: Optimized Sequential Video Watching

Correct

Coding Medium Greedy Java

Question description

A learner is given a sequential playlist of *n* videos to enhance their knowledge. Implement a function to calculate the minimum time required to complete a total of *m* viewings while adhering to the platform's constraints.

System Constraints

- Sequential Viewing:
  - The learner must watch videos in the order they appear in the playlist.
  - To watch a video at index *i*, the learner must first watch all videos from index 0 to *i-1* at least once.
- Initial Full Viewing:
  - To view any video at index *i* for the first time, the learner must spend *firstWatch[i] + repeatWatch[i]* minutes. This ensures a complete understanding of the video.
- Subsequent Viewings:
  - For subsequent viewings of a video at index *i*, the learner spends only *repeatWatch[i]* minutes.
  - At any time, they can rewatch any video they have already watched.
- Minimum Total Watch Count:
  - The learner must achieve at least *m* total viewings across all videos.
  - Videos can be rewatched as desired, and not all videos need to be watched equally.

Return the minimum time required to complete *m* viewings of videos while following these constraints.

Example

If *n* = 4, *m* = 4, *firstWatch* = [1, 5, 9, 11], and *repeatWatch* = [2, 7, 10, 11], the optimal strategy is as follows:

- The learner watches the 0th video for the first time, spending *firstWatch*[0] + *repeatWatch*[0] = 1 + 2 = 3 minutes.
- The learner then rewatches the 0th video 3 more times in, spending *repeatWatch*[0]*3 = 2 * 3 = 6 minutes.

- The learner has successfully completed 4 viewings. Thus, the total time required is 3 + 6 = 9 minutes, and 9 is returned.

Function Description

Complete the function *findMinMinutes* in the editor below.

Function Parameters

int m: the total number of video viewings to complete

int firstWatch[n]: the minutes required to watch each video the first time

int repeatWatch[n]: the minutes required to rewatch each video

Returns

long: the minimum minutes required for the learner to reach their target number of viewings

Constraints

- $1 \le n \le 10^5$
- $1 \le m \le 10^9$
- $1 \le firstWatch[i], repeatWatch[i] \le 10^9$

▼ INPUT FORMAT FOR CUSTOM TESTING

The first line contains an integer, *m*.

The next line contains an integer, *n,* the size of *firstWatch*.

Each of the next *n* lines contains an integer, *firstWatch[i]*.

The next line contains an integer, *n,* the size of *repeatWatch*.

Each of the next *n* lines contains an integer, *repeatWatch[i]*.

▼ SAMPLE CASE 0

Sample Input 0

```
STDIN    FUNCTION
-----    --------
5        m = 5
3        firstWatch[] size n = 3
6        firstWatch = [6, 8, 9]
8
9
3        repeatWatch[] size n = 3
4        repeatWatch = [4, 2, 10]
```

```
2
10
```

Sample Output 0

```
26
```

Explanation

The goal is to complete 5 viewings. One optimal strategy is:

- The learner watches the 0th video for the first time, so the time required is *firstWatch*[0] + *repeatWatch*[0] = 6 + 4 = 10 minutes.
- The learner watches the 1st video for the first time, so the time required is *firstWatch*[1] + *repeatWatch*[1] = 8 + 2 = 10 minutes.
- The learner then rewatches the 1st video 3 times. So the time taken = *repeatWatch*[1]*3 = 2 * 3 = 6 minutes.
- The total time required to complete 5 video viewings is 10 + 10 + 6 = 26 minutes.

▼ SAMPLE CASE 1

Sample Input 1

```
STDIN     FUNCTION
-----     --------
6         m = 6
5         firstWatch[] size n = 5
2         firstWatch = [2, 3, 7, 8, 4]
3
7
8
4
5         repeatWatch[] size n = 5
3         repeatWatch = [3, 6, 8, 7, 6]
6
8
7
6
```

Sample Output 1

```
20
```

Explanation

The goal is to complete 6 viewings. One optimal strategy is:

- The learner watches the 0th video for the first time in *firstWatch*[0] + *repeatWatch[0]* = 2 + 3 = 5 minutes.
- The learner then rewatches the 0th video 5 times in *repeatWatch[0]**5 = 3 * 5 = 15 minutes.
- The total time required to complete 6 viewings is 5 + 15 = 20 minutes.

Interviewer guidelines

▼ SOLUTION

Description

The greedy solution suggests that, at any given index, if the time to watch the video is less than at any other index between i+1 and n, the minimum total time will be the sum of the watch time up to index i-1, plus the repeat time of the ith video multiplied by (m-i).

Solution

```
class Result {

    /*
     * Complete the 'findMinMinutes' function below.
     *
     * The function is expected to return a LONG_INTEGER.
     * The function accepts following parameters:
     *  1. INTEGER m
     *  2. INTEGER_ARRAY firstWatch
     *  3. INTEGER_ARRAY repeatWatch
     */

    public static long findMinMinutes(int m, List<Integer> firstWatch, List<Integer> repeatWatch) {
        long minMinutes = Long.MAX_VALUE;
        long cur = 0;
        int n = firstWatch.size();

        for (int i = 0; i < Math.min(n,m); i++) {
            int a = firstWatch.get(i);
            int b = repeatWatch.get(i);

            minMinutes = Math.min(minMinutes, cur + ((long) (m - i) * b) + a);

            cur += a + b;
        }
        return minMinutes;
    }
```

```
}
```

▼ COMPLEXITY

Time Complexity - O(n)

The algorithm iterates through each number in *firstWatch* and *repeatWatch* exactly once, performing constant-time checks and arithmetic operations in each iteration. Thus, the time complexity is O(n), where *n* is the length of *firstWatch*.

Space Complexity - O(1)

Space usage is constant, only utilizing a fixed number of variables (*mn, cur,* etc.) that do not scale with the length of *firstWatch*. Therefore, the space complexity is O(1).

Candidate's Solution Language used: **Java 21**

```java
import java.io.*;
import java.math.*;
import java.security.*;
import java.text.*;
import java.util.*;
import java.util.concurrent.*;
import java.util.function.*;
import java.util.regex.*;
import java.util.stream.*;
import static java.util.stream.Collectors.joining;
import static java.util.stream.Collectors.toList;


class Result {

    /*
     * Complete the 'findMinMinutes' function below.
     *
     * The function is expected to return a LONG_INTEGER.
     * The function accepts following parameters:
     *  1. INTEGER m
     *  2. INTEGER_ARRAY firstWatch
     *  3. INTEGER_ARRAY repeatWatch
     */

```

```
    public static long findMinMinutes(int m, List<Integer> firstWatch, List<Integer> repeatWatch) {
    // Write your code here
    long totalTime=0;
    int views=0;
    long min = Long.MAX_VALUE;
    long answer = Long.MAX_VALUE;
        for(int i=0;i<firstWatch.size();i++){
            totalTime += firstWatch.get(i)+repeatWatch.get(i);
            views++;
            min = Math.min(min, repeatWatch.get(i));
            if(views>=m){
                answer = Math.min(answer, totalTime);
            }else{
                int remain = m - views;
                long cost = totalTime+remain*min;
                answer=Math.min(answer, cost);
            }
        }
        return answer;
    }

}

public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int m = Integer.parseInt(bufferedReader.readLine().trim());

        int firstWatchCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> firstWatch = IntStream.range(0, firstWatchCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
```

```
            .collect(toList());

        int repeatWatchCount = Integer.parseInt(bufferedReader.readLine().trim());

        List<Integer> repeatWatch = IntStream.range(0, repeatWatchCount).mapToObj(i -> {
            try {
                return bufferedReader.readLine().replaceAll("\\s+$", "");
            } catch (IOException ex) {
                throw new RuntimeException(ex);
            }
        })
            .map(String::trim)
            .map(Integer::parseInt)
            .collect(toList());

        long result = Result.findMinMinutes(m, firstWatch, repeatWatch);

        bufferedWriter.write(String.valueOf(result));
        bufferedWriter.newLine();

        bufferedReader.close();
        bufferedWriter.close();
    }
}

```

TESTCASE	DIFFICULTY	TYPE	STATUS	SCORE	TIME TAKEN	MEMORY USED
Testcase 2	Easy	Sample	Success	1	0.069 sec	37.5 KB
Testcase 0	Easy	Sample	Success	1	0.0627 sec	37.5 KB
Testcase 1	Easy	Sample	Success	1	0.0508 sec	37.7 KB
Testcase 3	Easy	Hidden	Success	4	0.0652 sec	37.3 KB

Testcase 4	Easy	Hidden	Success	4	0.058 sec	38.4 KB
Testcase 5	Easy	Hidden	Success	4	0.1215 sec	46.1 KB
Testcase 6	Medium	Hidden	Success	5	0.3294 sec	73.1 KB
Testcase 7	Medium	Hidden	Success	5	0.5693 sec	181 KB
Testcase 8	Medium	Hidden	Success	5	0.6254 sec	176 KB
Testcase 9	Medium	Hidden	Success	5	0.5276 sec	146 KB
Testcase 10	Medium	Hidden	Success	5	0.5094 sec	167 KB
Testcase 11	Medium	Hidden	Success	5	0.3794 sec	128 KB
Testcase 12	Hard	Hidden	Success	10	0.2475 sec	69.6 KB
Testcase 13	Hard	Hidden	Success	10	0.5833 sec	125 KB
Testcase 14	Hard	Hidden	Success	10	0.0695 sec	37.1 KB

No comments.