
Session 5

The Database Constraints



- Jayendra Khatod

- **Describe constraints**
- **Create and maintain constraints**

What are Constraints?

- **Constraints enforce rules at the table level.**
- **Constraints prevent the deletion of a table if there are dependencies.**
- **The following constraint types are valid:**
 - NOT NULL
 - UNIQUE
 - PRIMARY KEY
 - FOREIGN KEY
 - CHECK

Constraint Guidelines

- **Name a constraint or the Oracle server generates a name by using the SYS_Cn format.**
- **Create a constraint either:**
 - **At the same time as the table is created, or**
 - **After the table has been created**
- **Define a constraint at the column or table level.**
- **View a constraint in the data dictionary.**

Syntax

```
CREATE TABLE [schema.]table
    (column datatype [DEFAULT expr]
    [column_constraint],
    ...
    [table_constraint] [, ...]);
```

Defining Constraints

Example

```
CREATE TABLE employees(  
    employee_id    NUMBER(6),  
    first_name     VARCHAR2(20),  
    ...  
    job_id         VARCHAR2(10) NOT NULL,  
    CONSTRAINT emp_emp_id_pk  
    PRIMARY KEY (EMPLOYEE_ID));
```

Defining Constraints

- **Column constraint level**

```
column [CONSTRAINT constraint_name]  
constraint_type,
```

- **Table constraint level**

```
column, ...  
[CONSTRAINT constraint_name]  
  constraint_type  
  (column, ...),
```

The NOT NULL Constraint

Ensures that null values are not permitted for the

EMPLOYEE_ID	LAST_NAME	EMAIL	PHONE_NUMBER	HIRE_DATE	JOB_ID	SALARY	DEPARTMENT_ID
100	King	SKING	515.123.4567	17-JUN-87	AD_PRES	24000	90
101	Kochhar	NKOCHHAR	515.123.4568	21-SEP-89	AD_VP	17000	90
102	De Haan	LDEHAAN	515.123.4569	13-JAN-93	AD_VP	17000	90
103	Hunold	AHUNOLD	590.423.4567	03-JAN-90	IT_PROG	9000	60
104	Ernst	BERNST	590.423.4568	21-MAY-91	IT_PROG	6000	60
178	Grant	KGRANT	011.44.1644.429263	24-MAY-99	SA_REP	7000	
200	Whalen	JWHALEN	515.123.4444	17-SEP-87	AD_ASST	4400	10

...
20 rows selected.

↑
NOT NULL constraint
(No row can contain
a null value for
this column.)

↑
**NOT NULL
constraint**

↑
**Absence of NOT NULL
constraint**
(Any row can contain
null for this column.)

The NOT NULL Constraint

Is defined at the column level:

```
CREATE TABLE employees(  
    employee_id    NUMBER(6),  
    last_name      VARCHAR2(25) NOT NULL,  
    salary         NUMBER(8,2),  
    commission_pct NUMBER(2,2),  
    hire_date      DATE  
    CONSTRAINT emp_hire_date_nn  
    NOT NULL,  
    ...
```

← **System
named**

← **User
named**

The UNIQUE Constraint

EMPLOYEES

EMPLOYEE_ID	LAST_NAME	EMAIL
100	King	SKING
101	Kochhar	NKOCHHAR
102	De Haan	LDEHAAN
103	Hunold	AHUNOLD
104	Ernst	BERNST

...

INSERT INTO

208	Smith	JSMITH
209	Smith	JSMITH

UNIQUE constraint

Allowed

Not allowed:
already exists

The UNIQUE Constraint

Defined at either the table level or the column level:

```
CREATE TABLE employees(  
    employee_id      NUMBER(6) ,  
    last_name        VARCHAR2(25) NOT NULL ,  
    email            VARCHAR2(25) ,  
    salary           NUMBER(8,2) ,  
    commission_pct   NUMBER(2,2) ,  
    hire_date        DATE NOT NULL ,  
    ...  
    CONSTRAINT emp_email_uk UNIQUE(email)) ;
```

The PRIMARY KEY Constraint

DEPARTMENTS

PRIMARY KEY

DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
10	Administration	200	1700
20	Marketing	201	1800
50	Shipping	124	1500
60	IT	103	1400
80	Sales	149	2500

...

Not allowed
(Null value)

INSERT INTO

	Public Accounting		1400
50	Finance	124	1500

Not allowed
(50 already exists)

The PRIMARY KEY Constraint

Defined at either the table level or the column level:

```
CREATE TABLE departments (  
    department_id          NUMBER(4) ,  
    department_name        VARCHAR2(30)  
        CONSTRAINT dept_name_nn NOT NULL,  
    manager_id            NUMBER(6) ,  
    location_id            NUMBER(4) ,  
    CONSTRAINT dept_id_pk PRIMARY KEY(department_id)) ;
```

The FOREIGN KEY Constraint

DEPARTMENTS

DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
10	Administration	200	1700
20	Marketing	201	1800
50	Shipping	124	1500
60	IT	103	1400
80	Sales	149	2500

**PRIMARY
KEY**



...

EMPLOYEES

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
100	King	90
101	Kochhar	90
102	De Haan	90
103	Hunold	60
104	Ernst	60
107	Lorentz	60

**FOREIGN
KEY**



...

INSERT INTO

200	Ford	9
201	Ford	60

**Not allowed
(9 does not
exist)**



Allowed



The FOREIGN KEY Constraint

Defined at either the table level or the column level:

```
CREATE TABLE employees (  
    employee_id      NUMBER(6) ,  
    last_name        VARCHAR2(25) NOT NULL ,  
    email            VARCHAR2(25) ,  
    salary            NUMBER(8,2) ,  
    commission_pct   NUMBER(2,2) ,  
    hire_date        DATE NOT NULL ,  
    ...  
    department_id    NUMBER(4) ,  
    CONSTRAINT emp_dept_fk FOREIGN KEY (department_id)  
        REFERENCES departments(department_id) ,  
    CONSTRAINT emp_email_uk UNIQUE(email)) ;
```

FOREIGN KEY Constraint Keywords

- **FOREIGN KEY:** Defines the column in the child table at the table constraint level
- **REFERENCES:** Identifies the table and column in the parent table
- **ON DELETE CASCADE:** Deletes the dependent rows in the child table when a row in the parent table is deleted.
- **ON DELETE SET NULL:** Converts dependent foreign key values to null

The CHECK Constraint

- **Defines a condition that each row must satisfy**
- **The following expressions are not allowed:**
 - **References to CURRVAL, NEXTVAL, LEVEL, and ROWNUM pseudocolumns**
 - **Calls to SYSDATE, UID, USER, and USERENV functions**
 - **Queries that refer to other values in other rows**

```
..., salary  NUMBER(2)  
      CONSTRAINT emp_salary_min  
      CHECK (salary > 0),...
```

Adding a Constraint Syntax

Use the ALTER TABLE statement to:

- **Add or drop a constraint, but not modify its structure**
- **Enable or disable constraints**
- **Add a NOT NULL constraint by using the MODIFY clause**

```
ALTER TABLE table  
ADD [CONSTRAINT constraint] type (column);
```

Adding a Constraint

Add a FOREIGN KEY constraint to the EMPLOYEES table indicating that a manager must already exist as a valid employee in the EMPLOYEES table.

```
ALTER TABLE      employees
ADD CONSTRAINT    emp_manager_fk
FOREIGN KEY(manager_id)
REFERENCES employees(employee_id);
Table altered.
```

Dropping a Constraint

- **Remove the manager constraint from the EMPLOYEES table.**

```
ALTER TABLE      employees
DROP CONSTRAINT    emp_manager_fk;
Table altered.
```

- **Remove the PRIMARY KEY constraint on the DEPARTMENTS table and drop the associated FOREIGN KEY constraint on the EMPLOYEES.DEPARTMENT_ID column.**

```
ALTER TABLE      departments
DROP PRIMARY KEY CASCADE;
Table altered.
```

Disabling Constraints

- **Execute the DISABLE clause of the ALTER TABLE statement to deactivate an integrity constraint.**
- **Apply the CASCADE option to disable dependent integrity constraints.**

```
ALTER TABLE          employees  
DISABLE CONSTRAINT    emp_emp_id_pk CASCADE;  
Table altered.
```

Enabling Constraints

- **Activate an integrity constraint currently disabled in the table definition by using the ENABLE clause.**

```
ALTER TABLE          employees
ENABLE CONSTRAINT      emp_emp_id_pk;
Table altered.
```

- **A UNIQUE or PRIMARY KEY index is automatically created if you enable a UNIQUE key or PRIMARY KEY constraint.**

Cascading Constraints

- **The CASCADE CONSTRAINTS clause is used along with the DROP COLUMN clause.**
- **The CASCADE CONSTRAINTS clause drops all referential integrity constraints that refer to the primary and unique keys defined on the dropped columns.**
- **The CASCADE CONSTRAINTS clause also drops all multicolumn constraints defined on the dropped columns.**

Cascading Constraints

Example:

```
ALTER TABLE test1  
DROP (pk) CASCADE CONSTRAINTS;  
Table altered.
```

```
ALTER TABLE test1  
DROP (pk, fk, col1) CASCADE CONSTRAINTS;  
Table altered.
```


Viewing Constraints

Query the USER_CONSTRAINTS table to view all constraint definitions and names.

```
SELECT constraint_name, constraint_type,  
       search_condition  
FROM   user_constraints  
WHERE  table_name = 'EMPLOYEES';
```

CONSTRAINT_NAME	C	SEARCH_CONDITION
EMP_LAST_NAME_NN	C	"LAST_NAME" IS NOT NULL
EMP_EMAIL_NN	C	"EMAIL" IS NOT NULL
EMP_HIRE_DATE_NN	C	"HIRE_DATE" IS NOT NULL
EMP_JOB_NN	C	"JOB_ID" IS NOT NULL
EMP_SALARY_MIN	C	salary > 0
EMP_EMAIL_UK	U	

...

Viewing the Columns Associated with Constraints

View the columns associated with the constraint names in the USER_CONS_COLUMNS view.

```
SELECT constraint_name, column_name
FROM   user_cons_columns
WHERE  table_name = 'EMPLOYEES';
```

CONSTRAINT_NAME	COLUMN_NAME
EMP_DEPT_FK	DEPARTMENT_ID
EMP_EMAIL_NN	EMAIL
EMP_EMAIL_UK	EMAIL
EMP_EMP_ID_PK	EMPLOYEE_ID
EMP_HIRE_DATE_NN	HIRE_DATE
EMP_JOB_FK	JOB_ID
EMP_JOB_NN	JOB_ID

...

In this lesson, you should have learned how to create constraints.

- **Types of constraints:**
 - NOT NULL
 - UNIQUE
 - PRIMARY KEY
 - FOREIGN KEY
 - CHECK
- **You can query the USER_CONSTRAINTS table to view all constraint definitions and names.**

सी डैक
CDAC

Thank You !

ऑक्टस
acts