# An Autonomous Edge-to-Core Intrusion Detection and Adaptive Mitigation Architecture for Heterogeneous IoT Ecosystems

**Lead Cybersecurity & Embedded Systems Researcher**
Department of Computer Science and Network Engineering
Laboratory for Advanced IoT Security & Systems Intelligence • *Correspondence: research-team@netpulse-iot.org*

**ABSTRACT**

*The proliferation of Internet of Things (IoT) deployments across industrial, healthcare, and enterprise environments has introduced severe network attack surfaces characterized by firmware vulnerabilities, insecure default configurations, and absent host-level security agents. Conventional perimeter defenses fail to isolate internal lateral movements once an edge node is compromised, while signature-based Intrusion Detection Systems (IDS) remain ineffective against zero-day and multi-vector botnet intrusions. This paper presents* ***NetPulse IoT****, a closed-loop edge-to-core security platform providing continuous flow-level anomaly detection, multi-factor risk quantification, and autonomous zero-touch quarantine containment.*

*Our system couples physical microcontroller sensing nodes (ESP32) and heterogeneous IoT fleets with a high-throughput asynchronous core engine. Traffic telemetry is reduced to a 9-dimensional flow feature vector and evaluated via an ensemble Random Forest classifier benchmarked against the 33-attack-class CICIoT2023 taxonomy. To eliminate false-positive operational disruptions, raw machine learning inferences are synthesized within a transparent 0–100 multi-factor risk scoring engine that factors volumetric bursts, transport-layer handshake failures, historical infractions, and external domain reputation heuristics. Entities exhibiting critical risk ($R \geq 81$) trigger instantaneous permanent blacklisting, whereas elevated anomalies ($61 \leq R \leq 80$) undergo automated time-to-live (TTL) quarantine managed by an asynchronous state-recovery worker. Experimental evaluation demonstrates that the proposed architecture achieves a classification accuracy of 99.4%, sub-millisecond per-flow inference latency (1.42 ms), and an end-to-end automated mitigation response time under 35 ms, confirming its viability for real-world, latency-critical IoT operational environments.*

**Keywords:** Internet of Things (IoT) Security, Intrusion Detection and Prevention Systems (IDPS), Random Forest Classifier, Dynamic Risk Scoring, Edge Microcontrollers, Automated Quarantine, Network Flow Analysis.

## 1. INTRODUCTION

The integration of low-cost microcontrollers, embedded single-board computers, and specialized sensing hardware has driven the rapid expansion of the Internet of Things (IoT). From smart grid infrastructure and hospital monitoring systems to automated industrial manufacturing, billions of connected nodes continuously transmit telemetry and execute actuation commands. However, the architectural reality of IoT ecosystems introduces unique cybersecurity challenges that diverge substantially from traditional enterprise computing environments.

Most IoT devices operate under strict physical and computational constraints: (1) *Minimal Hardware Capabilities:* Constrained 8-bit or 32-bit microcontrollers (such as ESP8266 or basic ARM Cortex-M units) lack the RAM, storage, and CPU cycles required to run traditional Endpoint Detection and Response (EDR) software; (2) *Insecure Firmware & Protocols:* Many commercial off-the-shelf devices ship with legacy Linux distributions containing known Common Vulnerabilities and Exposures (CVEs), hardcoded administrative credentials, unencrypted communication channels, and absent firmware update pipelines; (3) *Pervasive Attack Amplification:* Compromised edge nodes are routinely aggregated into distributed denial-of-service (DDoS) botnets (such as Mirai, Mozi, and Gafgyt) or repurposed as reconnaissance proxies to pivot laterally into protected internal corporate subnets.




### 1.1 Research Contributions

- **Dual-Tier Edge & Simulation Testbed:** We develop genuine, compilable C++ Arduino firmware for physical ESP32 microcontrollers featuring multi-SSID failover, environmental telemetry dispatch, and hardware LED diagnostics, operating alongside a concurrent multi-profile IoT simulation engine.
- **Streamlined Flow Feature Representation:** Rather than performing computationally prohibitive deep packet inspection across full payloads, we isolate a 9-dimensional statistical flow vector capturing volume, packet dynamics, connection velocities, handshake failures, and destination port distributions.
- **Ensemble Machine Learning on CICIoT2023:** We train an ensemble Random Forest classifier on a structured dataset aligned with the 33-attack-class Canadian Institute for Cybersecurity benchmark, demonstrating high discrimination across DoS, DDoS, Reconnaissance, Brute Force, Web, Spoofing, and Mirai attack vectors.
- **Multi-Factor Dynamic Risk Engine:** We formulate a transparent composite risk index R in [0, 100] that synthesizes probabilistic ML classifications with volumetric thresholds, failed connection rates, domain reputation heuristics, and historical incident history.
- **Autonomous Closed-Loop Mitigation with Time-Decayed Quarantine:** We implement zero-touch network isolation policies directly within the ingestion boundary. High-severity threats are quarantined under an automated time-to-live (TTL) window governed by an asynchronous state-recovery worker, restoring legitimate nodes upon threat cessation without operator intervention.

## 2. RELATED WORK AND THEORETICAL FOUNDATION

**2.1 IoT Threat Landscapes and Botnet Dynamics:** The rise of large-scale IoT botnets fundamentally altered network security. As documented by Antonakakis et al. [1] in their landmark analysis of the Mirai botnet, millions of embedded cameras, DVRs, and home routers were commandeered via automated Telnet credential scanning over TCP ports 23 and 2323. Once infected, these devices execute coordinated TCP SYN floods, UDP volumetric saturation, and DNS water torture attacks capable of exceeding multi-terabit per second throughput. Subsequent strains (such as Hajime, Reaper, and Mozi) incorporated peer-to-peer (P2P) command-and-control (C2) topologies, custom binary encryption, and automated exploitation of unauthenticated remote code execution (RCE) flaws. Consequently, intrusion detection must focus on flow-level statistical behavioral invariants rather than static payload contents.

**2.2 Machine Learning in Network Intrusion Detection:** Applying machine learning to network intrusion detection has been studied extensively across benchmark datasets such as KDD99, NSL-KDD, and UNSW-NB15. However, earlier datasets fail to reflect modern IoT protocols (MQTT, CoAP, RTSP) and modern hardware topologies. The introduction of the CICIoT2023 dataset by Netto et al. [2] provided a standardized benchmark comprising 33 attack classes executed across a realistic

topology of 105 IoT devices. Prior works have evaluated Support Vector Machines (SVM), Deep Neural Networks (DNN), and Decision Trees. While DNNs achieve strong classification, their inference latency (15–50 ms) and black-box nature hinder real-time deployment. Random Forests [3] offer an optimal compromise by mitigating tree variance via bagging while preserving sub-millisecond inference and explainable Gini feature importances.

**2.3 Shortcomings of Existing Mitigation Approaches:** A pronounced gap persists between ML classification and automated remediation. First, most models output binary labels (0/1) without confidence calibration, inducing false-positive disruptions in critical environments. Second, existing firewalls require manual administrator intervention to unblock isolated hosts. Third, standard flow classifiers inspect transport headers in isolation while neglecting external fully qualified domain name (FQDN) reputations. NetPulse IoT bridges these gaps by synthesizing ML outputs, domain heuristics, and automated state-decay quarantine workflows.

## 3. SYSTEM ARCHITECTURE AND OPERATIONAL PIPELINE

The NetPulse IoT architecture is partitioned into four decoupled layers: the Edge Hardware & Fleet Simulation Layer, the Asynchronous Ingestion & Processing Core, the Machine Learning & Risk Quantification Engine, and the Real-Time Presentation & Policy Enforcement Boundary.




**3.1 Edge Microcontroller Firmware Architecture:** The physical edge nodes are built on Espressif ESP32 dual-core microcontrollers clocked at 240 MHz. The firmware implements multi-AP failover using WiFiMulti, an interrupt-safe LED state machine on GPIO 2 providing visual diagnostic feedback, physical DHT11/22 sensor sampling on GPIO 4 with a stochastic fallback generator, and periodic JSON serialization dispatched every 10 seconds.

**3.2 Ingestion Core and Concurrency Design:** The backend utilizes Python 3.13 and FastAPI running asynchronously via Uvicorn. Data integrity is enforced via Pydantic v2 schemas. Persistence is handled through SQLAlchemy ORM targeting an optimized local SQLite engine (netpulse.db) with write-ahead logging (WAL) enabled, seamlessly reconfigurable to PostgreSQL clusters for enterprise deployments.

## 4. THREAT CLASSIFICATION METHODOLOGY

**4.1 Feature Extraction and Flow Dimensionality:** To eliminate the computational overhead of full payload parsing, we isolate a 9-dimensional flow feature vector $\mathbf{x} = [x_1, x_2, ..., x_9]^T$:

| Feature | Data Type | Diagnostic Significance & Behavioral Mapping |
|---|---|---|
| $x_1$: *traffic_volume* | Integer (Bytes) | Detects volumetric saturation, data exfiltration, and buffer overflow surges. |
| $x_2$: *packet_count* | Integer | Monitors burst density, packet fragmentation anomalies, and transmission rate surges. |
| $x_3$: *request_frequency* | Float ($sec^{-1}$) | Identifies aggressive API endpoint abuse, HTTP Slowloris, and polling anomalies. |
| $x_4$: *connection_frequency* | Float ($min^{-1}$) | Quantifies socket creation velocity, distinguishing scans from normal operations. |
| $x_5$: *failed_connections* | Integer | Captures rejected TCP SYN handshakes, closed port hits, and auth rejections. |
| $x_6$: *protocol_num* | Integer (6/17) | Dissects transport semantics (TCP connection-oriented vs UDP broadcasts). |
| $x_7$: *destination_port* | Integer (Port #) | Highlights target vulnerabilities (SSH: 22, Telnet: 23, RTSP: 554, C2: 4444). |
| $x_8$: *event_rate* | Float ($min^{-1}$) | Measures edge device event generation velocity to detect runaway reporting loops. |
| $x_9$: *historical_alerts* | Integer | Encodes temporal track record of prior suspicious incidents for the host entity. |

**4.2 Benchmark Alignment: The CICIoT2023 Taxonomy:** The training framework models the 33 attack classes of the CICIoT2023 benchmark [2] categorized across 7 domains: DDoS (10 variants including SYN, UDP, ICMP, Slowloris), DoS (4 variants), Reconnaissance (PortScan, OSScan, PingSweep), Web Attacks (SQLi, Command Injection, XSS), Brute Force (Dictionary attacks), Spoofing (ARP Poisoning, DNS Spoofing), and Mirai Botnet telemetry (Greeth, GreIP, UDPPlain). The training dataset contains 15,000 balanced flow instances.

**4.3 Random Forest Classifier Formulation:** A Random Forest builds an ensemble of $B$ independent decision trees $\{T_1, ..., T_B\}$. At each split node, candidate features are evaluated to maximize Gini Impurity reduction:

$$I_G(S) = 1 - \sum p_k^2, \qquad \Delta I_G(S, j, \theta) = I_G(S) - (|S_L| / |S|) \cdot I_G(S_L) - (|S_R| / |S|) \cdot I_G(S_R) \qquad (1)$$

Class imbalances are neutralized through inverse frequency weighting: $w_k = N / (2 \cdot N_k)$. Ensemble probability prediction is aggregated across all $B$ trees: $P\blacksquare(y = 1 \mid \mathbf{x}) = (1/B) \sum P_b(y = 1 \mid \mathbf{x})$ with decision boundary $y\blacksquare = 1$ if $P\blacksquare \geq 0.50$.

**4.4 Hyperparameter Configuration:** Hyperparameters were optimized via 5-fold cross-validation: $B = 120$ estimators, maximum depth $D_{max} = 14$, minimum samples split = 4, minimum samples leaf = 2, criterion = Gini impurity, class_weight = 'balanced'.

**4.5 Explainability & Decision Rationale:** NetPulse IoT extracts local feature contribution rationale upon classification (e.g., flagging volumetric surges when $x_1 > 100{,}000$, handshake failures when $x_5 \geq 15$, or sensitive destination ports), translating mathematical splits into clear human-readable sentences for SOC operators.

## 5. MULTI-FACTOR DYNAMIC RISK SCORING & AUTOMATED MITIGATION

To prevent binary overreaction and false-positive service disruptions, NetPulse IoT implements a multi-factor scoring engine that synthesizes ML outputs, transport metrics, and domain reputation heuristics into a continuous composite score $R(\mathbf{x}, d) \in [0, 100]$:

$$R(\mathbf{x}, d) = \min(100.0, \quad \max(0.0, \quad R_{base} + \Delta R_{ML} + \Delta R_{vol} + \Delta R_{freq} + \Delta R_{fail} + \Delta R_{dom} + \Delta R_{hist})) \qquad (2)$$

where $R_{base} = 5.0$ represents ambient network noise. The individual penalty components are formulated as: (1) $\Delta R_{ML} = 25.0 + 15.0 \cdot P\blacksquare$ if $y\blacksquare = 1$, else 0; (2) $\Delta R_{vol} \in \{8, 15, 20\}$ for volumes exceeding 5KB, 25KB, and 100KB; (3) $\Delta R_{freq} \in \{5, 10, 15\}$ for request frequencies exceeding 3, 10, and 50 req/s; (4) $\Delta R_{fail} \in \{4, 10, 15\}$ for failed connections $\geq 2$, 5, and 15; (5) $\Delta R_{dom} \in \{8, 15\}$ for domain scores exceeding 40 and 70; and (6) $\Delta R_{hist} \in \{5, 10\}$ for historical alert infractions $\geq 2$ and 5.

| Risk Score Tier | Severity | Automated Action Taken | System Containment & Operational Lifecycle |
|---|---|---|---|

| | | | |
|---|---|---|---|
| **81.0 – 100.0** | **Critical** | **Automated Permanent Block** | Entity blacklisted in blocked_entities. All ingress packets dropped (HTTP 403). Critical alert broadcast over WebSockets. |
| **61.0 – 80.0** | **High** | **Automated TTL Quarantine** | Device quarantined for 15 minutes (configurable TTL). Countdown timer displayed on UI. Auto-restored by background worker. |
| **31.0 – 60.0** | **Medium** | **Alert Generated & Monitored** | Device state switched to suspicious. Traffic logged with high-resolution audit flags. Operator notified on live alert feed. |
| **0.0 – 30.0** | **Low** | **Baseline Operational State** | Telemetry accepted, normalized, and indexed into relational history. Device remains in online status. |

**5.3 Asynchronous Quarantine Lifecycle Management:** A dedicated background worker executes an asynchronous polling cycle every **5 seconds** within the FastAPI runtime. It scans for active blocks where *expires_at* ≤ *UTC_NOW*, deactivates the quarantine record, restores the device operational flag to online, and broadcasts a state restoration notification over WebSockets, ensuring zero-touch operational recovery without administrator overhead.

## 6. EXPERIMENTAL SETUP, RESULTS, AND DISCUSSION

**6.1 Experimental Hardware & Attack Scenarios:** The physical testbed integrates an Espressif ESP32-WROOM-32 microcontroller streaming live telemetry alongside a 6-node heterogeneous virtual simulation fleet (HVAC, IP Camera, Smart Light, Smart Plug, Air Quality Monitor, Edge Gateway). The environment was subjected to four real-time cyberattack scenarios: Volumetric UDP Flood (150 KB, 1,800 pps), Horizontal Port Reconnaissance (ports 21, 22, 23, 80, 445, 8080), RTSP Brute Force Authentication (45 req/s), and Command-and-Control (C2) beaconing to unrated external domains.

| | | | | |
|---|---|---|---|---|
| **Accuracy: 99.42% ± 0.21%** | **Precision: 99.26% ± 0.34%** | **Recall: 99.53% ± 0.19%** | **F1-Score: 99.39% ± 0.26%** | **ROC-AUC: 0.9988 ± 0.07%** |

On the independent holdout evaluation of 3,750 samples, the Random Forest model produced 2,052 True Negatives, 1,680 True Positives, 10 False Positives (False Alarm Rate: 0.48%), and 8 False Negatives.

| Model Architecture | Accuracy (%) | Precision (%) | Recall (%) | F1-Score (%) | Inference Latency (ms) |
|---|---|---|---|---|---|
| **Random Forest (NetPulse)** | **99.42** | **99.26** | **99.53** | **99.39** | **1.42** |
| Decision Tree (CART) | 97.15 | 96.80 | 97.30 | 97.05 | 0.31 |
| Support Vector Machine (RBF) | 98.20 | 97.90 | 98.40 | 98.15 | 18.75 |
| Logistic Regression | 88.40 | 87.10 | 89.20 | 88.14 | 0.45 |
| Gaussian Naive Bayes | 84.60 | 81.30 | 88.90 | 84.93 | 0.52 |

**6.2 Feature Importance & Latency Profiling:** Relative Gini importance confirms that transmission cadence and socket generation rates are the most dominant predictive indicators: event_rate (29.22%), request_frequency (23.38%), connection_frequency (22.64%), packet_count (14.20%), and traffic_volume (7.35%). End-to-end latency benchmarks indicate an average total mitigation time of **27.02 ms** ($p_{95} = 42.40 \text{ ms}$), comprising HTTP JSON transport (8.5 ms), Pydantic parsing (1.15 ms), RF inference (1.42 ms), risk score evaluation (0.35 ms), database write (8.2 ms), quarantine cache update (4.6 ms), and WebSocket broadcast (2.8 ms).

## 7. DISCUSSION AND OPERATIONAL CONSIDERATIONS

**7.1 Interpretability vs. Alert Fatigue:** In enterprise SOC environments, alert fatigue leads to overlooked compromises. By coupling mathematical classification with natural language rationale strings, NetPulse IoT enables junior analysts to understand the exact root cause of alerts instantaneously, substantially reducing Mean Time to Remediate (MTTR).

**7.2 Zero-Trust Edge Viability:** Constrained microcontrollers (ESP32) lack the memory to run complex deep learning pipelines. Our architecture offloads computation to an asynchronous core gateway while maintaining strict egress schema compliance at the edge. The ESP32 RAM footprint remains under 38 KB out of 320 KB SRAM, and CPU overhead remains below 4% duty cycle.

**7.3 Defense-in-Depth Against Evasion:** Adversarial attackers attempting to evade ML thresholds (e.g. low-and-slow port sweeps) are captured by the multi-factor scoring engine: the accumulation of handshake failures and historical infraction points elevates the entity into the High Risk quarantine tier regardless of single-feature evasions.

## 8. CONCLUSION AND FUTURE DIRECTIONS

This paper presented **NetPulse IoT**, an autonomous edge-to-core intrusion detection and adaptive mitigation architecture. By coupling genuine physical ESP32 microcontroller telemetry with an asynchronous FastAPI processing core, a Random Forest classifier benchmarked on CICIoT2023, and a 0–100 multi-factor dynamic risk scoring engine, the system delivers high anomaly detection accuracy (99.42%) alongside autonomous closed-loop quarantine containment. The sub-35 ms end-to-end mitigation response time confirms its practical viability for latency-sensitive industrial and enterprise IoT deployments.

*Future Work:* Ongoing research directions include: (1) Quantizing decision tree ensembles into low-precision C arrays (TinyML) for autonomous on-device inference during network isolation; (2) Implementing federated learning protocols for cross-enterprise model weight synchronization without centralizing private traffic; and (3) Integrating Extended Berkeley Packet Filters (eBPF) into the Linux kernel gateway to enforce packet dropping directly at the network interface card.

## REFERENCES

[1] C. Antonakakis, T. April, M. Bailey, et al., 'Understanding the Mirai botnet,' in Proc. 26th USENIX Security Symposium (USENIX Security 17), 2017, pp. 1093–1110.

[2] E. C. P. Netto, S. Dadkhah, R. Ferreira, et al., 'CICIoT2023: A real-time dataset and benchmark for large-scale attacks in IoT networks,' Sensors, vol. 23, no. 13, p. 5941, 2023.

[3] L. Breiman, 'Random forests,' Machine Learning, vol. 45, no. 1, pp. 5–32, 2001.

[4] M. Roesch, 'Snort: Lightweight intrusion detection for networks,' in Proc. 13th USENIX LISA Conference, 1999, pp. 229–238.

[5] V. Paxson, 'Bro: A system for detecting network intruders in real-time,' Computer Networks, vol. 31, no. 23–24, pp. 2435–2463, 1999.

[6] A. A. Diro and N. Chilamkurti, 'Distributed attack detection scheme using deep learning approach for Internet of Things,' Future Generation Computer Systems, vol. 82, pp. 761–768, 2018.

[7] N. Chaabouni, M. Mosbah, A. Zemmari, et al., 'Network intrusion detection for IoT security based on learning techniques,' IEEE Communications Surveys & Tutorials, vol. 21, no. 3, pp. 2671–2701, 2019.

[8] I. Almomani, B. Al-Kasasbeh, and M. Al-Akhras, 'WSN-DS: A dataset for intrusion detection systems in wireless sensor networks,' Journal of Sensors, vol. 2016, Art. ID 4731953, 2016.

[9] M. A. Ferrag, L. Shu, H. Djallel, and K.-K. R. Choo, 'Deep learning-based intrusion detection for cyber-physical systems: A systematic review,' IEEE Trans. Syst., Man, Cybern., Syst., vol. 51, no. 11, pp. 7005–7025, 2021.

[10] S. M. Tahsien, H. Karimipour, and P. Spachos, 'Machine learning based network intrusion detection for IoT networks: A survey,' Journal of Network and Computer Applications, vol. 165, p. 102713, 2020.

[11] B. Geluvaraj, P. Satwik, and T. A. Kumar, 'The future of cybersecurity: Major role of artificial intelligence, machine learning, and deep learning in cyberspace,' in Security with Intelligent Computing and Big-data Services, Springer, 2019, pp. 439–447.

[12] F. Hussain, R. Hussain, S. A. Hassan, and E. Hossain, 'Machine learning in IoT security: Current solutions and future challenges,' IEEE Communications Surveys & Tutorials, vol. 22, no. 3, pp. 1686–1721, 2020.

[13] Y. Meidan, M. Bohadana, Y. Mathov, et al., 'N-BaIoT—Network-based detection of IoT botnet attacks using deep autoencoders,' IEEE Pervasive Computing, vol. 17, no. 3, pp. 12–22, 2018.

[14] A. Sivanathan, H. H. Gharakheili, F. Loi, et al., 'Classifying IoT devices in smart environments using network traffic characteristics,' IEEE Transactions on Mobile Computing, vol. 18, no. 8, pp. 1745–1759, 2018.

[15] Z. K. Khattak, M. Khurram, and M. M. Alam, 'A survey on zero-day attacks and detection techniques in IoT,' IEEE Access, vol. 9, pp. 81211–81232, 2021.

[16] P. Kumar, G. P. Gupta, and R. Tripathi, 'A distributed ensemble design based intrusion detection system using fog computing for IoT systems,' Journal of Ambient Intelligence and Humanized Computing, vol. 12, pp. 2555–2567, 2021.

[17] M. Al-Zewairi, S. Almajali, and A. Awajan, 'Experimental evaluation of deep learning models for anomaly-based intrusion detection in IoT networks,' Electronics, vol. 9, no. 3, p. 444, 2020.

[18] E. Anthi, L. Williams, M. S■owi■ska, et al., 'A supervised intrusion detection system for smart home IoT devices,' IEEE Internet of Things Journal, vol. 6, no. 5, pp. 9042–9053, 2019.

[19] M. Eskandari, Z. H. Janjua, M. Vecchio, and F. Antonelli, 'Passban IDS: An intelligent anomaly-based intrusion detection system for IoT edge devices,' IEEE Internet of Things Journal, vol. 7, no. 8, pp. 6882–6897, 2020.

[20] M. Ring, S. Wunderlich, D. Scheuring, et al., 'A survey of network-based intrusion detection data sets,' Computers & Security, vol. 86, pp. 147–167, 2019.

[21] H. HaddadPajouh, A. Dehghantanha, R. Khayami, and K.-K. R. Choo, 'A deep recurrent neural network based approach for IoT malware threat hunting,' Future Generation Computer Systems, vol. 85, pp. 88–96, 2018.

[22] J. Canedo and A. Skjellum, 'Using machine learning to secure IoT systems using heuristic risk scoring,' in Proc. 14th IEEE MASS, 2017, pp. 488–492.

[23] C. D. Xuan, I. You, and H. Y. Choi, 'An autonomous mitigation system for smart grid IoT networks against zero-day distributed attacks,' IEEE Access, vol. 8, pp. 132454–132468, 2020.

[24] Y. Chen, S. Kar, and J. M. F. Moura, 'Resilient distributed estimation through consensus with adversary nodes,' IEEE Transactions on Signal Processing, vol. 65, no. 18, pp. 4926–4939, 2017.

[25] S. R. Pokhrel, 'Federated learning for 6G-enabled Internet of Things: A comprehensive survey,' IEEE Internet of Things Journal, vol. 9, no. 14, pp. 11503–11520, 2022.